Eink 元太科技
E Ink Holdings

PD050VXB

Version : 1.0

TECHNICAL   SPECIFICATION MODEL   NO. : PD050VXB

The content of this information is subject to be changed without notice.

Please contact E Ink or its agent for further information.

☐Customer's Confirmation

Customer _____

Date _____

By _____

☐E Ink's Confirmation

Approve By _____

Confirmed By _____

Prepared By _____

PD050VXB

Revision History

Rev.	Issued Date	Revised Contents
1.0	August 23,2011	New

TECHNICAL SPECIFICATION

CONTENTS

E ink 元太科技
E Ink Holdings

1.Application

This data sheet applies to a color TFT LCD module, PD050VXB.This module applies to OA product, computer peripheral, industrial meter, image communication and multi-media. If you must use in severe reliability environment, please don't extend over E Ink's reliability test conditions. If you use PD050VXB, Elnk Holding Inc advises your systems use E Ink's timing controller IC (PVI-2003A) which will generate proper timing signals to control it.

2. Features

. VGA (640*480 pixels) resolution
. Amorphous silicon TFT LCD panel with back-light unit
. Pixel in stripe configuration
. Thin and light weight
. Display Colors：262,144 colors
. Portrait mode
. TTL transmission interface

3.Mechanical Specifications

Parameter	Specifications	Unit
Screen Size	5.0(diagonal)	inch
Display Format	640(H)×(R, G, B)×480(V)	dot
Display Colors	262,144	
Active Area	74.88 (H)×101.76(V)	mm
Pixel Pitch	0.156(H)×0.159(V)	mm
Pixel Configuration	Stripe	
Surface Treatment	AG+EWV	
Outline Dimension	91.4(H)×119.3 (V)×7.9(D)	mm
Weight	116±10	g
Back-light	LED	
Display mode	Normally white	
Gray scale inversion direction	3 o`clock [ref. to Note 13-1]	

PD050VXB

4.Mechanical Drawing of TFT-LCD Module

PD050VXB

PD050VXB

5. Input / Output Terminals
5-1) TFT-LCD Panel Driving
CN 1

LCD Module Connector
30 Pins , Pitch : 0.5 mm

Pin No.	Symbol	I/O	Function	Remark
1	DIO1	I/O	Horizontal Start Pulse Signal Input or Output	Note 5-6
2	VSS1	I	Ground	
3	VDD1	I	Power Supply for Source	
4	CLK	I	Horizontal Shift Clock	
5	VSS1	I	Ground	
6	R/L	I	Right/Left selection	Note 5-6
7	R0	I	Red Data (LSB)	
8	R1	I	Red Data	
9	R2	I	Red Data	
10	R3	I	Red Data	
11	R4	I	Red Data	
12	R5	I	Red Data (MSB)	
13	VSS1	I	Ground	
14	G0	I	Green Data (LSB)	
15	G1	I	Green Data	
16	G2	I	Green Data	
17	G3	I	Green Data	
18	G4	I	Green Data	
19	G5	I	Green Data (MSB)	
20	VSS1	I	Ground	
21	B0	I	Blue Data (LSB)	
22	B1	I	Blue Data	
23	B2	I	Blue Data	
24	B3	I	Blue Data	
25	B4	I	Blue Data	
26	B5	I	Blue Data (MSB)	
27	LD	I	Load output signal	Note 5-7
28	REV	I	Data invert control	Note 5-8
29	POL	I	Polarity selection	Note 5-9
30	DIO2	I/O	Horizontal Start Pulse Signal Input or Output	Note 5-6

E ink 元太科技
E Ink Holdings

PD050VXB

CN 2

Pin No.	Symbol	I/O	Function	Remark
1	VSS2	I	Ground	
2	V1	I	Gamma Voltage 1	Note 5-10
3	V2	I	Gamma Voltage 2	Note 5-10
4	V3	I	Gamma Voltage 3	Note 5-10
5	V4	I	Gamma Voltage 4	Note 5-10
6	V5	I	Gamma Voltage 5	Note 5-10
7	V6	I	Gamma Voltage 6	Note 5-10
8	V7	I	Gamma Voltage 7	Note 5-10
9	VSS2	I	Ground	
10	V8	I	Gamma Voltage 8	Note 5-10
11	V9	I	Gamma Voltage 9	Note 5-10
12	V10	I	Gamma Voltage 10	Note 5-10
13	V11	I	Gamma Voltage 11	Note 5-10
14	V12	I	Gamma Voltage 12	Note 5-10
15	V13	I	Gamma Voltage 13	Note 5-10
16	V14	I	Gamma Voltage 14	Note 5-10
17	VSS2	I	Ground	
18	VDD2	I	Voltage for analog circuit	Note 5-10
19	VCOM	I	Common Voltage	
20	XON	I	NC	
21	OE	I	Output Enable	Note 5-5
22	U/D	I	Up/Down selection	Note 5-3
23	CKV	I	Vertical Shift Clock	Note 5-4
24	STVU	I/O	Vertical Shift Pulse Signal Input or Output	Note 5-3
25	STVD	I/O	Vertical Shift Pulse Signal Input or Output	Note 5-3
26	VGG	I	Gate On Voltage	Note 5-2
27	GND	I	Ground	
28	VCC	I	Voltage for logic circuit	
29	GND	I	Ground	
30	VEE	I	Gate Off Voltage	Note 5-1

Note 5-1: Gate off voltage, V_{EE}=-5.5V

Note 5-2: Gate on voltage, V_{GG}=+15.4V

Note 5-3: Select up or down shift

U/D	STVU	STVD	Shift
1	Hi-Z	Input	Down to Up
0	Input	Hi-Z	Up to Down

Note 5-4: Gate driver shift clock

Note 5-5: When OE is connected to high "1", the driver outputs are disabled (Gate output = V_{EE}). Under this condition, the operation of registers will not be affected.

Note 5-6: Select left or right shift

R/L	DIO1	DIO2	Shift
1	Input	Hi-Z	Left to right
0	Hi-Z	Input	Right to left

Note 5-7: Latch the polarity of outputs and switch the new data to outputs. At the rising edge (LD), latch the "POL" signal to control the polarity of the outputs.

Note 5-8: Control whether the Data R0~G5 are inverted or not. (E Ink suggests connecting to GND) When "REV=1", these data will be inverted. EX: "00"→"3F", "07"→"38", "15"→"2A"

Note 5-9: Polarity selector for dot-inversion control. Available at the rising edge of LD. When POL=1: Even outputs range from V1~V7, and Odd outputs range from V8~V14; When POL=0: Even outputs range from V8~V14, and Odd outputs range from V1~V7.

Note 5-10: $V_{DD2} = +7.7V$

Typical Application Circuit (When $V_1 = +7.7V$)

E ink 元太科技
E Ink Holdings

5-2) Backlight driving

Pin No	Symbol	Description	Remark
1	+	Input terminal(Anode)	Red
2	NC	No connect	-
3	-	Input terminal(Cathode)	Black

6.Absolute Maximum Ratings:

$V_{SS1}=V_{SS2}=GND=0V$, Ta=25℃

Parameters	Symbol	MIN.	MAX.	Unit	Remark
Supply Voltage	V_{DD1}	-0.5	5.0	V	
	V_{CC}	-0.3	6.0	V	
	V_{DD2}	-0.5	12.0	V	
	V_{GG}	-0.3	40.0	V	
	$V_{GG}-V_{EE}$	-0.3	40.0	V	
	V_{EE}	-20	0.3	V	
Storage Temperature	Tst	-30	80	℃	
Operation Temperature	Top	-20	70	℃	

7.Electrical Characteristics

7-1) Recommended Operating Conditions:

$V_{SS1}=V_{SS2}=GND=0V$, Ta=25℃

Item	Symbol	Min.	Typ.	Max.	Unit	Remark
Supply Voltage for Source Driver	V_{DD1}	2.3	3.3	3.6	V	
	V_{DD2}	6.5	7.7	13.5	V	
Supply Voltage for Gate Driver	V_{GG}	14.4	15.4	16.4	V	
	V_{EE}	-6.0	-5.5	-5.0	V	
	V_{CC}	2.3	3.3	5.5	V	
V_{com} Voltage	V_{com}	-	2.6	-	V	
Digital Input Voltage	V_{IH}	0.7 V_{CC}	-	V_{CC}	V	
	V_{IL}	0	-	0.3 V_{CC}	V	

Eink 元太科技
E Ink Holdings

PD050VXB

7-2) Recommended Driving Condition for Back Light

$Ta = 25°C$

Parameter	Symbol	Min	TYP	MAX	Unit	Remark
Supply voltage of LED backlight	V_{LED}	-	-	11.5	V	Note 7-1
Supply current of LED backlight	I_{LED}	-	20	30	mA	Note 7-2
Backlight Power Consumption	P_{LED}	-	-	2.3	W	Note 7-1 /Note 7-3

Note 7-1 : I_{LED} = 20mA,Constant Current. Customer system design for driving should be constant current.

Note 7-2: The LED driving condition is defined for each LED module. (3 LED Serial)
Input current = 20 mA *10=200mA

Note 7-3: $P_{LED} = V_{LED-1} * I_{LED-1} + V_{LED-2} * I_{LED-2} ….. + V_{LED-9} * I_{LED-9} + V_{LED-10} * I_{LED-10}$
$(P_{LED})_{MAX} = (V_{LED})_{MAX} * (I_{LED})_{TYP} *$ Number of LED parallel

7-3) Power Consumption

Parameter	Symbol	Condition	Typ.	Max.	Unit	Remark
Supply Current for Gate Driver (Hi level)	I_{GG}	V_{GG}=+15.4V	0.1	0.3	mA	
Supply Current for Gate Driver (Low level)	I_{EE}	V_{EE}=-5.5V	0.1	0.3	mA	
Supply Current for Source Driver (Digital)	I_{DD1}	V_{DD1}=+3.3V	4.7	9.4	mA	
Supply Current for Source Driver (Analog)	I_{DD2}	V_{DD2}=+7.7V	17.0	34.0	mA	
Supply Current for Gate Driver (Digital)	I_{CC}	V_{CC}=+3.3V	0.1	0.3	mA	
LCD Panel Power Consumption		-	148.8	300.0	mW	Note 7-4
Back Light Power Consumption		-	-	2.3	W	Note 7-5

Note 7-4: The power consumption for back light is not included.

Note 7-5: Back light power consumption is calculated by $I_L×V_L$.

8. Pixel Arrangement

The LCD module pixel arrangement is the stripe.

Eink 元太科技
E Ink Holdings

9.Display Color and Gray Scale Reference

Color		Input Color Data																	
		Red						Green						Blue					
		R5	R4	R3	R2	R1	R0	G5	G4	G3	G2	G1	G0	B5	B4	B3	B2	B1	B0
Basic Colors	Black	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
	Red (63)	1	1	1	1	1	1	0	0	0	0	0	0	0	0	0	0	0	0
	Green (63)	0	0	0	0	0	0	1	1	1	1	1	1	0	0	0	0	0	0
	Blue (63)	0	0	0	0	0	0	0	0	0	0	0	0	1	1	1	1	1	1
	Cyan	0	0	0	0	0	0	1	1	1	1	1	1	1	1	1	1	1	1
	Magenta	1	1	1	1	1	1	0	0	0	0	0	0	1	1	1	1	1	1
	Yellow	1	1	1	1	1	1	1	1	1	1	1	1	0	0	0	0	0	0
	White	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1
Red	Red (00)	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
	Red (01)	0	0	0	0	0	1	0	0	0	0	0	0	0	0	0	0	0	0
	Red (02)	0	0	0	0	1	0	0	0	0	0	0	0	0	0	0	0	0	0
	Darker ↓ Brighter	↓	↓	↓	↓	↓	↓	↓	↓	↓	↓	↓	↓	↓	↓	↓	↓	↓	↓
	Red (61)	1	1	1	1	0	1	0	0	0	0	0	0	0	0	0	0	0	0
	Red (62)	1	1	1	1	1	0	0	0	0	0	0	0	0	0	0	0	0	0
	Red (63)	1	1	1	1	1	1	0	0	0	0	0	0	0	0	0	0	0	0
Green	Green (00)	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
	Green (01)	0	0	0	0	0	0	0	0	0	0	0	1	0	0	0	0	0	0
	Green (02)	0	0	0	0	0	0	0	0	0	0	1	0	0	0	0	0	0	0
	Darker ↓ Brighter	↓	↓	↓	↓	↓	↓	↓	↓	↓	↓	↓	↓	↓	↓	↓	↓	↓	↓
	Green (61)	0	0	0	0	0	0	1	1	1	1	0	1	0	0	0	0	0	0
	Green (62)	0	0	0	0	0	0	1	1	1	1	1	0	0	0	0	0	0	0
	Green (63)	0	0	0	0	0	0	1	1	1	1	1	1	0	0	0	0	0	0
Blue	Blue (00)	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
	Blue (01)	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	1
	Blue (02)	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	1	0
	Darker ↓ Brighter	↓	↓	↓	↓	↓	↓	↓	↓	↓	↓	↓	↓	↓	↓	↓	↓	↓	↓
	Blue (61)	0	0	0	0	0	0	0	0	0	0	0	0	1	1	1	1	0	1
	Blue (62)	0	0	0	0	0	0	0	0	0	0	0	0	1	1	1	1	1	0
	Blue (63)	0	0	0	0	0	0	0	0	0	0	0	0	1	1	1	1	1	1

PD050VXB

10. Block Diagram

10-1) TFT-module Block Diagram

If you use **PD050VXB**, you can apply PVI-2003A(Timing controller) which will gemerate timing signals to support **PD050VXB**.

11. Interface Timing

11.1) Timing Parameters

AC Electrical Characteristics ($V_{CC}=V_{DD1}=3.3V$, $V_{DD2}=7.7V$, $GND=V_{SS1}=V_{SS2}=0V$, Ta=25℃)

Parameter	Symbol	Min.	Typ.	Max.	Unit
CLK Frequency	Fclk	-	25	40	MHz
CLK Pulse Width	Tcw	25	40	-	ns
Data Set-up Time	Tsu	4	-	-	ns
Data Hold Time	Thd	2	-	-	ns
Propagation Delay of DIO2/1	Tphl	6	10	15	ns
Time That The Last Data to LD	Tld	1	-	-	Tcw
Pulse width of LD	Twld	2	-	-	Tcw
Time That LD to DIO1/2	Tlds	5	-	-	Tcw
POL Set-up Time	Tpsu	6	-	-	ns
POL Hold Time	Tphd	6	-	-	ns
OE Pulse Width	T_{OEV}	1	-	-	μs
CKV Pulse Width	T_{CKV}	500	-	-	ns
STV Set-up Time	T_{SUV}	400	-	-	ns
STV Hold Time	T_{HDV}	400	-	-	ns
Horizontal Display Period	T_{HDP}	-	640	-	Tcw
Horizontal Period Timing Range	T_{HP}	-	800	-	Tcw
Horizontal Lines Per Field	T_V	520	525	640	T_{HP}
Vertical Display Timing Range	T_{DV}	-	480	-	T_{HP}

PD050VXB

11.2) Timing Diagram

Fig. 11-1 Horizontal timing (1)

PD050VXB

CLK

LD

DIO 1/2 (Input)

LD

POL

Odd outputs

Even outputs

Fig. 11-2 Horizontal timing(2)

Fig. 11-3 Vertical shift clock timing

Fig. 11-4 Vertical timing

(HSY)

(VSY)

STVU/STVD

POL(Odd Field)

POL(Even Field)

T_{HDP} T_{HP}

PD050VXB

12. Power On/Off Sequence

1. $10ms \leqq T1 < T2$
2. $0ms < T3 \leqq T4 \leqq 10ms$

13. Optical Characteristics

13-1) Specification:

Ta=25℃

| Parameter		Symbol	Condition	MIN.	TYP.	MAX.	Unit	Remarks
Viewing Angle	Vertical	$\theta 11,12$	CR≧10	70	75		deg	Note 13-1
	Horizontal	$\theta 22$ (3 o'clock)		65	70	-	deg	
		$\theta 21$ (9 o'clock)		45	50	-	deg	
Contrast Ratio		CR		500	600	-	-	Note 13-2
Response time	Rise	Tr	$\theta =0°$	-	15	30	ms	Note 13-3
	Fall	Tf		-	25	50	ms	
Brightness		L	$\theta =0°/ \varphi =0$	700	900	-	cd/㎡	
Luminance Uniformity		U		70	75	-	%	Note 13-4
Life Time				20000	-	-	hrs	Note 13-6
White Chromaticity		x		0.27	0.31	0.35	-	
		y		0.32	0.36	0.40	-	
Cross Talk			$\theta =0°$	-	-	3.5	%	Note 13-5

E ink 元太科技
E Ink Holdings

All the optical measurement shall be executed 30 minutes after backlight being turn-on. The optical characteristics shall be measured in dark room (ambient illumination on panel surface less than 1 Lux). The measuring configuration shows as following figure.

Photometer (TOPCON BM-5A or BM-7 fast)

500 mm +/- 50 mm

Field = 1°

TFT-LCD module

DC/AC Inverter

Optical characteristics measuring configuration

Topcon BM-5A or BM-7 fast luminance meter 1° field of view is used in the testing (after 30 minutes' operation).

Note 13-1: The definitions of viewing angles are as follow

θ = 0°
Θ21
Θ11
6
9
Θ12
Θ22
3
12

Note 13-2: The definition of contrast ratio $CR = \dfrac{\text{Luminance at gray level 63}}{\text{Luminance at gray level 0}}$

Note 13-3: Definition of Response Time T_r and T_f:

Note 13-4: The uniformity of LCD is defined as

$U = \dfrac{\text{The Minimum Brightness of the 9 testing Points}}{\text{The Maximum Brightness of the 9 testing Points}}$

Luminance meter : BM-5A or BM-7 fast(TOPCON)

Measurement distance : 500 mm +/- 50 mm

Ambient illumination : < 1 Lux

Measuring direction : Perpendicular to the surface of module

The test pattern is white (Gray Level 63).

Note 13-5: Cross Talk (CTK) = $\dfrac{|YA-YB|}{YA} \times 100\%$

        YA: Brightness of Pattern A

   YB: Brightness of Pattern B

        Luminance meter : BM 5A or BM-7 fast (TOPCON)

        Measurement distance : 500 mm +/- 50 mm

        Ambient illumination : < 1 Lux

        Measuring direction : Perpendicular to the surface of module

Pattern A
(Gray Level 31)

Pattern B
(Gray Level 31, central black box exclusive)

✕: Measuring Point (A and B are at the same point.)

Black
(Gray Level 0)

Note 13-6: The "LED Life time " is defined as the module brightness decrease to 50% original
Brightness that the ambient temperature is 25℃ and I_{LED} =200mA
As the performance of an LED may differ when assembled as a monitor together with a
TFT panel due to different environmental temperature.
Estimated lifetime could vary on a different temperature and usually higher
temperature could reduce the life significantly.

E ink 元太科技
E Ink Holdings

14. Handling Cautions

14-1) Mounting of module

 a) Please power off the module when you connect the input/output connector.
 b) Polarizer which is made of soft material and susceptible to flaw must be handled carefully.
 c) Protective film (Laminator) is applied on surface to protect it against scratches and dirt.
 d) Please following the tear off direction as figure14-1 to remove the protective film as slowly as possible, so that electrostatic charge can be minimized.

14-2) Precautions in mounting

 a) When metal part of the TFT-LCD module (shielding lid and rear case) is soiled, wipe it with soft dry cloth.
 b) Wipe off water drops or finger grease immediately. Long contact with water may cause discoloration or spots.
 c) TFT-LCD module uses glass which breaks or cracks easily if dropped or bumped on hard surface. Please handle with care.
 d) Since CMOS LSI is used in the module. So take care of static electricity and earth yourself when handling.

14-3) Adjusting module

 a) Adjusting volumes on the rear face of the module have been set optimally before shipment.
 b) Therefore, do not change any adjusted values. If adjusted values are changed, the specifications described may not be satisfied.

14-4) Others

 a) Do not expose the module to direct sunlight or intensive ultraviolet rays for many hours.
 b) Store the module at a room temperature place.
 c) The voltage of beginning electric discharge may over the normal voltage because of leakage current from approach conductor by to draw lump read lead line around.
 d) If LCD panel breaks, it is possibly that the liquid crystal escapes from the panel. Avoid putting it into eyes or mouth. When liquid crystal sticks on hands, clothes or feet. Wash it out immediately with soap.
 e) Observe all other precautionary requirements in handling general electronic components.
 f) Please adjust the voltage of common electrode as material of attachment by 1 module.

Figure 14-1 the way to peel off protective film

Eink | 元太科技
E Ink Holdings

15. Reliability Test

No	Test Item	Test Condition	Remark
1	High Temperature Storage Test	Ta = +80℃, 240 hrs	
2	Low Temperature Storage Test	Ta = -30℃, 240hrs	
3	High Temperature Operation Test	Ta = +70℃, 240 hrs	
4	Low Temperature Operation Test	Ta = -20℃, 240hrs	
5	High Temperature & High Humidity Operation Test	Ta = +60℃, 90%RH, 240 hrs (No Condensation)	
6	Thermal Cycling Test (non-operating)	-30℃→+80℃, 100 Cycles 30min　30min	
7	Vibration Test (non-operating)	Frequency：10～55 H$_Z$, Amplitude：1 mm Sweep time: 11 min Test Period: 6 Cycles for each direction of X, Y, Z	
8	Shock Test (non-operating)	100G, 6ms Direction: ±X, ±Y, ±Z　Cycle: 3 times	
9	Electrostatic Discharge Test (non-operating)	200pF, 0Ω ±200V 1 time / each terminal	

Ta : ambient temperature
Note : The protective film must be removed before temperature test.

[Criteria]
In the standard conditions, there is not display function NG issue occurred. (Including：line defect, no image) All the cosmetic specification is judged before the reliability stress.

PD050VXB

16. Packing Diagram

ZONE	REV.	DOCUUMENT NO.	DESCRIPTION	DATE	REV.BY

NOTE:
1.Q'TY: 40 pcs panel/carton.
2.Dimension: 530*295*230mm
3.Weight: 8 Kg

ITEM	PART NO. DESCRIPTION	QTY	REMARK
4	CARTON	1	
3	PINK Bag 195*105mm	40	抗靜電
2	PD050VX4 Panel	40	
1	瓦楞隔板緩衝材	1	上蓋＋ 底座

MTL.SPEC.	UNSPECIFIED TOL'S		REMARK		
	ANGLE				
	ROUGHNESS				
APPROVE Patrick '11.08.16	SCALE	UNIT	SHEET 1 OF 1	DWG.TITLE	
CHECK Patrick '11.08.16				PD050VXB Packing Draw	
DRAWN Doris '11.08.16	MTL.NO.			DWG FILE:	REV. 01 A4 SIZE