

PT150X0M-N10
Product Specification (RGB)

BEIJING BOE OPTOELECTRONICS TECHNOLOGY

SPEC. NUMBER	PRODUCT GROUP	REV.	ISSUE DATE	PAGE
S801-5127	TFT-LCD	0	2019.02.18	1 OF 25

BOE	PRODUCT GROUP	REV	ISSUE DATE
	TFT LCD PRODUCT	0	2019.02.18

Contents

No.	Items	Page
1.0	General Description	4
2.0	Absolute Maximum ratings	6
3.0	Electrical specifications.	7
4.0	Optical specifications.	9
5.0	Interface Connection	13
6.0	Signal Timing Specifications	15
7.0	Power Sequence	16
8.0	Mechanical Characteristics	17
9.0	Reliability Test	18
10.0	Handling & Cautions.	19
11.0	Label	20
12.0	Packing information	22
13.0	Mechanical Outline Dimension	23


SPEC. NUMBER S801-5127	SPEC TITLE PT150X0M-N10 Product Specification	PAGE 3 OF 25
---------------------------	---	-----------------

BOE	PRODUCT GROUP	REV	ISSUE DATE
	TFT LCD PRODUCT	0	2019.02.18

1.0 GENERAL DESCRIPTION

1.1 Introduction

PT150X0M-N10 is a color active matrix TFT LCD module using amorphous silicon TFT's (Thin Film Transistors) as an active switching devices. This module has a 15.0 inch diagonally measured active area with XGA resolutions (1024 horizontal by 768 vertical pixel array). Each pixel is divided into RED, GREEN, BLUE dots which are arranged in vertical stripe and this module can display 16.2M colors. The TFT-LCD panel used for this module is adapted for a low reflection and higher color type.



1.2 Features

- LED back-light
- LED light bar replaceable
- LVDS interface
- RoHS Compliant

1.3 Application

- TFT-LCD Monitor
- Reliability Application

SPEC. NUMBER	SPEC TITLE	PAGE
S801-5127	PT150X0M-N10 Product Specification	4 OF 25

BOE	PRODUCT GROUP	REV	ISSUE DATE
	TFT LCD PRODUCT	0	2019.02.18

1.4 General Specification

< Table 1. General Specifications >

Parameter	Specification	Unit	Remarks
Active area	304.128 (H) × 228.096(V)	mm	
Number of pixels	1024(H) × 768(V)	Pixels	
Pixel pitch	0.297(H) × 0.297 (V)	mm	
Pixel arrangement	RGB Vertical stripe		
Display colors	16.2M	Colors	6bit+FRC
Display mode	Normally White		
Dimensional outline	326.5 (H) × 253.5(V) × 9.7(D) typ.	mm	10max
Weight	850	g	typ
Surface treatment	Haze 25%, 3H		
Back-light	Edge side, 1-LED Lighting Bar Type		27*LED
LED life	50000	hr	

SPEC. NUMBER S801-5127	SPEC TITLE PT150X0M-N10 Product Specification	PAGE 5 OF 25
---------------------------	--	-----------------

2.0 ABSOLUTE MAXIMUM RATINGS

The followings are maximum values which, if exceed, may cause faulty operation or damage to the unit. The operational and non-operational maximum voltage and current values are listed in Table 2.

< Table 2. LCD Module Electrical Specifications > [Ta =25±2 °C]

Parameter	Symbol	Min.	Max.	Unit	Remarks
Back-light Power Supply Voltage	HV _{DDOUT}	-0.3	24	V	
Back-light LED Reverse Voltage	V _R	-	40	V	
Operating Temperature	T _{OP}	-20	70	°C	
Storage Temperature	T _{ST}	-20	70	°C	

3.0 ELECTRICAL SPECIFICATIONS

3.1 TFT LCD Module

< Table 3. LCD Module Electrical Specifications >

[Ta =25±2 °C]

Parameter	Symbol	Values			Unit	Notes
		Min	Typ	Max		
Power Supply Input Voltage	V _{DD}	3.0	3.3	3.6	V	Note 1
Power Supply Current	I _{DD}	-	520	700	mA	
LED Driver Power Supply Voltage	H _{VDD}	10.8	12	12.6	V	Note 2
LED Driver Power Supply Current	I _{HVDD}	467	500	534	mA	
LED Power Consumption	P _{LED}	5.6	6.0	6.4	W	
Positive-going Input Threshold Voltage	V _{IT+}	-	-	+100	mV	V _{com} = 1.2V typ.
Negative-going Input Threshold Voltage	V _{IT-}	-100	-	-	mV	
Differential input common mode voltage	V _{com}	-	1.2	-	V	V _{IH} =100mV, V _{IL} =-100mV

Notes : 1. The supply voltage is measured and specified at the interface connector of LCM.
The current draw and power consumption specified is for 3.3V at 25 °C
Max value at Black Pattern

2. Calculated value for reference $I_{LED} \times V_{LED} \div 0.85 = P_{LED}$

3.2 Back-light Unit

< Table 4. LED Driving guideline specifications >

Ta=25+/-2°C

Parameter			Min.	Typ.	Max.	Unit	Remarks
LED Life-Time		N/A	50,000	-	-	Hour	IF = 60mA Note 2
Power supply voltage for Back light		V _{LED}	26.1	27.9	29.7	V	
Power supply Current for Back light		I _{LED}	-	180	-	mA	
Power supply for Back light		P _{LED}	4.7	5.1	5.4	W	Note 1
EN Control Level	Backlight on	V _{ENH}	2	-	-	V	EN logic high v oltage
	Backlight off	V _{ENL}	-	-	0.6	V	EN logic low vol tage
PWM Control Level	PWM High Level	V _{PML}	2	-	-	V	
	PWM Low Level	V _{PML}	-	-	0.6	V	
PWM Control Frequency		F _{PWM}	0.12	-	1	KHz	
Duty Ratio		-	5	-	100	%	

Notes : 1. Calculator Value for reference $I_{LED} \times V_{LED} = P_{LED}$

2. The LED Life-time define as the estimated time to 50% degradation of initial luminous under the condition of the ambient temperature of 25°C.

BOE	PRODUCT GROUP	REV	ISSUE DATE
	TFT LCD PRODUCT	0	2019.02.18

4.0 OPTICAL SPECIFICATION

4.1 Overview

The test of view angle range shall be measured in a dark room (ambient luminance $\leq 1\text{lux}$ and temperature = $25\pm 2^{\circ}\text{C}$) with the equipment of Luminance meter system (Goniometer system and TOPCON CS2000/CA310) and test unit shall be located at an approximate distance 50cm from the LCD surface at a viewing angle of θ and Φ equal to 0° . We refer to $\theta\varnothing=0$ ($=\theta_3$) as the 3 o'clock direction (the "right"), $\theta\varnothing=90$ ($=\theta_{12}$) as the 12 o'clock direction ("upward"), $\theta\varnothing=180$ ($=\theta_9$) as the 9 o'clock direction ("left") and $\theta\varnothing=270$ ($=\theta_6$) as the 6 o'clock direction ("bottom"). While scanning θ and/or \varnothing , the center of the measuring spot on the Display surface shall stay fixed. The luminance, color and uniformity (etc) should be tested by CS2000/CA310. The backlight should be operating for 10 minutes prior to measurement. VDD shall be $3.3 \pm 0.3\text{V}$ at 25°C . Optimum viewing angle direction is 6 'clock

<Table 5. Optical Specifications>

Parameter		Symbol	Condition	Min.	Typ.	Max.	Unit	Remark
Viewing Angle range	Horizontal	Θ_3	CR > 10	-	80	-	Deg.	Note 1
		Θ_9		-	80	-	Deg.	
	Vertical	Θ_{12}		-	80	-	Deg.	
		Θ_6		-	80	-	Deg.	
Luminance Contrast ratio		CR	$\Theta = 0^\circ$	400	700	-		Note 2
Luminance of White	Center	Y_w	$\Theta = 0^\circ$	280	350	-	cd/m ²	Note 3
White Luminance uniformity	9 Points	ΔY_9		75	80	-	%	Note 4
Reproduction of color	White	W_x	$\Theta = 0^\circ$	Typ -0.03	0.313	Typ +0.03		Note 5
		W_y			0.329			
Response Time		T_{RT}	Ta= 25° C $\Theta = 0^\circ$	-	8	12	ms	Note 6
Cross Talk		CT	$\Theta = 0^\circ$	-	-	2.0	%	Note 7


SPEC. NUMBER S801-5127	SPEC TITLE PT150X0M-N10 Product Specification	PAGE 9 OF 25
---------------------------	---	-----------------

BOE	PRODUCT GROUP	REV	ISSUE DATE
	TFT LCD PRODUCT	0	2019.02.18
<p>Notes : 1. Viewing angle is the angle at which the contrast ratio is greater than 10. The viewing angles are determined for the horizontal or 3, 9 o'clock direction and the vertical or 6, 12 o'clock direction with respect to the optical axis which is normal to the LCD surface (see FIGURE 1).</p> <p>2. Contrast measurements shall be made at viewing angle of $\Theta = 0$ and at the center of the LCD surface. Luminance shall be measured with all pixels in the view field set first to white, then to the dark (black) state . (see FIGURE 1) Luminance Contrast Ratio (CR) is defined mathematically.</p> $CR = \frac{\text{Luminance when displaying a white raster}}{\text{Luminance when displaying a black raster}}$ <p>3. Luminance of white is defined as luminance values of center of the LCD surface. Luminance shall be measured with all pixels in the view field set first to white. This measurement shall be taken at the locations shown in FIGURE 2 for a total of the measurements per display. The luminance is measured by CS2000/CA310 when the LED current is set at 60mA.</p> <p>4. The White luminance uniformity on LCD surface is then expressed as : $\Delta Y = \text{Minimum Luminance of 9 points} / \text{Maximum Luminance of 9 points}$ (see FIGURE 2).</p> <p>5. The color chromaticity coordinates specified in Table 5. shall be calculated from the spectral data measured with all pixels first in red, green, blue and white. Measurements shall be made at the center of the panel.</p> <p>6. The electro-optical response time measurements shall be made as FIGURE 3. The times needed for the luminance to change from 10% to 90% is T_r, and 90% to 10% is T_f.</p> <p>7. Cross-Talk of one area of the LCD surface by another shall be measured by comparing the luminance (Y_A) of a 25mm diameter area, with all display pixels set to a gray level, to the luminance (Y_B) of that same area when any adjacent area is driven dark. (See FIGURE 4).</p>			
SPEC. NUMBER S801-5127	SPEC TITLE PT150X0M-N10 Product Specification		PAGE 10 OF 25

BOE	PRODUCT GROUP	REV	ISSUE DATE
	TFT LCD PRODUCT	0	2019.02.18


4.2 Optical measurements

Figure 1. Measurement Set Up



View angel range, uniformity, etc. measurement setup Flicker, measurement setup

Figure 2. White Luminance and Uniformity Measurement Locations (9 points)



Luminance of white is defined as luminance values of center of the LCD surface. Luminance shall be measured with all pixels in the view field set first to white. This measurement shall be taken at the locations shown in FIGURE 2 for a total of the measurements per display.

The White luminance uniformity on LCD surface is then expressed as : $\Delta Y9 = \text{Minimum Luminance of 9 points} / \text{Maximum Luminance of 9points}$ (see FIGURE 2).

SPEC. NUMBER	SPEC TITLE	PAGE
S801-5127	PT150X0M-N10 Product Specification	11 OF 25

BOE	PRODUCT GROUP	REV	ISSUE DATE
	TFT LCD PRODUCT	0	2019.02.18

Figure 3. Response Time Testing

Display data

Black (TFT OFF)

White (TFT ON)

Black (TFT OFF)

Optical Response

100%

90%

10%

0%

Time

Tr

Tf

The electro-optical response time measurements shall be made as shown in FIGURE 3. The times needed for the luminance to change from 10% to 90% is Tr and 90% to 10% is Tf.

Figure 4. Cross Modulation Test Description

1/3

1/8

L0

L127

YC

1/3

1/8

L255

L127

YB

1/3

1/8

L127

YA

White Bar Cross-Talk(%) = $\left| \frac{YB - YA}{YA} \right| \times 100$

Black Bar Cross-Talk(%) = $\left| \frac{YC - YA}{YA} \right| \times 100$

Where:

YA = Initial luminance of measured area (cd/m2)

YB = Subsequent luminance of measured area (cd/m2) @White Bar

YC = Subsequent luminance of measured area (cd/m2) @Black Bar

The location measured will be exactly the same in both patterns

SPEC. NUMBER	SPEC TITLE	PAGE
S801-5127	PT150X0M-N10 Product Specification	12 OF 25

B2006-5006-O (3/3)

A4(210 X 297)

5.0 INTERFACE CONNECTION.

5.1 Electrical Interface Connection

The electronics interface connector is DF14H-20P-1.25H.

The LED connector is 3808K-F05N-03L

The connector interface pin assignments are listed in Table 6 and 7.

<Table 6. Pin Assignments for the Interface Connector>

Terminal	Symbol	Functions
Pin No.	Symbol	Description
1	VDD	Power Supply,3.3V(typical)
2	VDD	Power Supply,3.3V(typical)
3	VSS	Ground
4	NC	No Connection
5	RIN0-	-LVDS differential data input
6	RIN0+	+LVDS differential data input
7	VSS	Ground
8	RIN1-	-LVDS differential data input
9	RIN1+	+LVDS differential data input
10	VSS	Ground
11	RIN2-	-LVDS differential data input
12	RIN2+	+LVDS differential data input
13	VSS	Ground
14	CLKIN-	-LVDS differential clock input
15	CLKIN+	+LVDS differential clock input
16	VSS	Ground
17	RIN3-	-LVDS differential data input
18	RIN3+	+LVDS differential data input
19	VSS	Ground
20	SEL 6/8	LVDS 6/8 bit select function control High -> 6bit input mode Low -> 8bit input mode

<Table 7. Pin Assignments for the LED Connector>

Terminal	Symbol	Functions
Pin No.	Symbol	Description
1	NC	No Connection
2	Dimming	PWM Dimming
3	Enable	5V-On / 0V-Off
4	GND	Ground
5	VCC	12V

<div>BOE</div>	PRODUCT GROUP	REV	ISSUE DATE
	TFT LCD PRODUCT	0	2019.02.18

5.2 Data Input Format

Figure 5. Pixel Format





Figure 6. Scan direction



SPEC. NUMBER	SPEC TITLE	PAGE
S801-5127	PT150X0M-N10 Product Specification	14 OF 25

BOE	PRODUCT GROUP	REV	ISSUE DATE
	TFT LCD PRODUCT	0	2019.02.18

6.0 SIGNAL TIMING SPECIFICATION


6.1 The PT150X0M-N10 is operated by the DE only.

Parameter	Symbol	Value			Unit
		Min.	Typ.	Max.	
DCLK Frequency	fclk	52	58	71	MHz
Horizontal display area	thd	1024			pixel
HSYNC period time	th	1114	1200	1400	pixel
HSYNC blanking	thb+ thfp	90	320	376	pixel
Vertical display area	Tvd	768			H
Frequency	fV	48	60	65	Hz
VSYNC period time	Tv	778	806	845	H
VSYNC blanking	Tvb+ Tvfp	10	38	77	H

SPEC. NUMBER S801-5127	SPEC TITLE PT150X0M-N10 Product Specification	PAGE 15 OF 25
---------------------------	---	------------------

7.0 POWER SEQUENCE

To prevent a latch-up or DC operation of the LCD module, the power on/off sequence shall be as shown in below



Parameter	Values			Units
	Min	Typ	Max	
T1	0	-	10	ms
T2	0	-	50	ms
T3	200	-	-	ms
T4	500	-	-	ms
T5	0	-	50	ms
T6	0	-	10	ms
T7	500	-	-	ms

BOE	PRODUCT GROUP	REV	ISSUE DATE
	TFT LCD PRODUCT	0	2019.02.18

8.0 MECHANICAL CHARACTERISTICS

8.1 Dimensional Requirements

<Table 8. Dimensional Parameters>

Parameter	Specification	Unit
Active Area	304.128 (H) × 228.096(V)	mm
Number of pixels	1024(H) X768 (V) (1 pixel = R + G + B dots)	
Pixel pitch	0.297(H) × 0.297 (V)	mm
Pixel arrangement	RGB Vertical stripe	
Display colors	16.2M (6bit+FRC)	colors
Display mode	Normally White	
Dimensional outline	326.5 (H) × 253.5(V) × 9.7(D) (Typ.)	10mm (Max)
Weight	850 ± 30	gram
Back-light	Edge side, 1-LED Lighting Bar Type	
LED life	50,000 (Min.)	hr

SPEC. NUMBER S801-5127	SPEC TITLE PT150X0M-N10 Product Specification	PAGE 17 OF 25
---------------------------	--	------------------

BOE	PRODUCT GROUP		REV	ISSUE DATE
	TFT LCD PRODUCT		0	2019.02.18
9.0 RELIABILITY TEST The Reliability test items and its conditions are shown in below. <div><Table 9. Reliability test></div>				
Item			Test condition	
High temperature storage			70 ℃, 240 hrs	
Low temperature storage			-20℃, 240 hrs	
High temperature & high humidity operation			50 ℃, 80%RH, 240hrs	
High temperature operation			70 ℃, 240hrs	
Low temperature operation			-20℃, 240hrs	
Vibration test	Frequency	10/ 200/10 Hz,Sine X/Y/Z Direction		
	Gravity / AMP	1.5 G		
	Period	±X, ±Y, ±Z 30 min		
Shock test	Gravity	50G		
	Pulse width	11msec, Half-sine wave		
	Direction	±X, ±Y, ±Z		
On/Off test			On/5sec, Off/5sec, 3,000 cycles	
ESD	Air	± 15KV, 150pF(330) 1sec, 100 points, 1 times/ point		
	Contact	± 8KV, 150pF(330) 1sec, 100 points, 1 times/ point		
SPEC. NUMBER	SPEC TITLE			PAGE
S801-5127	PT150X0M-N10 Product Specification			18 OF 25

BOE	PRODUCT GROUP	REV	ISSUE DATE
	TFT LCD PRODUCT	0	2019.02.18

10.0 HANDLING & CAUTIONS

(1) Cautions when taking out the module

- Pick the pouch only, when taking out module from a shipping package.

(2) Cautions for handling the module

- As the electrostatic discharges may break the LCD module, handle the LCD module with care. Peel a protection sheet off from the LCD panel surface as slowly as possible.
- As the LCD panel and back - light element are made from fragile glass material, impulse and pressure to the LCD module should be avoided.
- As the surface of the polarizer is very soft and easily scratched, use a soft dry cloth without chemicals for cleaning.
- Do not pull the interface connector in or out while the LCD module is operating.
- Put the module display side down on a flat horizontal plane.
- Handle connectors and cables with care.

(3) Cautions for the operation

- When the module is operating, do not lose CLK, ENAB signals. If any one of these signals is lost, the LCD panel would be damaged.
- Obey the supply voltage sequence. If wrong sequence is applied, the module would be damaged.

(4) Cautions for the atmosphere

- Dew drop atmosphere should be avoided.
- Do not store and/or operate the LCD module in a high temperature and/or humidity atmosphere. Storage in an electro-conductive polymer packing pouch and under relatively low temperature atmosphere is recommended.

(5) Cautions for the module characteristics

- Do not apply fixed pattern data signal to the LCD module at product aging.
- Applying fixed pattern for a long time may cause image sticking.

(6) Other cautions

- Do not disassemble and/or re-assemble LCD module.
- Do not re-adjust variable resistor or switch etc.
- When returning the module for repair or etc., Please pack the module not to be broken. We recommend to use the original shipping packages.


SPEC. NUMBER S801-5127	SPEC TITLE PT150X0M-N10 Product Specification	PAGE 19 OF 25
---------------------------	---	------------------

BOE	PRODUCT GROUP	REV	ISSUE DATE
	TFT LCD PRODUCT	0	2019.02.18

(2) Box label

Label Size: 110 mm (L) × 56 mm (W)

Contents
Model: **PT150X0M-N10**
Q`ty: Module Q`ty in one box
Date: Packing Date
Internal use of Product



- ① MODEL : FG-CODE(The first 12 numbers)
- ② QTY : Quantum
- ③ SERIAL NO : Box ID
- ④ DATE : Box Packing date
- ⑤ Box ID Bar-Code
- ⑥ FG-CODE(The last 4 numbers)

SPEC. NUMBER	SPEC TITLE	PAGE
S801-5127	PT150X0M-N10 Product Specification	21 OF 25

BOE	PRODUCT GROUP	REV	ISSUE DATE
	TFT LCD PRODUCT	0	2019.02.18

(3) Pallet label

Label Size: 110 mm (L) × 56 mm (W)

Contents

Model: **PT150X0M-N10** Q`ty: Module Q`ty in one box

Date: Packing Date


Pallet ID

MODEL : PT150X0M-N10 ①

QTY : 180 ②

PACK DATE : 2019/2/20 12:00 ③

PALLET : 20192AM00001 ④



⑤







18P0A0 ⑥

- 1.FG-CODE
- 2.Pallet Quantum
- 3.Pallet Packing date
- 4.Pallte ID
- 5.Bar-Code
- 6.FG-CODE(The last 4 numbers)+Product grade

SPEC. NUMBER	SPEC TITLE	PAGE
S801-5127	PT150X0M-N10 Product Specification	22 OF 25

BOE	PRODUCT GROUP	REV	ISSUE DATE
	TFT LCD PRODUCT	0	2019.02.18

12.0 PACKING INFORMATION

<p>将 2 EPS Pad放入到1 Inner Box中。 2 EPS Pad/Inner Box</p>	<p>将1 MDL & 1 EPE Pad装入1 PE Bag中， 再放入Inner Box中。 10 MDL & 10 EPE Pad & 10 Bag/1 Inner Box</p>	<p>将1 EPS Cover 扣合在产品上方。 1 EPS Cover/Inner Box</p>
 <p>Step 1</p>	 <p>Step 2</p>	 <p>Step 3</p>
<p>采用“H”形封箱方式，对Box进行封箱， 并在Box的Mark处粘贴相应标签。 10 MDL/Inner Box</p>	<p>按“田”字型对Inner Box进行码拍，按照 3x3x2码拍。 18 Inner Box/Outer Box</p>	<p>扣合Outer Box及Top Cover，“井”字形 打包，并粘贴Pallet标签。 1 Outer Box & Top Cover/Pallet， 180 MDL/Pallet</p>
 <p>Step 4</p>	 <p>Step 5</p>	 <p>Step 6</p>

Packing Note:


- Box Dimension : 365mm (L) × 340mm (W) × 450mm (H)
- Package Quantity : 10pcs MDL/Box , 18pcs Box /Pallet , 180pcs MDL/Pallet ,
- Package Weight : 10kg/Box , 202kg/Pallet.

SPEC. NUMBER S801-5127	SPEC TITLE PT150X0M-N10 Product Specification	PAGE 23 OF 25
---------------------------	---	------------------

BOE	PRODUCT GROUP	REV	ISSUE DATE
	TFT LCD PRODUCT	0	2019.02.18

13.0 MECHANICAL OUTLINE DIMENSION


Figure 5. TFT-LCD Module Outline Dimension (Front View)




SPEC. NUMBER S801-5127	SPEC TITLE PT150X0M-N10 Product Specification	PAGE 24 OF 25
---------------------------	--	------------------

BOE	PRODUCT GROUP	REV	ISSUE DATE
	TFT LCD PRODUCT	0	2019.02.18

Figure 6. TFT-LCD Module Outline Dimensions (Rear view)



APP. : LVDS &BLU Cable Lead Direction



SPEC. NUMBER S801-5127	SPEC TITLE PT150X0M-N10 Product Specification	PAGE 25 OF 25
---------------------------	---	------------------