



PROPRIETARY NOTE

THIS SPECIFICATION IS THE PROPERTY OF BOE BJ AND SHALL NOT BE REPRODUCED OR COPIED WITHOUT THE WRITTEN PERMISSION OF BOE BJ AND MUST BE RETURNED TO BOE BJ UPON ITS REQUEST

SPEC. NUMBER

PRODUCT GROUP

Rev.

ISSUE DATE

PAGE

TFT-LCD

P1

2016.09.19

1 OF 34

NV126A1M-N51

Preliminary Product Specification

Rev. P1

HEFEI BOE OPTOELECTRONICS TECHNOLOGY CO.,LTD

BOE	PRODUCT GROUP	REV	ISSUE DATE
	TFT- LCD PRODUCT	P1	2016.09.19
SPEC. NUMBER	SPEC. TITLE NV126A1M-N51 Preliminary Product Specification		PAGE 3 OF 34

Contents


No.	Items	Page
	REVISION HISTORY	2
	CONTENTS	3
1.0	General Description	4
2.0	Absolute Maximum ratings	6
3.0	Electrical specifications.	7
4.0	Optical specifications.	10
5.0	Interface Connection	15
6.0	Signal Timing Specification	18
7.0	Input Signals, Display Colors & Gray Scale of Colors	20
8.0	Power Sequence	21
9.0	Connector description	22
10.0	Mechanical Characteristics	23
11.0	Reliability Test	24
12.0	Handling & Cautions.	24
13.0	Label	25
14.0	Packing information	27
15.0	Mechanical Outline Dimension	28
16.0	EDID Table	30

BOE	PRODUCT GROUP	REV	ISSUE DATE
	TFT- LCD PRODUCT	P1	2016.09.19
SPEC. NUMBER	SPEC. TITLE NV126A1M-N51 Preliminary Product Specification	PAGE 4 OF 34	

1.0 GENERAL DESCRIPTION

1.1 Introduction

NV126A1M-N51 is a color active matrix TFT LCD module using amorphous silicon TFT's (Thin Film Transistors) as an active switching devices. This module has a 12.6 inch diagonally measured active area with A1M resolutions (2880 horizontal by 1920 vertical pixel array). Each pixel is divided into RED, GREEN, BLUE dots which are arranged in vertical Stripe and this module can display 16.7M colors. The TFT-LCD panel used for this module is a higher color type. Therefore, this module is suitable for Notebook PC. The LED Driver for back-light driving is built in this model. All input signals are eDP1.3 interface compatible.



1.2 Features

- 4 lane eDP1.3 Interface with 5.4Gbps Link Rates
- Thin and light weight
- True 8bit, display 16.7M colors
- Single LED Lighting Bar. (Down side/Horizontal Direction)
- Thin Mounting frame
- Green Product (RoHS & Halogen free product)
- On board LED Driving circuit
- Low driving voltage and low power consumption
- On board EDID chip

BOE	PRODUCT GROUP	REV	ISSUE DATE
	TFT- LCD PRODUCT	P1	2016.09.19
SPEC. NUMBER	SPEC. TITLE NV126A1M-N51 Preliminary Product Specification	PAGE 5 OF 34	

1.3 Application

- Notebook PC (Wide type)

1.4 General Specification

The followings are general specifications at the model NV126A1M-N51. (listed in Table 1.)

<Table 1. General Specifications>

Parameter	Specification	Unit	Remarks
Active area	266.112(H) × 177.408(V)	mm	
Number of pixels	2880(H) × 1920(V)	pixels	
Pixel pitch	0.0924(H) × 0.0924(V)	mm	
Pixel arrangement	RGB Vertical stripe		
Display colors	16.7M	Colors	
Display mode	Normally Black (HADS)		
Outline dimension	271.71(H) × 190.56(V)	Mm	
Weight	161(max)	G	
Surface treatment	Hard Coating		
Back-light	Lower Down side, 1-LED Lighting Bar type		Note 1
Power consumption	P _D : 1.50(max)	W	@mosaic
	P _{BL} : 3.44(max)	W	with driver
	P _{total} : 4.94(max)	W	

Notes : 1. LED Lighting Bar (48*LED Array)

BOE	PRODUCT GROUP	REV	ISSUE DATE
	TFT- LCD PRODUCT	P1	2016.09.19
SPEC. NUMBER	SPEC. TITLE NV126A1M-N51 Preliminary Product Specification	PAGE 6 OF 34	

2.0 ABSOLUTE MAXIMUM RATINGS


The followings are maximum values which, if exceed, may cause faulty operation or damage to the unit. The operational and non-operational maximum voltage and current values are listed in Table 2.

< Table 2. Absolute Maximum Ratings >

Ta=25+/-2°C

Parameter	Symbol	Min.	Max.	Unit	Remarks
Power Supply Voltage	V _{DD}	-0.3	4.0	V	Note 1
Logic Supply Voltage	V _{IN}	V _{SS} -0.3	V _{DD} +0.3	V	
Operating Temperature	T _{OP}	0	+50	°C	Note 2
Storage Temperature	T _{ST}	-20	+60	°C	

- Notes : 1. Permanent damage to the device may occur if maximum values are exceeded functional operation should be restricted to the condition described under normal operating conditions.
2. Temperature and relative humidity range are shown in the figure below.
95 % RH Max. (40 °C ≥ Ta)
Maximum wet - bulb temperature at 39 °C or less. (Ta > 40 °C) No condensation.



BOE	PRODUCT GROUP	REV	ISSUE DATE
	TFT- LCD PRODUCT	P1	2016.09.19
SPEC. NUMBER	SPEC. TITLE NV126A1M-N51 Preliminary Product Specification		PAGE 7 OF 34

3.0 ELECTRICAL SPECIFICATIONS

3.1 Electrical Specifications

< Table 3. Electrical specifications >

Ta=25+/-2°C

Parameter		Min.	Typ.	Max.	Unit	Remarks
Power Supply Voltage	V _{DD}	3.0	3.3	3.6	V	Note 1
Permissible Input Ripple Voltage	V _{RF}	-	-	100	mV	At V _{DD} = 3.3V
Power Supply Current	I _{DD}	-	TBD	-	mA	Note 1
Differential Input Voltage	V _{ID}	100	200	-	mV	-
Power Consumption	P _D	-	-	1.5	W	Note 1
	P _{BL}	-	-	3.44	W	Note 2
	P _{total}	-	-	4.94	W	-

- Notes : 1. The supply voltage is measured and specified at the interface connector of LCM.
The current draw and power consumption specified is for 3.3V at 25°C.
2. Calculated value for reference (V_{LED} × I_{LED} / Efficiency)
3. Mosaic Pattern: 1.5(W) Max

BOE	PRODUCT GROUP	REV	ISSUE DATE
	TFT- LCD PRODUCT	P1	2016.09.19
SPEC. NUMBER	SPEC. TITLE NV126A1M-N51 Preliminary Product Specification	PAGE 8 OF 34	

3.2 Backlight Unit

< Table 4. LED Driving guideline specifications >

Ta=25+/-2°C

Parameter		Min.	Typ.	Max.	Unit	Remarks	
LED Forward Voltage		V _F	-	2.86	3.0	V	-
LED Forward Current		I _F	-	20	21	mA	-
LED Power Consumption		P _{LED}	-	-	3.44	W	Note 1
LED Life-Time		N/A	15,000	-	-	Hour	I _F = 20mA
Power supply voltage for LED Driver		V _{LED}	4.2	-	24	V	-
EN Control Level	Backlight on	-	2	-	-	V	-
	Backlight off	-	-	-	0.8	V	-
PWM Control Level	PWM High Level	-	1.5	-	-	V	-
	PWM Low Level	-	-	-	0.6	V	-
PWM Control Frequency		F _{PWM}	200	-	25,000	Hz	-
Duty Ratio		-	1	-	100	%	Note3

Notes : 1. Power supply voltage 24V for LED Driver


Calculator Value for reference $I_F \times V_F \times 48 / \text{efficiency} = P_{LED}$

2. The LED Life-time define as the estimated time to 50% degradation of initial luminous.

3. 1% duty cycle is achievable for the frequency range from 200Hz to 1KHz.

BOE	PRODUCT GROUP	REV	ISSUE DATE
	TFT- LCD PRODUCT	P1	2016.09.19
SPEC. NUMBER	SPEC. TITLE NV126A1M-N51 Preliminary Product Specification		PAGE 9 OF 34

3.3 LED structure



BOE	PRODUCT GROUP		REV	ISSUE DATE
	TFT- LCD PRODUCT		P1	2016.09.19
SPEC. NUMBER	SPEC. TITLE NV126A1M-N51 Preliminary Product Specification			PAGE 10 OF 34

4.0 OPTICAL SPECIFICATION

4.1 Overview

The test of Optical specifications shall be measured in a dark room (ambient luminance ≤ 1 lux and temperature = $25 \pm 2^\circ\text{C}$) with the equipment of Luminance meter system (Goniometer system and TOPCON BM-5) and test unit shall be located at an approximate distance 50cm from the LCD surface at a viewing angle of θ and Φ equal to 0° . We refer to $\theta\Phi=0$ ($=\theta_3$) as the 3 o'clock direction (the "right"), $\theta\Phi=90$ ($=\theta_{12}$) as the 12 o'clock direction ("upward"), $\theta\Phi=180$ ($=\theta_9$) as the 9 o'clock direction ("left") and $\theta\Phi=270$ ($=\theta_6$) as the 6 o'clock direction ("bottom"). While scanning θ and/or Φ , the center of the measuring spot on the Display surface shall stay fixed. The backlight should be operating for 30 minutes prior to measurement. VDD shall be $3.3 \pm 0.3\text{V}$ at 25°C . Optimum viewing angle direction is 6 'clock.

4.2 Optical Specifications

<Table 5. Optical Specifications>

Parameter		Symbol	Condition	Min.	Typ.	Max.	Unit	Remark
Viewing Angle range	Horizontal	Θ_3	CR > 10	80	85	-	Deg.	Note 1
		Θ_9		80	85	-	Deg.	
	Vertical	Θ_{12}		80	85	-	Deg.	
		Θ_6		80	85	-	Deg.	
Luminance Contrast ratio		CR	$\Theta = 0^\circ$	700	1000	-	-	Note 2
Luminance of White	Center Point	Y_w	$\Theta = 0^\circ$ I _{LED} = 20mA	272	320	-	cd/m ²	Note 3
White Luminance uniformity	5 Points	ΔY_5		80%	85%	-	-	Note 4
	13 Points	ΔY_{13}		67%	72%	-	-	
White Chromaticity		x_w	$\Theta = 0^\circ$	-0.03	0.305	0.03	-	Note 5
		y_w			0.320		-	
Reproduction of color	Red	x_R	$\Theta = 0^\circ$	-0.03	0.667	+0.03	-	-
		y_R			0.322		-	
	Green	x_G			0.273		-	
		y_G			0.655		-	
	Blue	x_B			0.146		-	
		y_B			0.070		-	
					Gamut		-	
Response Time (Rising + Falling)		T _{RT}	Ta= 25° C $\Theta = 0^\circ$	-	25	30	ms	Note 6
Cross Talk		CT	$\Theta = 0^\circ$	-	-	2.0	%	Note 7

10

BOE	PRODUCT GROUP	REV	ISSUE DATE
	TFT- LCD PRODUCT	P1	2016.09.19
SPEC. NUMBER	SPEC. TITLE NV126A1M-N51 Preliminary Product Specification		PAGE 11 OF 34

Notes :

1. Viewing angle is the angle at which the contrast ratio is greater than 10. The viewing angles are determined for the horizontal or 3, 9 o'clock direction and the vertical or 6, 12 o'clock direction with respect to the optical axis which is normal to the LCD surface (see FIGURE 1).

2. Contrast measurements shall be made at viewing angle of $\Theta = 0$ and at the center of the LCD surface. Luminance shall be measured with all pixels in the view field set first to white, then to the dark (black) state .

(see FIGURE 1) Luminance Contrast Ratio (CR) is defined mathematically.

$$CR = \frac{\text{Luminance when displaying a white raster}}{\text{Luminance when displaying a black raster}}$$

3. Center Luminance of white pattern on the LCD surface. Luminance shall be measured with all pixels in the view field set first to white. This measurement shall be taken at the locations shown in active area center point.

4. TThe White luminance uniformity on LCD surface is then expressed as : $\Delta Y = \text{Minimum Luminance of 5(or 13) points} / \text{Maximum Luminance of 5(or 13) points}$.
(see FIGURE 2 and FIGURE 3).

5. The color chromaticity coordinates specified in Table 5 shall be calculated from the spectral data measured with all pixels first in red, green, blue and white. Measurements shall be made at the center of the panel.

6. The electro-optical response time measurements shall be made as FIGURE 4 by switching the "data" input signal ON and OFF. The times needed for the luminance to change from 10% to 90% is T_r , and 90% to 10% is T_d .

7. Cross-Talk of one area of the LCD surface by another shall be measured by comparing the luminance (Y_A) of a 25mm diameter area, with all display pixels set to a gray level, to the luminance (Y_B) of that same area when any adjacent area is driven dark.
(See FIGURE 5).

BOE	PRODUCT GROUP	REV	ISSUE DATE
	TFT- LCD PRODUCT	P1	2016.09.19
SPEC. NUMBER	SPEC. TITLE NV126A1M-N51 Preliminary Product Specification	PAGE 12 OF 34	

4.3 Optical measurements

Figure 1. Measurement Set Up






Figure 2. Uniformity Measurement Locations (5 points)




BOE	PRODUCT GROUP	REV	ISSUE DATE
	TFT- LCD PRODUCT	P1	2016.09.19
SPEC. NUMBER	SPEC. TITLE NV126A1M-N51 Preliminary Product Specification	PAGE 13 OF 34	

Figure 3. Uniformity Measurement Locations (13 points)



The White luminance uniformity on LCD surface is then expressed as : ΔY_5 = Minimum Luminance of five points / Maximum Luminance of five points (see FIGURE 2) , ΔY_{13} = Minimum Luminance of 13 points /Maximum Luminance of 13 points (see FIGURE 3).


Figure 4. Response Time Testing



The electro-optical response time measurements shall be made as shown in FIGURE 4 by switching the “data” input signal ON and OFF. The times needed for the luminance to change from 10% to 90% is T_r and 90% to 10% is T_f .

BOE	PRODUCT GROUP	REV	ISSUE DATE
	TFT- LCD PRODUCT	P1	2016.09.19
SPEC. NUMBER	SPEC. TITLE NV126A1M-N51 Preliminary Product Specification	PAGE 14 OF 34	

Figure 5. Cross Modulation Test Description



$$\text{Cross-Talk (\%)} = \left| \frac{Y_B - Y_A}{Y_A} \right| \times 100$$

Where:
Y_A = Initial luminance of measured area (cd/m²)
Y_B = Subsequent luminance of measured area (cd/m²)
The location measured will be exactly the same in both patterns

Cross-Talk of one area of the LCD surface by another shall be measured by comparing the luminance (YA) of a 25mm diameter area, with all display pixels set to a gray level, to the luminance (YB) of that same area when any adjacent area is driven dark (Refer to FIGURE 5).

BOE	PRODUCT GROUP	REV	ISSUE DATE
	TFT- LCD PRODUCT	P1	2016.09.19
SPEC. NUMBER	SPEC. TITLE NV126A1M-N51 Preliminary Product Specification		PAGE 15 OF 34

5.0 INTERFACE CONNECTION.

5.1 Electrical Interface Connection

The electronics interface connector is IPEX 20455-040E-66


The connector interface pin assignments are listed in Table 6.

<Table 6. Pin Assignments for the Interface Connector>

Terminal	Symbol	Functions	Terminal	Symbol	Functions
Pin No.	Symbol	Description	Pin No.	Symbol	Description
1	CABC	Content Adaptive Brightness Control function	21	LCD_VCC	Power Supply, 3.3V (typ.)
2	H_GND	Ground	22	LCD _ Self_Test	Panel self test enable
3	LANE3_N	eDP RX channel 3 negative	23	LCD_GND	LCD Ground
4	LANE3_P	eDP RX channel 3 positive	24	LCD_GND	LCD Ground
5	H_GND	Ground	25	LCD_GND	LCD Ground
6	LANE2_N	eDP RX channel 2 negative	26	LCD_GND	LCD Ground
7	LANE2_P	eDP RX channel 2 positive	27	HPD	Hot plug detect output
8	H_GND	Ground	28	BL_GND	LED Ground
9	LANE1_N	eDP RX channel 1 negative	29	BL_GND	LED Ground
10	LANE1_P	eDP RX channel 1 positive	30	BL_GND	LED Ground
11	H_GND	Ground	31	BL_GND	LED Ground
12	LANE0_N	eDP RX channel 0 negative	32	BL_ENABLE	LED enable pin(+3.3V Input)
13	LANE0_P	eDP RX channel 0 positive	33	BL_PWM	System PWM Signal Input
14	H_GND	Ground	34	SCL	For BOE Internal USE
15	AUX_CH_P	eDP AUX CH positive	35	SDA	For BOE Internal USE
16	AUX_CH_N	eDP AUX CH negative	36	BL_POWER	LED Power Supply 5V-21V
17	H_GND	Ground	37	BL_POWER	LED Power Supply 5V-21V
18	LCD_VCC	Power Supply, 3.3V (typ.)	38	BL_POWER	LED Power Supply 5V-21V
19	LCD_VCC	Power Supply, 3.3V (typ.)	39	BL_POWER	LED Power Supply 5V-21V
20	LCD_VCC	Power Supply, 3.3V (typ.)	40	NC	No Connection

BOE	PRODUCT GROUP	REV	ISSUE DATE
	TFT- LCD PRODUCT	P1	2016.09.19
SPEC. NUMBER	SPEC. TITLE NV126A1M-N51 Preliminary Product Specification		PAGE 16 OF 34


5-2. eDP Interface




Note. Transmitter : NT71394MBG or equivalent.
Transmitter is not contained in Module.

BOE	PRODUCT GROUP	REV	ISSUE DATE
	TFT- LCD PRODUCT	P1	2016.09.19
SPEC. NUMBER	SPEC. TITLE NV126A1M-N51 Preliminary Product Specification	PAGE 17 OF 34	

5.3.eDP Input signal



Main Link V_{ID} and V_{IC} definition



AUX CH V_{ID_AUX} and V_{IC_AUX} definition

BOE	PRODUCT GROUP	REV	ISSUE DATE
	TFT- LCD PRODUCT	P1	2016.09.19
SPEC. NUMBER	SPEC. TITLE NV126A1M-N51 Preliminary Product Specification		PAGE 18 OF 34

5.4 Back-light & LCM Interface Connection

Interface Connector : STM MSK24022P10D

<Table 7. Pin Assignments for the BLU & LCM Connector>


Pin No.	Symbol	Description	Pin No.	Symbol	Description
1	GND	Ground	6	FB5	LED cathode connection
2	FB1	LED cathode connection	7	FB6	LED cathode connection
3	FB2	LED cathode connection	8	NC	NC
4	FB3	LED cathode connection	9	Vout	LED anode connection
5	FB4	LED cathode connection	10	Vout	LED anode connection

BOE	PRODUCT GROUP	REV	ISSUE DATE
	TFT- LCD PRODUCT	P1	2016.09.19
SPEC. NUMBER	SPEC. TITLE NV126A1M-N51 Preliminary Product Specification	PAGE 19 OF 34	

6.0 SIGNAL TIMING SPECIFICATION

6.1 The NV126A1M-N51 is operated by the DE only.

ITEM	Symbol		Min	Typ	Max	Unit	Note
CLK	Period	t_{CLK}	-	2.77	-	ns	
	Frequency	-	-	353.86	-	Mbps	
Hsync	Period	t_{HP}	-	3040	-	t_{CLK}	
	Frequency	f_H	-	182.4	-	KHz	
Vsync	Period	t_{VP}	-	1940	-	t_{HP}	
	Frequency	f_V	-	116.4	-	Hz	
Horizontal Active Display Term	Valid	t_{HV}	-	2880	-	t_{CLK}	
	Total	t_{HP}	-	3040	-	t_{CLK}	
Vertical Active Display Term	Valid	t_{VV}	-	1920	-	t_{HP}	
	Total	t_{VP}	-	1940	-	t_{HP}	




BOE	PRODUCT GROUP	REV	ISSUE DATE
	TFT- LCD PRODUCT	P1	2016.09.19
SPEC. NUMBER	SPEC. TITLE NV126A1M-N51 Preliminary Product Specification	PAGE 20 OF 34	

6.2 eDP Rx Interface Timing Parameter

The specification of the eDP Rx interface timing parameter is shown in Table 8.

<Table 8. eDP Rx Interface Timing Specification>

Item	Symbol	Min	Typ	Max	Unit	Remark
Differential peak-to-peak input voltage at package pins	VRX-DIFFp-p	120	-	-	mV	
Rx input DC common mode Voltage	VRX_DC_CM	0	-	2.0	V	
Differential termination resistance	RRX-DIFF		100		Ω	
Rx short circuit current limit	IRX_SHORT			50	mA	
Intra-pair skew at Rx package pins (HBR) RX intra-pair skew tolerance at HBR	LRX_SKEW_INTRA_PAIR	-	-	60	ps	



BOE	PRODUCT GROUP	REV	ISSUE DATE
	TFT- LCD PRODUCT	P1	2016.09.19
SPEC. NUMBER	SPEC. TITLE NV126A1M-N51 Preliminary Product Specification	PAGE 21 OF 34	


7.0 INPUT SIGNALS, BASIC DISPLAY COLORS & GRAY SCALE OF COLORS

Color & Gray Scale		RED DATA								GREEN DATA								BLUE DATA							
		R7	R6	R5	R4	R3	R2	R1	R0	G7	G6	G5	G4	G3	G2	G1	G0	B7	B6	B5	B4	B3	B2	B1	B0
Basic Colors	Black	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
	Blue	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	1	1	1	1	1	1	1	1
	Green	0	0	0	0	0	0	0	0	1	1	1	1	1	1	1	1	0	0	0	0	0	0	0	0
	Cyan	0	0	0	0	0	0	0	0	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1
	Red	1	1	1	1	1	1	1	1	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
	Magenta	1	1	1	1	1	1	1	1	0	0	0	0	0	0	0	0	1	1	1	1	1	1	1	1
	Yellow	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	0	0	0	0	0	0	0	0
	White	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1
Gray Scale of RED	Black	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
	△	0	0	0	0	0	0	0	1	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
	Darker	0	0	0	0	0	0	1	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
	△	↑								↑								↑							
	▽	↓								↓								↓							
	Brighter	1	1	1	1	1	1	0	1	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
	▽	1	1	1	1	1	1	1	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
	Red	1	1	1	1	1	1	1	1	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
Gray Scale of GREEN	Black	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
	△	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	1	0	0	0	0	0	0	0	0
	Darker	0	0	0	0	0	0	0	0	0	0	0	0	0	0	1	0	0	0	0	0	0	0	0	0
	△	↑								↑								↑							
	▽	↓								↓								↓							
	Brighter	0	0	0	0	0	0	0	0	1	1	1	1	1	1	0	1	0	0	0	0	0	0	0	0
	▽	0	0	0	0	0	0	0	0	1	1	1	1	1	1	0	0	0	0	0	0	0	0	0	0
	Green	0	0	0	0	0	0	0	0	1	1	1	1	1	1	1	1	0	0	0	0	0	0	0	0
Gray Scale of BLUE	Black	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
	△	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	1
	Darker	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	1	0
	△	↑								↑								↑							
	▽	↓								↓								↓							
	Brighter	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	1	1	1	1	1	1	0	1
	▽	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	1	1	1	1	1	1	1	0
	Blue	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	1	1	1	1	1	1	1	1
Gray Scale of WHITE	Black	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
	△	0	0	0	0	0	0	0	1	0	0	0	0	0	0	0	1	0	0	0	0	0	0	0	1
	Darker	0	0	0	0	0	0	1	0	0	0	0	0	0	0	1	0	0	0	0	0	0	0	1	0
	△	↑								↑								↑							
	▽	↓								↓								↓							
	Brighter	1	1	1	1	1	1	0	1	1	1	1	1	1	1	0	1	1	1	1	1	1	1	0	1
	▽	1	1	1	1	1	1	1	0	1	1	1	1	1	1	0	1	1	1	1	1	1	1	1	0
	White	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1

BOE	PRODUCT GROUP	REV	ISSUE DATE
	TFT- LCD PRODUCT	P1	2016.09.19
SPEC. NUMBER	SPEC. TITLE NV126A1M-N51 Preliminary Product Specification	PAGE 22 OF 34	

8.0 POWER SEQUENCE

To prevent a latch-up or DC operation of the LCD module, the power on/off sequence shall be as shown in below



- 0.5ms ≤ T1 ≤ 10 ms
 - 0ms ≤ T2 ≤ 200 ms
 - 0ms ≤ T3 ≤ 200 ms
 - 0ms ≤ T13
 - 0ms ≤ T14
 - 0ms ≤ T17
- 0ms ≤ T7 ≤ 50ms
 - 200ms ≤ T8
 - 0ms ≤ T10 ≤ 500 ms
 - 0 ms ≤ T11 ≤ 10 ms
 - 150ms ≤ T12
 - 0ms ≤ T15
 - 0ms ≤ T16
 - 0ms ≤ T18
- Notes:

- When the power supply VDD is 0V, keep the level of input signals on the low or keep high impedance.
- Do not keep the interface signal high impedance when power is on. Back Light must be turn on after power for logic and interface signal are valid.

BOE	PRODUCT GROUP	REV	ISSUE DATE
	TFT- LCD PRODUCT	P1	2016.09.19
SPEC. NUMBER	SPEC. TITLE NV126A1M-N51 Preliminary Product Specification		PAGE 23 OF 34

9.0 Connector Description

Physical interface is described as for the connector on LCM.

These connectors are capable of accommodating the following signals and will be following components.

9.1 TFT LCD Module

Connector Name /Description	For Signal Connector
Manufacturer	IPEX
Type/ Part Number	20455-040E-66 or Compatible
Mating housing/ Part Number	or Compatible

BOE	PRODUCT GROUP	REV	ISSUE DATE
	TFT- LCD PRODUCT	P1	2016.09.19
SPEC. NUMBER	SPEC. TITLE NV126A1M-N51 Preliminary Product Specification	PAGE 24 OF 34	

10.0 MECHANICAL CHARACTERISTICS

10.1 Dimensional Requirements

FIGURE 6 shows mechanical outlines for the model NV126A1M-N51.
Other parameters are shown in Table 9.

<Table 9. Dimensional Parameters>

Parameter	Specification	Unit
Active Area	266.112(H) × 177.408(V)	
Number of pixels	2880(H) × 1920(V)	
Pixel pitch	0.0924(H) × 0.0924(V)	
Pixel arrangement	RGB Vertical stripe	
Display colors	16.7M	
Display mode	HADS	
Dimensional outline	271.71(H) × 190.56(V)	mm
Weight	161 Max	gram
Back Light	Connector :STM MSK24022P10D	
	6P*8S	

10.2 Mounting

See FIGURE 6.

10.3 Glare and Polarizer Hardness.

The surface of the LCD has a glare coating to maximize readability and hard coating to reduce scratching.

10.4 Light Leakage

There shall not be visible light from the back-lighting system around the edges of the screen as seen from a distance 50cm from the screen with an overhead light level of 350lux.

BOE	PRODUCT GROUP	REV	ISSUE DATE
	TFT- LCD PRODUCT	P1	2016.09.19
SPEC. NUMBER	SPEC. TITLE NV126A1M-N51 Preliminary Product Specification	PAGE 25 OF 34	

11.0 RELIABILITY TEST

The Reliability test items and its conditions are shown in below.

<Table 10. Reliability test>

No	Test Items	Conditions
1	High temperature storage test	Ta = 60 °C , 240 hrs
2	Low temperature storage test	Ta = -20 °C , 240 hrs
3	High temperature & high humidity operation test	Ta = 50 °C , 80%RH, 240 hrs
4	High temperature operation test	Ta = 50 °C , 240 hrs
5	Low temperature operation test	Ta = 0 °C , 240 hrs
6	Thermal shock	Ta = -20 °C ↔ 60 °C (0.5 hr), 100 cycle
7	Vibration test (non-operating)	1.5G, 10~500Hz, Half Sine X,Y,Z / Sweep rate : 1 hour
8	Shock test (non-operating)	220G, Half Sine Wave 2msec ± X, ± Y, ± Z Once for each direction
9	Electro-static discharge test (non-operating)	Air : 150 pF, 330Ω, 15 KV Contact : 150 pF, 330Ω, 8 KV

12.0 HANDLING & CAUTIONS

(1) Cautions when taking out the module

- Pick the pouch only, when taking out module from a shipping package.

(2) Cautions for handling the module

- As the electrostatic discharges may break the LCD module, handle the LCD module with care. Peel a protection sheet off from the LCD panel surface as slowly as possible.
- As the LCD panel and back - light element are made from fragile glass material, impulse and pressure to the LCD module should be avoided.
- As the surface of the polarizer is very soft and easily scratched, use a soft dry cloth without chemicals for cleaning.
- Do not pull the interface connector in or out while the LCD module is operating.
- Put the module display side down on a flat horizontal plane.
- Handle connectors and cables with care.

(3) Cautions for the operation

- When the module is operating, do not lose CLK, ENAB signals. If any one of these signals is lost, the LCD panel would be damaged.
- Obey the supply voltage sequence. If wrong sequence is applied, the module would be damaged.

BOE	PRODUCT GROUP	REV	ISSUE DATE
	TFT- LCD PRODUCT	P1	2016.09.19
SPEC. NUMBER	SPEC. TITLE NV126A1M-N51 Preliminary Product Specification	PAGE 26 OF 34	
<p>(4) Cautions for the atmosphere</p> <ul style="list-style-type: none">• Dew drop atmosphere should be avoided.• Do not store and/or operate the LCD module in a high temperature and/or humidity atmosphere. Storage in an electro-conductive polymer packing pouch and under relatively low temperature atmosphere is recommended. <p>(5) Cautions for the module characteristics</p> <ul style="list-style-type: none">• Do not apply fixed pattern data signal to the LCD module at product aging.• Applying fixed pattern for a long time may cause image sticking. <p>(6) Other cautions</p> <ul style="list-style-type: none">• Do not disassemble and/or re-assemble LCD module.• Do not re-adjust variable resistor or switch etc.• When returning the module for repair or etc., Please pack the module not to be broken. We recommend to use the original shipping packages.			

26

BOE	PRODUCT GROUP	REV	ISSUE DATE
	TFT- LCD PRODUCT	P1	2016.09.19
SPEC. NUMBER	SPEC. TITLE NV126A1M-N51 Preliminary Product Specification	PAGE 27 OF 34	

13.0 LABEL

(1) MDL ID





NV126A1M-N51 V3.1



XXXXXXXXXXXXXXXXXXXX

<1>

<2>

<3>

序列号	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17
代码	X	X	P	3	1	5	A	X	X	X	X	0	0	1	E	E	J
描述	GBN 代码		等级	B 3	年份		月	FG Code后四位					序列号				

(2) Box ID


BOE BOE Technology Group Co., Ltd.

MODEL: NV126A1M-N51 ①

QTY: XX ②


SERIAL NO: XXXXXXXXXXXX ③

DATE: 20XX / XX / XX ④



18010-12600100 ⑥

XXXX ⑤



- 蓝色字体为后打印标识,
Label Size: 115mm*55mm
1. FG-CODE
2. Box 产品数量
3. Box ID, 编码规则如下
4. Box Packing 日期
5. FG-CODE 后四位


序列号	1	2	3	4	5	6	7	8	9	10	11	12	13
代码	X	X	P	3	1	2	7	0	0	0	1	H	D
描述	GBN代码		等级	B3	年份		月	Rev	序列号				

BOE	PRODUCT GROUP	REV	ISSUE DATE
	TFT- LCD PRODUCT	P1	2016.09.19
SPEC. NUMBER	SPEC. TITLE NV126A1M-N51 Preliminary Product Specification	PAGE 28 OF 34	

14.0 PACKING INFORMATION

14.1 Packing order

2ea Panel per Tray




4layers per Pallet, 4 inner boxes per layer

Pallet outer package : Protective film & Paper Corner

640pcs Panels per Pallet

2EA Cushion -EPE Board per Inner Box
40pcs MDL per Inner Box




14.2 Notes

- Box Dimension: 510mm × 410mm × 250mm
- Package Quantity in one Box: 40pcs

BOE	PRODUCT GROUP	REV	ISSUE DATE
	TFT- LCD PRODUCT	P1	2016.09.19
SPEC. NUMBER	SPEC. TITLE NV126A1M-N51 Preliminary Product Specification	PAGE 29 OF 34	


15.0 MECHANICAL OUTLINE DIMENSION

Figure 6. TFT-LCD Module Outline Dimension (Front View)



BOE	PRODUCT GROUP	REV	ISSUE DATE
	TFT- LCD PRODUCT	P1	2016.09.19
SPEC. NUMBER	SPEC. TITLE NV126A1M-N51 Preliminary Product Specification	PAGE 30 OF 34	

Figure 7. TFT-LCD Module Outline Dimensions (Rear view)



BOE	PRODUCT GROUP	REV	ISSUE DATE
	TFT- LCD PRODUCT	P1	2016.09.19
SPEC. NUMBER	SPEC. TITLE NV126A1M-N51 Preliminary Product Specification		PAGE 31 OF 34

16.0 EDID Table

Address (HEX)	Function	Hex	Dec	crc	Input values.	Notes
00	Header	00	0		0	EDID Header
01		FF	255		255	
02		FF	255		255	
03		FF	255		255	
04		FF	255		255	
05		FF	255		255	
06		FF	255		255	
07		00	0		0	
08	ID Manufacturer Name	09	9		BOE	ID = BOE
09		E5	229			
0A	ID Product Code	AC	172		1708	ID = 1708
0B		06	6			
0C	32-bit serial No.	00	0			
0D		00	0			
0E		00	0			
0F		00	0			
10	Week of manufacture	01	1		1	
11	Year of Manufacture	19	25		2015	Manufactured in 2015
12	EDID Structure Ver.	01	1		1	EDID Ver 1.0
13	EDID revision #	04	4		4	EDID Rev. 0.4
14	Video input definition	A5	165		-	
15	Max H image size	1A	26		27	26.6 cm (Approx)
16	Max V image size	11	17		18	17.7 cm (Approx)
17	Display Gamma	78	120		2.2	Gamma curve = 2.2
18	Feature support	2	2			RGB display, Preferred Timming mode
19	Red/Green low bits	99	153		-	Red / Green Low Bits
1A	Blue/White low bits	23	35		-	Blue / White Low Bits

BOE	PRODUCT GROUP	REV	ISSUE DATE
	TFT- LCD PRODUCT	P1	2016.09.19
SPEC. NUMBER	SPEC. TITLE NV126A1M-N51 Preliminary Product Specification	PAGE 32 OF 34	

Address (HEX)	Function	Hex	Dec	crc	Input values.	Notes
1B	Red x high bits	A7	167	670	0.655	Red (x) = 10100111 (0.655)
1C	Red y high bits	54	84	337	0.330	Red (y) = 01010100 (0.33)
1D	Green x high bits	47	71	286	0.280	Green (x) = 01000111 (0.28)
1E	Green y high bits	A1	161	645	0.630	Green (y) = 10100001 (0.63)
1F	Blue x high bits	25	37	148	0.145	Blue (x) = 00100101 (0.145)
20	Blue y high bits	10	16	66	0.065	Blue (y) = 00010000 (0.065)
21	White x high bits	4E	78	312	0.305	White (x) = 01001110 (0.305)
22	White y high bits	52	82	327	0.320	White (y) = 01010010 (0.32)
23	Established timing 1	00	0		-	
24	Established timing 2	00	0		-	
25	Established timing 3	00	0		-	
26	Standard timing #1	01	1			Not Used
27		01	1			
28	Standard timing #2	01	1			Not Used
29		01	1			
2A	Standard timing #3	01	1			Not Used
2B		01	1			
2C	Standard timing #4	01	1			Not Used
2D		01	1			
2E	Standard timing #5	01	1			Not Used
2F		01	1			
30	Standard timing #6	01	1			Not Used
31		01	1			
32	Standard timing #7	01	1			Not Used
33		01	1			
34	Standard timing #8	01	1			Not Used
35		01	1			

BOE	PRODUCT GROUP	REV	ISSUE DATE
	TFT- LCD PRODUCT	P1	2016.09.19
SPEC. NUMBER	SPEC. TITLE NV126A1M-N51 Preliminary Product Specification		PAGE 33 OF 34

Address (HEX)	Function	Hex	Dec	crc	Input values.	Notes
36	Detailed timing/monitor descriptor #1	3E	62		353.9	353.9MHz Main clock
37		8A	138			
38		40	64		2880	Hor Active = 2880
39		A0	160		160	Hor Blanking = 160
3A		B0	176		-	4 bits of Hor. Active + 4 bits of Hor. Blanking
3B		80	128		1920	Ver Active = 1920
3C		14	20		20	Ver Blanking = 20
3D		70	112		-	4 bits of Ver. Active + 4 bits of Ver. Blanking
3E		30	48		48	Hor Sync Offset = 48
3F		20	32		32	H Sync Pulse Width = 32
40		84	132		8	V sync Offset = 8 line
41		00	0		4	V Sync Pulse width : 4 line
42		0A	10		266	Horizontal Image Size = 266 mm (Low 8 bits)
43		B1	177		177	Vertical Image Size = 177 mm (Low 8 bits)
44		10	16		-	4 bits of Hor Image Size + 4 bits of Ver Image Size
45		00	0		0	Hor Border (pixels)
46		00	0		0	Vertical Border (Lines)
47		1A	26			Refer to right table
48	Detailed timing/monitor descriptor #2	26	38		235.9	235.9MHz Main clock
49		5C	92			
4A		40	64		2880	Hor Active = 2880
4B		A0	160		160	Hor Blanking = 160
4C		B0	176		-	4 bits of Hor. Active + 4 bits of Hor. Blanking
4D		80	128		1920	Ver Active = 1920
4E		14	20		20	Ver Blanking = 20
4F		70	112		-	4 bits of Ver. Active + 4 bits of Ver. Blanking
50		30	48		48	Hor Sync Offset = 48
51		20	32		32	H Sync Pulse Width = 32
52		84	132		8	V sync Offset = 8 line
53		00	0		4	V Sync Pulse width : 4 line
54		0A	10		266	Horizontal Image Size = 266 mm (Low 8 bits)
55		B1	177		177	Vertical Image Size = 177 mm (Low 8 bits)
56		10	16		-	4 bits of Hor Image Size + 4 bits of Ver Image Size
57		00	0		0	Hor Border (pixels)
58		00	0		0	Vertical Border (Lines)
59		1A	26			33

BOE	PRODUCT GROUP	REV	ISSUE DATE
	TFT- LCD PRODUCT	P1	2016.09.19
SPEC. NUMBER	SPEC. TITLE NV126A1M-N51 Preliminary Product Specification	PAGE 34 OF 34	

Address (HEX)	Function	Hex	Dec	crc	Input values.	Notes
5A	Detailed timing/monitor descriptor #3	00	0			ASCII Data Sting Tag
5B		00	0			
5C		00	0			
5D		FE	254			
5E		00	0			
5F		42	66		B	Manufacture name : BOEHF
60		4F	79		O	
61		45	69		E	
62		20	32			
63		48	72		H	
64		46	70		F	
65		0A	10			
66		20	32			
67		20	32			
68		20	32			
69		20	32			
6A		20	32			
6B		20	32			
6C	Detailed timing/monitor descriptor #4	00	0			Product Name Tag (ASCII)
6D		00	0			
6E		00	0			
6F		FE	254			
70		00	0			
71		4E	78		N	Model name : NV126A1M-N51
72		56	86		V	
73		31	49		1	
74		32	50		2	
75		36	54		6	
76		41	65		A	
77		31	49		1	
78		4D	77		M	
79		2D	45		-	
7A		4E	78		N	
7B		35	53		5	
7C		31	49		1	
7D		0A	10			
7E	Extension flag	00	0			
7F	Checksum	64	100	100	-	