Subject: Re: W4WG & Novell
From: cctr132@csc.canterbury.ac.nz (Nick FitzGerald PC Software Consultant, CSC, UoC, NZ)
Reply-To: Nick FitzGerald Csc.canterbury ac.nz
Organization: University of Canterbury, Christchury ac.nz
Nntp-Posting-Host Canterbury ac.nz
Lines: 27

In article <1rh2mi\$ea4@msuinfo.cl.msu.edu bilan@cps.msu.edu (Thomas J Bilan) writes:

> If I put LASTDRIVE = Z in my config.sys, NETX will run out I can't access
> drive f: to log in to Novell.
> If I don't put LASTDRIVE = Z in my config.sys I can't access other W4WG
> drives from the file-manager.
> It seems that the Spould be a way to make NETX withouthe LASTDRIVE =
> statement in my Systems and the way Netware in general (and

The problem is the LASTDRIVE command and the way NetWare in general (and in this case NETX in particular) adds drives to the device chain. Setting LASTDRIVE=Z means there are no "unassigned" (as opposed to "unused") drive letters for NetWare to use, as it tacks its drive mappings -onto the end- of the existing list of drives. W4WG obviously attaches its network drives to "existing, unused" drive letters.

I'd guess the next thing I'd try is something like LASTDRIVE=M, which on most machines will leave a fair swathe of drives for W4WG and still allow up to 13 NetWare drive mappings as well.