

Assignment 3

This assignment focuses on getting comfortable with working with multidimensional data and linear regression. Key items include:

- Creating random n-dimensional data
- Creating a Model that can handle the data
- Plot a subset of the data along with the prediction
- Using a Dataset to read in and choose certain columns to produce a model
- Create several models from various combinations of columns
- Plot a few of the results


```
In [1]: import numpy as np
import matplotlib.pyplot as plt
%matplotlib inline
```

1. Create a 4 dimensional data set with 64 elements and show all 4 scatter 2D plots of the data x_1 vs. y , x_2 vs. y , x_3 vs. y , x_4 vs. y

```
In [2]: n = 64
x = np.linspace(0, 1, n) + np.random.rand(4, n)
x = np.vstack([x, np.ones(len(x.T))]).T
y = np.linspace(0, 1, n) + np.random.rand(n) - 1
```


```
In [3]: plt.scatter(x.T[0], y)
```

```
Out[3]: <matplotlib.collections.PathCollection at 0x7f9a386854c0>
```




```
In [4]: plt.scatter(x.T[1], y)
```

```
Out[4]: <matplotlib.collections.PathCollection at 0x7f9a484d1af0>
```




```
In [5]: plt.scatter(x.T[2], y)
```

```
Out[5]: <matplotlib.collections.PathCollection at 0x7f9a6ab75610>
```



```
In [6]: plt.scatter(x.T[3], y)
```

```
Out[6]: <matplotlib.collections.PathCollection at 0x7f9a6ac87520>
```



2. Create a Linear Regression model (like we did in class) to fit the data. Use the example from Lesson 3 and do not use a library that calculates automatically. We are expecting 5 coefficients to describe the linear model.

After creating the model (finding the coefficients), create a new column $y_p = \sum \beta_n \cdot x_n$

```
In [7]: left = np.linalg.inv(np.dot(x.T, x))
```

```
In [8]: right = np.dot(y.T, x)
```

```
In [9]: beta = np.dot(left, right)
beta
```


```
Out[9]: array([ 0.19910577,  0.17422601,  0.1333519 ,  0.2471695 , -0.81746548])
```

```
In [10]: pred = np.dot(x, beta)
```

3. Plot the model's prediction as a different color on top of the scatter plot from Q1 in 2D for all 4 of the dimensions ($x_1 \rightarrow y_p, x_2 \rightarrow y_p, x_3 \rightarrow y_p, x_4 \rightarrow y_p$)


```
In [11]: plt.scatter(x.T[0], pred, c='red')
plt.scatter(x.T[0], y, c='b')
```

```
Out[11]: <matplotlib.collections.PathCollection at 0x7f9a48685310>
```




```
In [12]: plt.scatter(x.T[1], pred, c='red')
plt.scatter(x.T[1], y, c='b')
```

```
Out[12]: <matplotlib.collections.PathCollection at 0x7f9a486eeca0>
```




```
In [13]: plt.scatter(x.T[2], pred, c='red')
plt.scatter(x.T[2], y, c='b')
```

```
Out[13]: <matplotlib.collections.PathCollection at 0x7f9a48781b20>
```



```
In [14]: plt.scatter(x.T[3], pred, c='red')
plt.scatter(x.T[3], y, c='b')
```

```
Out[14]: <matplotlib.collections.PathCollection at 0x7f9a386bcee0>
```



4. Read in `m\l\n\data\Credit.csv` with Pandas and build a Linear Regression model to predict Credit Rating (Rating). Use only the numeric columns in your model, but feel free to

experiment which which columns you believe are better predictors of Credit Rating (Column Rating)

```
In [15]: import pandas as pd
credit = pd.read_csv('../data/Credit.csv', index_col=0)
credit.head()
```

```
Out[15]:
```

	Income	Limit	Rating	Cards	Age	Education	Gender	Student	Married	Ethnicity	Balance
1	14.891	3606	283	2	34	11	Male	No	Yes	Caucasian	333
2	106.025	6645	483	3	82	15	Female	Yes	Yes	Asian	903
3	104.593	7075	514	4	71	11	Male	No	No	Asian	580
4	148.924	9504	681	3	36	11	Female	No	No	Asian	964
5	55.882	4897	357	2	68	16	Male	No	Yes	Caucasian	331

Choose multiple columns as inputs beyond Income and Limit but clearly, don't use Rating

```
In [16]: columns = ['Income', 'Limit', 'Age', 'Education', 'Balance']
X = credit[columns].values

X = np.vstack([X.T, np.ones(len(X))]).T
X
```

```
Out[16]: array([[1.48910e+01, 3.60600e+03, 3.40000e+01, 1.10000e+01, 3.33000e+02,
1.00000e+00],
[1.06025e+02, 6.64500e+03, 8.20000e+01, 1.50000e+01, 9.03000e+02,
1.00000e+00],
[1.04593e+02, 7.07500e+03, 7.10000e+01, 1.10000e+01, 5.80000e+02,
1.00000e+00],
...,
[5.78720e+01, 4.17100e+03, 6.70000e+01, 1.20000e+01, 1.38000e+02,
1.00000e+00],
[3.77280e+01, 2.52500e+03, 4.40000e+01, 1.30000e+01, 0.00000e+00,
1.00000e+00],
[1.87010e+01, 5.52400e+03, 6.40000e+01, 7.00000e+00, 9.66000e+02,
1.00000e+00]])
```

```
In [17]: y = credit['Rating']
y
```

```
Out[17]: 1      283
2      483
3      514
4      681
5      357
...
396    307
397    296
398    321
399    192
400    415
Name: Rating, Length: 400, dtype: int64
```


```
In [18]: left_2 = np.linalg.inv(np.dot(X.T, X))
right_2 = np.dot(y.T, X)
```

```
beta_2 = np.dot(left_2, right_2)
pred_2 = np.dot(X, beta_2)
```

5. Plot your results using scatter plots (just like in class). Show as many of your columns vs. credit rating that you can.


```
In [19]: plt.scatter(X.T[0], y, c='b')
plt.scatter(X.T[0], pred_2, c='orange')
```

Out[19]: <matplotlib.collections.PathCollection at 0x7f9a6b43d6a0>




```
In [20]: plt.scatter(X.T[1], y, c='b')
plt.scatter(X.T[1], pred_2, c='orange')
```

Out[20]: <matplotlib.collections.PathCollection at 0x7f9a38d091c0>




```
In [21]: plt.scatter(X.T[2], y, c='b')
plt.scatter(X.T[2], pred_2, c='orange')
```

Out[21]: <matplotlib.collections.PathCollection at 0x7f9a38d68b50>



```
In [22]: plt.scatter(X.T[3], y, c='b')
plt.scatter(X.T[3], pred_2, c='orange')
```

Out[22]: <matplotlib.collections.PathCollection at 0x7f9a38d52940>



```
In [23]: plt.scatter(X.T[4], y, c='b')
plt.scatter(X.T[4], pred_2, c='orange')
```

Out[23]: <matplotlib.collections.PathCollection at 0x7f9a38e9eb80>

