IoT Product Design and Coding Bootcamp

Brian Rashap, Ph.D.

05-Oct-2020

IoT Fun

I THINK MY NEST SMOKE ALARM IS GOING OFF. GOOGLE ADWORDS JUST PITCHED ME A FIRE EXTINGUISHER AND AN OFFER FOR TEMPORARY HOUSING.
TOM FISH BURNE
© marketoonist.com

Brian Rashap, Ph.D.

- Proud husband of Krista and father of Shelby (22) and Ethan (18)
- Electrical Engineer with 25 years industrial experience
- High School track coach
- Hobbies: running, cycling, reading, spending time with family

Introductions

INTRODUCTIONS

Class Rules

- Respect Each Other, Help Each Other
- Ask Questions
- Be On Time (let us know via Slack if you won't be here)
- Keep Your Workspace and the Classroom Neat and Tidy
- If you are struggling, let me, Susan, or Esteban know. We are here to HELP!

Grading

Class assignments will total 1000 points. You will need to earn at least 750 total points and at least 225 points on your Capstone to graduate.

1. IoT assignments + Lab Notebooks: 300 pts
2. Fusion 360 assignments: 100 pts
3. Weekly quizzes: 100 pts
4. Midterm Projects: Smart Room Controller/Plant Watering System: 200 pts
5. Team Capstone Project: 300 pts

More information later today on how assignments are turned in

Credit for Prior Learning (CPL)

Approved for CPL	
CIS 1605	Internet of Things
CIS 1275	Introduction to C++
BCIS 1110	Fundamentals of Information Literacy and Systems
BUSA 1130	Business Professionalism
BUSA 1198	Project Management Fundamentals
CSIS 1151	Intro to Programming for Non-Majors of CS*

* CSIS 1151 credit requires appropriate math prerequisites

Under Review for CPL	
RPID 1005	3 Dimensional CAD
RPID 1010	Design and Simulation
RPID 1015	Prototype Fabrication I
RPID 1020	Prototype Fabrication II

Evolution of Industry

Components of Industry 4.0

IoT and Data Science

IoT 2025

Home
Chore automation and security
$200B–350B
Vehicles
Autonomous vehicles and condition-based maintenance
$210B–740B
Offices
Security and energy
$70B–150B
9 settings
gave us a cross-sector view of a total potential impact of
$3.9 trillion–11.1 trillion per year in 2025
Cities
Public health and transportation
$930B–1.7T
Factories
Operations and equipment optimization
$1.2T–3.7T
SHOP
Outside
Logistics and navigation
$560B–850B
Retail environments
Automated checkout
$410B–1.2T
Human
Health and fitness
$170B–1.6T
Worksites
Operations optimization/ health and safety
$160B–930B

Smart Facilities

Healthcare 2025

Smart World

Libelium Smart World
Air Pollution
Control of CO_2 emissions of factories, pollution emitted by cars and toxic gases generated in farms.
Forest Fire Detection
Monitoring of combustion gases and preemptive fire conditions to define alert zones.
Wine Quality Enhancing
Monitoring soil moisture and trunk diameter in vineyards to control the amount of sugar in grapes and grapevine health.
Offspring Care
Control of growing conditions of the offspring in animal farms to ensure its survival and health.
Sportsmen Care
Vital signs monitoring in high performance centers and fields.
Structural Health
Monitoring of vibrations and material conditions in buildings, bridges and historical monuments.
Quality of Shipment Conditions
Monitoring of vibrations, strokes, container openings or cold chain maintenance for insurance purposes.
Smartphones Detection
Detect iPhone and Android devices and in general any device which works with Wifi or Bluetooth interfaces.
Perimeter Access Control
Access control to restricted areas and detection of people in non-authorized areas.
Radiation Levels
Distributed measurement of radiation levels in nuclear power stations surroundings to generate leakage alerts.
Electromagnetic Levels
Measurement of the energy radiated by cell stations and WiFi routers.
Traffic Congestion
Monitoring of vehicles and pedestrian affluence to optimize driving and walking routes.
Smart Roads
Warning messages and diversions according to climate conditions and unexpected events like accidents or traffic jams.
Smart Lighting
Intelligent and weather adaptive lighting in street lights.
Intelligent Shopping
Getting advices in the point of sale according to customer habits, preferences, presence of allergic components for them or expiring dates.
Noise Urban Maps
Sound monitoring in bar areas and centric zones in real time.
Water Leakages
Detection of liquid presence outside tanks and pressure variations along pipes.
Vehicle Auto-diagnosis
Information collection from CanBus to send real time alarms to emergencies or provide advice to drivers.
Item Location
Search of individual items in big surfaces like warehouses or harbours.
Waste Management
Detection of rubbish levels in containers to optimize the trash collection routes.
Smart Parking
Monitoring of parking spaces availability in the city.
Water Quality
Study of water suitability in rivers and the sea for fauna and eligibility for drinkable use.
Golf Courses
Selective irrigation in dry zones to reduce the water resources required in the green.
libelium
www.libelium.com

And Out of This World

IoT Growth

Billions of Devices
50
40
30
20
10
0
1988
1992
1996
2000
2004
2008
2012
2016
2020
1992
1M
2003
0.5B
2009
IoT
Inception
2012
8.7B
2013
11.2B
2014
14.2B
2015
18.2B
2016
22.9B
2017
28.4B
2018
34.8B
2019
42.1B
2020
50.1B

Let's Begin Our Journey

Computer Languages

Mother Tongues

Tracing the roots of computer languages through the ages

Just like half of the world's spoken tongues, most of the 2,300-plus computer programming languages are either endangered or extinct. As powerhouses C/C++, Visual Basic, Cobol, Java and other modern source codes dominate our systems, hundreds of older languages are running out of life.

An ad hoc collection of engineers-electronic lexicographers, if you will-aim to save, or at least document the lingo of classic software. They're combing the globe's 9 million developers in search of coders still fluent in these nearly forgotten lingua frangas. Among the most endangered are Ada, APL, B (the predecessor of C), Lsp, Oberon, Smalltalk, and Simula.

Code-raker Grady Booch, Rational Software's chief scientist, is working with the Computer History Musuem in Silicon Valley to record and, in some cases, maintain languages by writing new compilers so our ever-changing hardware can grok the code. Why bother? "They tell us about the state of software practice, the minds of their inventors, and the technical, social, and economic forces that shaped history at the time," Booch explains. "They'll provide the raw material for software archaeologists, historians, and developers to learn what worked, what was brilliant, and what was an utter failure." Here's a peek at the strongest branches of programming's family tree. For a nearly exhaustive rundown, check out the Language List at *HTTP://www.informatik.uni-freiburg.de/Java/misc/lang_list.html*. - Michael Mendeno

Key

- 1954 Year Introduced
- **Active:** thousands of users
- **Protected:** taught at universities; compilers available
- **Endangered:** usage dropping off
- **Extinct:** no known active users or up-to-date compilers
- **Lineage continues**

Computer Languages

Why C++

Features of C++
Simple
Portability
Compiler-Based
Mid-Level Programming
Dynamic Memory Allocation
Rich Library
Recursion
Case Sensitive
Fast
Object-Oriented Programming
www.educba.com

CLI vs GUI

[root@localhost ~]# cd /var
[root@localhost var]# ls -la
total 72
drwxr-xr-x. 18 root root 4096 Jul 30 22:43 .
drwxr-xr-x. 23 root root 4096 Sep 14 20:42 ..
drwxr-xr-x. 2 root root 4096 May 14 00:15 account
drwxr-xr-x. 11 root root 4096 Jul 31 22:26 cache
drwxr-xr-x. 3 root root 4096 May 18 16:03 db
drwxr-xr-x. 3 root root 4096 May 18 16:03 empty
drwxr-xr-x. 2 root root 4096 May 18 16:03 games
drwxrwxr-x. 1 root root 6 May 14 00:12 run
drwxr-xr-x. 14 root root 4096 May 18 16:03 spool
drwxrwxrwt. 4 root root 4096 Sep 12 23:50 tmp
drwxr-xr-x. 2 root root 4096 May 18 16:03 yp
[root@localhost var]# yum search wiki
plugins: langpacks, presto, refresh-packagekit,
73% [
Start
VS

Command Line Interface - Basic Navigation

The Command Line Interface (CLI) will allow us to directly navigate the computers operating system. We will use:

- macOS or Linux: Terminal
- Windows: PowerShell

The following commands will work on all three system, except where noted below. macOS and Linux are case-sensitive, Windows is not.

- pwd: Show the present working directory.
- ls: To get the list of all the files or folders.
- cd: Used to change the directory.
- du: Show disk usage. (not available in PowerShell).
- man: Used to show the manual of any command.

Command Line Interface - File and Directory Manipulation

- mkdir: Used to create a directory if it does not already exist. It accepts directory name as input parameter.
- rmdir: It is used to delete a directory if it is empty.
- cp: This command will copy the files and directories from source path to destination path. It can copy a file/directory with new name to the destination path. It accepts source file/directory and destination file/directory.
- mv: Used to move the files or directories. This command's working is almost similar to cp command but it deletes copy of file or directory from source path.
- rm: Used to remove files or directories.
- touch: Used to create or update a file. (PowerShell New-Item).

Command Line Interface - Displaying the file contents

- cat: It is generally used to concatenate the files. It gives the output on the standard output.
- more: It is a filter for paging through text one screenful at a time.

The below commands are not available in PowerShell:

- less: It is used for viewing the files instead of opening the file. Similar to more command but it allows backward as well as forward movement.
- head: Used to print the first N lines of a file. It accepts N as input and the default value of N is 10.
- tail: Used to print the last N-1 lines of a file. It accepts N as input and the default value of N is 10.

On all systems, commands can be "piped" together: ls | more < *file* >

IoT Fun

he joy of tech™
by Nitrozac & Snaggy
FATTYPANTS IS KIDDING HIMSELF IF HE THINKS HE'S EATING LESS THAN 2000 CALORIES A DAY!
HE SPENT A FORTUNE ON US SMARTBULBS AND HE ONLY USES THE "WHITE LIGHT" SETTING! *SIGH*
DUMMY NEEDS TO TEST ME NOW AND THEN, OR AT LEAST CHECK MY APP!
AT LEAST YOU GET USED! I NEVER DO! ALL HE EATS IS TAKE-OUT!
DON'T BOTHER HIM! THE PREVIOUS SMOKE DETECTOR, HE BEAT TO DEATH WITH A BROOM HANDLE!!
DID YOU SEE WHAT TIME HE GOT IN LAST NIGHT? SCANDALOUS!
HEY GUYS! THE HOUSE SMARTMETER IS TELLING EVERYONE THAT SCAREDY CAT STILL USES A NIGHT LIGHT! HA HA!
I REFUSE TO PICK UP THIS FRENCH FRY. LAZYBONES CAN DO IT HIMSELF!
What your Internet of Things is saying about you...
© 2014 Geek Culture
joyoftech.com

Our First Microcontroller

Smart Room Controller

Teensy 3.2

- Cortex-M4 72MHz (overclocked to 96 MHz)
- 34 GPIO pins
- 3.3V and 5.0V operating voltages
- 500mA of available power with USB

Arduino IDE for Teensy

We are going to start off using the Arduino IDE[1]. The Arduino IDE is programmed essentailly using C++ code, but makes the compiling and loading onto the microcontroller simpler.

We begin by installing the Arduino IDE:
https://www.arduino.cc/en/main/software

Then, we install the Teensyduino add-on:
https://www.pjrc.com/teensy/td_download.html

[1] An IDE, or Integrated Development Environment, enables programmers to consolidate the different aspects of writing a computer program.

Other Software

1. Git
   - https://git-scm.com/downloads
2. Fritzing
   - IoT Bootcamp Teams Site
3. Drawio
   - https://app.diagrams.net/
4. Fusion 360
   - Instructional Videos - Teams Site
5. Formlab's Preform
   - https://formlabs.com/software/
6. Ultimaker's Cura
   - https://ultimaker.com/software/ultimaker-cura

GITHUB Simplified

```
// In Powershell go to ./Documents/<yourname>
// Get a repository that already exists and pull
   it into your local machine
  git clone <URL of repository>

// From the repository directory, get updates
  git pull

// Send your changes up to the repository
  git add .
  git commit -m "<comment>"
  git push

// You may get asked to enter your GIT username
git config --global user.email "you@example.com"
```

GITHUB First Clone

ddc-iot-classroom-2

Accept the assignment — L01_HelloWorld

Once you accept this assignment, you will be granted access to the `l01-helloworld-brashap` repository in the ddc-iot organization on GitHub.

Accept this assignment

You're ready to go!

You accepted the assignment, **L01_HelloWorld**.

Your assignment repository has been created:

https://github.com/ddc-iot/l01-helloworld-brashap

```
brian:~$ cd Documents/
brian:Documents$ mkdir IoT
brian:Documents$ cd IoT
brian:IoT$ git clone https://github.com/ddc-iot/L01_helloWorld-brashap
Cloning into 'L01_helloWorld'...
Username for 'https://github.com': brashap
Password for 'https://brashap@github.com':
  remote: Enumerating objects: 4, done.
  remote: Counting objects: 100% (4/4), done.
  remote: Compressing objects: 100% (3/3), done.
  remote: Total 4 (delta 0), reused 4 (delta 0), pack-reused 0
  Unpacking objects: 100% (4/4), 321 bytes | 53.00 KiB/s, done.
```

Second Clone: https://github.com/ddc-iot/class_slides

Teensy on Breadboard

Basic Structure of Arduino Sketch

```
// the "header" is used for GLOBALS

void setup() {
  // code in setup() runs once
  // it is used to initialize objects,
  // begin processes, and set variables
  pinMode(13, OUTPUT);  //set Pin 13 as an Output
}

void loop() {
  // functionality of your code
  // this loops indefinitely
}
```

Class Assignments

1. Lab Notebook - flow chart
2. Lab Notebook - schematic
3. Fritzing breadboad layout
4. Arduino code with comments

```
/*
 * Project:     Title of Project
 * Description: Description of Project
 * Author:      Your Name
 * Date:        Today's Date
 */

// Single Line Comments
```

Assignment L01_01_HelloWorld

We will write our first program together as a class, using:

- pinMode(pin,mode)
- digitalWrite(pin,state)
- delay(delay_time)

Introduction to Electrical Circuits

Energy

Copyright © The McGraw-Hill Companies, Inc. Permission required for reproduction or display.
Potential energy
Energy in
Energy out
Kinetic energy
Kinetic energy

Ohm's Law

Georg Ohm (16 March 1789 – 6 July 1854) was a German physicist and mathematician. As a school teacher, Ohm began his research with the new electrochemical cell, invented by Italian scientist Alessandro Volta. Ohm found that there is a direct proportionality between the potential difference (voltage) applied across a conductor and the resultant electric current. This relationship is known as Ohm's law:

Resistor Color Bands

COLOR	1ST BAND	2ND BAND	3RD BAND	MULTIPLIER	TOLERANCE
Black	0	0	0	1Ω	
Brown	1	1	1	10Ω	± 1% (F)
Red	2	2	2	100Ω	± 2% (G)
Orange	3	3	3	1KΩ	
Yellow	4	4	4	10KΩ	
Green	5	5	5	100KΩ	± 0.5% (D)
Blue	6	6	6	1MΩ	± 0.25% (C)
Violet	7	7	7	10MΩ	± 0.10% (B)
Grey	8	8	8	100MΩ	± 0.05%
White	9	9	9	1GΩ	
Gold				0.1Ω	± 5% (J)
Silver				0.01Ω	± 10% (K)

Measuring Voltage, Current, and Resistance

Power from the Teensy 3.2

The Teensy 3.2 has three pins related to power:

- 3.3V: 250mA of power to be used for most hardware
- V_{in}: 5V from the USB cable to power 5V hardware
- GND: The ground pin to close the electrical loop

One Resistor

Kirchhoff's First Law

Gustav Robert Kirchhoff (12 March 1824 – 17 October 1887) was a German physicist who contributed to the fundamental understanding of electrical circuits. His first law:

> In an electrical circuit, the sum of currents flowing into that node is equal to the sum of currents flowing out of that node

Kirchhoff's Second Law

The directed sum of the potential differences (voltages) around any closed loop is zero.

Resistors in Series and Parallel

Resistors in Series and Parallel

Parallel resistors

$$\frac{1}{R_{equivalent}} = \frac{1}{R_1} + \frac{1}{R_2}$$

Series resistors

$$R_{equivalent} = R_1 + R_2$$

Assignment: L02_00_Resistors

- In your lab notebook, draw the circuit diagrams
  1. Series: $4.7k\Omega$ and $2.2k\Omega$
  2. Parallel: $4.7k\Omega$ and $2.2k\Omega$
  3. Combined: Two $4.7k\Omega$ in series with $2.2k\Omega$
- Calculate the combined resistance and the voltage at each node, as well as the current through each component.
- Create Fritzing diagram
- Build **(one at a time)** on your breadboard and test your calculations with a multimeter.

Schematics in Fritzing

In Fritzing, go to the Schematic tab and layout your resistors.

NOTE: The schematic for the Teensy does not match it's physical layout.

Diodes

The key function of a diode is to control the direction of current-flow. Current passing through a diode can only go in one direction, called the forward direction. Current trying to flow the reverse direction is blocked.

Light Emitting Diodes

LEDs (that's "ell-ee-dees") are a particular type of diode that convert electrical energy into light.

Current Limiting Resistors

As a LED has very little resistance, when it is connected directly to a power supply, the current draw will exceed its specs and it will burn out.

$$V_{pp} - V_{LED} = IR \Longrightarrow R >= \frac{V_{pp} - V_{LED}}{I_{max}}$$

For a 3.3V power supply, a 0.43V across the LED, and a max current of 100mA, the resistor needs to be greater than 29Ω.

Assignment L02_01_helloLED

- Using Pin 5 as an output and the appropriate current limiting resistor, blink the LED once per second.
- Measure the voltage at both leads of the LED and record in your notebook.
- Change the resistor to $1k\Omega$ and then $10k\Omega$. What happens to the brightness? Measure the voltage and current in each case. Record in your notebook.

REMEMBER: Lab notebook, Fritzing, breadboard, then code

Model Based Troubleshooting

Constants and Variables

It is often useful to give a name to something that will be used repeatedly in the code. They can be constants or variables:

- Constant is a declaration that does not change throughout the code. For example a the pin that an LED is attached to.
- Variable is a declaration that changes as the code processes. For example, a counter or index.

The use of Constants and Variables has several advantages:

- It improves readability by assigning names to items
- Items can be changed by changing a single declaration
- It allows the code to do math

The first two Data Types that we will be using:

- **int**: an Integer between $\pm 2,147,483,648$.
- **float**: a Floating point number with 7-digits precision

Constants and Variables Example

```
const int ledPin = 5;
const int ledDelay = 1000;
int i;

void setup() {
  pinMode(ledPin, OUTPUT);  // set ledPin as Output
  i = 100;
}
void loop() {
  digitalWrite(ledPin,HIGH);
  delay(ledDelay);
  digitalWrite(ledPin,LOW);
  delay(ledDelay+i);
  i = i + 100;
}
```

Assignment L02_02_helloLEDvar

- Convert L02_01_helloLED with constants and/or variables.

Pulse Width Modulation

Software Configurable:

- Digital Input: High/Low (3.3V/0V)
- Digital Output: High/Low (3.3V/0V)
- Analog Input: 0V to 3.3V
- Analog Output: 0V to 3.3V PWM

Assignment L02_03_helloLEDanalog

Use analogWrite to change the brightness of the LED, using values:

- 255
- 63
- 171
- 16

Measure the voltage with your multimeter at each value.

Flowcharts

Symbol	Name	Function
	Process	Indicates any type of internal operation inside the Processor or Memory
	input/output	Used for any Input / Output (I/O) operation. Indicates that the computer is to obtain data or output results
	Decision	Used to ask a question that can be answered in a binary format (Yes/No, True/False)
	Connector	Allows the flowchart to be drawn without intersecting lines or without a reverse flow.
	Predefined Process	Used to invoke a subroutine or an Interrupt program.
	Terminal	Indicates the starting or ending of the program, process, or interrupt program
	Flow Lines	Shows direction of flow.

Loops

FOR LOOP
initialize index
Condition?
Do something
increment index
WHILE LOOP
Condition?
Do something
DO WHILE LOOP
Do something
Condition?

FOR Loop syntax

```
// FOR loop syntax
for (initialization; condition; increment) {
  // statement(s);
}

// EXAMPLE
for (j=0; j <= 255; j++) {
  analogWrite(ledPin, j);
}
```

WHILE loop syntax

```
// WHILE loop syntax
while (condition) {
  // statement(s)
}


// EXAMPLE
while (button == HIGH) {
  digitalWrite(ledPin, HIGH);
} //continue this loop until button is released
```

For vs While Loops

For vs While Loop

Comparison Chart

For Loop	While Loop
The for loop is used for definite loops when the number of iterations is known.	The while loop is used when the number of iterations is not known.
For loops can have their counter variables declared in the declaration itself.	There is no built-in loop control variable with a while loop.
This is preferable when we know exactly how many times the loop will be repeated.	The while loop will continue to run infinite number of times until the condition is met.
The loop iterates infinite number of times if the condition is not specified.	If the condition is not specified, it shows a compilation error.

DifferenceBetween.net

Assignment L02_04_helloLEDtri

Using a FOR Loop, have the LEDs follow a Triangle Wave function from off to full brightness with a period of 10 seconds.

While or Do While

Number Systems

Bits, Nibbles, Bytes, and Words

Data Types: Numbers

Data Type	8-bit AVR systems (Arduino Uno)			32-bit ARM systems (Teensy 3.2)		
	bytes	range (signed)	range (unsigned)	bytes	range (signed)	range (unsigned)
char	1	-128 to 127	0 to 255	1	-128 to 127	0 to 255
short	2	+/- 32,767	0 to 65,353	2	+/- 32,767	0 to 65,353
int	2	+/- 32,767	0 to 65,353	4	+/- 2,147,483,648	0 - 4,294,967,295
long	4	+/- 2,147,483,648	0 - 4,294,967,295	4	+/- 2,147,483,648	0 - 4,294,967,295
long long	8	+/- 9,223,372,036,854,770,000	0 to 18,446,744,073,709,551,615	8	+/- 9,223,372,036,854,770,000	0 to 18,446,744,073,709,551,615
float	4	3.4E +/- 38 (7 digits)	n/a	4	3.4E +/- 38 (7 digits)	n/a
double	4	3.4E +/- 38 (7 digits)	n/a	8	1.7E +/- 308 (15 digits)	n/a
long double	8	1.7E +/- 308 (15 digits)	n/a	8	1.7E +/- 308 (15 digits)	n/a
Unambiguous						
uint08_t	1	n/a	0 to 255	1	n/a	0 to 255
int08_t	1	-128 to 127	n/a	1	-128 to 127	n/a
uint16_t	2	n/a	0 to 65,353	2	n/a	0 to 65,353
int16_t	2	+/- 32,767	n/a	2	+/- 32,767	n/a
uint32_t	4	n/a	0 - 4,294,967,295	4	n/a	0 - 4,294,967,295
int32_t	4	+/- 2,147,483,648	n/a	4	+/- 2,147,483,648	n/a

There are $7.5x10^{18}$ grains of sand on Earth. A long long integer and the floating point numbers are larger than this.

Math Warning and Type Casting

Be cognizant of the data type when performing math operations.

```
int x = 3;
int y = 2;
float yf = 2.0;
float z;

//int divided by an int returns an int
z = x/y;                        // z = 1.0
z = x/yf;                       // z = 1.5
z = x / 2;                      // z = 1.0
z = x / 2.0;                    // z = 1.5

//type casting used to change datatype
z = (float) x / (float y);  // z = 1.5
z = x / (float) y;          // z = 1.5

z = (int) (x / yf);         // z = 1.0
y = x / yf;                 // y = 1
```

Type Casting is a way to ensure that you are correctly moving between datatypes.

Header Files

A header file is a file with the extension .h which contains C function declarations and macro definitions to be shared between several source files. There are two types of header files: those that the programmer writes and those that come with the compiler.

Both the user and system header files are included using the preprocessing directive #include. It has the following two forms:

- #include $<$ *file.h* $>$ for system header files.
- #include "*file.h*" for user created header files in the directory that contains the current code.

An example is the math.h header that defines various mathematical functions.

Basic Structure of Arduino Sketch Revisited

```
#include <math.h>       // include header files
const int ledPin = 5; // declare constants
float Vout;           // declare variables
float n;

void setup() {            // runs once
  pinMode(13, OUTPUT);  // system settings
  n = 0;              // set variables
}

void loop() {             // loops indefinitely
  Vout = sin(2*PI*n);
  n = n+0.01;
}
```

Assignment L02_05_helloLEDsin

Use a sin() function to vary brightness of your LED

- Use math.h
- Function sin takes a double as an input and returns at double.
- Set the period to 5 seconds. One cycle of $sin(2\pi\nu)$ for each integer of n.

The function millis() returns milliseconds since Teensy has been powered on. The frequency (ν) is then defined by millis()/period in milliseconds. For example, for a period of 5 seconds, the frequency $\nu =$ (millis()/5000.0).

IoT Fun

PARENTING in 1984
Did you REALLY brush your teeth or did you just WET THE BRISTLES to make it seem like you did?
www.ITworld.com
PARENTING in 2014
Did you REALLY brush your teeth or did you just HACK YOUR TOOTHBRUSH to make it seem like you did?
PJ

Data Types: Boolean

Boolean datatype (bool) holds either a TRUE or FALSE

Boolean Logic Operations (condition statements)

1. NOT (!): true if operand is false and visa-versa
   - $x = !x$
2. AND (&&): true if both operands are true
   - $z = x \&\& y$
3. OR (||): true if either operand is true
   - $z = x \parallel y$

Boolean In Action

```
x = !x;        // invert x

if (!x) {      // if x is false
  // statements
}

// if both pins read HIGH
if ((digitalRead(pin1) == HIGH) && (digitalRead(pin2) == HIGH) {
  //statements
}

// if either value is greater than zero
if (x > 0 || y > 0) {
  // statements
}
```

Displaying to the Screen: The Serial Monitor

```
void setup() {

// Enable Serial Monitor
  Serial.begin (9600);
  while (!Serial);  // wait for Serial monitor
  Serial.println ("Ready to Go");
}

void loop() {
  for (i=0; i <=13; i++){
  Serial.print(i);
  delay(printDelay);
  }
}
```

Print Statements

1. Serial.print() prints data to the monitor through the serial port as human-readable text:
   - Serial.print('N') prints: N
   - Serial.print("Hello World") prints: Hello World
   - Serial.print(78) prints: 78
   - Serial.print(3.141592) prints 3.14
   - Serial.print(3.141592,5) prints 3.14159
2. Serial.println() displays the print() followed by a carriage return (\r) or newline (\n).
3. Serial.printf() displays a formatted print.

Format Specifiers Statements

specifier	Output	Example
d or i	Signed decimal integer	392
u	Unsigned decimal integer	7235
o	Unsigned octal	610
x	Unsigned hexadecimal integer	7fa
X	Unsigned hexadecimal integer (uppercase)	7FA
f	Decimal floating point, lowercase	392.65
F	Decimal floating point, uppercase	392.65
e	Scientific notation (mantissa/exponent), lowercase	3.9265e+2
E	Scientific notation (mantissa/exponent), uppercase	3.9265E+2
g	Use the shortest representation: %e or %f	392.65
G	Use the shortest representation: %E or %F	392.65
a	Hexadecimal floating point, lowercase	-0xc.90fep-2
A	Hexadecimal floating point, uppercase	-0XC.90FEP-2
c	Character	a
s	String of characters	sample
p	Pointer address	b8000000
n	Nothing printed. The corresponding argument must be a pointer to a signed int. The number of characters written so far is stored in the pointed location.	
%	A % followed by another % character will write a single % to the stream.	%

Serial.printf("Print an integer %i and a float %0.4f \n", count, value);
Where count is an int and value is a float.

Assignment L03_00_SerialMonitor

1. Print Hello World to your monitor screen.
2. Next, display to the screen a count from 0 to 13, separated by commas, by using:
   - Serial.print();
   - Serial.println();
   - Serial.printf();

Hello World - What a microcontroller sees

HelloWorld.ino

```
void setup() {
  Serial.begin(9600);
  Serial.printf("Hello World! \n");
}

void loop() {}
```

Hex Code and Assembly Language

```
HelloWorld.bin:     file format binary
Disassembly of section .data:
00000000 <.data>:
    101c: bd10        pop {r4, pc}
    101e: 4402        add r2, r0
    1020: 4603        mov r3, r0
    1022: 4293        cmp r3, r2
    1024: d002        beq.n 0x102c
    1026: f803 1b01   strb.w  r1, [r3], #1
    102a: e7fa        b.n 0x1022
    102c: 4770        bx  lr
    102e: 0000        movs  r0, r0
    1030: b538        push  {r3, r4, r5, lr}
```

One Pin - Many Functions

Software Programmable: Input or Output and Digital or Analog.

Digital Input/Output

Digital electronics rely on binary logic to store, process, and transmit data or information. Binary Logic refers to one of two states – ON or OFF. This is commonly translated as a binary 1 or binary 0. A binary 1 is also referred to as a HIGH signal and a binary 0 is referred to as a LOW signal.

- digitalWrite(pin,value);
- inputValue = digitalRead(pin);

where, value equals HIGH or LOW.

Switches

Types of Switches

Our First Button and Pull Down Resistors

Wait - why is there a resistor connected to ground?

Assignment: Buttons

- Labbook: draw circuit
- Fritzing diagram
- Wire your circuit
- Write the code

1. L03_01_button
   - Connect button (Pin 23)
   - Print button state to the screen.
   - Now, remove the pull-down resistor and restart your code.
2. L03_02_button_pullup
   - Replace the pull-down resistor with a pull-up resistor.
     - Not pressed: 3.3V
     - Pressed: GND
     - How does the logic change?
3. L03_03_button_input_pullup
   - Remove the pull-up resistor
   - Implement: pinMode(pin,INPUT_PULLUP);

IF-ELSE Statements

IF-ELSE Statements

```
// IF statement SYNTAX
if (condition) {
  //statement(s)
}
else {
  // else statement(s)
}

// EXAMPLE
if (button == HIGH) {
  Serial.printf("Button is not pressed \n");
}
else {
  Serial.printf("Button is pressed \n");
}
```

Button and LED

Assignment: Buttons and LEDs

1. L03_04_buttonLED
   - Add an LED to Pin 5 and use the button to turn the LED on and off.
   - Also, print button state to the screen
2. L03_05_twobuttonLED
   - Add a second button (Pin 16) and LED (Pin 6)
   - Have each button control one LED
   - Also, print button states to the screen

Voltage Divider

Voltage Dividing

We are just using the Teensy to provide Power and GND.

- Use various combinations of resistors between $1k\Omega$ and $22k\Omega$.
- Calculate the Series resistance and the voltage between the two resistors in your Lab Notebook.
- Measure with your multimeter and compare.

Potentiometer - Variable Resistor

A potentiometer has 3 pins. Two terminals (the blue and green) are connected to a resistive element and the third terminal (the black one) is connected to an adjustable wiper.

Assignment L03_06_AnalogInput

1. Utilize analogRead() to measure analog input across potentiometer (voltage divider) using Pin 14.
2. Determine the range of the analogRead across the entire range of the potentiometer.

Anatomy of a Function

Types of Variables

```
int toadStools = 20;        // global variable

int seatsLeft(int toadStools) {
  int frogs  = 8;         // local variable
  static int toads = 2;   // static variable

  frogs = frogs - 2;
  toads = toads + 1;

  seatsLeft = toadStools - frogs - toads;
  return seatsLeft;
}
```

1. Global Variables
   - Accessible throughout the program and all functions.
2. Local Variables
   - Accessible only in the function
   - Created when function is called, destroyed when function is returned.
3. Static Local Variables
   - Accessible only in the function
   - Maintains value across multiple calls of a function.
   - Destroyed only when program is terminated.

Basic Structure of Arduino Sketch Revisited

```

int Num, doubleNum;

void setup() {
  Serial.begin(9600);  // Turn on Serial Monitor
  while(!Serial);      // Wait for Serial Monitor to be running
  Num = 1;               // Initialize Num;
}

void loop() {
  doubleNum = twotimes(Num);  // call the funciton twotimes
  Num = doubleNum;
  Serial.printf("The number is now %i \n", Num);
  Serial.printf("The number in HEX is %X \n", Num);
  delay(1000);
}

int twotimes(int number) {
  int answer;     // declare answer as a local variable
  answer = 2 * number;
  return answer;
}
```

Assignment L03_06_AnalogInput Revisited

1. Modify your code by adding a function, in2volts(), that converts the analog input value to voltage.
2. Print both the raw analogInput and the associated voltage to your screen.

IoT Humor

"I remember when you could only lose a chess game to a supercomputer."

Objects

Object-oriented programming
CLASS
Human
OBJECTS
Name
PROPERTIES
Email
Address
METHODS
Verify
Send mail
©2019 TECHTARGET. ALL RIGHTS RESERVED

Traffic Light

Let's use the traffic light to build our own Objects

State Machine - Traffic Lights, British Style

SWITCH...CASE syntax - multiple IFs

```
// SWITCH...CASE syntax
switch (var) {
  case label1:
    // statements
    break;
  case label2:
    // statements
    break;
  default:
    // statements
    break;
}
```

Where:

- var: variable whose value is compared to the case values
- label1, label2 are the case values (int or char)

Enumeration (enum)

The C-language has a declaration type, enum, which allows for multiple states.

- Within the enum declaration descriptive tags are used
- Then the compiler assigns the tags an integer value.

```
// ENUM example:
// A variable State with four states
enum State {
  GREEN,
  YELLOW,
  RED,
  RED_YELLOW
};
```

The compiler treats enum as your personal variable type. For example, the emum variable (e.g., State) can now be used within switch...case statements.

OneButton Library

The tick() method checks the input pin for a single click, double click or long press situation.

Basic Structure of Arduino Sketch - Revisited

```
// the "header" is used for GLOBALS
#include <bme280.h> // library files
#include <Adafruit_SSD1306.h>
Adafruit_BME280 bme; // name object in class
Adafruit_SSD1306 display(WIDTH, HEIGHT, &Wire);
bool onoffState;      // declare global variables

void setup() {
  display.begin(SSD1306_SWITCHCAPVCC, 0x3C);
  bme.begin(0x76);       // begin processes
  onoffState = false;     // set variables
}

void loop() {
}
```

OneButton Declarations

```
#include <OneButton.h>
OneButton button1(pin, activeLOW, pullUP);
void setup() {
  button1.attachClick(click1);
  button1.attachDoubleClick(doubleclick1);
  button1.attachLongPressStart(longPressStart1);
  button1.attachLongPressStop(longPressStop1);
  button1.attachDuringLongPress(longPress1);
  button1.setClickTicks(250);
  button1.setPressTicks(2000);
}
```

OneButton parameters (not variables):

- pin: the pin the button is connected to.
- activeLOW: "true" means input LOW when button pressed.
- pullUP: "true" is INPUT_PULLUP pinMode.

Using OneButton

```
void loop() {
  button1.tick();     // check the state of the button
}

void click1() {
  Serial.println("Hi, my name is Brian.");
}

void doubleClick1() {
  Serial.println("Hope your day is going well.");
}
```

Assignment: OneButton

- Notebook: flowchart
- Notebook: schematic
- Fritzing diagram
- Wire your circuit
- Write the code

1. L04_01_oneButton
   - Use OneButton libary and button on Pin 23.
   - Click() - toggle bool variable buttonState.
   - doubleClick() - toggle bool variable blinker.
2. L04_02_oneButtonLED
   - Toggle LED on/off with buttonState.
3. L04_03_oneButtonLEDblink
   - When ON, change from solid to blinking when the variable blinker is toggled.

Avoiding Delays

```
void loop() {
  //run constantly
  currentTime = millis();

  //run once per second
  if((currentTime-lastSecond)>1000) {
    Serial.print(".");
    lastSecond = millis();
  }

  //run once per minute
  if((currentTime-lastMinute)>60000) {
    Serial.println();
    Serial.println("Minute");
    lastMinute = millis();
  }
```

Arrays

- Syntax: datatype var[ ] = {element 1, element 2, element 3};
- Example: int ledArray[ ] = {greenPin, yellowPin, redPin};

Using Arrays

```
int myInts[6];
int myPins[] = {2, 4, 8, 3, 6};
int mySensVals[6] = {2, 4, -8, 3, 2};
char message[6] = "hello";

void loop() {
  mySensVals[0] = 10; //assign value to array
  x = mySensVals[4]; //retrieve value from array
  for (i = 0; i < 5; i = i + 1) {
      Serial.println(myPins[i]);
  }
}
```

NOTE: The array index starts at 0 (not 1).

Assignment: OneButton

- Notebook: flowchart
- Notebook: schematic
- Fritzing diagram
- Wire your circuit
- Write the code

1. L04_04_oneButtonArray
   - Use 3 LEDs and one Button
   - Click() - toggle current LED on/off
   - doubleClick() - using an array, select the next LED
   - longPressStart() - light up the three LEDs in sequence
   - longPressStop() - light up the three LEDs in reverse order

Assignment: Serial Read

- SerialReadExample.ino

1. L04_05_timer - Create a Stop Watch and Countdown Timer
   - Click for start and stop
   - Double Click to switch between Stop Watch and Timer. In Timer mode, prompt the user on the Serial Monitor to enter the time to countdown from.
   - Long Press for reset

NeoPixels

NeoPixels are:

- Addressable RGB LEDs based on the WS2812 (or WS2811) LED/drivers.
- They come as individual pixels, in strips, in matrices, rings, etc.
- They can be programmed via your microcontroller to create a wide array of effects and animations.

NeoPixel Programming

WS2812 Protocol

LED-Chain

NeoPixel Declaration

Including the NeoPixel library and setting up the object: pixel.

```
#include <Adafruit_NeoPixel.h>

const int LED_PIN = 17;    // Pin the NeoPixels are connected to
const int LED_COUNT = 16;  // Total number of NeoPixels

Adafruit_NeoPixel pixel(LED_COUNT, LED_PIN, NEO_GRB + NEO_KHZ800);
/* Argument 1 = Number of pixels
 * Argument 2 = GPIO pin number
 * Argument 3 = Pixel type flags, add together:
 *  You will use:
 *    NEO_GRB     Pixels are wired for GRB bitstream (most NeoPixel products)
 *    NEO_KHZ800  800 KHz bitstream (WS2812)
 *
 *  Other options for Argument 3:
 *    NEO_KHZ400  400 KHz (WS2811)
 *    NEO_RGB     Pixels are wired for RGB bitstream (v1)
 *    NEO_RGBW    Pixels are wired for RGBW bitstream
 */
```

Using NeoPixel Methods

```
void setup() {
  pixel.begin();
  pixel.show(); //initialize all off
}

void loop() {
  pixel.setPixelColor(n, red, green, blue);
  pixel.setPixelColor(n, color); \\hex code
  pixel.fill(color, first, count);
  pixel.setBrightness(bri) \\ 0 - 255
  pixel.show(); \\nothing changes until show()
  pixel.clear();
  pixel.show();
}
```

Assignment: NeoPixels

- Notebook: flowchart
- Notebook: schematic
- Fritzing diagram
- Wire your circuit
- Write the code

1. L05_01_neoPixel
   - Light up the 4 pixels and the ring using a FOR-loop.
2. L05_02_colorHeader
   - Implement a header file that contains the pixel colors.
3. L05_03_pixelStrip, using FOR-loop, implement functions that:
   - Send a pixel of a random color down and back on the strip
   - Light the strip up as a rainbow
   - Send a pair of Maize and Blue lights down the strip.
4. L05_04_pixelFill
   - Light up 6 segments of different colors using the fill() method

Where do global header files go?

Generating Random Numbers

```
/*
 * The random function generates pseudo-random
   numbers.
 *     random(min,max)
 *     random(max)     //assumes min = 0
 * returns a number between min and max-1
 */

  // print a random number from 0 to 299
  randNumber = random(300);
  Serial.println(randNumber);

  // print a random number from 10 to 19
  randNumber = random(10, 20);
  Serial.println(randNumber);
```

IoT Humor

"WE HAVE TO GO OUT FOR DINNER. THE REFRIGERATOR ISN'T SPEAKING TO THE STOVE."

Capacitors

A capacitor is created out of two metal plates and an insulating material called a dielectric. The metal plates are placed very close to each other, in parallel, but the dielectric sits between them to make sure they don't touch.

- The dielectric can be made out of all sorts of insulating materials: paper, glass, rubber, ceramic, plastic, or anything that will impede the flow of current.
- The plates are made of a conductive material: aluminum, tantalum, silver, or other metals.

Capacitors

When current flows into a capacitor, the charges get "stuck" on the plates because they can not get past the insulating dielectric. Electrons build up on one of the plates, and it becomes overall negatively charged. The large amount of negative charges pushes away like charges on the other plate, making it positively charged.

The stationary charges on these plates create an electric field, which influences electric potential energy and voltage. When charges group together on a capacitor like this, the cap is storing electric energy just as a battery might store chemical energy.

Low Pass Filter - cutoff frequency f_c

- At low frequencies, there is plenty of time for the capacitor to charge up to practically the same voltage as the input voltage.
- At high frequencies, the capacitor only has time to charge up a small amount before the input switches direction. The output goes up and down only a small fraction of the amount the input goes up and down. At double the frequency, there's only time for it to charge up half the amount.

$$f_c = \frac{1}{2\pi\tau} = \frac{1}{2\pi RC}$$

Low Pass Filter Response

$$f_c = \frac{1}{2\pi RC} = \frac{1}{2\pi(500)(4.7x10^{-6})} = 67.5678Hz$$

Capacitors - does it matter how they are placed

- Some types of capacitors (electrolytic and tantalum) are polarized (the have + and - terminals). This is due to how the dielectric film has been deposited, the reverse polarity leads to degradation of the dielectric.
- Other capacitors (ceramic and film) do not have a polarity and can be installed in either direction.

Assignment: Low Pass Filters

Using Serial Plotter:

- Serial.begin(9600);
- Serial.printf("%i , %i, %0.3f \n",d1,d2,d3);
- Close Serial Monitor

1. L06_00_lowPass
   - Create code that generates a sine wave of frequency ν: $sin(2\pi\nu t)$
   - Connect the output to an input
   - Using the Serial Plotter, plot both the output and the input.
   - Create a low pass filter with $f_c \approx 67Hz$
   - Pass the output through the low pass filter before inputting back to the Teensy.
   - In code, vary the frequency and observe the difference between the two signals.
   - Use the potentiometer to now vary the frequency.

Encoders

Encoders

Clockwise Sequence

	A	B
t1	0	1
t2	0	0
t3	1	0
t4	1	1

Counter-Clockwise Sequence

	A	B
t1	1	0
t2	0	0
t3	0	1
t4	1	1

The Encoder Class

```
#include <Encoder.h>
Encoder myEnc(pinA,pinB);

void setup() {
}

void loop() {
  // read encoder position
  position = myEnc.read();

  // set encoder to a position
  myEnc.write(maxPos);
}
```

Mapping (or Converting)

Mapping is the conversion from one set of units to another. For example converting from Celsius to Fahrenheit:

$$Temp(^\circ F) = \frac{9}{5} * Temp(^\circ C) + 32$$

C++ provides us with a function to do this mapping:
newVal = map(value, fromLow, fromHigh, toLow, toHigh);

For example:
tempF = map(tempC,0,100,32,212);

Assignment: Encoders

- Notebook: schematic
- Fritzing diagram
- Wire your circuit
- Write the code

1. L06_01_encoder
   - Display the encoder position to the screen
2. L06_02_encoderScaled
   - The encoder has 96 positions. Mathematically map (without using the map() function) the encoder to 12 pos (0-7 = 0,8 - 15 = 1, etc.). Show your work to an instructor before moving on to the map() function.
   - Next, use the map() function.
3. L06_03_encoder_NeoPixel
   - Use the encoder to light up the pixel ring

Reminder of the syntax of the map() function:
newVal = map(value, fromLow, fromHigh, toLow, toHigh)

Encoder Jitter

Encoder - Low Pass Filter

Assignment: Encoders

- Notebook: schematic
- Fritzing diagram
- Wire your circuit
- Write the code

1. L06_04_encoder_switch
   - Connect your microcontroller to the encoder switch and LEDs
   - Use the switch to turn on/off the NeoPixels.
   - Also, the encoder LED should be red for off and green for on.
2. L06_05_rainbow1 - extra credit
   - Without OneButton: Use a button to cycle the NeoPixel ring colors through the colors of the rainbow. (i.e., one color change each time button is pressed).
3. L06_06_rainbow2 - extra credit
   - With OneButton: Have it continuously cycle (i.e, while pressed colors change every one second).

Buses and Interfaces

UART

Universal Asynchronous Receiver/Transmitter

Serial Peripheral Interface

- Master Out, Slave In (MOSI) connects to Data In
- Master In, Slave Out (MISO) connects to Data Out

Serial Peripheral Interface

Serial +/−

UART

SPI

Assignment: Write to μSD Card

- Notebook: schematic
- Fritzing diagram
- Wire your circuit
- Write the code

1. L07_01_dataLogger
   - String datatype
   - SPI and SD libraries
   - File object
   - SD.begin()
   - dataFile.print()
   - Simulate 3 data streams and write to SD card

The Internet

IP Addresses

- When a device joins the network it is given an internet address.
  - static or dynamic
- IPv4 (32-bit) - 4.2 billion
- IPv6 (128-bit) - 340 quadrilliard
- In Powershell, try: *ipconfig/all*
- In Terminal (MAC), try: ipconfig getifaddr en0

MAC Address

A MAC Address is a unique 6-byte (48-bit) address that is usually permanently burned into a network interface card (NIC) and uniquely identifies the device on an Ethernet-based network. The uniqueness of MAC addresses is ensured by IEEE.

If you are creating your own MAC address, the 2's place bit of the first byte, the "locally administered bit" should be set. The 1's place bit, the "globally administered" bit must be off.

Therefore, xA-xx-xx-xx-xx-xx is valid, while x7-xx-xx-xx-xx-xx is not.

Assignment: Wemo

- Notebook: schematic
- Fritzing diagram
- Wire your circuit
- Write the code

Create your own mac.h header file

1. L08_00_EthernetTest
   - Modify to use your mac.h file
2. L08_01_Wemo
   - Using the wemo.h library and WemoH_Example as a template, create code that turns on and off multiple Wemo Smart Outlets in the classroom.
3. L08_02_Wemo_Timer
   - Add to your code a timer that turns off a Wemo after 10 secs.
4. L08_03_Wemo_Object
   - Modify the wemo.h library to be a Class and Methods.
   - Modify your wemo code the create and use a wemo object.

Semiconductor

- A silicon atom has four electrons in its outer shell and bonds tightly with four surrounding silicon atoms creating a crystal matrix with eight electrons in the outer shells. The tight bonds make pure silicon non-conducting.
- Phosphorus has five electrons, and when combined, the fifth electron becomes a "free" electron that moves easily within the crystal when a voltage is applied.
- Boron has only three electrons in its outer shell and can bond with only three of surrounding silicon atoms. Thus one silicon atom has a vacant location in its outer shell, called a "hole," that readily accepts an electron.

pn junction diode

- When p-type and n-type semiconductors are bonded, holes and free electrons are attracted, combine, and disappear near the boundary. Since there are no carriers in this area, it is called a depletion layer and it is an insulator.
- A positive voltage applied to the p-type region causes electrons to flow sequentially from the n-type. The electrons will first disappear by combining with holes, but excess electrons move to the positive pole and current will flow.

Bipolar Junction Transistor

The transistor has three regions, namely base, emitter and collector. The emitter is a heavily doped terminal and emits electrons into the base. Base terminal is lightly doped and passes the emitter-injected electrons on to the collector. The collector terminal is intermediately doped and collects electrons from base. This collector is large as compared with other two regions so it dissipates more heat.

Bipolar Junction Transistor - Modes of Operation

- **Saturation:** Current freely flows from collector to emitter. (ON Switch)
- **Cut-off:** No current flows from collector to emitter. (OFF Switch)
- **Active:** The current from collector to emitter is proportional to the current flowing into the base. (Amplifier)
- **Reverse-Active:** Like active mode, the current is proportional to the base current, but it flows reverse from emitter to collector (not the purpose transistors were designed for).

NPN Modes

Voltage relations	NPN Mode	PNP Mode
$V_E < V_B < V_C$	Active	Reverse
$V_E < V_B > V_C$	Saturation	Cutoff
$V_E > V_B < V_C$	Cutoff	Saturation
$V_E > V_B > V_C$	Reverse	Active

Water Analogy

Active Mode NPN Transistor Circuit

If you apply a voltage V_{IN} that is high enough to forward-bias the base-to-emitter junction, current (I_B) will flow from the input terminal, through R_B, through the BE junction, to ground. Current (I_C) will also flow through R_C and the collector-to-emitter portion of the transistor.

NOTE: V_{OUT} is an amplified but inverted signal of V_{IN}.
This simple circuit will step-up a 0 - 3.3V output from the microcontroller to 0 - 5.0V (inverted). The low impedance of the output will also provide sufficient current to drive a higher current device (e.g., a relay).

PNP Transistor

NPN Transistors are more common than PNP for a number of reasons:

- The voltage and current behavior of an NPN transistor is significantly more intuitive.
- When a switch or driver circuit is required, NPNs provide a more straightforward interface to digital output signals (such as a control signal generated by a microcontroller).
- NPNs are higher performance (faster switching speeds) due to higher mobility of electrons vs holes.

Logic Voltage Level Standards

Data source: EETimes, A brief recap of popular logic standards (Mark Pearson, Maxim).

Or, what is wrong with the NeoPixels.

Emitter Follower

- NeoPixels are designed around 5V CMOS transistors
  - $V_{IH} > 3.5V$
  - 3.3V Microcontroller $V_{OH} = 3.3V$
- An Emitter Follower (i.e., a PNP transistor wired backwards) is a current amplifier, but will also produce a $V_{OUT} = 3.9V$.
- Alternatively, the first NeoPixel could be sacrificed by reducing its V_{cc} to 4.3V with a diode.

Emitter Follower Layout

Fritzing

Schematic

PCB Layout

NPN Pre-Amplifier Circuit

Two Stage Pre-Amplifier

Ohm's Law - Revisited

PreAmp vs PowerAmp

PreAmp:

- A preamp boosts the signal up to 'line level'.
- Guitar PreAmp
  - A pure guitar signal typically sounds weak and anaemic, as is seen if a guitar is directly plugged PA system.
  - A preamp is able to raise a guitar's signal up to an audible volume.
  - It can also be used to affect the audio characteristics.

PowerAmp:

- A power amp boosts that line level signal even more – so that it can be projected through speakers.

Power Amplifier

Op Amp Lesson - Under Construction

Inverting Op-amp

$$A = \frac{Vout}{Vin} = -\frac{Rf}{Rin}$$

Non-inverting Op-amp

$$A = \frac{Vout}{Vin} = 1 + \frac{Rf}{Rin}$$

Assignment: Amplifiers

1. L09_01_NeoPixel
   - Add a Emitter-Follower into your NeoPixel circuit to boost the pixel commands to 5V.
2. L09_02_NPNAmp (no Teensy)
   - Make NPN Preamp
   - Test your NPN Preamp with the signal generator and oscilloscope.
3. L09_03_OpAmp
   - Create an OpAmp circuit to amplify your mic.
   - Use a NeoPixel string (either your ring or a strip) to display the audio level.

IoT Humor

Inter-integrated Circuit (I^2C)

I^2C vs SPI

I2C v/s SPI

I2C	SPI
Speed limit varies from 100kbps, 400kbps, 1mbps, 3.4mbps depending on i2c version.	More than 1mbps, 10mbps till 100mbps can be achieved.
Half duplex synchronous protocol	Full Duplex synchronous protocol
Support Multi master configuration	Multi master configuration is not possible
Acknowledgement at each transfer	No Acknowledgement
Require Two Pins only SDA, SCL	Require separate MISO, MOSI, CLK & CS signal for each slave.
Addition of new device on the bus is easy	Addition of new device on the bus is not much easy a I2C
More Overhead (due to acknowledgement, start, stop)	Less Overhead
Noise sensitivity is high	Less noise sensitivity

L10_00_I2CScanner

Let's create an I2C scanner

- Create a Fritzing diagram for adding the BME280 and the OLED to your Teensy.
- Follow along to create the I2C code.
  - Use library wire.h
  - Wire.begin();
  - Wire.beginTransmission(i);
  - Wire.endTranmission();
    - 0: Transmission Successful
    - 1: Data too long to fit in transmit buffer
    - 2: Received NACK (Negative Acknowledgment) on transmit of address
    - 3: Received NACK on transmit of data
    - 4: Other error
- Wire up your schematic and determine the I2C addresses of each device.

Assignment: I^2C

- Notebook: schematic
- Fritzing diagram
- Wire your circuit
- Write the code

1. L10_01_OLEDWrite
   - Install Adafruit_SSD1306 library
   - Review and run SSD_1306_128x32_i2c example
   - Create variables for your birthday. Using the syntax from testdrawstyles() print using printf():
     - Hello World
     - Your Name
     - Your Birthday
     - Your Favorite Color
   - Experiment with rotating the screen using the setRotation(int) method.

Assignment: BME280

1. Header - define BME280 object
   - I2C: Adafruit_BME280 bme;
   - SPI: Adafruit_BME280 bme(BME_CS);
2. Setup - start BME280
   - status = bme.begin(hex address);
   - if(status==false) → initialization failed
3. Loop - read from sensor
   - tempC = bme.readTemperature();
   - pressPA = bme.readPressure()/100.0;
   - humidRH = bme.readHumidity();

Assignment: I^2C

- Notebook: schematic
- Fritzing diagram
- Wire your circuit
- Write the code

1. L10_02_BME280
   - Read BME280 data
   - Convert to tempF and inHg
   - Print to Serial.Monitor
2. L10_03_BME280_OLED
   - Print data to the OLED display
3. L10_04_BME280_SDMicro
   - Add in saving data to the μSD card
   - Use your NeoPixels to give a visiual indication of room conditions

Phillips Hue API

Application Programming Interface: a set of functions and procedures allowing the creation of applications that access the features or data of an operating system, application, or other service.

SOAP vs REST

SOAP (WS-*)
SMTP
HTTP POST
MQ...
Endpoint URI
Application
SOAP

POX
RSS
JSON
...
HTTP GET
HTTP POST
HTTP PUT
HTTP DEL
Resource URI
Application
REST

Assignment: L11_01_Hue

- Notebook: schematic
- Fritzing diagram
- Wire your circuit
- Write the code

1. Using the hue.h library and HueH_Example as a template, create code that
   - button that turns on and off the Hue light at your pod
   - uses the encoder to change the brightness of the Hue bulb
   - has a method of cycling the Hue light through the colors of the rainbow.

Getting with GIT

Midterm Project - Smart Room Controller

1. Determine functionality of your Smart Room Controller
   - Use the components that we have learned over the last 3 weeks.
   - Get minimum requirements from the Instructor.
   - Sketch out the basic layout of your room controller in your lab notebook.
   - Draw flowcharts of the main functions you plan to implement.
   - Get feedback from at least 3 peers on your planned functionality.
2. Layout your circuitry in Fritzing along with a legible schematic.
3. Wire up your circuitry as if you're going to demo your controller for a perspective customer.
4. Code, debug, test.
5. Documentation and Demonstration:
   - Ensure all files are uploaded to GitHub with an appropriate README.md
   - Upload your project to hackster.io
   - Prepare a presentation/demonstration for the class on your controller
   - Participate in class demonstrations (Friday morning - Week 4)

Our Second Microcontroller

Expectations for the rest of the course

Expectations for the rest of the course

1. Most important: Be Consistent
2. Proper Indentation
3. Brace placement: K&R or BSD
4. Do not check boolean for equality.
5. A variable's name (noun) should describe its contents.
6. A function's name (verb) should describe the set of actions it performs.
7. Reduce duplication / Modularize
8. So, what about capitalization?
   - variableNames
   - nameFunction
   - CONSTANTS
   - Classes and Enum

Particle Argon

Main processor:

Nordic Semiconductor nRF52840 SoC

- ARM Cortex-M4F 32-bit processor @ 64MHz
- 1MB flash, 256KB RAM
- Bluetooth LE (BLE) central and peripheral support
- 20 mixed signal GPIO (6 x Analog, 8 x PWM), UART, I2C, SPI
- Supports DSP instructions, HW accelerated Floating Point Unit (FPU) calculations
- ARM TrustZone CryptoCell-310 Cryptographic and security module
- Up to +8 dBm TX power (down to -20 dBm in 4 dB steps)
- NFC-A radio

Argon Wi-Fi network coprocessor:

Espressif ESP32-D0WD 2.4 GHz Wi-Fi coprocessor

- On-board 4MB flash for the ESP32
- 802.11 b/g/n support
- 802.11 n (2.4 GHz), up to 150 Mbps

Argon general specifications:

- On-board additional 4MB SPI flash
- Micro USB 2.0 full speed (12 Mbps)
- Integrated Li-Po charging and battery connector
- JTAG (SWD) Connector
- RGB status LED
- Reset and Mode buttons
- On-board 2.4GHz PCB antenna for Bluetooth (does not support Wi-Fi)
- Two U.FL connectors for external antennas (one for Bluetooth, another for Wi-Fi)
- Meets the Feather specification in dimensions and pinout
- FCC, CE and IC certified
- RoHS compliant (lead-free)

Why Particle

- Global reach with over 200,000 IoT professionals
- Edge-to-Cloud infrastructure
- Prototyping to Production with same code
- WI-FI, Bluetooth, and Cellular
- Secure Device OS
- Built in cloud communication
- Real-Time OS that works across all products

Particle: Edge to Cloud

Particle: Prototyping to Production

Particle Argon Pin Layout

v1.0

Please Do Not Skip Ahead During Setup

Particle Software - ParticleCLI and Visual Studio Code

1. Create Particle login: `https://login.particle.io/signup`
2. Install Particle Command Line Interface. Download from `https://docs.particle.io/tutorials/developer-tools/cli/`.
   - On Windows, you need to run this by right-clicking on it and selecting "Run As Administrator."
   - Test that the Particle CLI installed correctly by going to PowerShell or Terminal and type particle
3. Download Particle Workbench / Visual Studio Code `https://docs.particle.io/quickstart/workbench/`.
   - Select all default values during install.
   - **Do NOT install Azure IoT.**
   - After it is installed, when you lauch it, it may ask you to Install Dependencies. If so, select yes.

Particle Setup

1. Attach the Wi-Fi antenna to your Argon. Use the correct connector, there are 3 U.FL connectors: WiFi, BT, and NFC.
2. Plug the Argon into a USB port. It should begin blinking blue.
3. Open PowerShell or Terminal.
4. Login into your Particle Account

```
particle login
```

5. Ensure you have the latest Particle CLI

```
particle update-cli
```

6. Put the Argon in DFU mode (blinking yellow) by holding down MODE. Tap RESET and continue to hold down MODE. The status LED will blink magenta (red and blue at the same time), then yellow. Release when it is blinking yellow.

Updating your Argon to latest Device OS

1. Update the device by running the following two commands. If the device goes out of blinking yellow after the first command, put it back into DFU mode. See Note [2].

```
particle update
particle flash --usb tinker
```

2. When the command reports Flash success!, reset the Argon. It should go back into listening mode (blinking dark blue).
3. Verify that the update worked by running the following command:

```
particle serial identify

Your device id is e00fce681ffffffffc08949b
Your system firmware version is 1.5.2
```

[2] paticle flash –usb tinker can be used for device troubleshooting

Setting Up WiFi

- Set your Argon into Listening Mode by holding the MODE button for three seconds, until the RGB LED begins blinking blue.
- Execute the command: particle serial wifi

```
brian:~$ particle serial wifi
? Should I scan for nearby Wi-Fi networks? No
? SSID DDCIOT
? Security Type WPA2
? Cipher Type AES+TKIP
? Wi-Fi Password ddcIOT2020
Done! Your device should now restart.
```

After setting, you Argon should go through the normal sequence of blinking green, blinking cyan (light blue), fast blinking cyan, and breathing cyan.

Claim Your Device

1. Claim the device to your account. This can only be done if it's breathing cyan. Replace e00fce681ffffffffc08949b with the device ID you got earlier from particle serial identify. Then, rename it to the name of your choice.

```
particle device add e00fce681ffffffffc08949b
particle device rename e00fce681ffffffffc08949b
    myArgon
```

2. Ensure that your setup flag is marked as done

```
particle usb setup-done
```

3. You have successfully set up your Argon!

Useful Particle CLI Commands

1. Enter DFU mode from the CLI

```
particle usb dfu
```

2. If Argon won't enter DFU mode, restore the base firmware

```
particle flash --usb tinker
```

3. Get a list of your Particle devices and their connection status

```
particle list
```

4. Search for available libraries

```
particle library search <search term>
```

Argon LED Modes

Mode	LED Status
Connected	Breathing Cyan
OTA Firmware Update	Blinking Magenta (red and blue together)
Looking for Internet	Blinking Green
Connecting to Cloud	Rapid Blinking Cyan
Listening Mode	Blinking Blue
Network Reset	Rapid Blinking Blue
WiFi Off	Breathing White
Safe Mode	Breathing Magenta (red and blue together)
DFU (Device Firmware Upgrade	Blinking Yellow
Restore Factory Firmware	Rapid Blinking Yellow
Factory Reset	Rapid Blinking White
Decryption Error	Blinking Cyan followed by 1 Orange Blink
No Internet	Blinking Cyan followed by 2 Orange Blink
No Particle Cloud	Blinking Cyan followed by 3 Orange Blink
Authentication Error	Blinking Cyan followed by 1 Magenta Blink
Handshake Error	Blinking Cyan followed by 1 Red Blink
Decryption Error	Blinking Cyan followed by 1 Orange Blink
SOS - Firmware Crash	Blinking Red - 3 short, 3 long, 3 short, error code

Directory Structure - VERY IMPORTANT

EXPLORER

OPEN EDITORS 1 UNSAVED
- PM25_Test.ino src 3

PM25_TEST
- .vscode
  - launch.json
  - settings.json
- lib \ Seeed_HM330X
  - examples \ basic_demo
    - basic_demo.ino
  - src
    - HM330XErrorCode.h
    - I2COperations.cpp
    - I2COperations.h
    - Seeed_HM330X.cpp
    - Seeed_HM330X.h
- src
  - PM25_Test.cpp
  - PM25_Test.ino 3
- target \ 1.5.0 \ argon
- project.properties
- README.md

PM25_Test.ino

src > PM25_Test.ino > ...

```cpp
/*
 * Project PM25
 * Description: 2.5um Particle Measurement with H3301 Sensor
 * Author:  Brian Rashap
 * Date:    17-APR-2020
 */
//#include <Particle.h>
#include <Seeed_HM330X.h>
#include <Wire.h>

/***************SetUp HM330X**************/
HM330X sensor;
uint8_t buf[30];
int PM25;

const char* str[] = {"sensor num: ", "PM1.0 concentration(CF=1,Standard particulate matter,
                     "PM2.5 concentration(CF=1,Standard particulate matter,unit:ug/m3): ",
                     "PM10 concentration(CF=1,Standard particulate matter,unit:ug/m3): ",
                     "PM1.0 concentration(Atmospheric environment,unit:ug/m3): ",
                     "PM2.5 concentration(Atmospheric environment,unit:ug/m3): ",
                     "PM10 concentration(Atmospheric environment,unit:ug/m3): ",
                    };

HM330XErrorCode print_result(const char* str, uint16_t value) {
    if (NULL == str) {
        return ERROR_PARAM;
    }
    Serial.print(str);
    Serial.println(value);
    return NO_ERROR1;
```

Command Palette - Ctrl-Shift-P

Assignment: L12_HelloParticle

- Notebook: schematic
- Fritzing diagram
- Wire your circuit
- Write the code

1. L12_01_HelloParticle
   - Blink the onboard LED (Pin D7)
2. L12_02_HelloNightLight
   - The anode of the photodiode is connected to Pin A0. Note, unlike an LED, the cathode (short pin) of the photodiode is connected to 3.3V.
   - The LED anode to Pin D4.
   - Using analogRead/digitalWrite, turn on the LED when photodiode is dark.
   - Using analogWrite, turn on LED slowly as room darkens
3. L12_03_HelloRes
   - Create code to determine the resolution (in bits) of read / write.
   - Use Serial Monitor via Command Palette

Particle Publish

One of the advantages of the Argon is seemless publishing to the Cloud.

EVENTS VITALS HEALTH CHECK

Search for events ADVANCED

NAME	DATA	DEVICE	PUBLISHED AT
particle/device/updat...	false	Lalonde	10/3/20 at 1:21:01 pm
spark/device/diagnost...	{"device":{"network":{"s...	Lalonde	10/3/20 at 1:21:00 pm
spark/device/app-hash	B665BE9CD4ABE921E3...	Lalonde	10/3/20 at 1:21:00 pm
Humidity	42.000000	Lalonde	10/3/20 at 1:20:58 pm
Pressure	29.780001	Lalonde	10/3/20 at 1:20:58 pm
Temperature	69.129997	Lalonde	10/3/20 at 1:20:58 pm
particle/device/updat...	false	Lalonde	10/3/20 at 1:20:58 pm
particle/device/updat...	true	Lalonde	10/3/20 at 1:20:58 pm
spark/device/last_reset	dfu_mode	Lalonde	10/3/20 at 1:20:58 pm
spark/status	online	Lalonde	10/3/20 at 1:20:58 pm

```
float temp, prs, hum;   // BME280 variables
String Temp, Prs, Hum;  // Strings to hold BME280 values

void loop() {
  Temp = String(temp);
  Prs = String(prs);
  Hum = String(hum);

  Particle.publish("Temperature", Temp, PRIVATE);
  Particle.publish("Pressure", Prs, PRIVATE);
  Particle.publish("Humidity", Hum, PRIVATE);
}
```

JSON

JSON (JavaScript Object Notation) is a lightweight data-interchange format. It is easy for humans to read and write. It is easy for machines to parse and generate. It is based on a subset of the JavaScript Programming Language Standard ECMA-262 3rd Edition - December 1999. JSON is a text format that is completely language independent but uses conventions that are familiar to programmers of the C-family of languages, including C, C++, C#, Java, JavaScript, Perl, Python, and many others. These properties make JSON an ideal data-interchange language.
JSON is built on two structures:

- A collection of name/value pairs. In various languages, this is realized as an object, record, struct, dictionary, hash table, keyed list, or associative array.
- An ordered list of values. In most languages, this is realized as an array, vector, list, or sequence.

JSON Parser Generator

Creating objects in JSON are straightforward but can be tedious. There is a JSON Parser available to simplify the process.

```
#include <JsonParserGeneratorRK.h>

void createEventPayLoad(float tempValue, float presValue, float humValue) {
  JsonWriterStatic<256> jw;
  {
    JsonWriterAutoObject obj(&jw);

    jw.insertKeyValue("Temperature", tempValue);
    jw.insertKeyValue("Pressure", presValue);
    jw.insertKeyValue("Humidity", humValue);
  }
  Particle.publish("env-vals",jw.getBuffer(), PRIVATE);
}
```

Assignment: L12_HelloParticle

1. L12_04_HelloPublish
   - Using Particle.publish() send the photodiode and LED values to the Particle Cloud
   - Additionally, send the same data using the JSON Generator

Servo Motors

A servo is any motor-driven system with a feedback element built in.
A servo motor basically has three core components:

- a DC motor,
- a controller circuit,
- a potentiometer or similar feedback mechanism.

Assignment: Servo.h library

There are a number of libraries that are automatically added into your Particle DeviceOS code, Servo.h is one of them.

1. Header
   - Servo myServo; - create object myServo of class Servo
2. void setup()
   - myServo.attach(pin) - attach the Servo object to a pin
3. void loop()
   - myServo.write(angle) - move servo to angle (in degrees)
   - myServo.read() - returns the current angle of the servo

Assignment: L13_Servo

- Notebook: schematic
- Fritzing diagram
- Wire your circuit
- Write the code

1. L13_01_Servo
   - Have your Servo cycle from 0 to 180 degrees
2. L13_02_ServoSine
   - Have the Servo move in a sine wave pattern
   - Add a button (using pinMode: INPUT_PULLDOWN) that starts and stops the motion.

SparkFun_Qwiic_Twist RGB Encoder

```
#include <SparkFun_Qwiic_Twist_Arduino_Library.h>
TWIST twist; //Create instance of this object

void setup() {
  Serial.begin(9600);
  Serial.println("Qwiic Twist Example");

  if(twist.begin() == false)
  {
    Serial.print("Twist does not appear to be connected.");
    Serial.println("Please check wiring. Freezing...");
    while(true);
  }
}
```

SparkFun_Qwiic_Twist Commands

- bool twist.begin() - initializes the sensor with basic settings and returns false if sensor is not detected
- int twist.getCount() - returns the number of indents the user has twisted the knob
- int twist.getDiff() - returns the difference between the last two getCount() calls
- bool twist.isMoved() - returns true if knob has been twisted
- int twist.timeSinceLastMovement() - returns the number of milliseconds since the last encoder movement
- bool twist.isClicked() - returns true if a click event has occurred
- int twist.timeSinceLastPress() - returns the number of milliseconds since the last button event (press and release)
- bool twist.isPressed() - returns true if button is currently being pressed
- void twist.setCount(pos) - set the encoder count to a specific pos
- void twist.setColor(R,G,B) - sets the color of the encoder.

Assignment: L13_Servo

- Notebook: schematic
- Fritzing diagram
- Wire your circuit
- Write the code

1. L13_03_Qwiic
   - Clone and place in <project folder>/<project name>/lib the appropriate library.
   - Print encoder position, only if Moved
   - Using ENUM, create 3 button pressed states lighting up different colors for each
   - Display time since last moved and last pressed
2. L13_04_QwiicServo
   - Create two states: OFF and ON. Red for OFF, Green for ON.
   - When OFF, encoder does nothing.
   - When ON, encoder moves Servo. Half rotation moves encoder from 0 to 180
   - When button is pressed and held, turning encoder changes ON color.

Too Much Time On My Hands

When the Particle Argon connects to the Particle Cloud, it synchronizes its clock to the current time.

```
void sync_my_time() {
  String DateTime, TimeOnly;
  char currentDateTime[25], currentTime[9];

  Time.zone(-7); // Set Time Zone to MDT(UTC-7)
  unsigned long cur=millis();

  // Request time synch from Particle Cloud
  Particle.syncTime();
  waitUntil(Particle.syncTimeDone);
}
```

Using Particle Time

```
// Get Current Time
DateTime = Time.timeStr();
TimeOnly = DateTime.substring(11,19);
Serial.println(DateTime);
Serial.println(TimeOnly);

// Using Time with Formatted Print Statements
DateTime.toCharArray(currentDateTime,25);
TimeOnly.toCharArray(currentTime,9);
Serial.printf("Date and time is %s\n",
    currentDateTime);
Serial.printf("Time is %s\n",currentTime);
```

Soil Moisture Sensors

Resistive Sensor

Capacitive Sensor

Installing Libraries

Assignment: L14_SoilMoisture

- Notebook: schematic
- Fritzing diagram
- Wire your circuit
- Write the code

1. L14_01_OLED
   - Install the Adafruit_SSD1306 library
   - NOTE: you have full 128x64 pixel access
   - Create sample code displaying your name and time to the OLED
2. L14_02_Moisture
   - Using the Capacitive Soil Moisture probe. In your notebook note the moisture readings when:
     - Empty Cup
     - Submerged in water to the notch
     - Dry Soil
     - Soil after watered
   - Display the moisture to the OLED with a Time-stamp

The Cloud

Cloud Computing
Servers
Virtual Desktop
Software Platform
Applications
Storage / Data
OS
Apps
Router
Switch
End User

MQTT: MQ Telemetry Transport

Adafruit.io

Let's create an Adafruit.io account

Assignment: L14_03_SubscribePublish

1. Modify the starter code for your Adafruit.io
2. Subscribe
   - Add a button to your Adafruit.io dashboard and connect it to a feed called buttonOnOff
   - Subscribe to the buttonOnOff and turn on the on board LED when pressed.
3. Publish
   - Publishing a random number to a feed once per minute (do not use a delay).
   - Create a line chart on your dashboard to display the random number.
4. Experiment with other blocks
   - Replace the button with a slider.
   - Control the brightness of an LED
   - Display data with other dashboard blocks.

Relays

- When a device (e.g. a pump) requires higher voltage ($> 5V$) or higher current, then a relay can be used as a switch for the device
- The relay is activated by a digital pin from the microcontroller.
  - However, as the relay requires 100mA from the digital pin, we will use a transistor switch to draw power directly from the USB connection.

Assignment: L14_04_PlantWater

PNP Emitter Follower

1. Integrate an 2N3906 Emitter Follower and Relay, as well as a BME280 and Display.
2. Publish soil moisture and room environmental data to a new dashboard
3. Automatically water your plant with the soil is too dry
   - Only turn on the pump for a very short period of time ($\frac{1}{2} sec$).
4. Integrate a button into your dashboard that manually waters the plant.

Seeed Sensors

Seeed Grove - Dust Sensor

Seeed Grove - Air Quality Sensor v1.3

Assignment: More L14

1. L14_05_PulseIn
   - Look up the pulseIn() command in the Arduino reference
   - Connect PWM pin to Analog input. Use pulseIn to measure length of PWM-pulse while varying voltage output with encoder.
2. L14_04_PlantWater (revisted): Integrate into your Plant Water project both Seeed sensors.
   - Look up the Seeed sensors online to see how they work.
   - Do not blindly copy the examples, only use the code you need.
   - By looking at the .cpp code, determine how to get a quantitative value for air quality, in addition to the qualitative level.
3. Include Hackster.io story

Negative Numbers

Question: How are negative numbers represented in binary?

Type	Storage size	Value range
char	1 byte	-128 to 127 or 0 to 255
unsigned char	1 byte	0 to 255
signed char	1 byte	-128 to 127
int	2 or 4 bytes	-32,768 to 32,767 or -2,147,483,648 to 2,147,483,647
unsigned int	2 or 4 bytes	0 to 65,535 or 0 to 4,294,967,295
short	2 bytes	-32,768 to 32,767
unsigned short	2 bytes	0 to 65,535
long	4 bytes	-2,147,483,648 to 2,147,483,647
unsigned long	4 bytes	0 to 4,294,967,295

Answer: Left-most bit is 1 to signify negative. But wait...

2's Compliment

2's compliment is used as it makes the math consistent.

Integer		2's Complement
Signed	Unsigned	
5	5	0000 0101
4	4	0000 0100
3	3	0000 0011
2	2	0000 0010
1	1	0000 0001
0	0	0000 0000
-1	255	1111 1111
-2	254	1111 1110
-3	253	1111 1101
-4	252	1111 1100
-5	251	1111 1011

The negative plus the positive equals zero.

Bitwise Operations

The following table lists the Bitwise operators supported by C. Assume variable 'A' holds 60 and variable 'B' holds 13, then –

Operator	Description	Example
&	Binary AND Operator copies a bit to the result if it exists in both operands.	(A & B) = 12, i.e., 0000 1100
|	Binary OR Operator copies a bit if it exists in either operand.	(A | B) = 61, i.e., 0011 1101
^	Binary XOR Operator copies the bit if it is set in one operand but not both.	(A ^ B) = 49, i.e., 0011 0001
~	Binary One's Complement Operator is unary and has the effect of 'flipping' bits.	(~A) = ~(60), i.e,. 1100 0011
<<	Binary Left Shift Operator. The left operands value is moved left by the number of bits specified by the right operand.	A << 2 = 240 i.e., 1111 0000
>>	Binary Right Shift Operator. The left operands value is moved right by the number of bits specified by the right operand.	A >> 2 = 15 i.e., 0000 1111

Bit Shifting

Logical Bit Shift

Arithmetic Bit Shift

BONUS: But what about Floating Point

Example:
$-36382.366 = -3.6382366 * 10^4 = 10000010111011110000100010111 10$

Electrically Erasable Programmable Read Only Memory

EEPROM emulation allows small amounts of data to be stored and persisted even across reset, power down, and user and system firmware flash operations. Since the data is spread across a large number of flash sectors, flash erase-write cycle limits should not be an issue in general.

```
len = EEPROM.length(); //available EEPROM bytes
// Argons have 4096 bytes of emulated EEPROM.
// Addresses 0x0000 through 0x0FFF

addr = 0x00AE;    //addr between 0 and len-1

val = 0x45;
EEPROM.write(addr, val);

value = EEPROM.read(addr);
```

Interrupts

Interrupts are a way to write code that is run when an external event occurs. As a general rule, interrupt code should be very fast, and non-blocking. This means performing transfers, such as I2C, Serial, TCP should not be done as part of the interrupt handler. Rather, the interrupt handler can set a variable which instructs the main loop that the event has occurred.

```
attachInterrupt(pin, function, mode);
```

Mode: defines when the interrupt should be triggered. Three constants are predefined as valid values:

- CHANGE to trigger the interrupt whenever the pin changes value,
- RISING to trigger when the pin goes from low to high,
- FALLING for when the pin goes from high to low.

L15_BEI Assignments

1. L15_01_ConvertStore
   - Convert random hex color into R, G, and B components using Bit Shifting and Bitwise AND.
     - First sketch out how this might be done in your lab notebook. Show to instructor.
     - Then, and only then, write the code.
   - Store the components of the color as bytes in the Argon's EEPROM
2. L15_02_RetrieveShow
   - Retrieve the color from EEPROM memory
   - Convert to Hex code
   - Display color in NeoPixel.
3. L15_03_Interrupt Create an interrupt Stop Button
   - Wire a button, a GREEN and a RED LED to your Argon
   - Using delays, blink your GREEN LED (once per second)
   - Using an Interrupt, when the button is pressed, the GREEN turns off and the RED lights up.

MPU6050 Accelerometer

- Data Output - 16 Bit
- Gyros range: $\pm$ 250 500 1000 2000 °/s
- Accel range: $\pm$ 2 $\pm$ 4 $\pm$ 8 $\pm$ 16g

- The interrupt pin lets the MPU be notified about available data. To reduce power consumption the processor can go into sleep mode, the interrupt can be used as a wake up.
- XDA and XCL refer to the I2C bus that the MPU-6050 controls, so it can read from slave devices such as magnetometers etc.

Accelerometers

Gravity and Orientation

$$a_y = g * cos(\theta)$$

Initializing MPU6050

```
// Begin I2C communications
Wire.begin();

// begin transmission to GY-521
Wire.beginTransmission(MPU_ADDR);

// Select and write to PWR_MGMT1 register
Wire.write(0x6B);
Wire.write(0); // set to 0 (wakes up MPU-6050)

// end transmission
Wire.endTransmission(true);
```

Initializing MPU6050

```
// Using Wire.requestFrom()
// Wire.requestFrom(address, quantity, stop)

Wire.beginTransmission(MPU_ADDR);
Wire.write(0x3B); // starting with register 0x3B
Wire.endTransmission(false); // keep active.

// Request and then read 2 bytes

int16_t accel_z, accel_z_h, accel_z_l      // 16-bit int
Wire.requestFrom(MPU_ADDR, 2, true);
accel_z_h = Wire.read(); // x accel MSB
accel_z_l = Wire.read(); // x accel LSB

accel_x = accel_z_h << 8 | accel_z_l;     // what happens if declared int instead?
```

Note, the data is stored in Big Endian Byte Order. The most significant byte (the "big end") of the data is placed at the byte with the lowest address. The rest of the data is placed in the next byte.

Assignment: L16_Motion

- Notebook: schematic
- Fritzing diagram
- Wire your circuit
- Write the code

1. L16_01_MPU6050
   - Connect the GY-521 and OLED
   - Read the memory addresses for X, Y, and Z acceleration
   - Convert the returned bytes to acceleration measured in G.
2. L16_02_AutoRotate
   - Create a Clock on your OLED
   - Use GY-521 to auto-rotate the OLED
3. L16_03_Airplane
   - Calculate pitch $\theta = asin(a_x)$
   - Calculate roll $\phi = atan2(a_y/a_z)$
4. L16_04_Shock
   - Store a_{tot} in an array every 10ms for 5s
   - Find and print the max value
   - Repeat

Pitch and Roll Improved

Figure 8. Three Axis for Measuring Tilt

$$\rho = \arctan\left(\frac{A_X}{\sqrt{A_Y^2 + A_Z^2}}\right)$$

$$\phi = \arctan\left(\frac{A_Y}{\sqrt{A_X^2 + A_Z^2}}\right)$$

$$\theta = \arctan\left(\frac{\sqrt{A_X^2 + A_Y^2}}{A_Z}\right)$$

Stepper Motors

28BYJ Stepper Motor

- 2048 steps per revolution
  - 32 steps per rotor revolution
  - Gear ratio 1:64
- Capable of 10-15 RPM (at 5V)
- ULN2003 Darlington Array driver

Stepper.h

- Stepper myStepper (spr,IN1,IN3,IN2,IN4)
- myStepper.setSpeed(speed)
- myStepper.step(steps)

ULN2003 Darlington Array

Assignment: L16_Motion

- Notebook: schematic
- Fritzing diagram
- Wire your circuit
- Write the code

1. L16_05_StepperGyro
   - Wire the Stepper Motor noting the order: IN1, IN3, IN2, IN4
   - Move the motor 2 rotations clockwise, pause, 1 rotation counter-clockwise, repeat.
2. L16_06_Gyro
   - Connect the GY-521 to your system
   - Obtain the z-axis rotation from the appropriate register on the GY-521.
   - Map the change in gyro position (signed 16-bit) to one revolution of the Stepper (signed 11-bit)
   - Move the stepper the amount of steps corresponding to the mapped gyro change.

Hall Effect Sensor

Discovered by Edwin Hall in 1879, the Hall Effect is the production of a voltage difference (the Hall voltage) across an electrical conductor, transverse to an electric current in the conductor and to an applied magnetic field perpendicular to the current.

Assignment: L16_Motion

- Notebook: schematic
- Fritzing diagram
- Wire your circuit
- Write the code

1. L16_07_Alarm
   - Connect Hall Effect Sensor, button, and Neopixel
   - Use the button to enable / disable alarm
   - When armed:
     - Green when magnet detected
     - Blinking Red when magnet not detected
2. L16_08_RPM
   - Place magnet on shaft of Lathe
   - Using Hall Sensor, measure time per rotation
   - Convert to rotations per minute
   - Display on Adafruit.io databoard
   - EXTRA: Create a jig to hold the sensor
   - EXTRA: Measure RPM on other equipment at FUSE.

Piezoelectric Elements

- The piezoelectric effect is the appearance of electrical potential (voltage) across the side of a crystal when subject to mechanical stress.
- Conversely, a crystal becomes mechanically stressed (deformed in shape) when a voltage is applied across opposite faces.
- By utilizing an analogRead(), the vibration (change in mechanical stress) can be monitored over time.

2-dimensional arrays

- Declare Array: int a[3][4] = {{0,1,2,3},{4,5,6,7},{8,9,10,11}};
- Set a Cell: a[1][2] = 7;
- Access a Cell: x = a[0][0];

Assignment: L16_Motion

- Notebook: schematic
- Fritzing diagram
- Wire your circuit
- Write the code

1. L16_09_Vibration
   - Connect the Piezo and a Button to your Argon
   - Executing a loop 4096 times:
     - Every 500μsec, collect piezoelectric data
     - Save the pizeo data and a time stamp (in seconds) to a 2-dimensional array
   - When the loop is complete, time stamp and data to a file.
   - Collect vibration data from Lathe, cellphone vibration, other machines at FUSE
   - Use Excel and the FFT Tutorial (Class_Slides) to resample graph data in frequency domain (this process will be reviewed as a class).

Load Cells

1. A load cell is a force transducer. It converts a force such as tension, compression, pressure, or torque into an electrical signal that can be measured and standardized. As the force applied to the load cell increases, the electrical signal changes proportionally. The most common types of load cells used are hydraulic, pneumatic, and strain gauge.
2. HX711 module is a precision 24-bit analog-to-digital converter (ADC) designed for weigh scales and industrial control applications to interface directly with a bridge sensor.

Wheatstone Bridge

1. The Wheatstone bridge was invented by Samuel Hunter Christie in 1833 and improved and popularized by Sir Charles Wheatstone in 1843.
2. A Wheatstone bridge is an electrical circuit used to measure an unknown electrical resistance by balancing two legs of a bridge circuit, one leg of which includes the unknown component.
3. The primary benefit of the circuit is its ability to provide extremely accurate measurements (in contrast with something like a simple voltage divider)

HX711A Library

```
#include "HX711.h"
HX711 myScale(DOUT,CLK);

void setup() {
  myScale.set_scale();
  delay(5000);        // let scale settle
  myScale.tare();     // set the tare weight (or zero)

  myScale.set_scale(cal_factor); //adjust calibration
}

void loop() {
// Using data from loadcell
// samples is the number of samples to average

offset = myScale.get_offset();
calibration = myScale.get_scale();

// rawData is the raw loadcell reading minus the offset
rawData = myScale.get_value(samples);

// value is the rawData divided by calibration
value = myScale.get_units(samples);

// more stable is short weight between readings
delay(5000);
}
```

Assignment: L16_Motion (Learn to Calibrate)

- Notebook: schematic
- Fritzing diagram
- Wire your circuit
- Write the code

1. L16_10_Scale
   - Set initial cal_factor to 1000 and measure calibration_weight
   - Revise cal_factor to get proper measurement in grams
   - Post data to Adafruit.io (once / min)
   - Send text via IFTTT

IFTTT

If This Then That, also known as IFTTT, is a freeware web-based service that creates chains of simple conditional statements, called applets.
An applet is triggered by changes that occur within other web services such as Gmail, Facebook, Telegram, Instagram, or Pinterest.

ThingSpeak Follow Along

We will be learning how to use Particle Webhooks to publish between cloud services. For this, you will need:

1. Particle Argon
2. BME280

JSON

JSON (JavaScript Object Notation) is a lightweight data-interchange format. It is easy for humans to read and write. It is easy for machines to parse and generate. It is based on a subset of the JavaScript Programming Language Standard ECMA-262 3rd Edition - December 1999. JSON is a text format that is completely language independent but uses conventions that are familiar to programmers of the C-family of languages, including C, C++, C#, Java, JavaScript, Perl, Python, and many others. These properties make JSON an ideal data-interchange language.
JSON is built on two structures:

- A collection of name/value pairs. In various languages, this is realized as an object, record, struct, dictionary, hash table, keyed list, or associative array.
- An ordered list of values. In most languages, this is realized as an array, vector, list, or sequence.

JSON Parser Generator

Creating objects in JSON are straightforward but can be tedious. There is a JSON Parser available to simplify the process.

```
#include <JsonParserGeneratorRK.h>

void createEventPayLoad(int moistValue, float tempValue, float presValue, float humValue,
      int waterED) {
  JsonWriterStatic<256> jw;
  {
    JsonWriterAutoObject obj(&jw);

    jw.insertKeyValue("Moisture", moistValue);
    jw.insertKeyValue("Temperature", tempValue);
    jw.insertKeyValue("Pressure", presValue);
    jw.insertKeyValue("Humidity", humValue);
    jw.insertKeyValue("Plant Watered", waterED);
  }
  Particle.publish("env-vals",jw.getBuffer(), PRIVATE);
}
```

ThingSpeak Dashboard

Step 1 - Create ThingSpeak Channel

ThingSpeak™ | Channels | Apps | Support | Commercial Use | How to Buy | Account | Sign Out

My Channels

New Channel

Search by tag

Name	Created	Updated
FUSEMakerspace Private Public Settings Sharing API Keys Data Import / Export	2020-01-09	2020-03-27 16:04
Home IoT Plant Watering Private Public Settings Sharing API Keys Data Import / Export	2020-04-16	2020-04-16 19:56
Dew Point Measurement Private Public Settings Sharing API Keys Data Import / Export	2020-04-16	2020-04-19 13:38
Home Weather Station Private Public Settings Sharing API Keys Data Import / Export	2020-04-17	2020-04-17 18:52

Help

Collect data in a ThingSpeak channel from a device, from another channel, or from the web.

Click **New Channel** to create a new ThingSpeak channel.

Click on the column headers of the table to sort by the entries in that column or click on a tag to show channels with that tag.

Learn to create channels, explore and transform data.

Learn more about ThingSpeak Channels.

Examples

- Arduino
- Arduino MKR1000
- ESP8266
- Raspberry Pi
- Netduino Plus

Upgrade

Need to send more data faster?

Need to use ThingSpeak for a commercial project?

Upgrade

Step 2 - Get API Key

ThingSpeak™ | Channels | Apps | Support | Commercial Use | How to Buy | Account | Sign Out

Dew Point Measurement

Channel ID: **1039626**
Author: mwa0000017234878
Access: Private

Private View | Public View | Channel Settings | Sharing | API Keys | Data Import / Export

Write API Key

Key: BK1I6D1UTGPQ5B5H

Generate New Write API Key

Read API Keys

Key: SQG42O05TWWWF26R

Note:

Save Note | Delete API Key

Add New Read API Key

Help

API keys enable you to write data to a channel or read data from a private channel. API keys are auto-generated when you create a new channel.

API Keys Settings

- **Write API Key**: Use this key to write data to a channel. If you feel your key has been compromised, click **Generate New Write API Key.**
- **Read API Keys**: Use this key to allow other people to view your private channel feeds and charts. Click **Generate New Read API Key** to generate an additional read key for the channel.
- **Note**: Use this field to enter information about channel read keys. For example, add notes to keep track of users with access to your channel.

API Requests

Write a Channel Feed

```
GET https://api.thingspeak.com/update?api_key=BK1I6D1UTGPQ5B
```

Read a Channel Feed

```
GET https://api.thingspeak.com/channels/1039626/feeds.json?a
```

Read a Channel Field

```
GET https://api.thingspeak.com/channels/1039626/fields/1.jso
```

Read Channel Status Updates

```
GET https://api.thingspeak.com/channels/1039626/status.json?
```

Learn More

Step 3 - Create Webhook

From `console.particle.io`:

Step 4 - Add JSON Data

Personal

Integrations > Edit Integration

WEBHOOK BUILDER CUSTOM TEMPLATE

Read the Particle webhook guide

Event Name
env-vals

URL
https://api.thingspeak.com/update

Request Type
POST

Request Format
Web Form

Device
Herbert

Advanced Settings

For information on dynamic data that can be sent in any of the fields below, please visit our docs.

FORM FIELDS

Default Custom

api_key	xxxxxxxxxxxxxxxxxx
field1	{{{Moisture}}}
field2	{{{Temperature}}}
field3	{{{Pressure}}}
field4	{{{Humidity}}}
field5	{{{Plant Watered}}}

Step 5 - Particle Cloud Events

Step 6 - Create Channel

Home IoT Plant Watering

Channel ID: **1039355**
Author: mwa0000017234878
Access: Public

Plant Watering in Home IoT Classroom

Private View | Public View | Channel Settings | Sharing | API Keys | Data Import

Channel Settings

Percentage complete	50%
Channel ID	1039355
Name	Home IoT Plant Watering
Description	Plant Watering in Home IoT Classroom
Field 1	Moisture ☑
Field 2	Temperature ☑
Field 3	Pressure ☑
Field 4	Humidity ☑
Field 5	Watered ☑
Field 6	☐
Field 7	☐
Field 8	☐
Metadata	JSON

Help

Channels
eight field
status dat
visualize i

Chanr

- Per
cha
cha
- Cha
- Des
- Fiel
cha
- Met
- Tag
- Lin
Thi
- Sho
- Vid
info

Step 7 - Create Dashboard

You can change the colors of your lines, by editing the graph. The hex codes are found at `https://htmlcolorcodes.com/color-picker/`

NCD.io ControlEverywhere

NCDio TMG3993 Proximity/Color Sensor

- From Address 0x94
- Request 9 bytes
  - Byte 0 / 1 - LSB / MSB of Infrared Luminance
  - Byte 2 / 3 - LSB / MSB of Red Luminance
  - Byte 4 / 5 - LSB / MSB of Green Luminance
  - Byte 6 / 7 - LSB / MSB of Blue Luminance
  - Byte 9 - Proximity

TMG3993 Initialization

```
  Serial.println("Initializing TMG3993");
  Wire.beginTransmission(Addr);
  // Select Enable register
  Wire.write(0x80);
  // Power ON, ALS enable, Proximity enable, Wait enable
  Wire.write(0x0F);
  Wire.endTransmission();

  Wire.beginTransmission(Addr);
  // Select ADC integration time register
  Wire.write(0x81);
  // ATIME : 712ms, Max count = 65535 cycles
  Wire.write(0x00);
  Wire.endTransmission();

  Wire.beginTransmission(Addr);
  // Select Wait time register
  Wire.write(0x83);
  // WTIME : 2.78ms
  Wire.write(0xFF);
  Wire.endTransmission();

  Wire.beginTransmission(Addr);
  // Select control register
  Wire.write(0x8F);
  // AGAIN is 1x
  Wire.write(0x00);
  Wire.endTransmission();
}
```

NCDio ACD121C MQ9 CO Sensor

12-Bit Analog to Digital Conversion

- From Address 0x00
- Request 2 bytes (raw_adc)
  - Byte 0 - MSB
  - Byte 1 - LSB
- CO (ppm) $= \frac{1000}{4096} * raw_adc + 10$

NCDio ACD121C MQ131 Ozone Sensor

12-Bit Analog to Digital Conversion

- From Address 0x00
- Request 2 bytes (raw_adc)
  - Byte 0 - MSB
  - Byte 1 - LSB
- O_3 (ppm) $= \frac{1.99}{4095} * raw_adc + 0.01$

NCDio PECMAC Current Sensor

- 1 to 8 channels
- Full range between 10 and 100 amps
- Simple to use. Simply run an AC power wire through the opening of the current sensor. This controller will read the magnetic field inducted onto the current sensor and provide you with a real-world current measurement value that is 98 percent accurate (prior to calibration).

Pointers

1. A pointer is a variable whose value is the address of another variable.
2. When you declare a pointer, the $*$ symbol denotes that this variable is a pointer variable. For example:
   - Pointer to an Integer: int *ptr;
3. Reference operator (&) gives the address of a variable.
4. To get the value stored in the memory address, we use the dereference operator ($*$).

Pointers

```
int data = 13;
int data2;
int *ptr;

void setup() {
  Serial.begin(9600);
  delay(1000);
  ptr = &data;          //point ptr to the memory location of data
  data2 = *ptr;         //set data2 to value of data (13)

  // Print the Value and Address of the Variables
  Serial.printf("Variable         Value      Address \n");
  Serial.printf("  data            %i       0x%X   \n",data, &data);
  Serial.printf("  ptr           0x%X       0x%X   \n",ptr, &ptr);
  Serial.printf("  data2           %i       0x%X   \n",data2,&data2);
}
```

```
Serial monitor opened successfully:
Variable          Value       Address
  data              13        0x2003E380
  ptr          0x2003E380     0x2003E3F4
  data2             13        0x2003E3F0
```

Finding Average of an Array

```
// This function finds the average of an array
// The array is passed to it as a pointer

float getAve(int *array,int size) {
  int j;
  float total=0;
  for(j=0;j<size;j++) {
    total += array[j];
  }
  return total/size;
}
```

Finding Average of Arrays in Action

```
int xArray[4], yArray[256];
int *pointerX, *pointerY;
float average;
int i, sizeX, sizeY;

void setup() {
  pointerX=&xArray[0];
  sizeX=sizeof(xArray)/4;
  pointerY=&yArray[0];
  sizeY=sizeof(yArray)/4;

  for(i=0;i<sizeX;i++) {
    xArray[i] = random(0,255);
  }
  for(i=0;i<sizeY;i++) {
    yArray[i] = random(256,512);
  }

  average = getAve(pointerX, sizeX);
  average = getAve(pointerY, sizeY);
```

```
Array X Average = 162.50
Array Y Average = 388.35
xArray[0] value: 173, *pointerX:     173, pointerX:   0x2003E3DC
xArray[1] value: 179, *(pointerX+1): 179, pointerX+1: 0x2003E3E0
xArray[2] value: 110, *(pointerX+2): 110, pointerX+2: 0x2003E3E4
xArray[3] value: 188, *(pointerX+3): 188, pointerX+3: 0x2003E3E8
```

Struct datatype and Member Operators

```
struct geo {
  float lat;
  float lon;
  int alt;
  };
geo myLoc;
geo *ptLoc;

void setup() {
  Serial.begin(9600);
  delay(500);

  ptLoc = &myLoc;
  myLoc.lat = 35.120606;
  myLoc.lon = -106.65818;
  myLoc.alt = 1517;

  Serial.printf("Location: lat %f, lon %f, alt %i  \n",myLoc.lat,myLoc.lon,myLoc.alt);
  Serial.printf("Location: lat %f, lon %f, alt %i \n",ptLoc->lat,ptLoc->lon,ptLoc->alt);
}
```

The . (dot) operator and the $->$ (arrow) operator are used to reference individual members of structures.

- The dot operator is applied to the actual object.
- The arrow operator is used with a pointer to an object.

Linked Lists and Doubly Linked Lists

Inserting a "cell" into an Array

Inserting a "cell" into a Linked List

Capstone Projects

Intent:

- Based on a direct observation or a need expressed by one of our guest speakers.
- Original work demonstrating the skills obtained in this class.
- Demonstrate the ability to work as part of a team.
- A pitch to potential employers or investors.

Guidelines:

- Break class into 3 or 4 teams.
- Practical application of smart home, manufacturing, city environment or immersive entertainment.
- Needs to include a Cloud Dashboard component.
- Project will include a video presentation as well as a Hackster.io post.

Previous capstone projects can been found at: `https://www.youtube.com/playlist?list=PL0t2Pk5ETDgxfVptdyr6xbL6MW1-5CJey`

Capstone Project Timeline

1. Select Capstone teams (Aug 12)
2. Teambuilding exercise with Sue/Esteban (Aug 12)
3. Review of Rev 0 ideas with instructors (Aug 20)
4. Start work on CapStone (Aug 26)
5. Videos due to Digital Media (Sept 4)
6. Employer Roundtable (Sept 11)

The Big Question: What about main()

```
#include <Arduino.h>

extern "C" int main(void)
{
#ifdef USING_MAKEFILE

  // To use Teensy 3.0 without Arduino, simply put your code here.
  // For example:

  pinMode(13, OUTPUT);
  while (1) {
    digitalWriteFast(13, HIGH);
    delay(500);
    digitalWriteFast(13, LOW);
    delay(500);
  }


#else
  // Arduino's main() function just calls setup() and loop()....
  setup();
  while (1) {
    loop();
    yield();
  }
#endif
}
```

WORK
IN PROGRESS

Thevenin Equivalent Circuits

Léon Charles Thévenin (30 March 1857 – 21 September 1926) was a French telegraph engineer who extended Ohm's law to complex circuits.

Any combination of batteries and resistances with two terminals can be replaced by a single voltage source V_{th} and a single series resistor R_{th}.

Equivalent Circuit

Useful relationships