
ELF & Dynamic Linker


CS ~~240~~ 340LX

Motivation


How we ran programs on Pi so far




./labs/../your-lab-directory




./libpi



test.c
my-driver.c
my-asm.S
Compile
gpio.c
uart.c
kmalloc.o
./labs/../your-lab-directory
./libpi




./labs/../your-lab-directory




./libpi



ELF!!
test.o
my-driver.o
my-asm.o
gpio.o
uart.o
kmalloc.o
./labs/../your-lab-directory
./libpi



./labs/../your-lab-directory



./libpi


test.o
my-driver.o
libpi.a
my-asm.o





ELF Executable


test

ELF Executable

Up to this point, nothing different from the “usual” way





typedef struct {
unsigned char e_ident[16];
uint16_t e_type;
uint16_t e_machine;
uint32_t e_version;
uint64_t e_entry;
uint64_t e_phoff;
uint64_t e_shoff;
uint32_t e_flags;
uint16_t e_ehsize;
uint16_t e_phentsize;
uint16_t e_phnum;
uint16_t e_shentsize;
uint16_t e_shnum;
uint16_t e_shstrndx;
} Elf64_Ehdr;
ET_REL | ET_EXEC | ET_DYN
EM_ARM | EM_386 | EM_x86_64 | ...
EV_CURRENT
0 1 2 3 4 5 6 7 8 15
0x7f E L F ...
EI_CLASS
EI_DATA
EI_VERSION
EI_OSABI
EI_ABIVERSION
EI_PAD
Header
Executable header
Program headers
Program header
PF_X | PF_W | PF_R | ...
PT_LOAD | PT_DYNAMIC | PT_INTERP | ...
typedef struct {
uint32_t p_type;
uint32_t p_flags;
uint64_t p_offset;
uint64_t p_vaddr;
uint64_t p_paddr;
uint64_t p_filesz;
uint64_t p_memsz;
uint64_t p_align;
} Elf64_Phdr;
Sections
Section
Important sections:
.interp
.init
.plt
.text
.fini
.rodata
.data
.bss
.shstrtab
SHF_WRITE | SHF_ALLOC | SHF_EXECINSTR | ...
SHT_PROGBITS | SHT_SYMTAB | SHT_STRTAB
| SHT_RELA | SHT_DYNSYM | SHT_DYNAMIC | ...
typedef struct {
uint32_t sh_name;
uint32_t sh_type;
uint64_t sh_flags;
uint64_t sh_addr;
uint64_t sh_offset;
uint64_t sh_size;
uint32_t sh_link;
uint32_t sh_info;
uint64_t sh_addralign;
uint64_t sh_entsize;
} Elf64_Shdr;
Section headers
Section header



Header
Program headers
Sections
Section
Section headers
REMOVE
REMOVE
KEEP →
.rodata
.data
.bss


test.bin


Raw binary (just .text, .rodata, .data)





test.bin


Unix-side
Bootloader
Your Computer
test.bin
Pi-side
Bootloader
0x8000
RAM
Raspberry Pi



test.bin
Pi-side
Bootloader
RAM
Raspberry Pi





Main Problem: Redundancy
(+ can't run "normal" executables, can't use external libraries, etc etc)



Raspberry Pi


libpi.so
test1.bin
libpi.a
test2.bin
libpi.a
test3.bin
libpi.a
Pi-side Bootloader
libpi.a
RAM
Raspberry Pi


test1.bin
test2.bin
test3.bin
libpi.so
Pi-side Bootloader
RAM
FAT32
Raspberry Pi



test1.bin
test2.bin
test3.bin
Dynamically link during runtime!
Pi-side Bootloader
RAM
libpi.so
FAT32
Raspberry Pi

test1.bin

test2.bin

test3.bin

Dynamically link during runtime!



Raspberry Pi


Full ELF executables

test1.elf


test2.elf

test3.elf

Dynamically link during runtime!
+
Read ELF files, not stripped binary!



Raspberry Pi



test1.elf
test2.elf
test3.elf
Problem for today: too much time wasted on compile -> move to pi
Pi-side Bootloader + Dynamic Linker + ELF Parser
RAM
libpi.so
FAT32
Raspberry Pi

test1.elf

test2.elf


test3.elf

Step 1. Just use the original bootloader




Raspberry Pi

Step 2. Move the ELF executables to FAT32




Step 3. Compile our
ELF parser + dynamic linker
in our usual way (stripped binary)

ELF_Parser_Dynamic_Linker.bin



Step 4. Send our ELF parser + dynamic linker to the bootloader, have it read the ELF file from the FAT32



Results

ELF parsing

Shared lib loading

Jumping to entry point

Auto-resolving symbols during runtime (printf, clean_reboot, _cstart, ….)

```
[MY-ELF] ELF file loaded into memory (0x0 - 0xfc0)
[MY-ELF] ELF file loaded into memory (0x10000000 - 0x10015e20)
[MY-ELF] ELF file magic number verified
[MY-ELF] ELF file type verified
[MY-ELF] ELF file architecture verified
[MY-ELF] ELF file magic number verified
[MY-ELF] ELF file type verified
[MY-ELF] ELF file architecture verified
[MY-ELF] BSS section zero-initialized (0x854 - 0x858)
[MY-ELF] BSS section zero-initialized (0x100101cc - 0x100107e4)
[MY-DL] Identifying ELF32 dynamic sections...
[MY-DL] Found dynamic sections: .hash: 0x744, .dynsym: 0x5bc, .dynstr: 0x69c, .g
[MY-DL] Identifying ELF32 dynamic sections...
[MY-DL] Found dynamic sections: .hash: 0x1000ea38, .dynsym: 0x1000ce10, .dynstr:
[MY-DL] Resolving undefined symbols in shared library...
[MY-DL] Resolving symbol <notmain>...
[MY-DL] Found symbol: notmain at 0x524
[MY-DL] Performing load-time relocation of all the symbols in shared library
[MY-ELF] Entry point: 0x500
[MY-ELF] Branching to the entry point
[MY-DL] Dynamic linker: Unresolved symbol encountered: <_cstart>. Dynamic linker
[MY-DL] Resolving symbol <_cstart>...
[MY-DL] Found symbol: _cstart at 0x10007ed0
[MY-DL] Dynamic linker: Resolved symbol _cstart to 0x10007ed0
[MY-DL] Dynamic linker: Unresolved symbol encountered: <printk>. Dynamic linker
[MY-DL] Resolving symbol <printk>...
[MY-DL] Found symbol: printk at 0x10006e8c
[MY-DL] Dynamic linker: Resolved symbol printk to 0x10006e8c
BSS var: 0
Hello, world!
[MY-DL] Dynamic linker: Unresolved symbol encountered: <clean_reboot>. Dynamic l
[MY-DL] Resolving symbol <clean_reboot>...
[MY-DL] Found symbol: clean_reboot at 0x10007e80
[MY-DL] Dynamic linker: Resolved symbol clean_reboot to 0x10007e80
DONE!!!
```

Enjoy!