External Project Doc Automated DR Failover Ansible Playbook

File Edit View Insert Format Tools Extensions Help

# Automated DR Failover - Ansible Playbook

## Scope of Work

This scope defines the scenarios that are required for centralized management and Hypercore cluster settings.

## User Stories – Automated DR Playbook

These are the core user stories that will steer the design and development of an Ansible playbook for Scale Computing HyperCore Collection. During the project execution we will be refining these stories to better suit the identified use cases and REST API constraints.

***HyperCore Automated DR Failover***

Following user stories should be supported:

1. As a user I would like to run an Ansible playbook against my primary and DR HyperCore clusters on a pre-defined schedule that detects if the primary cluster is online or offline, and automatically clones and powers on DR replicas on the remote system if primary is offline:
    a. A rough outline of playbook operations includes:
        i. Get remote cluster information
        ii. Check if the primary cluster is connected (replication connection) to the DR cluster - from DR target /rest/v1/RemoteClusterConnection
            1. If connected (connectionStatus": "ESTABLISHED",), the playbook should end (failover not required)
        iii. Further Checks if the primary cluster is online
            1. This can be done via pinging the IP addresses of all nodes in the cluster.
                a. Open question: is there a better, single source of truth to ping?
            2. If primary cluster does not respond to first ping, retry a user settable number of additional times (with a 5 second delay per ping)
            3. **If primary cluster can be pinged, the playbook should end**
        iv. Check if the DR cluster is online
            1. This can be done via pinging the IP addresses of all nodes in the cluster.
                a. Open question: is there a better, single source of truth to ping?
                b.
            2. If DR cluster does not respond to first ping, retry a user settable number of additional times (with a 5 second delay per ping)
            3. We can also read the conditions that are set on the target (DR) cluster to assess the health/availability of DR
                a. GET /Condition
                i. If the following conditions are set, do not attempt to

Justin Cinkelj
4:09 PM Jan 8
**Add:** *"Some steps to implement this role Test infra setup - MUST 2 VSNSs, HC3 v9.4, setup replication - MUS..."*

Justin Cinkelj
3:44 AM Dec 12
Why is this different from a.ii "DR cluster /rest/v1/RemoteClusterConnection"?
Because we need to ping all N nodes?

What if only some DR nodes respond?

Dragan Radolović
10:11 AM Dec 17
should we check cluster's IP or VM's IPs - all nodes should be available on the cluster..
This can be resolved with ping - there is an API endpoint to check this. If single node is not available then we cannot access and check health. - Check disk availability etc.

Dave Demlow
7:22 AM Dec 3