


\*. (20 points) The speed of sound in steel is 5941 m/s. Steel has a density of around 7900 kg/m<sup>3</sup> (depends somewhat on the alloy content).

a. (2 points) Based on this information, what is the bulk modulus of steel?

$$v = \sqrt{B/\rho} \Rightarrow B = \rho v^2 = (7900 \text{ kg/m}^3)(5941 \text{ m/s})^2 = 2.788 \times 10^{11} \text{ Pa}$$

b. (8 points) A steel rod of cross-sectional area  $A$  is placed on the  $x$ -axis. The following sound pulse is sent through the steel rod in the  $+x$  direction:

$$f(x) = s(x, 0) = \begin{cases} s_m(1 - |x|/a) & |x| < a \\ 0 & |x| \geq a \end{cases}$$



Determine the total energy of this pulse.

$$p_u = \frac{1}{2} B \left( \frac{\partial s}{\partial x} \right)^2 = \frac{1}{2} B \left( \pm s_m/a \right)^2 = \frac{1}{2} B s_m^2 / a^2 \quad (-a \leq x - vt \leq +a)$$

$$p_k = \frac{1}{2} \rho \left( \frac{\partial s}{\partial t} \right)^2 = \frac{1}{2} \rho \left( -v \frac{\partial s}{\partial x} \right)^2 = \frac{1}{2} \underbrace{\rho v^2}_B \left( \frac{\partial s}{\partial x} \right)^2 = p_u$$

$$p_e = p_u + p_k = B s_m^2 / a^2 \quad (-a \leq x - vt \leq +a)$$

$$E = \int p_e dV = p_e (2a)(A) = 2 B s_m^2 A / a$$

c. (10 points) Now suppose a sinusoidal sound wave with frequency 440 Hz is sent through steel with a sound level of 100 dB. Calculate  $s_m$  and  $\Delta p_m$  for this sound wave.

$$\omega = 2\pi f = 2764.6 \text{ rad/s}$$

$$\beta = (10 \text{ dB}) \log_{10} (\langle I \rangle / I_0) = 100 \text{ dB}$$

$$\Rightarrow \langle I \rangle = I_0 10^{10} = 10^{-2} \text{ W/m}^2$$

$\uparrow$   
 $10^{-12} \text{ W/m}^2$

$$\langle I \rangle = 10^{-2} \text{ W/m}^2 = \frac{1}{2} \rho \omega^2 s_m^2 v$$

$$\Rightarrow s_m = \sqrt{\frac{2\langle I \rangle}{\rho \omega^2 v}} = \sqrt{\frac{2(10^{-2} \text{ W/m}^2)}{(7900 \text{ kg/m}^3)(2764.6 \text{ rad/s})^2(5941 \text{ m/s})}}$$

$$= 7.4669 \text{ nm}$$

$$\Delta p_m = B s_m k = \rho v^2 s_m k = \rho \omega s_m v$$

$$= (7900 \text{ kg/m}^3)(2764.6 \text{ rad/s})(7.4669 \times 10^{-9} \text{ m})(5941 \text{ m/s})$$

$$= 968.85 \text{ Pa} \quad (\sim 1\% \text{ atm})$$