SERVER PROGRAM

```
#include<stdio.h>
#include<sys/socket.h>
#include<netinet/in.h>
#include<string.h>
#include<arpa/inet.h>
#include<unistd.h>
void main()
{
int server,newSock;
char buffer[1024];
struct sockaddr_in servAddr;
struct sockaddr_storage store;
socklen_t addrsize;
server=socket(AF_INET,SOCK_STREAM,0);
servAddr.sin_family=AF_INET;
servAddr.sin_port=htons(6265);
servAddr.sin_addr.s_addr=inet_addr("127.0.0.1");
bind(server,(struct sockaddr*)&servAddr,sizeof(servAddr));
if(listen(server,5)==0)
printf("listening\n");
else
printf("error/n");
newSock=accept(server,(struct sockaddr*)&store ,&addrsize);
recv(newSock,buffer,1024,0);
printf("2.data recieved:%s",buffer);
strcpy(buffer,"hi this is server/n");
send(newSock,buffer,19,0);
close(newSock);
close(server);
}
```

CLIENT PROGRAM

```
#include <stdio.h>
#include <sys/socket.h>
#include<netinet/in.h>
#include<string.h>
#include<arpa/inet.h>
#include<unistd.h>
void main()
{
int client;
char buffer[1024];
struct sockaddr_in servAddr;
socklen_t addrSize;
client=socket(AF_INET,SOCK_STREAM,0);
servAddr.sin_family=AF_INET;
servAddr.sin_port=htons(6265);
servAddr.sin_addr.s_addr=inet_addr("127.0.0.1");
connect(client,(struct sockaddr*)&servAddr,sizeof servAddr);
printf("/Sending Data to server\n");
strcpy(buffer,"Hi This is a client\n");
send(client,buffer,19,0);
recv(client,buffer,1024,0);
printf("4.data received;%s",buffer);
close(client);
}
```

Output

Client

Sending Data to server

Data received: hi this is server

Server

Listening

Data received: Hi This is a client