

Aspect/Modifier Classification Analysis

Project Links ¶

Below is the link for the GitHub project page.

[Github link \(https://github.com/ddey117/ABSA_Project_4\)](https://github.com/ddey117/ABSA_Project_4)

Import research papers for development of parser logic. Includes pdf links for spaCy research paper as well as VADER sentiment intensity analyzer. Much work has been done on aspect based sentiment analysis. Please feel free to check out some previous work in the link below.

[Research Papers \(https://github.com/ddey117/ABSA_Project_4/tree/main/research_papers\)](https://github.com/ddey117/ABSA_Project_4/tree/main/research_papers)

For another way to navigate of my overall project, please feel free to check out a HTML version of my project overview at the link below. There is also a link in this directory to see an example of what exactly a Turk worker was looking at when they were labeling data for this project.

[html project directory \(https://github.com/ddey117/ABSA_Project_4/tree/main/html\)](https://github.com/ddey117/ABSA_Project_4/tree/main/html)

Overview

The target for this project is an established e-commerce business with a large amount of review data, such as Amazon.com or other online retailers. The goal of this project is to take advantage of technology and models provided by Spacy combined with a pretrained sentiment intensity classifier provided by the NLTK toolkit in order to perform more fine grained sentiment analysis at scale in an efficient manner. This project takes advantage of the parsing and part of speech tagging capabilities of Spacy's pipeline in order to extract aspect/opinion/sentiment triplets. After the aspects are identified, they can be grouped using unsupervised machine learning clustering techniques; in this case k-means clustering for model speed and simplicity. The business can use the finished product to quickly transform a large amount of informal review data (text data from reviews that may ramble for pages) and transform it into helpful graphs in order to tune into a small number of categories and help funnel resources into areas where they are most needed. Amazon Turk was taken advantage of to crowd source human labels to analyze the performance of the model.

Data Exploration Notebook



Author: Dylan Dey

The Author can be reached by email: ddey2985@gmail.com (<mailto:ddey2985@gmail.com>)



Buisness Problem

Aspect
Category



Sentiment



Customer Service



Value



quality



design

Sentiment analysis involves computationally identifying and categorizing the sentiment expressed by an author in a body of text. It has a wide range of applications in industry from stock speculation using sentiment expressed in news and blogs, to identifying customer satisfaction from their reviews and social media posts.

Today, most e-commerce website designs include a section where their customers can post reviews for products or services. Customers are free to write how they feel about fine grained aspects of a product at length. From a business perspective, very valuable information can be extracted from this section, such as customers' opinion on a product, understanding of a product, etc..

On Amazon.com the rating can be between 1 and 5 where 1 is the worst and 5 is the best. A customer can leave as lengthy of a review as they wish about a product to explain why a given rating was posted. For example, a customer may give a product a low rating because they didn't like someone they spoke to in customer service but liked everything else about the product. In typical sentiment analysis, these kinds of nuances would be missed since it could only be determined if the overall body of the review contained positive, neutral, or negative sentiment. Valuable information would be left on the table.

There is potentially a disconnect from the amazon review ratings, and the overall sentiment of the body text explaining the review, especially if you begin to break down the text into smaller aspects. Thus, Aspect Based Sentiment Analysis (ABSA) was chosen to see if a deeper understanding of each product can be gained by breaking down each review into aspect categories to be paired with predicted sentiment, which will then be compared with the overall rating (1-5).

It is often difficult to efficiently get useful data from a large collection of text data. A lot of e-commerce websites have thousands of reviews and more incoming all of the time. Thousands of reviews with hundreds of words of mostly unhelpful information seems fairly unmanageable to most companies. While the reviews are rather informal, if they are carefully broken down there is information worth saving before generalizing again for efficiency. Aspect Based Sentiment Analysis can transform a messy collection of thousands of informal reviews into a neat and manageable collection of a few aspect categories, in this case 4 different categories using the out of box Aspect/Opinion/Sentiment Triplet Extractor. Each category will have an associated degree of sentiment related to it, and therefore graphics can easily be prepared and presented to digest more precisely what it is that customers do and do not like about a product in a quickly digestible format in real time. By breaking it down into these categories, say for example Product Design, Value, Quality, and Customer Support, the mass of text data has now been transformed into a numerical representation of sentiment towards broad categories of a product that can be directly improved upon by the company. If a product scores very high sentiment for value and design b

but lower scores for customer support, then a company knows it doesn't need to invest more money into improving the product and actually needs to focus on improving how its forward facing employees interact with customers.

The Data

Helpful links:

[ReadMe file for Amazon Product Reviews \(https://s3.amazonaws.com/amazon-reviews-pds/readme.html\)](https://s3.amazonaws.com/amazon-reviews-pds/readme.html) | [MetaData \(https://s3.amazonaws.com/amazon-reviews-pds/tsv/index.txt\)](https://s3.amazonaws.com/amazon-reviews-pds/tsv/index.txt)

The Amazon Customer Reviews (Product Reviews) contains over 130+ million customer reviews available to researchers in TSV files in the amazon-reviews-pds S3 bucket in AWS US East Region, as per the provided readme file. The reviews were collected from 1995 to 2015. See the provided link for associated metadata. This project focuses on the dataset given by pulling

“https://s3.amazonaws.com/amazon-reviews-pds/tsv/amazon_reviews_us_Electronics_v1_00.tsv.gz” (https://s3.amazonaws.com/amazon-reviews-pds/tsv/amazon_reviews_us_Electronics_v1_00.tsv.gz%E2%80%9D) from the S3 bucket.

Product_id "[B0001FTVEK](https://www.amazon.com/Sennheiser-RS120-Wireless-Headphones-Charging/dp/B0001FTVEK)" (<https://www.amazon.com/Sennheiser-RS120-Wireless-Headphones-Charging/dp/B0001FTVEK>) was chosen to showcase the triplet extractor as it had a large amount of verified reviews and a pair of headphones seemed like a reasonable choice for aspect based sentiment analysis.

Clean Data

Text data trends towards exponential growth with increasing dataset size. Therefore, text cleaning and preprocessing was a major consideration of this project. Please refer to my [Text Preprocessing Toolset \(https://github.com/ddey117/preprocess_ddey117\)](https://github.com/ddey117/preprocess_ddey117) that I created to use for this and other projects that involve text data preprocessing.

Unlabeled Data Created Through Unsupervised Learning

This project showcases an out of box product for extracting opinion/aspect/sentiment triplets from a large amount of messy text data and converting it into a neat set of categories for analysis. To do this, however, it takes advantage of some simple clustering techniques from the sklearn cluster library. For this project, kmeans clustering was chosen for speed and simplicity. Error analysis will be discussed later in more detail in regards to how the model performs with clustering the reviews appropriately into categories and what issues it may run into when parsing internet language. Error analysis for the [SentimentIntensityClassifier \(https://www.nltk.org/howto/sentiment.html\)](https://www.nltk.org/howto/sentiment.html) offered by the Natural Language ToolKit (NLTK library) will be tested against this 'newly' generated data from my unsupervised learning will be performed by comparing to a separate set of hand labeled aspect/modifier pairs by humans in an experimental setting.

experimental setup

Using the following [Turk Form HTML \(html/Turk_Instructions.html\)](html/Turk_Instructions.html) I crowdsourced some labels from humans using Amazon Mechanical Turk to compare to my model using the SentimentIntensityAnalyzer for each aspect/modifier pair extracted from the Amazon reviews. Amazon Mechanical Turk works by quickly dispersing large amounts of data to a large number of people in order to complete simple tasks for a reward. This experiment was set up to reward a penny for each aspect/modifier pair labeled for sentiment from very negative to very positive with an option for NA from a drop down menu (see html above for reference). In total, 410 workers submitted 6107 non-null aspect/opinion pairs for sentiment intensity pertaining to 1438 unique aspects. Duplicate pairs of aspect/opinion pairs were included to inspect variance of submission from human labels and machine labels for each opinion pair. No qualifications or screening was put in place before the workers were chosen, but I did review sections of the data and accept or reject what seemed reasonable.

All labels were generated using my triplet extractor on the dataset describing Product_id "B0001FTVEK" (<https://www.amazon.com/Sennheiser-RS120-Wireless-Headphones-Charging/dp/B0001FTVEK>) and randomized for different aspect/modifier pairs before sending out to humans for rating for sentiment.

[Amazon Product Reviews ReadME \(https://s3.amazonaws.com/amazon-reviews-pds/readme.html\)](https://s3.amazonaws.com/amazon-reviews-pds/readme.html)
| [Amazon Product Reviews MetaData \(https://s3.amazonaws.com/amazon-reviews-pds/tsv/index.txt\)](https://s3.amazonaws.com/amazon-reviews-pds/tsv/index.txt) | [Sennheiser-RS120-Wireless-Headphones \(https://www.amazon.com/Sennheiser-RS120-Wireless-Headphones-Charging/dp/B0001FTVEK\)](https://www.amazon.com/Sennheiser-RS120-Wireless-Headphones-Charging/dp/B0001FTVEK)

```

In [1]: 1 #import necessary libraries
2
3 import pandas as pd
4 import numpy as np
5 # import dataframe_image as dfi
6 import string
7 import re
8 from matplotlib import pyplot as plt
9 import seaborn as sns
10 from nltk.corpus import stopwords
11 from nltk import FreqDist, word_tokenize
12 # from nltk.tokenize import TweetTokenizer
13 from nltk.stem import WordNetLemmatizer
14 # from wordcloud import WordCloud, STOPWORDS
15 import re,string
16 import unicode
17 import html
18
19 import preprocess_ddey117 as pp
20
21
22 import requests
23 import os
24 import csv
25 import urllib.request
26 import gzip
27 import sys
28 import spacy
29 import json
30 # import boto3
31 # from boto.s3.connection import S3Connection
32
33 from collections import defaultdict
34 from sklearn import cluster
35 import seaborn as sns
36
37 import nltk
38 # nltk.download('vader_lexicon')
39
40 import spacy
41 nlp = spacy.load("en_core_web_lg")
42
43 from nltk.sentiment.vader import SentimentIntensityAnalyzer
44 sid = SentimentIntensityAnalyzer()
45
46 # from nltk.collocations import *
47 # bigram_measures = nltk.collocations.BigramAssocMeasures()
48 # trigram_measures = nltk.collocations.TrigramAssocMeasures()
49 # fourgram_measures = nltk.collocations.QuadgramAssocMeasures()

```

/Users/dylandey/anaconda3/envs/learn-env/lib/python3.6/site-packages/tensorflow/python/framework/dtypes.py:517: FutureWarning: Passing (type, 1) or 'ltype' as a synonym of type is deprecated; in a future version of numpy, it will be understood as (type, (1,)) / '(1,)type'.
 _np_qint8 = np.dtype [("qint8", np.int8, 1)]

```

/Users/dylandey/anaconda3/envs/learn-env/lib/python3.6/site-packages/
tensorflow/python/framework/dtypes.py:518: FutureWarning: Passing (ty
pe, 1) or 'ltype' as a synonym of type is deprecated; in a future ver
sion of numpy, it will be understood as (type, (1,)) / '(1,)type'.
_np_quint8 = np.dtype(["quint8", np.uint8, 1])
/Users/dylandey/anaconda3/envs/learn-env/lib/python3.6/site-packages/
tensorflow/python/framework/dtypes.py:519: FutureWarning: Passing (ty
pe, 1) or 'ltype' as a synonym of type is deprecated; in a future ver
sion of numpy, it will be understood as (type, (1,)) / '(1,)type'.
_np_qint16 = np.dtype(["qint16", np.int16, 1])
/Users/dylandey/anaconda3/envs/learn-env/lib/python3.6/site-packages/
tensorflow/python/framework/dtypes.py:520: FutureWarning: Passing (ty
pe, 1) or 'ltype' as a synonym of type is deprecated; in a future ver
sion of numpy, it will be understood as (type, (1,)) / '(1,)type'.

```

A large collection of amazon reviews that fall under the "electronics" category. For this project, product_id "[B0001FTVEK](https://www.amazon.com/Sennheiser-RS120-Wireless-Headphones-Charging/dp/B0001FTVEK)" (<https://www.amazon.com/Sennheiser-RS120-Wireless-Headphones-Charging/dp/B0001FTVEK>) was chosen as it had a large amount of verified reviews and a pair of headphones seemed like a reasonable choice for aspect based sentiment analysis.

In [2]:

```

1 # df = pd.read_csv('data/df_electronics.tsv', sep='\t')
2 # df.groupby('product_id').count().sort_values(by='star_rating').tail(2)

```

In [4]:

```

1 df = pd.read_csv('data/df_electronics.tsv', sep='\t')
2 df.groupby('product_id').count().sort_values(by='star_rating').tail(20)

```

Out[4]:

	marketplace	customer_id	review_id	product_parent	product_title	product_category	star_rating	helpful_votes	total_votes	vine	verified_purch
product_id											
B004LTEUDO	3997	3997	3997	3997	3997	3997	3997	3997	3997	3997	:
B004HHICKC	4213	4213	4213	4213	4213	4213	4213	4213	4213	4213	:
B001TH7GSW	4866	4866	4866	4866	4866	4866	4866	4866	4866	4866	:
B008KVUAGU	5015	5015	5015	5015	5015	5015	5015	5015	5015	5015	:
B003WGRUQQ	5072	5072	5072	5072	5072	5072	5072	5072	5072	5072	:
B002MAP7TU	5295	5295	5295	5295	5295	5295	5295	5295	5295	5295	:
B001GTT0VO	5580	5580	5580	5580	5580	5580	5580	5580	5580	5580	:
B0052SCU8U	5756	5756	5756	5756	5756	5756	5756	5756	5756	5756	:
B00316263Y	5813	5813	5813	5813	5813	5813	5813	5813	5813	5813	:
B00D5Q75RC	6062	6062	6062	6062	6062	6062	6062	6062	6062	6062	:
B004QK7HI8	6536	6536	6536	6536	6536	6536	6536	6536	6536	6536	:
B00F5NE2KG	6688	6688	6688	6688	6688	6688	6688	6688	6688	6688	:
B0019EHU8G	7586	7586	7586	7586	7586	7586	7586	7586	7586	7586	:
B000WYVBR0	7835	7835	7835	7835	7835	7835	7835	7835	7835	7835	:
B0001FTVEK	8793	8793	8793	8793	8793	8793	8793	8793	8793	8793	:
B0012S4APK	9359	9359	9359	9359	9359	9359	9359	9359	9359	9359	:
B003EM8008	9766	9766	9766	9766	9766	9766	9766	9766	9766	9766	:
B0002L5R78	11166	11166	11166	11166	11166	11166	11166	11166	11166	11166	:
B003L1ZYMM	15334	15334	15334	15334	15334	15334	15334	15334	15334	15334	:

```
In [3]: 1 #testing other dataframes not shown in this notebook
2
3
4
5 # df_hp1 = df.loc[df['product_id'] == 'B003EM8008'].copy()
6 # df_hp1.reset_index(drop=True, inplace=True)
7 # df_hp2 = df.loc[df['product_id'] == 'B0001FTVEK'].copy()
8 # df_hp2.reset_index(drop=True, inplace=True)
9 # df_hp3 = df.loc[df['product_id'] == 'B004RKQM8I'].copy()
10 # df_hp3.reset_index(drop=True, inplace=True)
11 # df_hp4 = df.loc[df['product_id'] == 'B0038W0K2K'].copy()
12 # df_hp4.reset_index(drop=True, inplace=True)
13
14 # df_sb1 = df.loc[df['product_id'] == 'B00D5Q75RC'].copy()
15 # df_sb1.reset_index(drop=True, inplace=True)
16 # df_sb2 = df.loc[df['product_id'] == 'B00F5NE2KG'].copy()
17 # df_sb2.reset_index(drop=True, inplace=True)
18
19 # df_mp1 = df.loc[df['product_id'] == 'B00020S7XK'].copy()
20 # df_mp1.reset_index(drop=True, inplace=True)
21 # df_mp2 = df.loc[df['product_id'] == 'B002MAPT7U'].copy()
22 # df_mp2.reset_index(drop=True, inplace=True)
23
24 # #dropping unnecessary columns
25
26 # columns_td = ['marketplace', 'customer_id', 'product_id',
27 #               'product_parent', 'product_title', 'product_category',
28 #               'helpful_votes', 'total_votes', 'vine', 'verified_purchase',
29 #               'review_headline', 'review_date']
30
31 # df2.drop(columns=columns_td, inplace=True)
32
33 #saving dataframe with chosen product for quick loading time
34
35 # df2.to_csv('data/df_electronics_example.csv', index=False)
```



```
In [4]: 1 #display important information about dataset
2 #Almost 9000 reviews, mostly 4 or 5 stars.
3
4 df = pd.read_csv("data/df_electronics_example.csv")
5 display(df.head())
6 print("\n")
7 print('star rating value counts')
8 display(df.star_rating.value_counts())
9 display(df.star_rating.hist())
10 df.info()
11 print("\n")
12 print("distribution of star rating")
```

	review_id	star_rating	review_body
0	R17U6AU06HR16Q	5	Great product.
1	R31Y01GPXH7P64	4	work great sounds amazing
2	RG40FO7CNWOG7	5	Works tremendously well.
3	R2Ci6TXIGZR6RU	5	THEY WORK GREAT
4	R37KF8VRBUZNQD	5	Works fine

star rating value counts

```
5    4715
4    1924
1     829
3     724
2     601
```

Name: star_rating, dtype: int64

<AxesSubplot:>

<class 'pandas.core.frame.DataFrame'>

RangeIndex: 8793 entries, 0 to 8792


Data columns (total 3 columns):

#	Column	Non-Null Count	Dtype
0	review_id	8793 non-null	object
1	star_rating	8793 non-null	int64
2	review_body	8793 non-null	object

dtypes: int64(1), object(2)

memory usage: 206.2+ KB

distribution of star rating



Function Definition

```
In [5]: 1  #I wrote a library for taking care of many common tasks for data language
2  #However, since this project must load spaCy for parsing the aspect/opi
3  #Some of the major processing will be handled by spaCy
4
5  #simple processing such as removing emails, html tags, urls
6  #accented characters and counting all words in the dataset
7  #are handled with my own toolset
8
9  def master_preprocess(df):
10     df['wordcounts'] = df['review_body'].apply(lambda x: pp.get_wordcou
11     df['review_body'] = df['review_body'].apply(lambda x: pp.remove_ema
12     df['review_body'] = df['review_body'].apply(lambda x: pp.remove_url
13     df['review_body'] = df['review_body'].apply(lambda x: pp.remove_htr
14     df['review_body'] = df['review_body'].apply(lambda x: pp.remove_acc
15     return df
```

```
In [6]: 1  df = master_preprocess(df)
```

```


In [7]: 1 #Looking at the statistics for wordcounts below
        2 #The median length for a amazon review
        3 #for this particular set of headphones is about 50 words
        4 #ranging from 1 to 1565 words for each review
        5 #Thus showing the wide range of informal data that is
        6 #allowed in the review body and how unmanageable it can
        7 #become
        8 #With this dataset the total amount of words
        9 #has already reached over half of a million words
       10
       11
       12 display(df.describe())
       13 df.wordcounts.sum()

```

	star_rating	wordcounts
count	8793.000000	8793.000000
mean	4.034346	74.089730
std	1.318899	91.416481
min	1.000000	1.000000
25%	4.000000	23.000000
50%	5.000000	47.000000
75%	5.000000	92.000000
max	5.000000	1565.000000

```
Out[7]: 651471
```

Explaining The Parser





Clustering and Polarity

A large number of amazon reviews produce a large number of aspect-modifier pairs. These pairs ultimately seemed to diverge to common topics, and therefore it would make sense to use machine learning to automatically figure out these categories for us. This leads to a better summation of insight from the total pool of customers who were kind enough to leave a review. Polarity scores are also averaged out of every cluster to give a quantifiable explanation to opinion to distinct categories of a given product.

Word Vectors and Clustering

In order to work with any amazon review data, first the text data must be converted into something that a machine can recognize. The most famous implementation of words vectors is the word2vec project. However, spaCy vectorization was chosen for this projec as it provides fast and easy access to over a million unique word vectors, and its multi-task CNN model is trained on 'web' data and not 'newspaper' data as in other libraries like NLTK.

The word vectors were then grouped using K-Means clustering algorithm in Scikit-Learn. Other clustering algorithms such as DBSCAN were tested. However, K-Means gave optimal results with four clusters. The clusers were labeled with input from a user after suggesting the top most common word for each cluster.


Below Is the pipeline design for spaCy and a description for the size and sources for the model loaded to run this project and parse the amazon reviews.

[en_core_web_large \(https://spacy.io/models/en#en_core_web_lg\)](https://spacy.io/models/en#en_core_web_lg)

CPU pipeline design

spaCy

Large model trained on "web" data



"spaCy uses the terms **head** and **child** to describe the words connected by a single arc in the

dependency tree. The term **dep** is used for the arc label, which describes the type of syntactic relation that connects the child to the head. As with other attributes, the value of .dep is a hash value. You can get the string value with .dep_." [Navigating The Parse Tree](https://spacy.io/usage/linguistic-features#navigating) (<https://spacy.io/usage/linguistic-features#navigating>).

First Rule of Dependency Parser: The Aspect (A) token is a subject noun with a child modifier (M) that has a relation of amod (adjectival modifier). This just means that the aspect and opinion share a simple adjective/noun relationship that can be extracted. However, there are certain caveats that need to be kept in mind when parsing the tree for this rule.

- First, it is important to check to see if there is an additional adverbial modifier that could adjust the intensity of the sentiment implied by the adjective and adverb combination in regards to the subject/aspect. This is important to keep in mind as we are taking advantage of NLTK vader sentiment intensity analyzer which can make use of additional adverbs to get a better understanding of sentiment.
- Another important thing to keep in mind when parsing for this rule is to be aware of the possibility of negating the adjective with 'no' as a determiner.

First Rule Examples

Example1: The comfortable headphones.

Example2: The most comfortable headphones.

Example3: No comfortable features.

- det = determiner
- A = aspect
- M = modifier
- amod = adjectival modifier

Second Rule of Dependency Parser: The aspect (A) is a child of something with a relation of nominal subject (nsubj.) while the modifier (M) is a child of the same something with a relationship of direct object. In this case, the adjective would be acting as the determiner of the clause. For simplicity's sake, it was determined to assume that each verb will have only one NSUBJ and DOBJ. This is a fair assumption for the application of this project, because even if there are multiple subjects, they will both be reviewing the same thing and will likely share the same opinion as it is written as a single review. For example, if an author were to say "My wife and I bought the awesome headphones", we still only want to extract the keywords 'awesome' and 'headphones.' If this sounds confusing, hopefully the example below will help clarify.

Second Rule Example

Example: I bought the awesome headphones.

- nsubj = nominal subject
- dobj =headphones
- det= awesome

Third Rule of Dependency Parser: The modifier (M) is a child of something with a relation of an adjectival complement (acom), while the aspect (A) is a child of that same something with a relation of nominal subject (nsubj).

- This rule needs to handle special cases in which the child is tagged as a modal verb with an auxiliary dependency. This would flag for phrases such as “the sound of the speakers could be better.” For special cases like this, the parser will add a negative prefix before scoring the aspect/modifier pairs for sentiment.

Third Rule Examples

Example1: Barb is happy about the sound quality.

Example2: This could be better.

Example2 would be extracted as A= "this" and M= "not better"

- A = aspect
- M = modifier

Fourth Rule of Dependency Parser: The aspect (A) is a child of something with a relationship of passive nominal subject (nsubjpass) while the modifier (M) is a child of that same something with a relationship of adverbial modifier (advmod). In other words, the modifier is an adverbial modifier to a passive verb.

- nsubjpass: A passive nominal subject is a noun phrase which is the syntactic subject of a passive clause.
- This step of the parser will also check to add a negative prefix before extracting and scoring for sentiment if necessary

Fourth Rule Examples

Example1: The headphones died quickly.

- A = aspect
- M = modifier

Fifth Rule of Dependency Parser: The aspect (A) is a child of the modifier with a relationship

of nominal subject, while the modifier has a child with a relation of copula(cop). Here the parser is looking for the complement of a copular verb. An often used copula verb is the word "is," as in the phrase "Bill is big."

- Assumption - A verb will have only one NSUBJ and DOBJ
- cop: copula A copula is the relation between the complement of a copular verb and the copular verb. (We normally take a copula as a dependent of its complement.

Fifth Rule Example

Example1: The sound is awesome.

- A = aspect
- M = modifier

Sixth Rule of Dependency Parser: Aspect/modifier are children of an interjection

- NTJ (interjections like bravo, great etc)

Sixth Rule Example

Example1: Bravo, headphones.

- A = aspect
- M = modifier

Seventh Rule of Dependency Parser: This rule is similar to rule 5, but makes use of the attr (attribute) tag instead. It seems to function similarly, in which an attribute is considered a noun phrase following a copular verb

- ATTR - link between a verb like 'is/seem/appear/became' and its complement

Seventh Rule Example

Example1: This is garbage.

- A = aspect
- M = modifier

For all Parsing: SpaCy has a large library of named entities it can recognize and tag. This logic is added for each step in the model.


```
In [8]: 1 spacy.explain('acomp')
```

```
Out[8]: 'adjectival complement'
```

Please feel free to review the following sections above under the spaCy documentation for `pos_tagging` if you would like to get an understanding of how the parser was designed in spaCy. Each link should be a direct link to the appropriate topic.

[Dependency Parsing with spaCy \(https://spacy.io/usage/linguistic-features#dependency-parse\)](https://spacy.io/usage/linguistic-features#dependency-parse)

[Navigating The Tree \(https://spacy.io/usage/linguistic-features#navigating\)](https://spacy.io/usage/linguistic-features#navigating)

[Named Entity Recognition \(https://spacy.io/usage/linguistic-features#named-entities\)](https://spacy.io/usage/linguistic-features#named-entities)

Hutto, C.J. & Gilbert, E.E. (2014). VADER: A Parsimonious Rule-based Model for Sentiment Analysis of Social Media Text. Eighth International Conference on Weblogs and Social Media (ICWSM-14). Ann Arbor, MI, June 2014.

[VADER sentiment](#)

https://www.researchgate.net/publication/275828927_VADER_A_Parsimonious_Rule-based_Model_for_Sentiment_Analysis_of_Social_Media_Text

The reasearch paper was published on release of the VADER intensity sentiment analyzer. Please feel free to read to get a better understanding of how this tool was developed before being taken advantage of in this project.

Detecting Product Aspects

```
In [9]: 1 display(spacy.explain('nsubjpass'))
2 display(spacy.explain('cop'))
3 display(spacy.explain('INTJ'))
4 spacy.explain('attr')
```

```
'nominal subject (passive)'
```

```
'copula'
```

```
'interjection'
```

```
Out[9]: 'attribute'
```

TABLE OF REFERENCE:

AMOD

adjectival modifier

ADVMOD

adverbial modifier

example: Genetically Modified Food, Less often

NSUBJ

"Nominal subject (nsubj) is a nominal which is the syntactic subject and the proto-agent of a clause. That is, it is in the position that passes typical grammatical test for subjecthood, and this argument is the more agentive, the do-er, or the proto-agent of the clause. This nominal may be headed by a noun, or it may be a pronoun or relative pronoun or, in ellipsis contexts, other things such as an adjective." Taken from the documentation.

example: Genetically Modified Food, Less often

DOBJ

The direct object of a VP is the noun phrase which is the (accusative) object of the verb

DET

Determiner. "The English DET covers most cases of Penn Treebank DT, PDT, WDT. However, when a Penn Treebank word with one of these tags stands alone as a noun phrase rather than modifying another word, then it becomes PRON." Taken from the documentation.

ACOMP

Adjective complement. A phrase that modifies an adjective.

cop

"A cop (copula) is the relation of a function word used to link a subject to a nonverbal predicate, including the expression of identity predication (e.g. sentences like "Kim is the President"). It is often a verb but nonverbal (pronominal) copulas are also frequent in the world's languages. Verbal copulas are tagged AUX, not VERB. Pronominal copulas are tagged PRON or DET." From the documentation.

INTJ

interjection. An interjection is a word that is used most often as an exclamation or part of an exclamation.

```

In [10]: 1 def apply_extraction(row,nlp=nlp,sid=sid):
2     review_body = row['review_body']
3     # review_id = row['review_id']
4     # review_marketplace = row['marketplace']
5     # customer_id = row['customer_id']
6     # product_id = row['product_id']
7     # product_parent = row['product_parent']
8     # product_title = row['product_title']
9     # product_category = row['product_category']
10    # date = str(row['review_date'])
11    # star_rating = row['star_rating']
12    # url = add_amazonlink(product_id)
13
14
15
16    doc=nlp(review_body)
17
18
19    ## FIRST RULE OF DEPENDANCY PARSE -
20    ## M - Sentiment modifier || A - Aspect
21    ## RULE = M is child of A with a relationshion of amod(adjectival
22    ner_heads = {ent.root.idx: ent for ent in doc.ents}
23    rule1_pairs = []
24    for token in doc:
25        A = "999999"
26        M = "999999"
27        if token.dep_ == "amod" and not token.is_stop:
28            M = token.text
29            if token.head in ner_heads:
30                A = ner_heads[token.head].text
31            else:
32                A = token.head.text
33
34            # add adverbial modifier of adjective (e.g. '*most* comfort
35            M_children = token.children
36            for child_m in M_children:
37                if(child_m.dep_ == "advmod"):
38                    M_hash = child_m.text
39                    M = M_hash + " " + M
40                    break
41
42            # negation in adjective, the "no" keyword is a 'det' of th
43            A_children = token.head.children
44            for child_a in A_children:
45                if(child_a.dep_ == "det" and child_a.text == 'no'):
46                    neg_prefix = 'not'
47                    M = neg_prefix + " " + M
48                    break
49
50            if(A != "999999" and M != "999999"):
51                rule1_pairs.append((A, M,sid.polarity_scores(token.text)['
52
53    ## SECOND RULE OF DEPENDANCY PARSE -
54    ## M - Sentiment modifier || A - Aspect
55    #Direct Object - A is a child of something with relationship of ns
56    # M is a child of the same something with relationship of dobj

```

```

57  #Assumption - A verb will have only one NSUBJ and DOBJ
58  #   ner_heads = {ent.root.idx: ent for ent in doc.ents}
59  rule2_pairs = []
60  for token in doc:
61      children = token.children
62      A = "999999"
63      M = "999999"
64      add_neg_pfx = False
65      for child in children :
66          if(child.dep_ == "nsubj" and not child.is_stop):
67              if child.idx in ner_heads:
68                  A = ner_heads[child.idx].text
69              else:
70                  A = child.text
71              # check_spelling(child.text)
72
73          if((child.dep_ == "dobj" and child.pos_ == "ADJ") and not
74             M = child.text
75             #check_spelling(child.text)
76
77          if(child.dep_ == "neg"):
78              neg_prefix = child.text
79              add_neg_pfx = True
80
81  if (add_neg_pfx and M != "999999"):
82      M = neg_prefix + " " + M
83
84      if(A != "999999" and M != "999999"):
85          rule2_pairs.append((A, M,sid.polarity_scores(M)[ 'compound'
86
87
88  ## THIRD RULE OF DEPENDANCY PARSE -
89  ## M - Sentiment modifier || A - Aspect
90  ## Adjectival Complement - A is a child of something with relation
91  ## M is a child of the same something with relationship of acomp
92  ## Assumption - A verb will have only one NSUBJ and DOBJ
93  ## "The sound of the speakers would be better. The sound of the sp
94
95
96  rule3_pairs = []
97
98  for token in doc:
99
100     children = token.children
101     A = "999999"
102     M = "999999"
103     add_neg_pfx = False
104     for child in children :
105         if(child.dep_ == "nsubj" and not child.is_stop):
106             if child.idx in ner_heads:
107                 A = ner_heads[child.idx].text
108             else:
109                 A = child.text
110             # check_spelling(child.text)
111
112         if(child.dep_ == "acomp" and not child.is_stop):
113             M = child.text

```

```

114
115     # example - 'this could have been better' -> (this, not be
116     if(child.dep_ == "aux" and child.tag_ == "MD"):
117         neg_prefix = "not"
118         add_neg_pfx = True
119
120     if(child.dep_ == "neg"):
121         neg_prefix = child.text
122         add_neg_pfx = True
123
124     if (add_neg_pfx and M != "999999"):
125         M = neg_prefix + " " + M
126         #check_spelling(child.text)
127
128     if(A != "999999" and M != "999999"):
129         rule3_pairs.append((A, M, sid.polarity_scores(M)['compound
130
131     ## FOURTH RULE OF DEPENDENCY PARSE -
132     ## M - Sentiment modifier || A - Aspect
133
134     #Adverbial modifier to a passive verb - A is a child of something
135     # M is a child of the same something with relationship of advmod
136
137     #Assumption - A verb will have only one NSUBJ and DOBJ
138
139     rule4_pairs = []
140     for token in doc:
141
142
143         children = token.children
144         A = "999999"
145         M = "999999"
146         add_neg_pfx = False
147         for child in children :
148             if((child.dep_ == "nsubjpass" or child.dep_ == "nsubj") and
149                 if child.idx in ner_heads:
150                     A = ner_heads[child.idx].text
151                 else:
152                     A = child.text
153                 # check_spelling(child.text)
154
155             if(child.dep_ == "advmod" and not child.is_stop):
156                 M = child.text
157                 M_children = child.children
158                 for child_m in M_children:
159                     if(child_m.dep_ == "advmod"):
160                         M_hash = child_m.text
161                         M = M_hash + " " + child.text
162                     break
163                 #check_spelling(child.text)
164
165             if(child.dep_ == "neg"):
166                 neg_prefix = child.text
167                 add_neg_pfx = True
168
169         if (add_neg_pfx and M != "999999"):
170             M = neg_prefix + " " + M

```

```

171
172         if(A != "999999" and M != "999999"):
173             rule4_pairs.append((A, M, sid.polarity_scores(M)[ 'compound'
174
175
176     ## FIFTH RULE OF DEPENDANCY PARSE -
177     ## M - Sentiment modifier || A - Aspect
178
179     #Complement of a copular verb - A is a child of M with relationshiphi
180     # M has a child with relationship of cop
181
182     #Assumption - A verb will have only one NSUBJ and DOBJ
183
184     rule5_pairs = []
185     for token in doc:
186         children = token.children
187         A = "999999"
188         buf_var = "999999"
189         for child in children :
190             if(child.dep_ == "nsubj" and not child.is_stop):
191                 if child.idx in ner_heads:
192                     A = ner_heads[child.idx].text
193                 else:
194                     A = child.text
195
196                 # check_spelling(child.text)
197
198             if(child.dep_ == "cop" and not child.is_stop):
199                 buf_var = child.text
200                 #check_spelling(child.text)
201
202         if(A != "999999" and buf_var != "999999"):
203             rule5_pairs.append((A, token.text, sid.polarity_scores(toke
204
205
206     ## SIXTH RULE OF DEPENDENCY PARSE -
207     ## M - Sentiment modifier || A - Aspect
208     ## INTJ (interjections like bravo, great etc)
209
210
211     rule6_pairs = []
212     for token in doc:
213         children = token.children
214         A = "999999"
215         M = "999999"
216         if(token.pos_ == "INTJ" and not token.is_stop):
217             for child in children :
218                 if(child.dep_ == "nsubj" and not child.is_stop):
219                     M = token.text
220                     if child.idx in ner_heads:
221                         A = ner_heads[child.idx].text
222                     else:
223                         A = child.text
224                     # check_spelling(child.text)
225
226         if(A != "999999" and M != "999999"):
227             rule6_pairs.append((A, M, sid.polarity_scores(M)[ 'compound'

```

```

228
229
230 ## SEVENTH RULE OF DEPENDENCY PARSE -
231 ## M - Sentiment modifier || A - Aspect
232 ## ATTR - link between a verb like 'be/seem/appear' and its comple
233 ## Example: 'this is garbage' -> (this, garbage)
234
235 rule7_pairs = []
236 for token in doc:
237     children = token.children
238     A = "999999"
239     M = "999999"
240     add_neg_pfx = False
241     for child in children :
242         if(child.dep_ == "nsubj" and not child.is_stop):
243             if child.idx in ner_heads:
244                 A = ner_heads[child.idx].text
245             else:
246                 A = child.text
247             # check_spelling(child.text)
248
249         if((child.dep_ == "attr") and not child.is_stop):
250             M = child.text
251             #check_spelling(child.text)
252
253         if(child.dep_ == "neg"):
254             neg_prefix = child.text
255             add_neg_pfx = True
256
257     if (add_neg_pfx and M != "999999"):
258         M = neg_prefix + " " + M
259
260     if(A != "999999" and M != "999999"):
261         rule7_pairs.append((A, M,sid.polarity_scores(M)[ 'compound'
262
263
264
265 aspects = []
266
267 aspects = rule1_pairs + rule2_pairs + rule3_pairs +rule4_pairs +ru
268 prod_pronouns = ['it', 'this', 'they']
269
270 # replace all instances of "it", "this" and "they" with "product"
271 aspects = [(A,M,P,r) if A not in prod_pronouns else ("product",M,P
272
273 #     dic = {"review_id" : review_id , "aspect_pairs" : aspects, "revi
274 #     , "customer_id" : customer_id, "product_id" : product_id, "produ
275 #     "product_title" : product_title, "product_category" : product_ca
276
277
278 return aspects
279
280
281
282 def remove_digits(x):
283     return " ".join([t for t in x.split() if not t.isdigit()])
284

```

```

285
286
287 def get_word_vectors(unique_aspects, nlp=nlp):
288     asp_vectors = []
289     for aspect in unique_aspects:
290         # print(aspect)
291         token = nlp(aspect)
292         asp_vectors.append(token.vector)
293     return asp_vectors
294
295
296 def get_aspect_freq_map(aspects):
297     aspect_freq_map = defaultdict(int)
298     for asp in aspects:
299         aspect_freq_map[asp] += 1
300     return aspect_freq_map
301
302
303
304 NUM_CLUSTERS = 4
305
306 def get_word_cluster_labels(unique_aspects, nlp=nlp):
307     # print("Found {} unique aspects for this product".format(len(unique_aspects)))
308     asp_vectors = get_word_vectors(unique_aspects, nlp)
309     # n_clusters = min(NUM_CLUSTERS, len(unique_aspects))
310     if len(unique_aspects) <= NUM_CLUSTERS:
311         # print("Too few aspects ({} ) found. No clustering required...")
312         return list(range(len(unique_aspects)))
313
314     # print("Running k-means clustering...")
315     n_clusters = NUM_CLUSTERS
316     kmeans = cluster.KMeans(n_clusters=n_clusters)
317     kmeans.fit(asp_vectors)
318     labels = kmeans.labels_
319     # dbscan = cluster.DBSCAN(eps = 0.2, min_samples = 2).fit(asp_vectors)
320     # labels = dbscan.labels_
321
322     # print("Finished running k-means clustering with {} labels".format(len(labels)))
323     # print(labels)
324     return labels
325
326
327
328 def get_cluster_names_map(asp_to_cluster_map, aspect_freq_map):
329     cluster_id_to_name_map = defaultdict()
330     # cluster_to_asp_map = defaultdict()
331     clusters = set(asp_to_cluster_map.values())
332     for i in clusters:
333         this_cluster_asp = [k for k, v in asp_to_cluster_map.items() if v == i]
334         filt_freq_map = {k: v for k, v in aspect_freq_map.items() if k in this_cluster_asp}
335         filt_freq_map = sorted(filt_freq_map.items(), key = lambda x: x[1])
336         cluster_id_to_name_map[i] = filt_freq_map[0][0]
337
338         # cluster_to_asp_map[i] = this_cluster_asp
339
340     # print(cluster_to_asp_map)
341     # print(cluster_id_to_name_map)

```



```

342     return cluster_id_to_name_map
343
344
345
346 #Two master functions below for applying above functions
347
348
349 def extract_aspect_sentiment_tuples(df):
350     df = master_preprocess(df)
351     df = df.loc[df['wordcounts'] > 10].copy()
352     df.reset_index(drop=True, inplace=True)
353     df['aspect_tups'] = df.apply(apply_extraction, axis=1)
354     df = df.explode('aspect_tups').copy()
355     df.dropna(inplace=True)
356     df['asp'] = df['aspect_tups'].apply(lambda x: x[0])
357     df['modifier'] = df['aspect_tups'].apply(lambda x: x[1])
358     df['modifier_sentiment'] = df['aspect_tups'].apply(lambda x: x[2])
359     df['rule_number'] = df['aspect_tups'].apply(lambda x: x[3])
360     return df
361
362
363 #This function will work with input from user
364 #to find best possible label name for clusters
365 def get_cluster_name_inputs(df):
366     print('loading...')
367     aspect_freq_map = get_aspect_freq_map(df['asp'].values)
368     unique_asp_array = df['asp'].unique()
369     mapped_labels = get_word_cluster_labels(unique_asp_array)
370     asp_labels_map = dict(zip(unique_asp_array, mapped_labels))
371     label_names_map = get_cluster_names_map(asp_labels_map, aspect_fre
372
373     df['asp_cluster_label'] = df['asp'].map(asp_labels_map)
374
375     print("write misc if low counts and special characters")
376     print("the top word is usually the best fit")
377
378     display(label_names_map[0][:10])
379     print("Pick a category for above words: ")
380     clust_0 = input()
381
382     display(label_names_map[1][:10])
383     print("Pick a category for above words: ")
384     clust_1 = input()
385
386     display(label_names_map[2][:10])
387
388     print("Pick a category for above words: ")
389     clust_2 = input()
390
391     display(label_names_map[3][:10])
392     print("Pick a category for above words: ")
393     clust_3 = input()
394
395     clusters = [clust_0] + [clust_1] + [clust_2] + [clust_3]
396
397
398     name_clust_dict = {0: clusters[0],

```

```

399         1: clusters[1],
400         2: clusters[2],
401         3: clusters[3]
402     }
403
404
405
406     df['cluster_name'] = df['asp_cluster_label'].map(name_clust_dict)
407
408     fig = plt.figure(figsize=(10,8))
409
410     df_senti.groupby(by='cluster_name')['modifier_sentiment'].sum().pl
411
412     plt.title("Clustered Aspect Sentiment Totals")
413
414     plt.savefig('images/extractor_example1.jpg')
415
416     return df
417
418
419
420
421     #function for visualizing variance in opinion for the same
422     #opinion/aspect couple among voters
423
424     def variance_visualizer(df, tup):
425         graph_s = df[df['tup_pair'] == tup]['sentiment'].value_counts()
426         fig = plt.figure(figsize=(6,4))
427
428
429         ax = graph_s.plot.bar()
430
431         #ADD TOTAL NUMBER OF VOTES
432         fig.text(0.9,
433                 0.9,
434                 s=f'Total Votes: {(graph_s.sum())} \n tuple: {tup}',
435                 ha='center',
436                 va='center',
437                 transform=ax.transAxes,
438                 size=12
439             )
440
441         plt.savefig('images/variance_graph_example.jpg');
442
443
444
445
446     #function for visualizing variance in opinion for the same
447     #opinion/aspect couple among voters
448
449     def sum_squares(df, tup):
450         s = df[df['tup_pair'] == tup]['sentiment'].value_counts()
451         # print(f'{tup} Residual sum of squares: {(np.sum((s-s.mean())**2)}
452         sum_s = np.sum((s-s.mean())**2)
453         return(tup,sum_s)

```

Running The Extractor

In [11]:

```
1 #aspect extractor ran in order to extract tuples from
2 #entire amazon review text body
3 df_senti = extract_aspect_sentiment_tuples(df)
4 df_senti.head()
```

Out[11]:

	review_id	star_rating	review_body	wordcounts	aspect_tups	asp	modifier	modif
0	RA8R84N9JMZLD	3	My Dad loves this, only issue is charging, it ...	32	(connection, proper, 0.0, 1)	connection	proper	
2	R1KL6IIDB77A2O	4	I would not have paid the original price for t...	58	(price, original, 0.3182, 1)	price	original	
2	R1KL6IIDB77A2O	4	I would not have paid the original price for t...	58	(bit, little, 0.0, 1)	bit	little	
2	R1KL6IIDB77A2O	4	I would not have paid the original price for t...	58	(star, how durable, 0.0, 1)	star	how durable	
2	R1KL6IIDB77A2O	4	I would not have paid the original price for t...	58	(price, lower, -0.296, 1)	price	lower	

```

In [12]: 1 #keep only columns of interest
2 df_senti_predicted = df_senti.loc[:, ['modifier', 'asp', 'modifier_sentiment', 'sentiment', 'tup_pair']]
3
4
5 #convert sentiment to Categorical to compare to human labels more easily
6 df_senti_predicted.loc[df_senti_predicted['modifier_sentiment'] < -.5, 'sentiment'] = 'Very Negative'
7 df_senti_predicted.loc[(df_senti_predicted['modifier_sentiment'] >= -.5) & (df_senti_predicted['modifier_sentiment'] < 0), 'sentiment'] = 'Negative'
8 df_senti_predicted.loc[(df_senti_predicted['modifier_sentiment'] >= 0) & (df_senti_predicted['modifier_sentiment'] < 0.5), 'sentiment'] = 'Neutral'
9 df_senti_predicted.loc[(df_senti_predicted['modifier_sentiment'] > 0.5), 'sentiment'] = 'Very Positive'
10
11
12 #convert aspects back to pair insted of triplet
13 #for easy comparison to human labels
14 df_senti_predicted['tup_pair'] = list(zip(df_senti_predicted['modifier'], df_senti_predicted['asp']))
15 #drop duplicate aspect pairs
16 df_to_turk2 = df_senti_predicted.drop_duplicates(subset='tup_pair')
17
18 df_to_turk2.sort_values(by='asp')

```

Out[12]:

	modifier	asp	modifier_sentiment	sentiment	tup_pair
1072	Able		0.0000	Neutral	(Able,)
7660	Though bulky		0.0000	Neutral	(Though bulky,)
1900	Only negative		-0.5719	Very Negative	(Only negative,)
6809	Really disappointed		-0.4767	Negative	(Really disappointed,)
6810	Otherwise excellent		0.5719	Very Positive	(Otherwise excellent,)
...
5475	fake	youout	-0.4767	Negative	(fake, youout)
3941	past	yrs	0.0000	Neutral	(past, yrs)
6229	dead	zone	-0.6486	Very Negative	(dead, zone)
197	sweet	zone	0.4588	Positive	(sweet, zone)
7059	extra	~\$20	0.0000	Neutral	(extra, ~\$20)

17675 rows × 5 columns

```

In [13]: 1 #sending data to create template
2 #for workers to submit labels
3 #using Amazon Turk
4 df_to_turk2 = df_senti_predicted.drop_duplicates(subset='tup_pair')
5 df_to_turk2.loc[:, ['modifier', 'asp']].to_csv('data/turk_data2.csv', index=False)

```

Below is an example of the extractor being run to cluster the aspects and return a bar graph of total sentiment (total summation of negative and positive from the VADER sentiment intensity analyzer) as well as a DataFrame with cluster names for further analyses. You can see that for the product_id "B0001FTVEK" (<https://www.amazon.com/Sennheiser-RS120->

[Wireless-Headphones-Charging/dp/B0001FTVEK](#)), which are RS120 Wireless Headphones, there is a lot of positive sentiment for the value and sound_quality categories as compared to the headphone_design and hiss/tech_diff categories. The hiss category is low enough that it should be the major focus for the company to funnel resources in response to customer demand for improving their product. If they can focus first on fixing the hiss mentioned in many amazon reviews, they can also put a few extra resources into improving some other design aspects of the headphones, such as the batteries or cradle.

```
In [14]: 1 df_senti = get_cluster_name_inputs(df_senti)
```

loading....

write misc if low counts and special characters
the top word is usually the best fit

```
[('headphones', 2382),  
 ('noise', 460),  
 ('batteries', 432),  
 ('headset', 425),  
 ('headphone', 289),  
 ('signal', 259),  
 ('static', 228),  
 ('unit', 213),  
 ('cradle', 206),  
 ('phones', 188)]
```

Pick a category for above words:
design

```
[('hiss', 227),  
 (' ', 186),
```


```
In [15]: 1 print('\nheadphone_design\n')
2 display(df_senti.loc[df_senti['cluster_name'] == 'design', 'asp'].value
3 print('\nheadphone_design\n')
4 df_senti.loc[df_senti['cluster_name'] == 'design', 'asp'].value_counts()
```

headphone_design

headphones	2382
noise	460
batteries	432
headset	425
headphone	289
signal	259
static	228
unit	213
cradle	206
phones	188
base	156
fit	150
audio	135
light	133
station	118
output	107
headsets	97
tuning	96
setup	84
device	82
frequency	81
earphones	80
Headphones	78
pads	78
transmitter	76
controls	75
channels	74
speakers	65
screen	65
battery	63

Name: asp, dtype: int64

headphone_design



Loading Turk Data

The DataFrames below are batch results loaded as csv files submitted from Amazon Mechanical Turk. As stated before, there are a total of 6107 non-null entries with information for 1438 unique aspects, submitted from a total of 410 different workers from around the globe. Duplicate pairs of aspect/opinion pairs were included to inspect variance of submission from human labels and machine labels for each opinion pair.

```
In [16]: 1 #Read all Turk Data
2
3 df1 = pd.read_csv("data/batch1_results.csv")
4 df2 = pd.read_csv("data/batch2_results.csv")
5 df3 = pd.read_csv("data/batch3_results.csv")
6 df4 = pd.read_csv("data/batch4_results.csv")
7 # df_lab = pd.read_csv("data/locally_sourced_labels.csv")
8
9 display(df1.info())
10 display(df2.info())
11 display(df3.info())
12 display(df4.info())
13 # df_lab.info()
```

```
<class 'pandas.core.frame.DataFrame'>
```

```
RangeIndex: 1020 entries, 0 to 1019
```

```
Data columns (total 32 columns):
```

#	Column	Non-Null Count	Dtype
0	HITId	1020 non-null	object
1	HITTypeId	1020 non-null	object
2	Title	1020 non-null	object
3	Description	1020 non-null	object
4	Keywords	1020 non-null	object
5	CreationTime	1020 non-null	object
6	MaxAssignments	1020 non-null	int64
7	RequesterAnnotation	1020 non-null	object
8	AssignmentDurationInSeconds	1020 non-null	int64
9	AutoApprovalDelayInSeconds	1020 non-null	int64
10	Expiration	1020 non-null	object
11	NumberOfSimilarHITS	0 non-null	float64
12	LifetimeInSeconds	0 non-null	float64
13	AssignmentId	1020 non-null	object


```

In [17]: 1 #concat turk data into one dataframe
2 #keep only necessary columns
3
4 df_turk = pd.concat([df1,df2,df3, df4])
5
6 num_turk = len(df_turk.WorkerId.unique())
7 print(f'Total number of Turk Workers: {num_turk}\n')
8
9 df_turk = df_turk.loc[:, ['Input.Modifier', 'Input.Aspect', 'Answer.se
10 df_turk.dropna(inplace=True)
11
12 num_aspects = len(df_turk["Input.Aspect"].unique())
13 print(f'Total number of Unique Aspects: {num_aspects}\n')
14
15 display(df_turk.info())
16
17 #rename to differentiate human labels
18 df_turk.rename({'Input.Modifier': 'modifier',
19                 'Input.Aspect': 'asp',
20                 'Answer.sentiment.label': 'sentiment_h'
21                 }, axis=1, inplace=True)
22
23
24
25 df_turk.sort_values(by='asp')

```

Total number of Turk Workers: 410

Total number of Unique Aspects: 1438

<class 'pandas.core.frame.DataFrame'>

Int64Index: 6107 entries, 0 to 3228

Data columns (total 3 columns):

#	Column	Non-Null Count	Dtype
0	Input.Modifier	6107 non-null	object
1	Input.Aspect	6107 non-null	object
2	Answer.sentiment.label	6107 non-null	object

dtypes: object(3)

memory usage: 190.8+ KB

None

Out[17]:

	modifier	asp	sentiment_h
32	extra	\$	Very Positive
115	more missing	1/2	Negative
646	single	1/8	Neutral
1659	stereo	1/8\\	Neutral
589	new	120s	Positive
...
3042	pair	years	Neutral

	modifier	asp	sentiment_h
1031	plus	years	Positive
1878	past	years	Positive
2296	fake	youout	Very Negative
299	sweet	zone	Positive

6107 rows × 3 columns

```
In [18]: 1 #create aspect/opinion pair to
2 #compare machine label vs human
3 df_turk['tup_pair'] = list(zip(df_turk['modifier'],df_turk['asp']))
4 display(df_turk.info())
5 df_senti_predicted.info()
```

```
<class 'pandas.core.frame.DataFrame'>
Int64Index: 6107 entries, 0 to 3228
Data columns (total 4 columns):
#   Column          Non-Null Count  Dtype
---  -
0   modifier        6107 non-null  object
1   asp              6107 non-null  object
2   sentiment_h     6107 non-null  object
3   tup_pair        6107 non-null  object
```

dtypes: object(4)

memory usage: 238.6+ KB

None

```
<class 'pandas.core.frame.DataFrame'>
Int64Index: 35355 entries, 0 to 7875
Data columns (total 5 columns):
#   Column              Non-Null Count  Dtype
---  -
0   modifier            35355 non-null  object
1   asp                  35355 non-null  object
2   modifier_sentiment  35355 non-null  float64
3   sentiment            35355 non-null  object
4   tup_pair            35355 non-null  object
```

dtypes: float64(1), object(4)

memory usage: 1.6+ MB

Results

```

In [19]: 1 #create merged DataFrame
2 #in order to compare human
3 #labeled aspect/opinion sentiment
4 #vs model aspect/opinion sentiment
5 #can check accuracy and precision
6
7 #how much do Turk workers agree with
8 #my model?
9
10 #How much do Turk workers agree with
11 #each other?
12
13 df_results = pd.merge(df_turk,
14                       df_senti_predicted,
15                       on='tup_pair',
16                       how='left'
17                       )
18
19 df_results.drop_duplicates(subset='tup_pair', inplace=True)
20 df_results.head()

```

Out[19]:

	modifier_x	asp_x	sentiment_h	tup_pair	modifier_y	asp_y	modifier_sentiment
0	old	father	Neutral	(old, father)	old	father	0.0
16	wireless	headphones	Neutral	(wireless, headphones)	wireless	headphones	0.0
748	charging	rack	Neutral	(charging, rack)	charging	rack	0.0
752	also available	headphones	Very Positive	(also available, headphones)	also available	headphones	0.0
753	impaired	husband	Negative	(impaired, husband)	impaired	husband	0.0

```

In [20]: 1 display(df_results.sentiment_h.value_counts())
2 df_results.sentiment.value_counts()

```

```

Positive      1860
Neutral       1521
Very Positive   790
Negative       692
Very Negative  223
Name: sentiment_h, dtype: int64

```

```

Out[20]: Neutral      3309
Positive    763
Very Positive 523
Negative    397
Very Negative 88
Name: sentiment, dtype: int64

```

```
In [21]: 1 df_results2 = df_results.reset_index(drop=True)
2 df_results2.dropna(inplace=True)
3
4 matching_predictions = df_results2.loc[df_results2['sentiment_h'] == df
5 mismatching_predictions = df_results2.loc[df_results2['sentiment_h'] !=
6
7 display(matching_predictions.sentiment.value_counts())
8 mismatching_predictions.sentiment.value_counts()
```

```
Neutral      1198
Positive     394
Very Positive 187
Negative     141
Very Negative 21
Name: sentiment, dtype: int64
```


```
Out[21]: Neutral      2111
Positive     369
Very Positive 336
Negative     256
Very Negative 67
Name: sentiment, dtype: int64
```

```
In [22]: 1 #create table to see accuracy and precision of extractor
2 #AS COMPARED TO MY AMAZON TURK HUMAN LABELS
3 #ARE MY HUMAN LABELS RELIABLE????
4
5 agree = matching_predictions.sentiment.value_counts().values
6 disagree = mismatching_predictions.sentiment.value_counts().values
7 total_arr = agree + disagree
8 precision = agree/total_arr
9 denom = 5*[5080]
10 accuracy = agree/denom
11 columns = matching_predictions.sentiment.value_counts().index
12 df_table = pd.DataFrame(data=[precision, accuracy], columns=columns)
13 df_table = df_table.apply(lambda x: round(x,4))
14 df_table.rename({0: 'precision', 1: 'accuracy'},
15                 inplace = True
16                 )
17
18 df_table.to_csv("data/acc_prec_table.csv", index=False)
19
20 df_table.head()
```

Out[22]:

	Neutral	Positive	Very Positive	Negative	Very Negative
precision	0.3620	0.5164	0.3576	0.3552	0.2386
accuracy	0.2358	0.0776	0.0368	0.0278	0.0041

Comparison of Turk Data to Extractor Data



VS



	Neutral	Positive	Very Positive	Negative	Very Negative
Precision	36.20%	51.64%	35.76%	35.52%	23.86%
Accuracy	23.58%	7.76%	3.68%	2.78%	0.41%

The precision values explain how many times the machine label correctly line up with the human labels for each aspect/opinion pair when guessing for that appropriate sentiment. That is, if the machine were to guess only for negative sentiment, it was in agreement with humans 35% of the time. The accuracy scores represent how many times the machine were right overall for the entire dataset when predicted a certain class. Due to the nature of the dataset, accuracy scores will be low for a lot of the classes strictly because of class imbalances. Therefore, precision is a better metric for judging the performance of my model. However, there were some major issues with the overall experimental setup that need to be discussed and analyzed.

Reliability of Experimental Setup

To quickly visualize the variance among the different Amazon Turk workers assigned to labeling the aspect/opinion pairs, a function was utilized to create a bargraph that displays the different labels each worker voted for each aspect/opinion set that appeared in the dataset more than 10 times. A more statistical approach will be carried out using sum of squares residuals further down in the notebook. It is very apparent that the Amazon turks had a lot of trouble coming to any agreement on sentiment. The task was setup to reward workers to label data as quickly as possible without much safeguard to the quality of the work being submitted other than a quick overview by myself. I am just one poorly funded individual. Without proper funding from a research grant it was difficult to setup a reliable experiment. This cast a large shadow of doubt on the reliability of this data to be used as a way to reliably test the accuracy of my model. In comparison, you can see that the extractor chooses the same sentiment for a unique aspect/opinion pair every single time it shows

up in the dataset. While the human data has been revealed to be severely flawed, it has brought up a shining example as to why machine learning may be a better substitute for labeling large amounts of tedious data in the first place.

```
In [23]: 1 #create dataframe for tuple_pairs with more than 10 votes from turk dat
2
3 multi_votes = df_turk['tup_pair'].value_counts()[df_turk['tup_pair'].va
4
5 df_turk2 = df_turk[df_turk["tup_pair"].isin(multi_votes)].copy()
6
7 df_turk2.rename({'sentiment_h': 'sentiment'},
8                 axis=1,
9                 inplace=True
10                )
11
12 unique_tup = df_turk2.tup_pair.unique()
13
14
15
16 #create dataframe for tuple_pairs with more than 10 votes from extracto
17
18 multi_votes_e = df_senti_predicted['tup_pair'].value_counts()[df_senti_
19
20 df_ex = df_senti_predicted[df_senti_predicted["tup_pair"].isin(multi_vo
21
22 unique_tup_e = df_ex.tup_pair.unique()
```


Partition Sum Of Squares to Measure Dispersion of Turk Data

[Partition Sum of Squares](https://en.wikipedia.org/wiki/Partition_of_sums_of_squares) (https://en.wikipedia.org/wiki/Partition_of_sums_of_squares)


For simplicity, sum of square statistical measurements were calculated for each aspect in the human labeled data as well as the machine labeled data that had more than 10 votes. This was chosen over entropy as a calculation for dispersion as the "sum of squares" for these data is a close enough estimate for the variance in categorical data for this experiment. Every single human labeled aspect with multiple aspects had a non-zero value for residual sum of squares, while every machine labeled aspect had zero residual error. This shows the difference in variance statistically and mathematically very clearly between the two and shows the unreliability of the turk data. See the figure below for the total range in the residual sum of square values for the tested aspects in each group.

```
In [24]: 1 for tup in unique_tup_e:
2         variance_visualizer(df_ex, tup)
```

/Users/dylandey/anaconda3/envs/learn-env/lib/python3.6/site-packages/ipykernel_launcher.py:426: RuntimeWarning: More than 20 figures have been opened. Figures created through the pyplot interface (`matplotlib.pyplot.figure`) are retained until explicitly closed and may consume too much memory. (To control this warning, see the rcParam `figure.max_open_warning`).



```
In [25]: 1 for tup in unique_tup:
2         variance_visualizer(df_turk2, tup)
```



```
In [26]: 1 for tup in unique_tup_e:
2         sum_squares(df_ex, tup)
```

```

In [27]: 1 emp_list = []
          2 for tup in unique_tup:
          3     emp_list.append(sum_squares(df_turk2, tup))
          4
          5
          6 df_turk_var = pd.DataFrame(emp_list, columns=['asp', 'sum_of_squares'])
          7 df_turk_var.to_csv('data/turk_var1.csv')
          8
          9 emp_list = []
         10 for tup in unique_tup_e:
         11     sum_squares(df_ex, tup)
         12
         13 df_ex_var = pd.DataFrame(emp_list, columns=['asp', 'sum_of_squares'])
         14 df_ex_var.to_csv('data/human_var1.csv')

```

```

In [28]: 1 df_turk_var

```

Out[28]:

	asp	sum_of_squares
0	(wireless, headphones)	232.750000
1	(second, set)	4.750000
2	(clear, sound)	26.000000
3	(sound, quality)	870.000000
4	(great, headphones)	19.000000
5	(second, pair)	11.200000
6	(good, sound)	60.750000
7	(rechargeable, batteries)	4.666667
8	(good, range)	16.666667
9	(great, quality)	58.750000
10	(Sound, quality)	4.500000
11	(great, product)	34.750000
12	(great, range)	18.666667
13	(great, sound)	60.666667
14	(good, quality)	83.000000
15	(long, time)	11.200000

```

In [29]: 1 # all values sum to zero
          2
          3 df_ex_var

```

Out[29]:

asp sum_of_squares

Further Discussion and Future Work

1) Due to a lack of funding from grants and some other issues in experimental design, I feel the most appropriate next step would be to repeat the experiment with more carefully collected labeled data. Increasing the reward per label and the requirements for submission (such as proving a proficiency in english) I believe can substantially improve the quality of the human labeled data and reduce the variance in this data significantly. Sourcing reliable test data is the number one priority in continuing future work for this project.

2) Integrate into AWS for scaling

3) integrate into a SQL server for data management


4) incorporate a flash based UI for viewing results at scale

THANK YOU

[Blog \(https://dev.to/ddey117\)](https://dev.to/ddey117) | [GitHub \(https://github.com/ddey117/ABSA_Project_4\)](https://github.com/ddey117/ABSA_Project_4) | [PreProcess Github \(https://github.com/ddey117/preprocess_ddey117\)](https://github.com/ddey117/preprocess_ddey117)

Dylan Dey

email: ddey2985@gmail.com (<mailto:ddey2985@gmail.com>)



Appendix

Text Data Preprocessing and Cleaning toolkit

Word Counts

```
In [30]: 1 ls data
```

```
acc_prec_table.csv          human_var1.csv
batch1_results.csv          locally_sourced_labels.csv
batch2_results.csv          modifier_aspect_unlabeled.csv
batch3_results.csv          turk_data2
batch4_results.csv          turk_data2.csv
df_electronics_example.csv  turk_var1.csv
```

```
In [31]: 1 df = df.sample(100)
```

```
In [32]: 1 len('this is text'.split())
```

```
Out[32]: 3
```

```
In [33]: 1 df['word_counts'] = df['review_body'].apply(lambda x: len(str(x).split())
```

```
In [34]: 1 df.sample(5)
```

```
Out[34]:
```

	review_id	star_rating	review_body	wordcounts	word_counts
1090	R2EV6UHK8ZZKPP	5	92 year old dad LOVED these! Said it was the ...	21	21
3360	R2F8Z2G2RSUZ8	3	I thought when I ordered this would be the sam...	69	69
5394	R2BG44IAP6EQH9	5	It opened a whole new world of voice and music...	23	23
378	R1YMTKNTUYLCJZ	5	My RS 120s are my third set of headphones. My...	106	106
123	R1BUZY42O4J4D6	5	Great Product! Keeps your partner happy when w...	18	18

```
In [35]: 1 df['word_counts'].max()
```

```
Out[35]: 474
```

```
In [36]: 1 df['word_counts'].min()
```

```
Out[36]: 1
```

```
In [37]: 1 df[df['word_counts']==1]
```

Out[37]:

	review_id	star_rating	review_body	wordcounts	word_counts
	2073	R1T3D9ZJKPQF9V	4	good	1

Characters Count

```
In [38]: 1 len('this is')
```

Out[38]: 7

```
In [39]: 1 def char_counts(x):
2         s = x.split()
3         x = ' '.join(s)
4         return len(x)
```

```
In [40]: 1 char_counts('this is')
```

Out[40]: 6

```
In [42]: 1 df['char_counts'] = df['review_body'].apply(lambda x: char_counts(str(x)))
```

```
In [43]: 1 df.sample(5)
```

Out[43]:

	review_id	star_rating	review_body	wordcounts	word_counts	char_counts
5702	R11YXEXQVPM3LJ	5	In the living room with the TV in the middle o...	86	86	345
5850	R2J9ADIZPDEMFR	1	This item has never worked. All I get is stati...	34	34	147
2345	RE17VN0I9T0X1	4	Earphones works great. I'd give it 5 stars, ex...	38	38	171
1578	R3O1FPZB3J46D6	5	I have had other head sets. they aren't even c...	36	36	152
8506	R36THE4Z3X3797	5	I searched everywhere to find the best headpho...	209	209	938

Average Word Length

```
In [44]: 1 x = 'this is' # 6/2 = 3
          2 y = 'thankyou guys' # 12/2 = 6
```

```
In [45]: 1 df['avg_word_len'] = df['char_counts']/df['word_counts']
```

```
In [46]: 1 df.sample(4)
```

Out[46]:

	review_id	star_rating	review_body	wordcounts	word_counts	char_counts	avg_wor
800	R3KVSFIW1PCEZ4	5	works great after initially adjusting tuning f...	7	7	48	6.8
5236	R7PV556J6UHKF	1	Was really hoping these would work well but th...	68	68	299	4.3
7581	R3QZYC0TDVCQYE	4	The overall iem is good. The fit is a little l...	17	17	71	4.1
3683	R1EHM1VMSNBDKI	4	THE ONLY CRITICISM I HAVE IS THAT THE EAR PHON...	26	26	118	4.5

Stop Words Count

```
In [47]: 1 print(stopwords)
```

<WordListCorpusReader in '.../corpora/stopwords' (not loaded yet)>

```
In [48]: 1 len(stopwords)
```

```
-----
--
TypeError                                Traceback (most recent call las
t)
<ipython-input-48-0e227a118e01> in <module>
----> 1 len(stopwords)

TypeError: object of type 'LazyCorpusLoader' has no len()
```

```
In [49]: 1 x = 'this is the text data'
```

```
In [50]: 1 x.split()
```

```
Out[50]: ['this', 'is', 'the', 'text', 'data']
```

```
In [51]: 1 [t for t in x.split() if t in stopwords]
```

```
-----
--
TypeError                                Traceback (most recent call las
t)
<ipython-input-51-d6f9f3c59f41> in <module>
----> 1 [t for t in x.split() if t in stopwords]

<ipython-input-51-d6f9f3c59f41> in <listcomp>(.0)
----> 1 [t for t in x.split() if t in stopwords]

TypeError: argument of type 'LazyCorpusLoader' is not iterable
```

```
In [ ]: 1 len([t for t in x.split() if t in stopwords])
```

```
In [ ]: 1 df['stop_words_len'] = df['tweets'].apply(lambda x: len([t for t in x.s
```

```
In [ ]: 1 df.sample(5)
```

Count #HashTags and @Mentions

```
In [52]: 1 x = 'this is #hashtag and this is @mention'
```

```
In [53]: 1 x.split()
```

```
Out[53]: ['this', 'is', '#hashtag', 'and', 'this', 'is', '@mention']
```

```
In [54]: 1 [t for t in x.split() if t.startswith('@')]
```

```
Out[54]: ['@mention']
```

```
In [55]: 1 len([t for t in x.split() if t.startswith('@')])
```

```
Out[55]: 1
```

```
In [58]: 1 df['hashtags_count'] = df['review_body'].apply(lambda x: len([t for t in x.split() if t.startswith('#')]))
```

```
In [59]: 1 df['mentions_count'] = df['review_body'].apply(lambda x: len([t for t in x.split() if t.startswith('@')]))
```

```
In [60]: 1 df.sample(5)
```

Out[60]:

	review_id	star_rating	review_body	wordcounts	word_counts	char_counts	avg_wor
6936	R1BJ04XPMLMDXU	3	I really liked almost everything about this un...	248	248	997	4.0
1052	RTV3GR33VC179	4	I like these headphones, I get good range and ...	96	96	409	4.2
5926	R93XGUJB1286	1	When I first received this product, the chargi...	27	27	132	4.8
5702	R11YXEXQVPM3LJ	5	In the living room with the TV in the middle o...	86	86	345	4.0
7985	R1SC5Z6J9E9OYG	1	I got this product on April 1 and when I tried...	128	128	522	4.0

If numeric digits are present in tweets

```
In [61]: 1 x = 'this is 1 and 2'
```

```
In [62]: 1 x.split()
```

Out[62]: ['this', 'is', '1', 'and', '2']

```
In [63]: 1 x.split()[3].isdigit()
```

Out[63]: False

```
In [64]: 1 [t for t in x.split() if t.isdigit()]
```

```
Out[64]: ['1', '2']
```

```
In [65]: 1 df['numerics_count'] = df['review_body'].apply(lambda x: len([t for t in x.split() if t.isdigit()]))
```

```
In [66]: 1 df.sample(5)
```

```
Out[66]:
```

	review_id	star_rating	review_body	wordcounts	word_counts	char_counts	avg_wo
4935	R2CZX0A7L8IWG2	5	Best headphones I ever owned. The sound qualit...	40	40	181	4.5
504	R2JGAAP0GCZUKN	3	Sound is pretty good. Charging base is nice. ...	100	100	410	4.1
976	RBXAL93CXFM2V	5	Exactly what I needed for a fair price with ti...	11	11	50	4.5
5850	R2J9ADIZPDEMFR	1	This item has never worked. All I get is stati...	34	34	147	4.3
48	R3UH6JAA5NRDWK	5	These are great, no more batteries and we can ...	16	16	66	4.1

UPPER case words count

```
In [67]: 1 x = 'I AM HAPPY'
2 y = 'i am happy'
```

```
In [68]: 1 [t for t in x.split() if t.isupper()]
```

```
Out[68]: ['I', 'AM', 'HAPPY']
```

```
In [69]: 1 df['upper_counts'] = df['review_body'].apply(lambda x: len([t for t in x.split() if t.isupper()]))
```

```
In [70]: 1 df.sample(5)
```

```
Out[70]:
```

	review_id	star_rating	review_body	wordcounts	word_counts	char_counts
4423	R18HP3Z44HMBC4	4	It is good but, sometimes have to adjust to ge...	27	27	117
4381	R10VX4AU06SV1B	4	I use these headphones all the time. The sound...	21	21	106
976	RBXAL93CXFM2V	5	Exactly what I needed for a fair price with ti...	11	11	50
2946	R4HM1MIPN5BOI	5	Wish I knew about this headset before going th...	58	58	251
8300	R3K0Z5RQKPVXT5	5	I bought the wireless headphones(sennheiser 12...	39	39	182

Lower Case Conversion

```
In [ ]: 1 x = 'this is Text'
```

```
In [ ]: 1 x.lower()
```

```
In [ ]: 1 x = 45.0
2 str(x).lower()
```

```
In [72]: 1 df['review_body'] = df['review_body'].apply(lambda x: str(x).lower())
```


In [73]:

1

df.sample(5)

Out[73]:

	review_id	star_rating	review_body	wordcounts	word_counts	char_counts	avg_wor
5595	R2G6GVNS929E0X	2	the little dial used to "tune" this headset in...	64	64	278	4.3
4423	R18HP3Z44HMBC4	4	it is good but, sometimes have to adjust to ge...	27	27	117	4.3
6027	R1YZZ822BSFSVF	1	the product is excelent, but this refurbished ...	22	22	100	4.5
4935	R2CZX0A7L8IWG2	5	best headphones i ever owned. the sound qualit...	40	40	181	4.5
6961	R26HOZU0XT9M06	5	after reviewing many different headphones in t...	75	75	333	4.4



Contraction to Expansion

```
In [77]: 1 #created using wikipedia
2
3 contractions = {
4     "a'ight": "alright",
5     "ain't": "am not",
6     "amn't": "am not",
7     "arencha": "are not you",
8     "aren't": "are not",
9     "'bout": "about",
10    "can't": "cannot",
11    "cap'n": "captain",
12    "'cause": "because",
13    "'cept": "except",
14    "could've": "could have",
15    "couldn't": "could not",
16    "couldn't've": "could not have",
17    "cuppa": "cup of",
18    "dammit": "damn it",
19    "daren't": "dared not",
20    "daresn't": "dare not",
21    "dasn't": "dare not",
22    "didn't": "did not",
23    "doesn't": "does not",
24    "don't": "do not",
25    "dunno": "do not know",
26    "d'ye": "do you",
27    "e'en": "even",
28    "e'er": "ever",
29    "'em": "them",
30    "everybody's": "everybody is",
31    "everyone's": "everyone is",
32    "finna": "fixing to",
33    "fo'c'sle": "forecastle",
34    "'gainst": "against",
35    "g'day": "good day",
36    "gimme": "give me",
37    "giv'n": "given",
38    "gi'": "give us",
39    "gonna": "going to",
40    "gon't": "go not",
41    "gotta": "got to",
42    "hadn't": "had not",
43    "had've": "had have",
44    "hasn't": "has not",
45    "haven't": "have not",
46    "he'd": "he would",
47    "he'll": "he will",
48    "helluva": "hell of a",
49    "he's": "he is",
50    "here's": "here is",
51    "how'd": "how would",
52    "howdy": "how do you fare",
53    "how'll": "how will",
54    "how're": "how are",
55    "how's": "how is",
56    "i'd": "i would",
```

```
57 "i'd've": "i would have",
58 "i'd'nt": "i would not",
59 "i'd'nt've": "i would not have",
60 "i'll": "i will",
61 "i'm": "i am",
62 "imma": "i am about to",
63 "i'm'o": "i am going to",
64 "innit": "is it not it",
65 "i've": "i have",
66 "isn't": "is not",
67 "it'd": "it would",
68 "it'll": "it will",
69 "it's": "it is",
70 "idunno": "i do not know",
71 "kinda": "kind of",
72 "let's": "let us",
73 "loven't": "love not",
74 "ma'am": "madam",
75 "mayn't": "may not",
76 "may've": "may have",
77 "methinks": " i think",
78 "mightn't": "might not",
79 "might've": "might have",
80 "mustn't": "must not",
81 "mustn't've": "must not have",
82 "must've": "must have",
83 "'neath": "beneath",
84 "needn't": "need not",
85 " nal ": " and all ",
86 "ne'er": "never",
87 " o'er" : " over ",
88 " ol '": " old ",
89 "oughtn'": "ought not",
90 "'round": "around",
91 "shalln't": "shall not",
92 "shan't": "shall not",
93 "she'd": "she would",
94 "she'll": "he will",
95 "she's": "she is",
96 "should've": "should have",
97 "shouldn't": "should not",
98 "shouldn't've": "should not have",
99 "somebody's": "somebody is",
100 "someone's": "someone is",
101 "something's": "something is",
102 "so're": "so are",
103 "so's": "so is",
104 "so've": "so have",
105 "that'll": "that shall",
106 "that're": "that are",
107 "that's": "that is",
108 "that'd": "that would",
109 "there'd": "there had",
110 "there'll": "there shall",
111 "there're": "there are",
112 "there's": "there is",
113 "these're": "these are",
```

```
114 "these've": "these have",
115 "they'd": "they would",
116 "they'll": "they will",
117 "they're": "they are",
118 "they've": "they have",
119 "this's": "this is",
120 "those're": "those are",
121 "those've": "those have",
122 "'thout": "without",
123 "'til": "until",
124 "'tis": "it is",
125 "to've": "to have",
126 "'twas": "it was",
127 "'tween": "between",
128 "'twere": "it were",
129 "w'all": "we all",
130 "wanna": "want to",
131 "wasn't": "was not",
132 " we'd ": " we would ",
133 "we'd've": "we would have",
134 "we'll": "we will",
135 "we're": "we are",
136 "we've": "we have",
137 "weren't": "were not",
138 "whatcha": "what are you",
139 "what'd": "what did",
140 "what'll": "what will",
141 "what're": "what are",
142 "what's": "what is",
143 "what've": "what have",
144 "when's": "when is",
145 "where'd": "where did",
146 "where'll": "where will",
147 "where're": "where are",
148 "where's": "where is",
149 "where've": "where have",
150 "which'd": "which would",
151 "which'll": "which will",
152 "which're": "which are",
153 "which's": "which is",
154 "which've": "which have",
155 "who'd": "who would",
156 "who'd've": "who would have",
157 "who'll": "who will",
158 "who're": " who are",
159 "who's": "who is ",
160 "who've": "who have",
161 "why'd": "why did",
162 "why're": "why are",
163 "why's": "why has ",
164 "willn't": "will not",
165 "won't": "will not",
166 "wonnot": "will not",
167 "would've": "would have",
168 "wouldn't": "would not",
169 "wouldn't've": "would not have",
170 "y'all": "you all ",
```

```

171 "y'all'd've": "you all would have",
172 "y'all'd'n't've": "you all would not have",
173 "y'all're": "you all are" ,
174 "y'all'ren't": "you all are not",
175 " y'at ": " you at ",
176 "yes'm": "yes madam",
177 "y'know": "you know",
178 " yessir ": " yes sir ",
179 "you'd": "you would",
180 "you'll": "you will",
181 "you're": "you are",
182 "you've": "you have",
183 "when'd": "when did",
184 "willn't": "will not",
185 #append extra web lingo
186 " u ": " you ",
187 " ur ": " your ",
188 " n ": " and ",
189 " dis ": " this ",
190 " bak ": " back ",
191 " brng ": " bring ",
192 "sux": "sucks",
193 "gr8": "great",
194 " amzing ": " amazing ",
195 " k ": "ok",
196 " kk ": "ok",
197 " il ": "i will"}

```

```
In [78]: 1 x = "i'm don't he'll" # "i am do not he will"
```

```
In [79]: 1 def cont_to_exp(x):
2     if type(x) is str:
3         for key in contractions:
4             value = contractions[key]
5             x = x.replace(key, value)
6         return x
7     else:
8         return x
9
```

```
In [80]: 1 cont_to_exp(x)
```

```
Out[80]: 'i am do not he will'
```

```
In [81]: 1 %%timeit
2 df['review_body'] = df['review_body'].apply(lambda x: cont_to_exp(x))
```

8.42 ms ± 94.7 µs per loop (mean ± std. dev. of 7 runs, 100 loops each)

Count and Remove Emails

In [82]: 1 **import** re

```
In [83]: 1 df[df['review_body'].str.contains('hotmail.com')]['treview_body'].apply
```

```
-----
--
KeyError                                Traceback (most recent call las
t)
~/anaconda3/envs/learn-env/lib/python3.6/site-packages/pandas/core/indexe
s/base.py in get_loc(self, key, method, tolerance)
    2645         try:
-> 2646             return self._engine.get_loc(key)
    2647         except KeyError:

pandas/_libs/index.pyx in pandas._libs.index.IndexEngine.get_loc()

pandas/_libs/index.pyx in pandas._libs.index.IndexEngine.get_loc()

pandas/_libs/hashtable_class_helper.pxi in pandas._libs.hashtable.PyObjec
tHashTable.get_item()

pandas/_libs/hashtable_class_helper.pxi in pandas._libs.hashtable.PyObjec
tHashTable.get_item()

KeyError: 'treview_body'
```

During handling of the above exception, another exception occurred:

```
KeyError                                Traceback (most recent call las
t)
<ipython-input-83-ef9c4442bc0c> in <module>
----> 1 df[df['review_body'].str.contains('hotmail.com')]['treview_body']
      .apply(print)

~/anaconda3/envs/learn-env/lib/python3.6/site-packages/pandas/core/frame.
py in __getitem__(self, key)
    2798         if self.columns.nlevels > 1:
    2799             return self._getitem_multilevel(key)
-> 2800         indexer = self.columns.get_loc(key)
    2801         if is_integer(indexer):
    2802             indexer = [indexer]

~/anaconda3/envs/learn-env/lib/python3.6/site-packages/pandas/core/indexe
s/base.py in get_loc(self, key, method, tolerance)
    2646         return self._engine.get_loc(key)
    2647         except KeyError:
-> 2648         return self._engine.get_loc(self._maybe_cast_inde
xer(key))
    2649         indexer = self.get_indexer([key], method=method, toleranc
e=tolerance)
    2650         if indexer.ndim > 1 or indexer.size > 1:

pandas/_libs/index.pyx in pandas._libs.index.IndexEngine.get_loc()

pandas/_libs/index.pyx in pandas._libs.index.IndexEngine.get_loc()

pandas/_libs/hashtable_class_helper.pxi in pandas._libs.hashtable.PyObjec
tHashTable.get_item()
```

```
pandas/_libs/hashtable_class_helper.pxi in pandas._libs.hashtable.PyObjectHashTable.get_item()
```

```
KeyError: 'treview_body'
```

```
In [ ]: 1 x = '@securerecs arggh me please markbradbury_16@hotmail.com'
```

```
In [ ]: 1 re.findall(r'([a-z0-9+._-]+@[a-z0-9+._-]+\.[a-z0-9+_-]+)', x)
```

```
In [ ]: 1 df['emails'] = df['review_body'].apply(lambda x: re.findall(r'([a-z0-9+._-]+@[a-z0-9+._-]+\.[a-z0-9+_-]+)', x))
```

```
In [ ]: 1 df['emails_count'] = df['emails'].apply(lambda x: len(x))
```

```
In [ ]: 1 df[df['emails_count']>0]
```

```
In [ ]: 1 re.sub(r'([a-z0-9+._-]+@[a-z0-9+._-]+\.[a-z0-9+_-]+)', "", x)
```

```
In [ ]: 1 df['review_body'] = df['review_body'].apply(lambda x: re.sub(r'([a-z0-9+._-]+@[a-z0-9+._-]+\.[a-z0-9+_-]+)', "", x))
```

```
In [ ]: 1 df[df['emails_count']>0]
```

Count URLs and Remove it

```
In [ ]: 1 x = 'hi, thanks to watching it. for more visit https://youtube.com/notr'
```

```
In [ ]: 1 #ssh://git@git.com:username/repo.git=riif?%
```

```
In [ ]: 1 re.findall(r'(http|https|ftp|ssh):\/\/([\w_-]+(?:\.[\w_-]+)+)([\w.,@?&#%'\s]*?)', x)
```

```
In [ ]: 1 df['url_flags'] = df['review_body'].apply(lambda x: len(re.findall(r'(http|https|ftp|ssh):\/\/([\w_-]+(?:\.[\w_-]+)+)([\w.,@?&#%'\s]*?)', x)))
```

```
In [ ]: 1 df[df['url_flags']>0].sample(5)
```



```
In [ ]: 1 x
```

```
In [ ]: 1 re.sub(r'(http|https|ftp|ssh):\/\/([\w_-]+(?:?:(?:\.[\w_-]+)+))([\w.,@?^=%&
```

```
In [ ]: 1 df['review_body'] = df['review_body'].apply(lambda x: re.sub(r'(http|ht
```

```
In [ ]: 1 df.sample(5)
```

Remove RT

```
In [ ]: 1 df[df['review_body'].str.contains('rt ')]
```

```
In [ ]: 1 x = "beautifully smart and simple idea rt @madebyma"
```

```
In [ ]: 1 re.sub(r'rt\ ', '', x).strip()
```

```
In [ ]: 1 df['review_body'] = df['review_body'].apply(lambda x: re.sub(r'rt\ ', ''
```

Special Chars removal or punctuation removal

```
In [ ]: 1 df.sample(10)
```

```
In [ ]: 1 x = '@mention (cnnmoney) for #sxsw 2011, any comput...'
```

```
In [ ]: 1 re.sub(r'^[\w ]+', "", x)
```

```
In [ ]: 1 df['review_body'] = df['review_body'].apply(lambda x: re.sub(r'^[\w ]+', ''
```

```
In [ ]: 1 df.sample(5)
```

Remove multiple spaces "hi hello "

```
In [84]: 1 x = 'i like my space but how are you'
```

```
In [85]: 1 ' '.join(x.split())
```

```
Out[85]: 'i like my space but how are you'
```

```
In [86]: 1 df['review_body'] = df['review_body'].apply(lambda x: ' '.join(x.split()))
```

Remove HTML tags

```
In [87]: 1 from bs4 import BeautifulSoup
```

```
In [88]: 1 x = '<html><h1> i love html so much </h1></html>'
```

```
In [89]: 1 # x.replace('<html><h1>', '').replace('</h1></html>', '') #don't
```

```
In [90]: 1 BeautifulSoup(x, 'lxml').get_text().strip()
```

```
Out[90]: 'i love html so much'
```

```
In [91]: 1 %%time
2 df['review_body'] = df['review_body'].apply(lambda x: BeautifulSoup(x,
```

CPU times: user 23.8 ms, sys: 2.4 ms, total: 26.2 ms

Wall time: 25.2 ms

Remove Accented Chars

```
In [92]: 1 x = 'Áccëntěd těxt'
```

```
In [93]: 1 import unicodedata
```

```
In [94]: 1 def remove_accented_chars(x):
2         x = unicodedata.normalize('NFKD', x).encode('ascii', 'ignore').decode()
3         return x
```

```
In [95]: 1 remove_accented_chars(x)
```

```
Out[95]: 'Accented text'
```

```
In [96]: 1 df['review_body'] = df['review_body'].apply(lambda x: remove_accented_c
```

Remove Stop Words

```
In [97]: 1 df['review_no_stop'] = df['review_body'].apply(lambda x: ' '.join([t for t in x.split() if t not in stopwords]))
```

```
-----
--
TypeError                                Traceback (most recent call last)
<ipython-input-97-ee168402147b> in <module>
----> 1 df['tweets_no_stop'] = df['review_body'].apply(lambda x: ' '.join
([t for t in x.split() if t not in stopwords]))

~/anaconda3/envs/learn-env/lib/python3.6/site-packages/pandas/core/series.py in apply(self, func, convert_dtype, args, **kwargs)
    3846         else:
    3847             values = self.astype(object).values
-> 3848             mapped = lib.map_infer(values, f, convert=convert
_dtype)
    3849
    3850         if len(mapped) and isinstance(mapped[0], Series):

pandas/_libs/lib.pyx in pandas._libs.lib.map_infer()

<ipython-input-97-ee168402147b> in <lambda>(x)
----> 1 df['tweets_no_stop'] = df['review_body'].apply(lambda x: ' '.join
([t for t in x.split() if t not in stopwords]))

<ipython-input-97-ee168402147b> in <listcomp>(.0)
----> 1 df['tweets_no_stop'] = df['review_body'].apply(lambda x: ' '.join
([t for t in x.split() if t not in stopwords]))

TypeError: argument of type 'LazyCorpusLoader' is not iterable
```

Convert into base or root form of word

```
In [98]: 1 nlp = spacy.load('en_core_web_sm')
```

```
-----
--
OSError                                Traceback (most recent call last)
<ipython-input-98-12102ff9e1a9> in <module>
----> 1 nlp = spacy.load('en_core_web_sm')

~/anaconda3/envs/learn-env/lib/python3.6/site-packages/spacy/__init__.py
in load(name, vocab, disable, exclude, config)
    50     """
    51     return util.load_model(
--> 52         name, vocab=vocab, disable=disable, exclude=exclude, config=config
    53     )
    54

~/anaconda3/envs/learn-env/lib/python3.6/site-packages/spacy/util.py in load_model(name, vocab, disable, exclude, config)
    425     if name in OLD_MODEL_SHORTCUTS:
    426         raise IOError(Errors.E941.format(name=name, full=OLD_MODEL_SHORTCUTS[name])) # type: ignore[index]
--> 427     raise IOError(Errors.E050.format(name=name))
    428
    429

OSError: [E050] Can't find model 'en_core_web_sm'. It doesn't seem to be
a Python package or a valid path to a data directory.
```

```
In [99]: 1 x = 'i having a craved chocolates. what is times? these dogs likes ball'
```

```
In [100]: 1 def make_to_base(x):
2     x = str(x)
3     x_list = []
4     doc = nlp(x)
5
6     for token in doc:
7         lemma = token.lemma_
8         if lemma == '-PRON-' or lemma == 'be':
9             lemma = token.text
10
11         x_list.append(lemma)
12     return ' '.join(x_list)
```

```
In [101]: 1 make_to_base(x)
```

```
Out[101]: 'I have a crave chocolate . what is time ? these dog like ball'
```

```
In [102]: 1 df['review_body'] = df['review_body'].apply(lambda x: make_to_base(x))
```

```
In [103]: 1 df.sample(5)
```

Out[103]:

	review_id	star_rating	review_body	wordcounts	word_counts	char_counts	avg_wor
2345	RE17VN0I9T0X1	4	earphone work great . I would give it 5 star ,...	38	38	171	4.5
1983	R11U8YGNFAH57P	5	these head phone are wonderful ! my husband ca...	34	34	120	3.5
927	R2EQGEKSVGSSXF	5	this is the 3rd set I have own . 1st one the b...	87	87	345	3.9
800	R3KVSFIW1PCEZ4	5	work great after initially adjust tuning frequ...	7	7	48	6.8
4449	RGEUGUCHQ9BU4	4	fit and sound well . I can move around the hou...	22	22	89	4.0

Common words removal

```
In [104]: 1 text = ' '.join(df['review_body'])
```

```
In [105]: 1 len(text)
```

Out[105]: 40530

```
In [106]: 1 text = text.split()
```

```
In [107]: 1 len(text)
```

Out[107]: 8514

```
In [108]: 1 freq_comm = pd.Series(text).value_counts()
```

```
In [109]: 1 f20 = freq_comm[:20]
```

```
In [110]: 1 f20
```

```
Out[110]: .          451  
the        442  
I          257  
to         239  
,         232  
and        214  
is         149  
a          143  
it         125  
they       112  
have       105  
of          98  
not         95  
you         93  
my          90  
for         75  
on          73  
in          72  
headphone  72  
are         66  
dtype: int64
```

```
In [111]: 1 df['review_body'] = df['review_body'].apply(lambda x: ' '.join([t for t
```

```
In [112]: 1 df.sample(5)
```

Out[112]:

	review_id	star_rating	review_body	wordcounts	word_counts	char_counts	avg_wor
4761	R16DZYDQG883HT	5	significant amount time elderly father been in...	355	355	1641	4.62
6917	RGHS0APBB60AY	4	like many wireless headset sound quality come ...	259	259	1180	4.56
3026	R1YI3CU3PJN55R	4	great sound price but do tend fall off when be...	26	26	105	4.00
6044	R3FPXDG1K7X8HC	4	were deliver very quickly quality function mer...	31	31	159	5.12
7607	R15BOFL2F3PHGF	1	do work base unit do work when arrive very poo...	17	17	71	4.17

Rare words removal

```
In [113]: 1 rare40 = freq_comm.tail(40)
          2 rare40
```

```
Out[113]: extra          1
          fool           1
          cx             1
          hit            1
          code           1
          shop           1
          selection      1
          laptop         1
          avoid          1
          else           1
          mids           1
          powerful       1
          discomfort     1
          minimum        1
          whatever       1
          less           1
          forward        1
          bear           1
          amazing        1
          shipment       1
          anymore        1
          yes            1
          tangle         1
          occasional     1
          appropriate    1
          aa             1
          acre           1
          improvement    1
          prompt         1
          retire         1
          nothing        1
          shopping       1
          between        1
          distinct       1
          digital        1
          space          1
          throw          1
          eart           1
          determine      1
          kill           1
          dtype: int64
```

```
In [114]: 1 df['review_body'] = df['review_body'].apply(lambda x: ' '.join([t for t
```



```
In [115]: 1 df.sample(5)
```

```
Out[115]:
```

	review_id	star_rating	review_body	wordcounts	word_counts	char_counts	avg_woi
7158	R35YV3AB2DV5IV	4	only gripe about these that instruction set up...	101	101	474	4.6
7926	RWUQH0N1HHZ0B	4	been very satisfied with cordless purchase hus...	63	63	283	4.4
2679	RBT5VQLABG9X3	5	top quality recommend	3	3	19	6.3
7255	R2IHRCMRRVZ0Y	4	buy this item few month ago because tend stay ...	88	88	397	4.5
2893	R38TG1Y9KFO7I	5	very very good	3	3	12	4.0

Word Cloud Visualization

```
In [116]: 1 # !pip install wordcloud
```

```
In [117]: 1 from wordcloud import WordCloud
2 import matplotlib.pyplot as plt
3 %matplotlib inline
```

```
In [118]: 1 text = ' '.join(df['review_body'])
```

```
In [119]: 1 len(text)
```

```
Out[119]: 29799
```



```

In [ ]: 1 # from gensim import corpora, models
2 # tfidf = models.TfidfModel(bow_corpus)
3 # corpus_tfidf = tfidf[bow_corpus]
4 # from pprint import pprint
5 # for doc in corpus_tfidf:
6 #     pprint(doc)
7 #     break
8
9
10 # lda_model = gensim.models.LdaMulticore(bow_corpus, num_topics=4, id2w
11
12 # for idx, topic in lda_model.print_topics(-1):
13 #     print('Topic: {} \nWords: {}'.format(idx, topic))
14
15
16 # lda_model_tfidf = gensim.models.LdaMulticore(corpus_tfidf, num_topics
17 # for idx, topic in lda_model_tfidf.print_topics(-1):
18 #     print('Topic: {} Word: {}'.format(idx, topic))
19
20
21 # from sklearn.cluster import DBSCAN
22 # from sklearn import metrics
23 # from sklearn.preprocessing import StandardScaler
24
25
26
27 # from sklearn.cluster import AffinityPropagation
28
29
30 # # #####
31 # # Compute Affinity Propagation
32 # af = AffinityPropagation(random_state=42).fit(word_vecs_scaled)
33 # cluster_centers_indices = af.cluster_centers_indices_
34 # labels = af.labels_
35
36 # n_clusters_ = len(cluster_centers_indices)
37
38 # print("Estimated number of clusters: %d" % n_clusters_)
39
40
41
42
43 # db = DBSCAN(eps=21, min_samples=3).fit(word_vecs_scaled)
44 # core_samples_mask = np.zeros_like(db.labels_, dtype=bool)
45 # core_samples_mask[db.core_sample_indices_] = True
46 # labels = db.labels_
47
48 # # Number of clusters in labels, ignoring noise if present.
49 # n_clusters_ = len(set(labels)) - (1 if -1 in labels else 0)
50 # n_noise_ = list(labels).count(-1)
51
52 # print("Estimated number of clusters: %d" % n_clusters_)
53 # print("Estimated number of noise points: %d" % n_noise_)
54 # print("Homogeneity: %0.3f" % metrics.homogeneity_score(labels_true, l
55 # print("Completeness: %0.3f" % metrics.completeness_score(labels_true,
56 # print("V-measure: %0.3f" % metrics.v_measure_score(labels_true, label

```

```
57 # print("Adjusted Rand Index: %0.3f" % metrics.adjusted_rand_score(labels_true, labels))
58 # print(
59 #     "Adjusted Mutual Information: %0.3f"
60 #     % metrics.adjusted_mutual_info_score(labels_true, labels)
61 # )
62 # print("Silhouette Coefficient: %0.3f" % metrics.silhouette_score(X, labels_true))
```

```

In [ ]: 1 # import gensim
2
3
4 # def get_aspect_gensim_dict(aspects):
5 #     aspect_freq_map = defaultdict(int)
6 #     for asp in aspects:
7 #         aspect_freq_map[asp] += 1
8 #     return aspect_freq_map
9
10
11 # from gensim.utils import simple_preprocess
12
13 # def preprocess(text):
14 #     result = []
15 #     for token in gensim.utils.simple_preprocess(text):
16 #         if token not in gensim.parsing.preprocessing.STOPWORDS and len(token) > 3:
17 #             result.append(token)
18 #     return result
19
20
21 # df_single_aspect['gensim_tokens'] = df_single_aspect['asp'].apply([preprocess] * len(df_single_aspect['asp']))
22
23 # dictionary = gensim.corpora.Dictionary(df_single_aspect['gensim_tokens'].tolist())
24
25
26 # count = 0
27 # for k, v in dictionary.iteritems():
28 #     print(k, v)
29 #     count += 1
30 #     if count > 10:
31 #         break
32
33 # dictionary.filter_extremes(no_below=15, no_above=0.5, keep_n=10000)
34
35
36 # bow_corpus = [dictionary.doc2bow(doc) for doc in df_single_aspect['gensim_tokens'].tolist()]
37
38 # from gensim import corpora, models
39 # tfidf = models.TfidfModel(bow_corpus)
40 # corpus_tfidf = tfidf[bow_corpus]
41 # from pprint import pprint
42 # for doc in corpus_tfidf:
43 #     pprint(doc)
44 #     break
45
46 # lda_model = gensim.models.LdaMulticore(bow_corpus, num_topics=4, id2word=dictionary, chunksize=1000)
47
48 # for idx, topic in lda_model.print_topics(-1):
49 #     print('Topic: {} \nWords: {}'.format(idx, topic))
50
51
52 # lda_model_tfidf = gensim.models.LdaMulticore(corpus_tfidf, num_topics=4, id2word=dictionary, chunksize=1000)
53 # for idx, topic in lda_model_tfidf.print_topics(-1):
54 #     print('Topic: {} Word: {}'.format(idx, topic))

```

In []:	1	
In []:	1	
In []:	1	
In []:	1	