

MidoNet Quick Start Guide

for Ubuntu 14.04 / Icehouse

2015.01 (2015-02-06 08:19 UTC)



docs.midonet.org

MidoNet Quick Start Guide for Ubuntu 14.04 / Icehouse

2015.01 (2015-02-06 08:19 UTC)

Copyright © 2014, 2015 Midokura SARL All rights reserved.

MidoNet is a network virtualization software for Infrastructure-as-a-Service (IaaS) clouds.

It decouples your IaaS cloud from your network hardware, creating an intelligent software abstraction layer between your end hosts and your physical network.

This guide walks through the minimum installation and configuration steps necessary to use MidoNet with OpenStack.

2015.01



Note

Please consult the [MidoNet Mailing Lists or IRC](#) if you need assistance.

Licensed under the Apache License, Version 2.0 (the "License"); you may not use this file except in compliance with the License. You may obtain a copy of the License at

<http://www.apache.org/licenses/LICENSE-2.0>

Unless required by applicable law or agreed to in writing, software distributed under the License is distributed on an "AS IS" BASIS, WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied. See the License for the specific language governing permissions and limitations under the License.

Table of Contents

Preface	iv
Conventions	iv
1. Architecture	1
Hosts and Services	1
2. Basic Environment Configuration	3
Networking Configuration	3
Repository Configuration	3
3. OpenStack Installation	5
Identity Service (Keystone)	5
Compute Services (Nova)	5
Networking Service (Neutron)	6
4. MidoNet Installation	10
NSDB Nodes	10
Controller Node	12
Midolman Installation	13
MidoNet Host Registration	13
5. Further Steps	15

Preface

Conventions

The MidoNet documentation uses several typesetting conventions.

Notices

Notices take these forms:



Note

A handy tip or reminder.



Important

Something you must be aware of before proceeding.



Warning

Critical information about the risk of data loss or security issues.

Command prompts

\$ prompt

Any user, including the root user, can run commands that are prefixed with the \$ prompt.

prompt

The root user must run commands that are prefixed with the # prompt. You can also prefix these commands with the **sudo** command, if available, to run them.

1. Architecture

Table of Contents

Hosts and Services	1
--------------------------	---



Important

This guide assumes the following system architecture, based on [Figure 1.2. Three-node architecture with OpenStack Networking \(neutron\)](#) of the OpenStack Documentation.

This architecture consists of three hosts:

- Controller Node (**controller**)
- Network Node (**network**)
- Compute Node (**compute1**)

The *MidoNet Network State Database (NSDB)* uses [ZooKeeper](#) and [Cassandra](#) to store network topology and state information. The NSDB components can be installed on separate hosts, but this guide assumes them to be installed on all three nodes (**controller**, **network**, **compute1**).

The *MidoNet Agent (Midolman)* has to be installed on all nodes where traffic enters or leaves the virtual topology, in this guide this are the **network** and **compute1** nodes.

The *Midonet API* can be installed on a separate host, but this guide assumes it to be installed on the **controller** node.

The *Midonet Command Line Interface (CLI)* can be installed on a separate host, but this guide assumes it to be installed on the **controller** node.

The *Midonet Neutron Plugin* replaces the ML2 Plugin and has to be installed on all three nodes (**controller**, **network**, **compute1**).

Hosts and Services

Controller Node (**controller**)

- General
 - Database (MySQL / MariaDB)
 - Message Broker (RabbitMQ)
- OpenStack
 - Identity Service (Keystone)
 - Image Service (Glance)
 - Compute (Nova)

- Networking (Neutron)
- Dashboard (Horizon)
- MidoNet
 - API
 - CLI
 - Neutron Plugin
 - Network State Database (NSDB)
 - Network Topology (ZooKeeper)
 - Network State Information (Cassandra)

Network Node (network)

- OpenStack
 - Networking (Neutron)
 - DHCP Agent
 - Metadata Agent
- MidoNet
 - Agent (Midolman)
 - Neutron Plugin
 - Network State Database (NSDB)
 - Network Topology (ZooKeeper)
 - Network State Information (Cassandra)

Compute Node (compute1)

- OpenStack
 - Compute (Nova)
 - Networking (Neutron)
- MidoNet
 - Agent (Midolman)
 - Neutron Plugin
 - Network State Database (NSDB)
 - Network Topology (ZooKeeper)
 - Network State Information (Cassandra)

2. Basic Environment Configuration

Table of Contents

Networking Configuration	3
Repository Configuration	3

Networking Configuration



Important

All hostnames must be resolvable, either via DNS or locally.

This guide assumes that you follow the instructions in [OpenStack Networking \(neutron\)](#) of the OpenStack Documentation.

Repository Configuration

Configure necessary software repositories and update installed packages.

1. Configure Ubuntu repositories

Edit the `/etc/apt/sources.list` file to contain the following:

```
# Ubuntu Main Archive
deb http://archive.ubuntu.com/ubuntu/ trusty main
deb http://security.ubuntu.com/ubuntu trusty-security main

# Ubuntu Universe Archive
deb http://archive.ubuntu.com/ubuntu/ trusty universe
deb http://security.ubuntu.com/ubuntu trusty-security universe
```

2. Configure DataStax repository

Create the `/etc/apt/sources.list.d/datastax.list` file and edit it to contain the following:

```
# DataStax (Apache Cassandra)
deb http://debian.datastax.com/community stable main
```

Download and install the repository's key:

```
# curl -L http://debian.datastax.com/debian/repo_key | apt-key add -
```

3. Configure MidoNet repositories

Create the `/etc/apt/sources.list.d/midonet.list` file and edit it to contain the following:

```
# MidoNet
deb http://repo.midonet.org/midonet/v2015.01 stable main

# MidoNet OpenStack Integration
deb http://repo.midonet.org/openstack-icehouse stable main
```

```
# MidoNet 3rd Party Tools and Libraries
deb http://repo.midonet.org/misc stable main
```

Download and install the repositories' key:

```
# curl -k http://repo.midonet.org/packages.midokura.key | apt-key add -
```

4. Install available updates

```
# apt-get update
# apt-get dist-upgrade
```

5. If necessary, reboot the system

```
# reboot
```


3. OpenStack Installation

Table of Contents

Identity Service (Keystone)	5
Compute Services (Nova)	5
Networking Service (Neutron)	6



Important

Follow the [OpenStack Icehouse Installation Guide for Ubuntu 12.04/14.04 \(LTS\)](#) , but **note the following differences**.

Identity Service (Keystone)



Important

Follow the OpenStack documentation's [Chapter 3. Configure the Identity Service](#) instructions, but **note the following additions**.

1. Create MidoNet API Service

As Keystone admin, execute the following command:

```
$ keystone service-create --name midonet --type midonet --description  
"MidoNet API Service"
```

2. Create MidoNet Administrative User

As Keystone admin, execute the following commands:

```
$ keystone user-create --name midonet --pass MIDONET_PASS --tenant admin  
$ keystone user-role-add --user midonet --role admin --tenant admin
```

Compute Services (Nova)



Important

Follow the OpenStack documentation's [Chapter 6. Configure Compute services](#) instructions, but **note the following differences**.

Controller Node



Note

Follow the OpenStack documentation's [Install Compute controller services](#) instructions as is.

Compute Node



Important

Follow the OpenStack documentation's [Configure a compute node](#) instructions, but **note the following additions**.

1. Configure libvirt

Edit the `/etc/libvirt/qemu.conf` file to contain the following:

```
user = "root"
group = "root"

cgroup_device_acl = [
    "/dev/null", "/dev/full", "/dev/zero",
    "/dev/random", "/dev/urandom",
    "/dev/ptmx", "/dev/kvm", "/dev/kqemu",
    "/dev/rtc", "/dev/hpet", "/dev/vfio/vfio",
    "/dev/net/tun"
]
```

2. Restart the libvirt service

```
# service libvirt-bin restart
```

1. Install nova-rootwrap network filters

```
# apt-get install nova-network
```

2. Restart the Compute service

```
# service nova-compute restart
```

Networking Service (Neutron)



Important

Follow the OpenStack documentation's [Chapter 7. Modular Layer 2 \(ML2\) plug-in](#) instructions, but **note the following differences**.

Controller Node



Important

Follow the OpenStack documentation's [Configure controller node](#) instructions, but **note the following differences**.

1. Prerequisites

Apply as is.

2. To install the Networking components

Do **not** apply.

a. Instead, install the following packages:

```
# apt-get install neutron-server python-neutron-plugin-midoNet
```

3. To configure the Networking server component

Do **not** apply step '5. Configure Networking to use the Modular Layer 2 (ML2) plug-in and associated services'.

- a. Instead, edit the `/etc/neutron/neutron.conf` file and add the following key to the `[DEFAULT]` section:

```
[DEFAULT]
...
core_plugin = midonet.neutron.plugin.MidonetPluginV2
```



Note

Make sure to not leave any space at the starting of lines in any configuration file (this applies to all configuration files).

4. To configure the Modular Layer 2 (ML2) plug-in

Do **not** apply.

Instead, perform the following steps.

- a. Create the directory for the MidoNet plugin:

```
mkdir /etc/neutron/plugins/midonet
```

- b. Create the `/etc/neutron/plugins/midonet/midonet.ini` file and edit it to contain the following:

```
[DATABASE]
sql_connection = mysql://neutron:NEUTRON_DBPASS@controller/neutron

[MIDONET]
# MidoNet API URL
midonet_uri = http://controller:8080/midonet-api
# MidoNet administrative user in Keystone
username = midonet
password = MIDONET_PASS
# MidoNet administrative user's tenant
project_id = admin
```

- c. Edit the `/etc/default/neutron-server` file to contain the following:

```
NEUTRON_PLUGIN_CONFIG="/etc/neutron/plugins/midonet/midonet.ini"
```

5. To configure Compute to use Networking

Apply as is.

6. To finalize installation

Apply as is.

Network Node



Important

Follow the OpenStack documentation's [Configure network node](#) instructions, but **note the following differences**.

1. Prerequisites

Apply as is.

2. To install the Networking components

Do not apply.

- a. Instead, install the following packages:

```
# apt-get install neutron-dhcp-agent neutron-metadata-agent python-  
neutron-plugin-midonet
```

3. To configure the Networking common components

Do not apply step '3. Configure Networking to use the Modular Layer 2 (ML2) plug-in and associated services'.

- a. Instead, edit the `/etc/neutron/neutron.conf` file and add the following key to the `[DEFAULT]` section:

```
[DEFAULT]  
...  
core_plugin = midonet.neutron.plugin.MidonetPluginV2
```

4. To configure the Layer-3 (L3) agent

Do not apply.

5. To configure the DHCP agent

Do not apply.

- a. Instead, edit the `/etc/neutron/dhcp_agent.ini` file to contain the following:

```
[DEFAULT]  
interface_driver =  
    neutron.agent.linux.interface.MidonetInterfaceDriver  
dhcp_driver = midonet.neutron.agent.midonet_driver.DhcpNoOpDriver  
use_namespaces = True  
enable_isolated_metadata = True  
  
[MIDONET]  
# MidoNet API URL  
midonet_uri = http://controller:8080/midonet-api  
# MidoNet administrative user in Keystone  
username = midonet  
password = MIDONET_PASS  
# MidoNet administrative user's tenant  
project_id = admin
```

6. To configure the metadata agent

Apply as is.

7. To configure the Modular Layer 2 (ML2) plug-in

Do not apply.

8. To configure the Open vSwitch (OVS) service

Do not apply.

9. To finalize the installation

Do **not** apply.

- a. Instead, restart the following services:

```
# service neutron-dhcp-agent restart
# service neutron-metadata-agent restart
```

Compute Node



Important

Follow the OpenStack documentation's [Configure compute node](#) instructions, but **note the following differences**.

1. Prerequisites

Apply as is.

2. To install the Networking components

Do **not** apply.

- a. Instead, install the following packages:

```
# apt-get install neutron-common python-neutron-plugin-midonet
```

3. To configure the Networking common components

Do **not** apply step '3. Configure Networking to use the Modular Layer 2 (ML2) plug-in and associated services'.

- a. Instead, Edit the `/etc/neutron/neutron.conf` file and add the following key to the `[DEFAULT]` section:

```
[DEFAULT]
...
core_plugin = midonet.neutron.plugin.MidonetPluginV2
```

4. To configure the Modular Layer 2 (ML2) plug-in

Do **not** apply.

5. To configure the Open vSwitch (OVS) service

Do **not** apply.

6. To configure Compute to use Networking

Apply as is.

7. To finalize the installation

Do **not** apply.

- a. Instead, restart the following service:

```
# service nova-compute restart
```

4. MidoNet Installation

Table of Contents

NSDB Nodes	10
Controller Node	12
Midolman Installation	13
MidoNet Host Registration	13

NSDB Nodes



Note

The NSDB components can be installed on separate hosts, but this guide assumes that you install them on all three nodes of the [Three-node architecture with OpenStack Networking \(neutron\)](#) example architecture.

ZooKeeper Installation

1. Install ZooKeeper packages

```
# apt-get install zookeeper zookeeperd zkdump
```

2. Configure ZooKeeper

a. Common Configuration

Edit the `/etc/zookeeper/conf/zoo.cfg` file to contain the following:

```
server.1=controller:2888:3888
server.2=network:2888:3888
server.3=compute1:2888:3888
```

b. Node-specific Configuration

i. Controller Node

Create the `/var/lib/zookeeper/myid` file and edit it to contain the host's ID:

```
# echo 1 > /var/lib/zookeeper/myid
```

ii. Network Node

Create the `/var/lib/zookeeper/myid` file and edit it to contain the host's ID:

```
# echo 2 > /var/lib/zookeeper/myid
```

iii. Compute Node

Create the `/var/lib/zookeeper/myid` file and edit it to contain the host's ID:

```
# echo 3 > /var/lib/zookeeper/myid
```

3. Restart ZooKeeper

```
# service zookeeper restart
```

Cassandra Installation

1. Install Cassandra packages

```
# apt-get install openjdk-7-jre-headless
# apt-get install dsc20=2.0.10-1 cassandra=2.0.10
# apt-mark hold dsc20 cassandra
```

2. Configure Cassandra

a. Common Configuration

Edit the `/etc/cassandra/cassandra.yaml` file to contain the following:

```
# The name of the cluster.
cluster_name: 'midonet'

...

# Addresses of hosts that are deemed contact points.
seed_provider:
  - class_name: org.apache.cassandra.locator.SimpleSeedProvider
    parameters:
      - seeds: "controller,network,compute1"
```

b. Node-specific Configuration

i. Controller Node

Edit the `/etc/cassandra/cassandra.yaml` file to contain the following:

```
# Address to bind to and tell other Cassandra nodes to connect to.
listen_address: controller

...

# The address to bind the Thrift RPC service.
rpc_address: controller
```

ii. Network Node

Edit the `/etc/cassandra/cassandra.yaml` file to contain the following:

```
# Address to bind to and tell other Cassandra nodes to connect to.
listen_address: network

...

# The address to bind the Thrift RPC service.
rpc_address: network
```

iii. Compute Node

Edit the `/etc/cassandra/cassandra.yaml` file to contain the following:

```
# Address to bind to and tell other Cassandra nodes to connect to.
listen_address: compute1

...
```

```
# The address to bind the Thrift RPC service.  
rpc_address: compute1
```

3. Clean existing data and restart Cassandra

```
# service cassandra stop  
# rm -rf /var/lib/cassandra/*  
# service cassandra start
```

Controller Node

MidoNet API Installation

1. Install MidoNet API package

```
# apt-get install midonet-api
```

2. Configure MidoNet API

Edit the `/usr/share/midonet-api/WEB-INF/web.xml` file to contain the following:

```
<context-param>  
  <param-name>rest_api-base_uri</param-name>  
  <param-value>http://controller:8080/midonet-api</param-value>  
</context-param>
```

```
<context-param>  
  <param-name>keystone-service_host</param-name>  
  <param-value>controller</param-value>  
</context-param>
```

```
<context-param>  
  <param-name>keystone-admin_token</param-name>  
  <param-value>ADMIN_TOKEN</param-value>  
</context-param>
```

```
<context-param>  
  <param-name>zookeeper-zookeeper_hosts</param-name>  
  <param-value>controller:2181,network:2181,compute1:2181</param-value>  
</context-param>
```

3. Install Tomcat package

```
# apt-get install tomcat7
```

4. Configure Tomcat's Entropy Source

Edit the `/usr/share/tomcat7/bin/catalina.sh` file to contain the following:

```
JAVA_OPTS="$JAVA_OPTS -Djava.security.egd=file:/dev/./urandom"
```

5. Configure MidoNet API context

Create the `/etc/tomcat7/Catalina/localhost/midonet-api.xml` file and edit it to contain the following:

```
<Context  
  path="/midonet-api"  
  docBase="/usr/share/midonet-api"
```



```
    antiResourceLocking="false"  
    privileged="true"  
/>
```

6. Restart Tomcat

```
# service tomcat7 restart
```

MidoNet CLI Installation

1. Install MidoNet CLI package

```
# apt-get install python-midonetclient
```

2. Configure MidoNet CLI

Create the `~/.midonetrc` file and edit it to contain the following:

```
[cli]  
api_url = http://controller:8080/midonet-api  
username = admin  
password = ADMIN_PASS  
project_id = admin
```

Midolman Installation

The Midolman agent shall be installed on all network and compute nodes.

1. Install Midolman package

```
# apt-get install midolman
```

2. Configure Network State Database (NSDB)

Edit the `/etc/midolman/midolman.conf` file to contain the following:

```
[zookeeper]  
zookeeper_hosts = controller:2181,network:2181,compute1:2181  
...  
[cassandra]  
servers = controller,network,compute1  
replication_factor = 3  
cluster = midonet
```

3. Configure Quagga

Edit the `/etc/midolman/midolman.conf` file to contain the following:

```
bgpd_binary = /usr/lib/quagga/
```

4. Restart Midolman

```
# service midolman restart
```

MidoNet Host Registration

1. Launch MidoNet CLI

```
$ midonet-cli
```

```
midonet>
```

2. Create tunnel zone

```
midonet> tunnel-zone create name gre type gre  
tzone0
```

3. Add hosts to tunnel zone

```
midonet> list host  
host host0 name network alive true  
host host1 name compute1 alive true  
  
midonet> tunnel-zone tzone0 add member host host0  
address ip_address_host0  
zone tzone0 host host0 address ip_address_host0  
  
midonet> tunnel-zone tzone0 add member host host1  
address ip_address_host1  
zone tzone0 host host1 address ip_address_host1
```

5. Further Steps

MidoNet installation and integration into OpenStack is completed.

You can now continue with the creation of initial networks in Neutron.



Note

Consult the **Operation Guide** for further instructions on operating MidoNet.