

MidoNet Quick Start Guide

for RHEL 7 / Liberty (OSP 8)

5.0-SNAPSHOT (2016-06-29 04:42 UTC)

DRAFT



MidoNet Quick Start Guide for RHEL 7 / Liberty (OSP 8)

5.0-SNAPSHOT (2016-06-29 04:42 UTC)

Copyright © 2016 Midokura SARL All rights reserved.

MidoNet is a network virtualization software for Infrastructure-as-a-Service (IaaS) clouds.

It decouples your IaaS cloud from your network hardware, creating an intelligent software abstraction layer between your end hosts and your physical network.

This guide walks through the minimum installation and configuration steps necessary to use MidoNet with OpenStack.



Caution

This document is a DRAFT. It may be MISSING relevant information or contain UNTESTED information. Use it at your own risk.



Note

Please consult the [MidoNet Mailing Lists or Chat](#) if you need assistance.

Licensed under the Apache License, Version 2.0 (the "License"); you may not use this file except in compliance with the License. You may obtain a copy of the License at

<http://www.apache.org/licenses/LICENSE-2.0>

Unless required by applicable law or agreed to in writing, software distributed under the License is distributed on an "AS IS" BASIS, WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied. See the License for the specific language governing permissions and limitations under the License.

Table of Contents

Preface	iv
Conventions	iv
1. Architecture	1
Hosts and Services	2
2. Basic Environment Configuration	4
Networking Configuration	4
SELinux Configuration	4
Repository Configuration	4
3. OpenStack Installation	6
Identity Service (Keystone)	6
Compute Services (Nova)	7
Networking Services (Neutron)	11
4. MidoNet Installation	15
NSDB Nodes	15
Controller Node	18
Midolman Installation	20
MidoNet Host Registration	21
5. Initial Network Configuration	23
6. Edge Router Setup	24
7. BGP Uplink Configuration	26
8. Further Steps	28

Preface

Conventions

The MidoNet documentation uses several typesetting conventions.

Notices

Notices take these forms:



Note

A handy tip or reminder.



Important

Something you must be aware of before proceeding.



Warning

Critical information about the risk of data loss or security issues.

Command prompts

\$ prompt

Any user, including the root user, can run commands that are prefixed with the \$ prompt.

prompt

The root user must run commands that are prefixed with the # prompt. You can also prefix these commands with the **sudo** command, if available, to run them.

1. Architecture

Table of Contents

Hosts and Services	2
--------------------------	---

This guide assumes the following example system architecture.

OpenStack Controller Node:

- Controller Node (**controller**)

Compute Node:

- Compute Node (**compute1**)

Since MidoNet is a distributed system, it does not have the concept of a Network Node as being used with the default OpenStack networking plugin. Instead it uses two or more Gateway Nodes that utilize [Quagga](#) to provide connectivity to external networks via the Border Gateway Protocol (BGP).

- Gateway Node 1 (**gateway1**)
- Gateway Node 2 (**gateway2**)

Three or more hosts are being used for the MidoNet Network State Database (NSDB) cluster which utilizes [ZooKeeper](#) and [Cassandra](#) to store virtual network topology and connection state information:

- NSDB Node 1 (**nsdb1**)
- NSDB Node 2 (**nsdb2**)
- NSDB Node 3 (**nsdb3**)



Important

Ideally, both the ZooKeeper transaction log and Cassandra data files need their own dedicated disks, with additional disks for other services on the host. However, for small POCs and small deployments, it is ok to share the Cassandra disk with other services and just leave the ZooKeeper transaction log on its own.

The *MidoNet Agent (Midolman)* has to be installed on all nodes where traffic enters or leaves the virtual topology. In this guide this are the **gateway1**, **gateway2** and **compute1** hosts.

The *Midonet Cluster* can be installed on a separate host, but this guide assumes it to be installed on the **controller** host.

The *Midonet Command Line Interface (CLI)* can be installed on any host that has connectivity to the MidoNet Cluster. This guide assumes it to be installed on the **controller** host.

The *Midonet Neutron Plugin* replaces the ML2 Plugin and has to be installed on the **controller**.

Hosts and Services

Controller Node (controller)

- General
 - Database (MariaDB)
 - Message Broker (RabbitMQ)
- OpenStack
 - Identity Service (Keystone)
 - Image Service (Glance)
 - Compute (Nova)
 - Networking (Neutron)
 - Neutron Server
 - Dashboard (Horizon)
- MidoNet
 - Cluster
 - CLI
 - Neutron Plugin

Compute Node (compute1)

- OpenStack
 - Compute (Nova)
 - Networking (Neutron)
- MidoNet
 - Agent (Midolman)

NSDB Nodes (nsdb1, nsdb2, nsdb3)

- Network State Database (NSDB)
 - Network Topology (ZooKeeper)
 - Network State Information (Cassandra)

Gateway Nodes (gateway1, gateway2)

- BGP Daemon (Quagga)

- MidoNet
 - Agent (Midolman)

2. Basic Environment Configuration

Table of Contents

Networking Configuration	4
SELinux Configuration	4
Repository Configuration	4

Networking Configuration



Important

All hostnames must be resolvable, either via DNS or locally.

This guide assumes that you follow the instructions in [Host Networking](#) of the OpenStack Documentation.

SELinux Configuration



Important

This guide assumes that SELinux (if installed) is either in permissive state or disabled.

To change the mode, execute the following command:

```
# setenforce Permissive
```

To permanently change the SELinux configuration, edit the `/etc/selinux/config` file accordingly:

```
SELINUX=permissive
```

Repository Configuration

Configure necessary software repositories and update installed packages.

1. Enable Red Hat base repository

```
# subscription-manager repos --enable=rhel-7-server-rpms
```

2. Enable Red Hat OSP repositories

```
# subscription-manager repos --enable=rhel-7-server-openstack-8-rpms
# subscription-manager repos --enable=rhel-7-server-openstack-8-optools-rpms
```

3. Enable DataStax repository

Create the `/etc/yum.repos.d/datastax.repo` file and edit it to contain the following:

```
# DataStax (Apache Cassandra)
```



```
[datastax]
name = DataStax Repo for Apache Cassandra
baseurl = http://rpm.datastax.com/community
enabled = 1
gpgcheck = 1
gpgkey = https://rpm.datastax.com/rpm/repo_key
```

1. Enable MidoNet repositories

Create the `/etc/yum.repos.d/midonet.repo` file and edit it to contain the following:

```
[midonet]
name=MidoNet
baseurl=http://builds.midonet.org/midonet-5.0/stable/el7/
enabled=1
gpgcheck=1
gpgkey=https://builds.midonet.org/midorepo.key

[midonet-openstack-integration]
name=MidoNet OpenStack Integration
baseurl=http://builds.midonet.org/openstack-liberty/stable/el7/
enabled=1
gpgcheck=1
gpgkey=https://builds.midonet.org/midorepo.key

[midonet-misc]
name=MidoNet 3rd Party Tools and Libraries
baseurl=http://builds.midonet.org/misc/stable/el7/
enabled=1
gpgcheck=1
gpgkey=https://builds.midonet.org/midorepo.key
```

2. Install available updates

```
# yum clean all
# yum upgrade
```

3. If necessary, reboot the system

```
# reboot
```


Compute Services (Nova)



Important

Follow the Red Hat documentation's [Chapter 8. Install The Compute Service](#) instructions, but **note the following differences**.

Controller Node



Important

Follow the Red Hat documentation's [8.2. Install a Compute Node](#) instructions, but **note the following differences and additions**.

1. 8.2.1. Install the Compute Service Packages

Do **not** apply as is.

Instead, install only the following packages:

```
# yum install openstack-nova-api openstack-nova-conductor openstack-nova-scheduler python-cinderclient
```



Note

The `openstack-nova-compute` package is going to be installed on the Compute Node instead.

2. 8.2.2. Create the Compute Service Database

Apply as is.

3. 8.2.3. Configure the Compute Service Database Connection

Apply as is.

4. 8.2.4. Create the Compute Service Identity Records

Apply as is.

5. 8.2.5. Configure Compute Service Authentication

Apply as is.

6. 8.2.6. Configure the Firewall to Allow Compute Service Traffic

Apply as is.

7. 8.2.7. Configure the Compute Service to Use SSL

Apply as is.

8. 8.2.8. Configure RabbitMQ Message Broker Settings for the Compute Service

Apply as is.

9. 8.2.9. Enable SSL Communication Between the Compute Service and the Message Broker

Apply as is.

10.8.2.10. Configure Resource Overcommitment

Apply as is.

11.8.2.11. Reserve Host Resources

Apply as is.

12.8.2.12. Configure Compute Networking

Apply as is, except the following topics:

a. 8.2.12.3. Configure the L2 Agent

Do not apply.

b. 8.2.12.4. Configure Virtual Interface Plugging

Configure the generic VIF driver.

13.8.2.13. Populate the Compute Service Database

Apply as is.

14.8.2.14. Launch the Compute Services

a. 1. Starting the Message Bus Service

Do not apply. Only required on the Compute Node.

b. 2. Starting the Libvirtd Service

Do not apply. Only required on the Compute Node.

c. 3. Starting the API Service

Apply as is.

d. 4. Starting the Scheduler

Apply as is.

e. 5. Starting the Conductor

Apply as is.

f. 6. Starting the Compute Service

Do not apply. Only required on the Compute Node.

Compute Node



Important

Follow the Red Hat documentation's [8.2. Install a Compute Node](#) instructions, but **note the following differences and additions**.

1. 8.2.1. Install the Compute Service Packages

Do **not** apply as is.

Instead, install only the following packages:

```
# yum install openstack-nova-compute openstack-utils
```

2. 8.2.2. Create the Compute Service Database

Do **not** apply. Has been done on the Controller Node.

3. 8.2.3. Configure the Compute Service Database Connection

Apply as is.

4. 8.2.4. Create the Compute Service Identity Records

Do **not** apply. Has been done on the Controller Node.

1. 8.2.5. Configure Compute Service Authentication

Apply as is.

1. 8.2.6. Configure the Firewall to Allow Compute Service Traffic

Apply as is.

2. 8.2.7. Configure the Compute Service to Use SSL

Apply as is.

3. 8.2.8. Configure RabbitMQ Message Broker Settings for the Compute Service

Apply as is.

4. 8.2.9. Enable SSL Communication Between the Compute Service and the Message Broker

Apply as is.

5. 8.2.10. Configure Resource Overcommitment

Apply as is.

6. 8.2.11. Reserve Host Resources

Apply as is.

7. 8.2.12. Configure Compute Networking

Apply as is, except the following topics:

a. 8.2.12.3. Configure the L2 Agent

Do **not** apply.

b. 8.2.12.4. Configure Virtual Interface Plugging

Do **not** apply.

8. 8.2.13. Populate the Compute Service Database

Do **not** apply. Has been done on the Controller Node.

9. 8.2.14. Launch the Compute Services

a. 1. Starting the Message Bus Service

Apply as is.

b. 2. Starting the Libvirtd Service

Apply as is.

c. 3. Starting the API Service

Do **not** apply. Only required on the Controller Node.

d. 4. Starting the Scheduler

Do **not** apply. Only required on the Controller Node.

e. 5. Starting the Conductor

Do **not** apply. Only required on the Controller Node.

f. 6. Starting the Compute Service

Apply as is.

10 Additionally, perform the following steps

a. Configure libvirt

Edit the `/etc/libvirt/qemu.conf` file to contain the following:

```
user = "root"
group = "root"

cgroup_device_acl = [
    "/dev/null", "/dev/full", "/dev/zero",
    "/dev/random", "/dev/urandom",
    "/dev/ptmx", "/dev/kvm", "/dev/kqemu",
    "/dev/rtc", "/dev/hpet", "/dev/vfio/vfio",
    "/dev/net/tun"
]
```

b. Restart the libvirt service

```
# systemctl restart libvirtd.service
```

c. Install nova-rootwrap network filters

```
# yum install openstack-nova-network
# systemctl disable openstack-nova-network.service
```

d. Restart the Compute service

```
# systemctl restart openstack-nova-compute.service
```

Networking Services (Neutron)

Controller Node



Important

Follow the Red Hat documentation's [Chapter 7. Install OpenStack Networking](#) instructions, but **note the following differences**.

1. 7.1. Install the OpenStack Networking Packages

Do **not** apply as is.

Instead, install the following packages:

```
# yum install openstack-neutron openstack-utils openstack-selinux  
python-networking-midonet
```

2. 7.2.1. Set the OpenStack Networking Plug-in

Do **not** apply. Instead, perform the following steps:

- Edit the `/etc/neutron/neutron.conf` file and configure the following keys in the `[DEFAULT]` section:

```
[DEFAULT]  
...  
core_plugin = midonet.neutron.plugin_v2.MidonetPluginV2  
service_plugins = midonet.neutron.services.l3.l3_midonet.  
MidonetL3ServicePlugin  
...  
dhcp_agent_notification = False  
...  
allow_overlapping_ips = True
```

- Create the directory for the MidoNet plugin:

```
mkdir /etc/neutron/plugins/midonet
```

- Create the `/etc/neutron/plugins/midonet/midonet.ini` file and edit it to contain the following:

```
[MIDONET]  
# MidoNet API URL  
midonet_uri = http://controller:8181/midonet-api  
# MidoNet administrative user in Keystone  
username = midonet  
password = MIDONET_PASS  
# MidoNet administrative user's tenant  
project_id = services
```

- Create a symbolic link to direct Neutron to the MidoNet configuration:

```
# ln -s /etc/neutron/plugins/midonet/midonet.ini /etc/neutron/plugin.  
ini
```

3. 7.2.2. Create the OpenStack Networking Database

Do **not** apply.

Instead, create the database as follows:

```
$ mysql -u root -p
CREATE DATABASE neutron character set utf8;
GRANT ALL PRIVILEGES ON neutron.* TO 'neutron'@'localhost' IDENTIFIED BY
'NEUTRON_DBPASS';
GRANT ALL PRIVILEGES ON neutron.* TO 'neutron'@'%' IDENTIFIED BY
'NEUTRON_DBPASS';
FLUSH PRIVILEGES;
quit
```

Afterwards, run the `neutron-db-manage` command:

```
# neutron-db-manage \
--config-file /usr/share/neutron/neutron-dist.conf \
--config-file /etc/neutron/neutron.conf \
--config-file /etc/neutron/plugin.ini \
upgrade head
```

Followed by the `midonet-db-manage` command:

```
# midonet-db-manage upgrade head
```

4. 7.2.3. Configure the OpenStack Networking Database Connection

Apply as is.

5. 7.2.4. Create the OpenStack Networking Identity Records

Apply as is.

6. 7.2.5. Configure OpenStack Networking Authentication

Apply as is.

7. 7.2.6. Configure the Firewall to Allow OpenStack Networking Traffic

Apply as is.

8. 7.2.7. Configure RabbitMQ Message Broker Settings for OpenStack Networking

Apply as is.

9. 7.2.8. Enable SSL Communication Between OpenStack Networking and the Message Broker

Apply as is.

10. 7.2.9. Configure OpenStack Networking to Communicate with the Compute Service

Apply as is.

11. Configure Load-Balancer-as-a-Service (LBaaS)

Additionally to the Red Hat Installation Guide, configure Load-Balancer-as-a-Service (LBaaS) as described in [the section called "Configure Load-Balancer-as-a-Service \(LBaaS\)" \[13\]](#).

12. Configure FireWall-as-a-Service (FWaaS)

Additionally to the Red Hat Installation Guide, configure FireWall-as-a-Service (FWaaS) as described in [the section called "Configure FireWall-as-a-Service \(FWaaS\)" \[14\]](#).

13.7.2.10. Launch OpenStack Networking

Apply as is.

14.7.3. Configure the DHCP Agent

Do not apply.

15.7.4. Create an External Network

Do not apply.

Instead, create the Neutron networks after the OpenStack and MidoNet installation is completed.

Any networks that are created before the MidoNet plug-in is active will not be visible to MidoNet.

16.7.5. Configure the Plug-in Agent

Do not apply.

17.7.6. Configure the L3 Agent

Do not apply.

Configure Load-Balancer-as-a-Service (LBaaS)

1. Install Neutron Load-Balancing-as-a-Service

```
# yum install python-neutron-lbaas
```

2. Enable the MidoNet driver

Enable the MidoNet driver by using the `service_provider` option in the `/etc/neutron/neutron.conf` file:

```
[service_providers]
service_provider = LOADBALANCER:Midonet:midonet.neutron.services.
loadbalancer.driver.MidonetLoadbalancerDriver:default
```

3. Enable the LBaaS plug-in

Enable the LBaaS plug-in by using the `service_plugins` option in the `[DEFAULT]` section of the `/etc/neutron/neutron.conf` file:

```
[DEFAULT]
service_plugins = lbaas
```



Note

When using multiple service plugins, separate them with commas:

```
[DEFAULT]
service_plugins = foo,bar,lbass
```

4. Enable load balancing in the dashboard

Change the `enable_lb` option to `True` in the `/etc/openstack-dashboard/local_settings` file:

```
OPENSTACK_NEUTRON_NETWORK = {  
    'enable_lb': True,  
    ...  
}
```

5. To finalize installation

Finalize the installation as described in [Neutron Controller Node Installation](#).

Configure FireWall-as-a-Service (FWaaS)

1. Install Neutron FireWall-as-a-Service

```
# yum install python-neutron-fwaas
```

2. Enable the MidoNet FWaaS plug-in

Enable the MidoNet FWaaS plug-in by using the `service_plugins` option in the `/etc/neutron/neutron.conf` file:

```
service_plugins = midonet.neutron.services.firewall.plugin.  
MidonetFirewallPlugin
```



Note

When using multiple service plugins, separate them with commas:

```
[DEFAULT]  
service_plugins = foo,bar,midonet.neutron.services.firewall.  
plugin.MidonetFirewallPlugin
```

3. Enable firewall in the dashboard

Change the `enable_firewall` option to `True` in the `/etc/openstack-dashboard/local_settings` file:

```
OPENSTACK_NEUTRON_NETWORK = {  
    'enable_firewall': True,  
    ...  
}
```

4. To finalize installation

Finalize the installation as described in [Neutron Controller Node Installation](#).


```
# echo 2 > /var/lib/zookeeper/data/myid
```

iii. NSDB Node 3

Create the `/var/lib/zookeeper/data/myid` file and edit it to contain the host's ID:

```
# echo 3 > /var/lib/zookeeper/data/myid
```

3. Create Java Symlink

```
# mkdir -p /usr/java/default/bin/  
# ln -s /usr/lib/jvm/jre-1.7.0-openjdk/bin/java /usr/java/default/bin/  
java
```

4. Enable and start ZooKeeper

```
# systemctl enable zookeeper.service  
# systemctl start zookeeper.service
```

5. Verify ZooKeeper Operation

After installation of all nodes has been completed, verify that ZooKeeper is operating properly.

A basic check can be done by executing the `ruok` (Are you ok?) command on all nodes. This will reply with `imok` (I am ok.) if the server is running in a non-error state:

```
$ echo ruok | nc 127.0.0.1 2181  
imok
```

More detailed information can be requested with the `stat` command, which lists statistics about performance and connected clients:

```
$ echo stat | nc 127.0.0.1 2181  
Zookeeper version: 3.4.5--1, built on 06/10/2013 17:26 GMT  
Clients:  
/127.0.0.1:34768[0](queued=0,recved=1,sent=0)  
/192.0.2.1:49703[1](queued=0,recved=1053,sent=1053)  
  
Latency min/avg/max: 0/4/255  
Received: 1055  
Sent: 1054  
Connections: 2  
Outstanding: 0  
Zxid: 0x260000013d  
Mode: follower  
Node count: 3647
```

Cassandra Installation

1. Install Cassandra packages

```
# yum install java-1.8.0-openjdk-headless  
# yum install dsc22
```

2. Configure Cassandra

a. Common Configuration

Edit the `/etc/cassandra/conf/cassandra.yaml` file to contain the following:

```
# The name of the cluster.
cluster_name: 'midonet'

...

# Addresses of hosts that are deemed contact points.
seed_provider:
  - class_name: org.apache.cassandra.locator.SimpleSeedProvider
    parameters:
      - seeds: "nsdb1,nsdb2,nsdb3"
```

b. Node-specific Configuration

i. NSDB Node 1

Edit the `/etc/cassandra/conf/cassandra.yaml` file to contain the following:

```
# Address to bind to and tell other Cassandra nodes to connect to.
listen_address: nsdb1

...

# The address to bind the Thrift RPC service.
rpc_address: nsdb1
```

ii. NSDB Node 2

Edit the `/etc/cassandra/conf/cassandra.yaml` file to contain the following:

```
# Address to bind to and tell other Cassandra nodes to connect to.
listen_address: nsdb2

...

# The address to bind the Thrift RPC service.
rpc_address: nsdb2
```

iii. NSDB Node 3

Edit the `/etc/cassandra/conf/cassandra.yaml` file to contain the following:

```
# Address to bind to and tell other Cassandra nodes to connect to.
listen_address: nsdb3

...

# The address to bind the Thrift RPC service.
rpc_address: nsdb3
```

3. Edit the service's init script

On installation, the `/var/run/cassandra` directory is created, but because it is located on a temporary file system it will be lost after system reboot. As a result it is not possible to stop or restart the Cassandra service anymore.

To avoid this, edit the `/etc/init.d/cassandra` file to create the directory on service start:

This step needs to happen only once, it will set up access to the NSDB for the MidoNet Cluster and Agent nodes.

Run the following command to set the cloud-wide values for the ZooKeeper and Cassandra server addresses:

```
$ cat << EOF | mn-conf set -t default
zookeeper {
    zookeeper_hosts = "nsdb1:2181,nsdb2:2181,nsdb3:2181"
}

cassandra {
    servers = "nsdb1,nsdb2,nsdb3"
}
EOF
```

Run the following command to set the Cassandra replication factor:

```
$ echo "cassandra.replication_factor : 3" | mn-conf set -t default
```

4. Configure Keystone access

This step needs to happen only once, it will set up access to Keystone for the MidoNet Cluster node(s).

This step will configure the local Midonet Cluster node to be able to use Keystone.

```
$ cat << EOF | mn-conf set -t default
cluster.auth {
    provider_class = "org.midonet.cluster.auth.keystone.KeystoneService"
    admin_role = "admin"
    keystone.tenant_name = "admin"
    keystone.admin_token = "ADMIN_TOKEN"
    keystone.host = controller
    keystone.port = 35357
}
EOF
```

5. Start the MidoNet Cluster

```
# systemctl enable midonet-cluster.service
# systemctl start midonet-cluster.service
```

MidoNet CLI Installation

1. Install MidoNet CLI package

```
# yum install python-midonetclient
```

2. Configure MidoNet CLI

Create the ~/.midonetr.c file and edit it to contain the following:

```
[cli]
api_url = http://controller:8181/midonet-api
username = admin
password = ADMIN_PASS
project_id = admin
```

Midolman Installation

The *MidoNet Agent (Midolman)* has to be installed on all nodes where traffic enters or leaves the virtual topology, in this guide this are the **gateway1**, **gateway2** and **compute1** nodes.

1. Install Midolman package

```
# yum install java-1.8.0-openjdk-headless
# yum install midolman
```

2. Set up mn-conf

Edit `/etc/midolman/midolman.conf` to point mn-conf to the ZooKeeper cluster:

```
[zookeeper]
zookeeper_hosts = nsdb1:2181,nsdb2:2181,nsdb3:2181
```

3. Configure resource usage

Run these steps on **each agent host** in order to configure resource usage.



Important

For production environments the **large** templates are strongly recommended.

a. Midolman resource template

Run the following command to configure the Midolman resource template:

```
$ mn-conf template-set -h local -t TEMPLATE_NAME
```

Replace **TEMPLATE_NAME** with one of the following templates:

```
agent-compute-large
agent-compute-medium
agent-gateway-large
agent-gateway-medium
default
```

b. Java Virtual Machine (JVM) resource template

Replace the default `/etc/midolman/midolman-env.sh` file with one of the below to configure the JVM resource template:

```
/etc/midolman/midolman-env.sh.compute.large
/etc/midolman/midolman-env.sh.compute.medium
/etc/midolman/midolman-env.sh.gateway.large
/etc/midolman/midolman-env.sh.gateway.medium
```

4. Configure MidoNet Metadata Proxy for all agents

This step needs to happen only once, it will set up MidoNet Metadata Proxy for all MidoNet Agent nodes.

Run the following commands to set the cloud-wide values for the MidoNet Metadata Proxy:

```
$ echo "agent.openstack.metadata.nova_metadata_url : \"http://
/controller:8775\"" | mn-conf set -t default
```



```
midonet> list tunnel-zone
tzone tzone0 name tz type vxlan

midonet> list host
host host0 name controller alive true
host host1 name gateway1 alive true
host host2 name gateway2 alive true
host host3 name compute1 alive true

midonet> tunnel-zone tzone0 add member host host0
address ip_address_of_host0
zone tzone0 host host0 address ip_address_of_host0

midonet> tunnel-zone tzone0 add member host host1
address ip_address_of_host1
zone tzone0 host host1 address ip_address_of_host1

midonet> tunnel-zone tzone0 add member host host2
address ip_address_of_host2
zone tzone0 host host2 address ip_address_of_host2

midonet> tunnel-zone tzone0 add member host host3
address ip_address_of_host3
zone tzone0 host host3 address ip_address_of_host3
```

5. Initial Network Configuration



Important

Follow the Red Hat documentation's [Create an external network](#) instructions, but **note the following differences**.

1. Creating and Configuring an External Network

Use the following command to create the external network:

```
$ neutron net-create ext-net --router:external
```

6. Edge Router Setup

Prior to v5.0, with Neutron, you could set up the gateway in only one way, which was to have a special singleton gateway router called the Provider Router created implicitly when an external network was created in Neutron. The provider router sits at the edge of the cloud and interfaces with the uplink router. The Provider Router is where BGP was typically configured. The biggest limitation of this approach was that it took away the scenario in which you wanted to have an L2 network at the edge instead of a router. Another limitation was that only one such router could exist for the entire cloud.

These limitations are removed in v5.0, where you could design your gateway to be either L2 network or router with as many routers as you wish, all using the Neutron API.

There are two main changes:

Edge Router

The Provider Router is no longer implicitly created upon the external network creation. Instead, the edge gateway routers, called the Edge Routers, are created explicitly using standard Neutron API. With this approach, multiple Edge Routers can be created, and they are optional.

Gateway Virtual Topology

In the previous model, the Provider Router was connected directly to the tenant routers, with the external networks hanging off of the Provider Router.

In the new model, the external networks exist between the edge and the tenant routers.

To create the gateway topology issue the following Neutron commands.

Create a standard neutron router:

```
neutron router-create <EDGE_ROUTER_NAME>
```

Attach the edge router to an external network:

```
neutron router-interface-add <EDGE_ROUTER_ID> <EXT_SUBNET_ID>
```

Create a special network called uplink network, representing the physical network outside of the cloud:

```
neutron net-create <UPLINK_NET_NAME> --tenant_id admin --  
provider:network_type uplink
```

Create a subnet for the uplink network matching the CIDR used in the uplink network (could just be /30 if linked directly to another router):

```
neutron subnet-create --tenant_id admin --disable-dhcp --name  
<UPLINK_SUBNET_NAME> <UPLINK_NET_NAME> <CIDR>
```

Create a port on the uplink network with a specific IP that you want to use and the binding details so that this virtual port gets bound to a specific NIC on the gateway host:

```
neutron port-create <UPLINK_NET_ID> --binding:host_id <HOST_NAME> --  
binding:profile type=dict interface_name=<INTERFACE_NAME> --fixed-ip  
ip_address=<IP_ADDR>
```

Attach the uplink port to the Edge Router:

```
neutron router-interface-add <EDGE_ROUTER_ID> port=<UPLINK_PORT_ID>
```

7. BGP Uplink Configuration

MidoNet utilizes the Border Gateway Protocol (BGP) for external connectivity.

For production deployments it is strongly recommended to use BGP due to its scalability and redundancy.

For demo or POC environments, alternatively static routing can be used.

The following instructions assume below sample environment:

- One floating IP network
 - *192.0.2.0/24*
- Two MidoNet gateway nodes
 - *gateway1*, connecting to *bgp1* via *eth1*
 - *gateway2*, connecting to *bgp2* via *eth1*
- Two remote BGP peers
 - *bgp1*, *198.51.100.1*, AS *64513*
 - *bgp2*, *203.0.113.1*, AS *64514*
- Corresponding MidoNet BGP peers
 - *198.51.100.2*, AS *64512*
 - *203.0.113.2*, AS *64512*

Follow these steps to configure the BGP uplinks.

1. Launch the MidoNet CLI and find the Edge Router

```
midonet-cli> router list
router router0 name Edge Router state up
router router1 name Tenant Router state up infiltrer chain0 outfilter
chain1
```

In this example the Edge Router is **router0**.

2. Create and bind virtual ports for the BGP sessions

Refer to [Chapter 6, “Edge Router Setup” \[24\]](#) for instructions on how to create the necessary ports and bind them to the Gateway hosts' physical network interfaces.

You can confirm the port configuration within MidoNet CLI by listing the Edge Router's ports:

```
midonet> router router0 port list
port port0 device router0 state up mac fa:16:3e:11:11:11
address 198.51.100.2 net 198.51.100.0/30
port port1 device router0 state up mac fa:16:3e:22:22:22
address 203.0.113.2 net 203.0.113.0/30
[...]
```

3. Configure basic BGP settings

```
midonet> router router0 set asn 64512

midonet> router router0 add bgp-peer asn 64513 address 198.51.100.1
router0:peer0

midonet> router router0 add bgp-peer asn 64514 address 203.0.113.1
router0:peer1

midonet> router router0 list bgp-peer
peer peer0 asn 64513 address 198.51.100.1
peer peer1 asn 64514 address 203.0.113.1
```

4. If needed, configure MD5 authentication:

```
midonet> router router0 bgp-peer peer0 set password BGP_PASSWORD
midonet> router router0 bgp-peer peer1 set password BGP_PASSWORD
```

5. If needed, configure custom timers that will take precedence over the default ones defined in the MidoNet configuration:

```
midonet> router router0 bgp-peer peer0 set connect-retry 10
midonet> router router0 bgp-peer peer0 set hold-time 5
midonet> router router0 bgp-peer peer0 set keep-alive 5
midonet> router router0 bgp-peer peer1 set connect-retry 10
midonet> router router0 bgp-peer peer1 set hold-time 5
midonet> router router0 bgp-peer peer1 set keep-alive 5
midonet> router router0 list bgp-peer
peer peer0 asn 64513 address 198.51.100.1 keep-alive 5 hold-time 5
connect-retry 10
peer peer1 asn 64514 address 203.0.113.1 keep-alive 5 hold-time 5
connect-retry 10
```

6. Add routes to the remote BGP peers

In order to be able to establish connections to the remote BGP peers, corresponding routes have to be added.

```
midonet> router router0 route add src 0.0.0.0/0 dst 198.51.100.0/30  
port router0:port0 type normal  
router0:route0  
  
midonet> router router0 route add src 0.0.0.0/0 dst 203.0.113.0/30  
port router0:port1 type normal  
router0:route1
```

7. Advertise BGP routes

In order to provide external connectivity for hosted virtual machines, the floating IP network has to be advertised to the BGP peers.

```
midonet> router router0 add bgp-network net 192.0.2.0/24
router0:net0

midonet> router router0 list bgp-network
net net0 net 192.0.2.0/24
```

8. Further Steps

MidoNet installation and integration into OpenStack is completed.



Note

Consult the **Operations Guide** for further instructions on operating MidoNet.