



### MidoNet Quick Start Guide for Ubuntu 14.04 / Kilo

5.0-SNAPSHOT (2015-11-13 20:48 JST)
Copyright © 2015 Midokura SARL All rights reserved.

MidoNet is a network virtualization software for Infrastructure-as-a-Service (IaaS) clouds.

It decouples your laaS cloud from your network hardware, creating an intelligent software abstraction layer between your end hosts and your physical network.

This guide walks through the minimum installation and configuration steps neccessary to use MidoNet with OpenStack.



### **Caution**

This document is a DRAFT. It may be MISSING relevant information or contain UNTESTED information. Use it at your own risk.



#### Note

Please consult the MidoNet Mailing Lists or Chat if you need assistance.

Licensed under the Apache License, Version 2.0 (the "License"); you may not use this file except in compliance with the License. You may obtain a copy of the License at

http://www.apache.org/licenses/LICENSE-2.0

Unless required by applicable law or agreed to in writing, software distributed under the License is distributed on an "AS IS" BASIS, WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied. See the License for the specific language governing permissions and limitations under the License.

# **Table of Contents**

Pr	eface	. iv
	Conventions	. iv
1.	Architecture	1
	Hosts and Services	. 2
2.	Basic Environment Configuration	. 4
	Networking Configuration	. 4
	Repository Configuration	. 4
3.	OpenStack Installation	. 6
	Identity Service (Keystone)	. 6
	Compute Services (Nova)	. 6
	Networking Services (Neutron)	. 7
4.	MidoNet Installation	11
	NSDB Nodes	11
	Controller Node	14
	Midolman Installation	15
	MidoNet Host Registration	16
5.	Edge Router Setup	
	BGP Uplink Configuration	
	Further Steps	

# **Preface**

# **Conventions**

The MidoNet documentation uses several typesetting conventions.

### **Notices**

Notices take these forms:



#### Note

A handy tip or reminder.



### **Important**

Something you must be aware of before proceeding.



### Warning

Critical information about the risk of data loss or security issues.

# **Command prompts**

### \$ prompt

Any user, including the root user, can run commands that are prefixed with the \$ prompt.

### # prompt

The root user must run commands that are prefixed with the # prompt. You can also prefix these commands with the **sudo** command, if available, to run them.

# 1. Architecture

### **Table of Contents**

This guide assumes the following example system architecture.

OpenStack Controller Node:

• Controller Node (controller)

Compute Node:

• Compute Node (compute1)

Since MidoNet is a distributed system, it does not have the concept of a Network Node as being used with the default OpenStack networking plugin. Instead it uses two or more Gateway Nodes that utilize Quagga to provide connectivity to external networks via the Border Gateway Protocol (BGP).

- Gateway Node 1 (gateway1)
- Gateway Node 2 (gateway2)

Three or more hosts are being used for the MidoNet Network State Database (NSDB) cluster which utilizes ZooKeeper and Cassandra to store virtual network topology and connection state information:

- NSDB Node 1 (nsdb1)
- NSDB Node 2 (nsdb2)
- NSDB Node 3 (nsdb3)



### **Important**

Ideally, both the ZooKeeper transaction log and Cassandra data files need their own dedicated disks, with additional disks for other services on the host. However, for small POCs and small deployments, it is ok to share the Cassandra disk with other services and just leave the ZooKeeper transaction log on its own.

The *MidoNet Agent (Midolman)* has to be installed on all nodes where traffic enters or leaves the virtual topology. In this guide this are the **controller**, **gateway1**, **gateway2** and **compute1** hosts.

The *Midonet Cluster* can be installed on a separate host, but this guide assumes it to be installed on the **controller** host.

The *Midonet Command Line Interface (CLI)* can be installed on any host that has connectivity to the MidoNet Cluster. This guide assumes it to be installed on the **controller** host.

The *Midonet Neutron Plugin* replaces the ML2 Plugin and has to be installed on the **controller**.

# **Hosts and Services**

### **Controller Node (controller)**

- General
  - Database (MariaDB)
  - Message Broker (RabbitMQ)
- OpenStack
  - Identity Service (Keystone)
  - Image Service (Glance)
  - Compute (Nova)
  - Networking (Neutron)
    - Neutron Server
    - DHCP Agent
    - Metadata Agent
  - Dashboard (Horizon)
- MidoNet
  - Cluster
  - CLI
  - Neutron Plugin

### **Compute Node (compute1)**

- OpenStack
  - Compute (Nova)
  - Networking (Neutron)
- MidoNet
  - Agent (Midolman)

### NSDB Nodes (nsdb1, nsdb2, nsdb3)

- Network State Database (NSDB)
  - Network Topology (ZooKeeper)
  - Network State Information (Cassandra)

### Gateway Nodes (gateway1, gateway2)

- BGP Daemon (Quagga)
- MidoNet
  - Agent (Midolman)

# 2. Basic Environment Configuration

### **Table of Contents**

Networking Configuration	4
Repository Configuration	4

# **Networking Configuration**



### **Important**

All hostnames must be resolvable, either via DNS or locally.

This guide assumes that you follow the instructions in OpenStack Networking (neutron) of the OpenStack Documentation.

# **Repository Configuration**

Configure necessary software repositories and update installed packages.

### 1. Configure Ubuntu repositories

Edit the /etc/apt/sources.list file to contain the following:

```
# Ubuntu Main Archive
deb http://archive.ubuntu.com/ubuntu/ trusty main
deb http://security.ubuntu.com/ubuntu trusty-security main

# Ubuntu Universe Archive
deb http://archive.ubuntu.com/ubuntu/ trusty universe
deb http://security.ubuntu.com/ubuntu trusty-security universe
```

### 2. Configure Ubuntu Cloud Archive repository

Create the /etc/apt/sources.list.d/cloudarchive-kilo.list file and edit it to contain the following:

```
# Ubuntu Cloud Archive deb http://ubuntu-cloud.archive.canonical.com/ubuntu trusty-updates/kilo main
```

### Install the repository's key:

```
# apt-get update
# apt-get install ubuntu-cloud-keyring
```

### 3. Configure DataStax repository

Create the /etc/apt/sources.list.d/datastax.list file and edit it to contain the following:

```
# DataStax (Apache Cassandra)
deb http://debian.datastax.com/community 2.0 main
```

Download and install the repository's key:

```
# curl -L https://debian.datastax.com/debian/repo_key | apt-key add -
```

### 4. Configure Java 8 repository

Since Ubuntu 14.04 does not provide a Java 8 runtime environment in its repositories, we are going to use the Launchpad PPA for OpenJDK.

Create the /etc/apt/sources.list.d/openjdk-8.list file and edit it to contain the following:

```
# OpenJDK 8
deb http://ppa.launchpad.net/openjdk-r/ppa/ubuntu trusty main
```

Download and install the repository's key:

```
# apt-key adv --keyserver hkp://keyserver.ubuntu.com:80 --recv-keys
0x86F44E2A
```

### 5. Configure MidoNet repositories

Create the /etc/apt/sources.list.d/midonet.list file and edit it to contain the following:

```
# MidoNet
deb http://builds.midonet.org/midonet-5 stable main

# MidoNet OpenStack Integration
deb http://builds.midonet.org/openstack-kilo stable main

# MidoNet 3rd Party Tools and Libraries
deb http://builds.midonet.org/misc stable main
```

Download and install the repositories' key:

```
# curl -L http://builds.midonet.org/midorepo.key | apt-key add -
```

#### 6. Install available updates

```
# apt-get update
# apt-get dist-upgrade
```

### 7. If necessary, reboot the system

```
# reboot
```

# DRAFT **DRAFT - DRAFT** ī DRA ı DRAFT DRAFT 1 DRAFT

# 3. OpenStack Installation

# **Table of Contents**

Identity Service (Keystone)	6
Compute Services (Nova)	6
Networking Services (Neutron)	



### **Important**

Follow the OpenStack Kilo Installation Guide for Ubuntu 14.04 (LTS), but note the following differences.

# **Identity Service (Keystone)**



### **Important**

Follow the OpenStack documentation's Chapter 3. Add the Identity service instructions, but note the following differences and additions.

### 1. Verify operation

Do **not** apply step '1. For security reasons, disable the temporary authentication token mechanism'.

The MidoNet API uses the Keystone admin token for authentication purposes, therefore **admin\_token\_auth** has to be kept in the corresponding configuration sections.

#### 2. Create MidoNet API Service

As Keystone admin, execute the following command:

```
$ openstack service create --name midonet --description "MidoNet API
Service" midonet
```

#### 3. Create MidoNet Administrative User

As Keystone admin, execute the following commands:

```
$ openstack user create --password-prompt midonet
$ openstack role add --project service --user midonet admin
```

# **Compute Services (Nova)**



### **Important**

Follow the OpenStack documentation's Chapter 5. Add the Compute service instructions, but **note the following differences**.

### **Controller Node**



DRAFT

1

RA

- DRA

RAFT

1

DRAFT

1

DRA

ī

DRAFT

- DRA

AFT

ď

1

### **Note**

Follow the OpenStack documentation's Install and configure controller node instructions as is.

### **Compute Node**



### **Important**

Follow the OpenStack documentation's Install and configure a compute node instructions, but note the following additions.

1. Configure libvirt

Edit the /etc/libvirt/gemu.conf file to contain the following:

```
user = "root"
group = "root"

cgroup_device_acl = [
    "/dev/null", "/dev/full", "/dev/zero",
    "/dev/random", "/dev/urandom",
    "/dev/ptmx", "/dev/kvm", "/dev/kqemu",
    "/dev/rtc","/dev/hpet", "/dev/vfio/vfio",
    "/dev/net/tun"
]
```

2. Restart the libvirt service

```
# service libvirt-bin restart
```

1. Install nova-rootwrap network filters

```
# apt-get install nova-network
```

2. Restart the Compute service

```
# service nova-compute restart
```

# **Networking Services (Neutron)**



### **Important**

Follow the OpenStack documentation's Chapter 6. OpenStack Networking (neutron) instructions, but note the following differences.

### **Controller Node**



### **Important**

Follow the OpenStack documentation's Install and configure controller node instructions, but note the following differences and additions.

1. To configure prerequisites

Apply as is.

### 2. To install the Networking components

Do **not** apply.

a. Instead, install the following packages:

```
# apt-get install neutron-server python-neutronclient python-neutron-
plugin-midonet
# apt-get purge neutron-plugin-ml2
```

### 3. To configure the Networking server component

Do **not** apply step 'd. Enable the Modular Layer 2 (ML2) plug-in, router service, and overlapping IP addresses'.

a. Instead, edit the /etc/neutron/neutron.conf file and configure the following key in the [DEFAULT] section:

```
[DEFAULT]
...
core_plugin = midonet.neutron.plugin_v2.MidonetPluginV2
```



### **Note**

Make sure to not leave any space at the starting of lines in any configuration file (this applies to all configuration files).

### 4. To configure the Modular Layer 2 (ML2) plug-in

Do **not** apply.

Instead, perform the following steps.

a. Create the directory for the MidoNet plugin:

```
mkdir /etc/neutron/plugins/midonet
```

b. Create the /etc/neutron/plugins/midonet/midonet.ini file and edit it to contain the following:

```
[DATABASE]
sql_connection = mysql://neutron:NEUTRON_DBPASS@controller/neutron

[MIDONET]
# MidoNet API URL
midonet_uri = http://controller:8181/midonet-api
# MidoNet administrative user in Keystone
username = midonet
password = MIDONET_PASS
# MidoNet administrative user's tenant
project_id = service
```

c. Edit the /etc/default/neutron-server file to contain the following:

```
NEUTRON_PLUGIN_CONFIG="/etc/neutron/plugins/midonet/midonet.ini"
```

### 5. To configure Compute to use Networking

Apply as is.

### 6. Configure Load-Balancer-as-a-Service (LBaaS)

Additionally to the OpenStack Installation Guide, configure Load-Balancer-as-a-Service (LBaaS) as described in the section called "Configure Load-Balancer-as-a-Service (LBaaS)" [9].

### 7. To finalize installation

Do not apply.

Instead, perform the following steps.

a. Populate the database:

```
# su -s /bin/sh -c "neutron-db-manage --config-file /etc/neutron/
neutron.conf --config-file /etc/neutron/plugins/midonet/midonet.ini
upgrade head" neutron
```

- # midonet-db-manage upgrade head
- b. Restart the Compute service:

```
# service nova-api restart
```

c. Restart the Networking service:

# service neutron-server restart

### **Configure Load-Balancer-as-a-Service (LBaaS)**



### **Important**

Follow the OpenStack documentation's Configure Load-Balancer-as-a-Service (LBaaS) instructions, but **note the following differences**.

### 1. Install the agent

Do **not** apply.

Instead install the package python-neutron-lbaas

```
# yum install python-neutron-lbaas
```

2. Enable the HAProxy plug-in by using the service\_provider option in the /etc/neutron/neutron.conf file:

Do **not** apply.

Instead, set service\_provider as follows:

```
[service_providers]
service_provider = LOADBALANCER:Midonet:midonet.neutron.services.
loadbalancer.driver.MidonetLoadbalancerDriver:default
```

3. Enable the load-balancing plug-in by using the service\_plugins option in the /etc/ neutron/neutron.conf file:

Apply as is.

4. Enable the HAProxy load balancer in the /etc/neutron/lbaas\_agent.ini file:

Do not apply.

5. Select the required driver in the /etc/neutron/lbaas\_agent.ini file:

Do **not** apply.

6. Create the required tables in the database:

Do not apply.

7. Apply the settings by restarting the neutron-server and neutron-lbaas-agent services.

Do **not** apply.

8. Enable load balancing in the Project section of the dashboard.

Apply as is.

9. To finalize installation

Finalize the installation as described in Neutron Controller Node Installation.

### **Compute Node**



### **Important**

Follow the OpenStack documentation's Install and configure compute node instructions, but note the following differences.

1. To configure prerequisites

Do not apply.

2. To install the Networking components

Do not apply.

3. To configure the Networking common components

Do **not** apply.

4. To configure the Modular Layer 2 (ML2) plug-in

Do **not** apply.

5. To configure the Open vSwitch (OVS) service

Do **not** apply.

6. To configure Compute to use Networking

Apply as is.

7. To finalize the installation

Do not apply.

a. Instead, restart the following service:

# service nova-compute restart

# 4. MidoNet Installation

# **Table of Contents**

NSDB Nodes	11
Controller Node	14
Midolman Installation	15
MidoNet Host Registration	16

### **NSDB** Nodes

# **ZooKeeper Installation**

1. Install ZooKeeper packages

```
# apt-get install openjdk-7-jre-headless
# apt-get install zookeeper zookeeperd zkdump
```

### 2. Configure ZooKeeper

a. Common Configuration

Edit the /etc/zookeeper/conf/zoo.cfg file to contain the following:

```
server.1=nsdb1:2888:3888
server.2=nsdb2:2888:3888
server.3=nsdb3:2888:3888
```



### **Important**

For production deployments it is recommended to configure the storage of snapshots in a different disk than the commit log. This can be set by changing the parameter dataDir in zoo.cfg to a different disk.

### b. Node-specific Configuration

i. NSDB Node 1

Create the /var/lib/zookeeper/myid file and edit it to contain the host's ID:

```
# echo 1 > /var/lib/zookeeper/myid
```

#### ii. NSDB Node 2

Create the /var/lib/zookeeper/myid file and edit it to contain the host's ID:

```
# echo 2 > /var/lib/zookeeper/myid
```

#### iii. NSDB Node 3

Create the /var/lib/zookeeper/myid file and edit it to contain the host's ID:

RAFT

1

```
# echo 3 > /var/lib/zookeeper/myid
```

#### 3. Restart ZooKeeper

```
# service zookeeper restart
```

### 4. Verify ZooKeeper Operation

After installation of all nodes has been completed, verify that ZooKeeper is operating properly.

A basic check can be done by executing the ruok (Are you ok?) command on all nodes. This will reply with imok (I am ok.) if the server is running in a non-error state:

```
$ echo ruok | nc 127.0.0.1 2181
imok
```

More detailed information can be requested with the stat command, which lists statistics about performance and connected clients:

```
$ echo stat | nc 127.0.0.1 2181
Zookeeper version: 3.4.5--1, built on 06/10/2013 17:26 GMT
Clients:
   /127.0.0.1:34768[0](queued=0,recved=1,sent=0)
   /192.0.2.1:49703[1](queued=0,recved=1053,sent=1053)

Latency min/avg/max: 0/4/255
Received: 1055
Sent: 1054
Connections: 2
Outstanding: 0
Zxid: 0x260000013d
Mode: follower
Node count: 3647
```

### **Cassandra Installation**

### 1. Install Cassandra packages

```
# apt-get install openjdk-7-jre-headless
# apt-get install dsc20
```

### 2. Configure Cassandra

### a. Common Configuration

Edit the /etc/cassandra/cassandra.yaml file to contain the following:

```
# The name of the cluster.
cluster_name: 'midonet'
...

# Addresses of hosts that are deemed contact points.
seed_provider:
    - class_name: org.apache.cassandra.locator.SimpleSeedProvider
    parameters:
    - seeds: "nsdb1,nsdb2,nsdb3"
```

### b. Node-specific Configuration

#### i. NSDB Node 1

Edit the /etc/cassandra/cassandra.yaml file to contain the following:

```
# Address to bind to and tell other Cassandra nodes to connect to.
listen_address: nsdb1
...
# The address to bind the Thrift RPC service.
rpc_address: nsdb1
```

#### ii. NSDB Node 2

Edit the /etc/cassandra/cassandra.yaml file to contain the following:

```
# Address to bind to and tell other Cassandra nodes to connect to.
listen_address: nsdb2
...
# The address to bind the Thrift RPC service.
rpc_address: nsdb2
```

### iii. NSDB Node 3

Edit the /etc/cassandra/cassandra.yaml file to contain the following:

```
# Address to bind to and tell other Cassandra nodes to connect to.
listen_address: nsdb3
...
# The address to bind the Thrift RPC service.
rpc_address: nsdb3
```

#### 3. Clean existing data and restart Cassandra

```
# service cassandra stop
# rm -rf /var/lib/cassandra/*
# service cassandra start
```

### 4. Verify Cassandra Operation

After installation of all nodes has been completed, verify that Cassandra is operating properly.



### **Important**

If Cassandra fails to start and prints a "buffer overflow" error message in its log file, you may try associating 127.0.0.1 with the hostname in etc/hosts (so that hostname –i will show 127.0.0.1). This may solve the Cassandra start problem.

A basic check can be done by executing the nodetool status command. This will reply with UN (Up / Normal) in the first column if the servers are running in a non-error state:

```
$ nodetool -host 127.0.0.1 status
[...]
Status=Up/Down
|/ State=Normal/Leaving/Joining/Moving
```

### **Controller Node**

# **MidoNet Cluster Installation**

### 1. Install MidoNet Cluster package

```
# apt-get install midonet-cluster
```

### 2. Set up mn-conf

Edit /etc/midonet/midonet.conf to point mn-conf to the ZooKeeper cluster:

```
[zookeeper]
zookeeper_hosts = nsdb1:2181,nsdb2:2181,nsdb3:2181
```

### 3. Configure access to the NSDB

This step needs to happen only once, it will set up access to the NSDB for the MidoNet Cluster and Agent nodes.

Run the following command to set the cloud-wide values for the ZooKeeper and Cassandra server addresses:

```
$ cat << EOF | mn-conf set -t default
zookeeper {
    zookeeper_hosts = "nsdb1:2181,nsdb2:2181,nsdb3:2181"
}
cassandra {
    servers = "nsdb1,nsdb2,nsdb3"
}
EOF</pre>
```

Run the following command to set the Cassandra replication factor:

```
$ echo "cassandra.replication_factor : 3" | mn-conf set -t default
```

### 4. Configure Keystone access

This step needs to happen only once, it will set up access to Keystone for the MidoNet Cluster node(s).

```
$ cat << EOF | mn-conf set -t default
cluster.auth {
   provider_class =
   "org.midonet.cluster.auth.keystone.v2_0.KeystoneService"
   admin_role = "admin"
   keystone.tenant_name = "admin"
   keystone.admin_token = "ADMIN_TOKEN"
   keystone.host = controller
   keystone.port = 35357
}
EOF</pre>
```

ī

RA

ı

4

ī

1

RA

RAI

ı

DRA

ı

AFT

ī

ī

RAFT

4

#### 5. Start the MidoNet Cluster

# service midonet-cluster start

### MidoNet CLI Installation

### 1. Install MidoNet CLI package

```
# apt-get install python-midonetclient
```

### 2. Configure MidoNet CLI

Create the ~/.midonetrc file and edit it to contain the following:

```
api_url = http://controller:8181/midonet-api
username = admin
password = ADMIN_PASS
project_id = admin
```

# **Midolman Installation**

The MidoNet Agent (Midolman) has to be installed on all nodes where traffic enters or leaves the virtual topology, in this guide this are the gateway1, gateway2 and compute1 nodes.

### 1. Install Midolman package

```
# apt-get install openjdk-8-jre-headless
# apt-get install midolman
```

### 2. Configure resource usage

Run these steps on each agent host in order to configure resource usage.



### **Important**

For production environments the large templates are strongly recommended.

### a. Midolman resource template

Run the following command to configure the Midolman resource template:

```
$ mn-conf template-set -h local -t TEMPLATE_NAME
```

Replace **TEMPLATE\_NAME** with one of the following templates:

```
agent-compute-large
agent-compute-medium
agent-gateway-large
agent-gateway-medium
default
```

### b. Java Virtual Machine (JVM) resource template

Replace the default /etc/midolman/midolman-env.sh file with one of the below to configure the JVM resource template:

```
/etc/midolman/midolman-env.sh.compute.large
/etc/midolman/midolman-env.sh.compute.medium
```

```
/etc/midolman/midolman-env.sh.gateway.large
/etc/midolman/midolman-env.sh.gateway.medium
```

### 3. Configure MidoNet Metadata Proxy for all agents

This step needs to happen only once, it will set up MidoNet Metadata Proxy for all MidoNet Agent nodes.

Run the following commands to set the cloud-wide values for the MidoNet Metadata Proxy:

```
$ echo "agent.openstack.metadata.nova_metadata_url : \"http:/
/nova_metadata_host:nova_metadata_port\"" | mn-conf set
$ echo "agent.openstack.metadata.shared_secret : shared_secret" | mn-conf set
$ echo "agent.openstack.metadata.enabled : true" | mn-conf set
```

**nova\_metadata\_host**, **nova\_metadata\_port**, and **shared\_secret** should be replaced with appropriate values. They need to match with the corresponding Nova Metadata API configuration.

**nova\_metadata\_host** and **nova\_metadata\_port** specify the address on which Nova accepts Metadata API requests. **shared\_secret** has to be the same as specified by the "metadata\_proxy\_shared\_secret" field in the "neutron" section of nova.conf.

The Nova side of the configuration for the metadata service is same as when using Neutron Metadata Proxy. See the OpenStack documentation for details:

Cloud Administrator Guide: Configure Metadata

### 4. Start Midolman

# service midolman start

# **MidoNet Host Registration**

### 1. Launch MidoNet CLI

```
$ midonet-cli
midonet>
```

#### 2. Create tunnel zone

MidoNet supports the Virtual Extensible LAN (VXLAN) and Generic Routing Encapsulation (GRE) protocols to communicate to other hosts within a tunnel zone.

To use the VXLAN protocol, create the tunnel zone with type 'vxlan':

```
midonet> tunnel-zone create name tz type vxlan tzone0
```

To use the GRE protocol, create the tunnel zone with type 'gre':

```
midonet> tunnel-zone create name tz type gre tzone0
```



### **Important**

Make sure to allow GRE/VXLAN traffic for all hosts that belong to the tunnel zone. For VXLAN MidoNet uses UDP port 6677 as default.

### 1. Add hosts to tunnel zone

```
midonet> list tunnel-zone
tzone tzone0 name tz type vxlan
midonet> list host
host host0 name controller alive true
host host1 name gateway1 alive true
host host2 name gateway2 alive true
host host3 name compute1 alive true
midonet> tunnel-zone tzone0 add member host host0
address ip_address_of_host0
zone tzone0 host host0 address ip_address_of_host0
midonet> tunnel-zone tzone0 add member host host1
address ip address of host1
zone tzone0 host host1 address ip_address_of_host1
midonet> tunnel-zone tzone0 add member host host2
address ip_address_of_host2
zone tzone0 host host2 address ip address of host2
midonet> tunnel-zone tzone0 add member host host3
address ip_address_of_host3
zone tzone0 host host3 address ip_address_of_host3
```

DRA

1

4

ď

1

1

4

ď

1

RA

ī

RA

ı

4 9

ī

DRA

ı

4

ď

1

# 5. Edge Router Setup

Prior to v5.0, with Neutron, you could set up the gateway in only one way, which was to have a special singleton gateway router called the Provider Router created implicitly when an external network was created in Neutron. The provider router sits at the edge of the cloud and interfaces with the uplink router. The Provider Router is where BGP was typically configured. The biggest limitation of this approach was that it took away the scenario in which you wanted to have an L2 network at the edge instead of a router. Another limitation was that only one such router could exist for the entire cloud.

These limitations are removed in v5.0, where you could design your gateway to be either L2 network or router with as many routers as you wish, all using the Neutron API.

There are two main changes:

### **Edge Router**

The Provider Router is no longer implicitly created upon the external network creation. Instead, the edge gateway routers, called the Edge Routers, are created explicitly using standard Neutron API. With this approach, multiple Edge Routers can be created, and they are optional.

### **Gateway Virtual Topology**

In the previous model, the Provider Router was connected directly to the tenant routers, with the external networks hanging off of the Provider Router.

In the new model, the external networks exist between the edge and the tenant routers.

To create the gateway topology issue the following Neutron commands.

Create a standard neutron router:

```
neutron router-create < EDGE_ROUTER_NAME>
```

Attach the edge router to an external network:

```
neutron router-interface-add <EDGE_ROUTER_ID> <EXT_SUBNET_ID>
```

Create a special network called uplink network, representing the physical network outside of the cloud:

```
neutron net-create <UPLINK_NET_NAME> --tenant_id admin --
provider:network_type uplink
```

Create a subnet for the uplink network matching the CIDR used in the uplink network (could just be /30 if linked directly to another router):

```
neutron subnet-create --tenant_id admin --disable-dhcp --name
<UPLINK_SUBNET_NAME> <UPLINK_NET_NAME> <CIDR>
```

Create a port on the uplink network with a specific IP that you want to use and the binding details so that this virtual port gets bound to a specific NIC on the gateway host:

```
neutron port-create <UPLINK_NET_ID> --binding:host_id <HOST_NAME> --
binding:profile type=dict interface_name=<INTERFACE_NAME> --fixed-ip
ip_address=<IP_ADDR>
```

Attach the uplink port to the Edge Router:

neutron router-interface-add <EDGE\_ROUTER\_ID> port=<UPLINK\_PORT\_ID>

# 6. BGP Uplink Configuration

MidoNet utilizes the Border Gateway Protocol (BGP) for external connectivity.

For production deployments it is strongly recommended to use BGP due to it's scalability and redundancy.

For demo or POC environments, alternatively static routing can be used. See the Operations Guide for details.

The following instructions assume below sample environment:

- One floating IP network
  - 192.0.2.0/24
- Two MidoNet gateway nodes
  - gateway1, connecting to bgp1 via eth1
  - gateway2, connecting to bgp2 via eth1
- Two remote BGP peers
  - bgp1, 198.51.100.1, AS 64513
  - bgp2, 203.0.113.1, AS 64514
- Corresponding MidoNet BGP peers
  - 198.51.100.2, AS 64512
  - 203.0.113.2, AS 64512

Follow these steps to configure the BGP uplinks.

1. Determine the Keystone admin tenant ID

Use the keystone command to determine the Keystone admin tenant's ID:

2. Launch the MidoNet CLI and find the Edge Router

```
$ midonet-cli
midonet-cli>
```

Because the Edge Router is not associated with a tenant, the active tenant has to be cleared (cleart) first.

```
midonet-cli> cleart

midonet-cli> router list
router router0 name Edge Router state up
router router1 name Tenant Router state up infilter chain0 outfilter
chain1
```

DRAI

ì

RAFT

1

In this example the Edge Router is router0.

#### 3. Load the admin tenant

Before continuing with further configuration, the admin tenant has to be set (sett). Use the ID you got from Keystone above.

```
midonet-cli> sett 12345678901234567890123456789012
tenant_id: 1234567890123456789012
```

### 4. Create virtual ports for the BGP sessions

For each remote BGP peer, create a port on the Edge Router that is going to be used for BGP communication.

```
midonet> router router0 add port address 198.51.100.2 net
198.51.100.0/30
router0:port0

midonet> router router0 add port address 203.0.113.2 net 203.0.113.0/30
router0:port1

midonet> router router0 port list
port port0 device router0 state up mac ac:ca:ba:11:11:11
address 198.51.100.2 net 198.51.100.0/30
port port1 device router0 state up mac ac:ca:ba:22:22:22
address 203.0.113.1 net 203.0.113.0/30
[...]
```

In this example the created ports are port0 and port1.

### 5. Configure BGP on the virtual ports

```
midonet> router router0 set asn 64512
midonet> router router0 add bgp-peer asn 64513 address 198.51.100.1
router0:peer0

midonet> router router0 list bgp-peer
peer peer0 asn 64513 address 198.51.100.1

midonet> router router0 add bgp-peer asn 64514 address 203.0.113.1
router0:peer1

midonet> router router0 list bgp-peer
peer peer0 asn 64513 address 198.51.100.1
peer peer1 asn 64514 address 203.0.113.1
```

#### 6. Add routes to the remote BGP peers

In order to be able to establish connections to the remote BGP peers, corresponding routes have to be added.

```
midonet> router router0 route add src 0.0.0.0/0 dst 198.51.100.0/30
port router0:port0 type normal
router0:route0

midonet> router router0 route add src 0.0.0.0/0 dst 203.0.113.0/30
port router0:port1 type normal
router0:route1
```

### 7. Advertise BGP routes

4

~

1

DRAFT

1

RAFT

1

- DRAFT

DRAFT

1

DRAFT

1

DRAFT

1

RAFT

Ω.

- DRAFT

RAFT

RAFT

1

In order to provide external connectivity for hosted virtual machines, the floating IP network has to be advertised to the BGP peers.

```
midonet> router router0 add bgp-network net 192.0.2.0/24
router0:net0
midonet> router router0 list bgp-network
net net0 net 192.0.2.0/24
```

8. Bind virtual ports to physical network interfaces

Bind the Edge Router's virtual ports to the physical network interfaces on the Gateway Nodes.



### **Important**

Ensure that physical interfaces are in state UP and do not have an IP address assigned.

a. List the MidoNet hosts and find the Gateway Nodes:

```
midonet> host list
host host0 name gateway1 alive true
host host1 name gateway2 alive true
[...]
```

In this example the hosts are host0 and host1.

b. List the Gateway Nodes' physical interfaces:

```
midonet> host host0 list interface
[...]

iface eth1 host_id host0 status 3 addresses [] mac 01:02:03:04:05:06

mtu 1500 type Physical endpoint PHYSICAL
[...]

midonet> host host1 list interface
[...]

iface eth1 host_id host0 status 3 addresses [] mac 06:05:04:03:02:01

mtu 1500 type Physical endpoint PHYSICAL
[...]
```

c. Bind the physical host interfaces to the Edge Router's virtual ports:

```
midonet> host host0 add binding port router0:port0 interface eth1
host host0 interface eth1 port router0:port0

midonet> host host1 add binding port router0:port1 interface eth1
host host1 interface eth1 port router0:port1
```

d. Configure a stateful port group:

```
midonet-cli> port-group create name uplink-spg stateful true pgroup0
```

e. Add the ports to the port group:

```
midonet> port-group pgroup0 add member port router0:port0
port-group pgroup0 port router0:port0
midonet> port-group pgroup0 add member port router0:port1
port-group pgroup0 port router0:port1
```

midonet> port-group pgroup0 list member port-group pgroup0 port router0:port0 port-group pgroup0 port router0:port1

# 7. Further Steps

MidoNet installation and integration into OpenStack is completed.

You can now continue with the creation of initial networks in Neutron.



- DRAFT - DRAFT - DRAFT

- DRAFT - DRAFT

- DRAFT - DRAFT

- DRAFT

- DRAFT - DRAFT

4

### Note

Consult the **Operations Guide** for further instructions on operating MidoNet.