

# MidoNet Operations Guide

5.0-SNAPSHOT (2015-11-26 07:25 UTC)

DRAFT



## MidoNet Operations Guide

5.0-SNAPSHOT (2015-11-26 07:25 UTC)

Copyright © 2015 Midokura SARL All rights reserved.

MidoNet is a network virtualization software for Infrastructure-as-a-Service (IaaS) clouds.

It decouples your IaaS cloud from your network hardware, creating an intelligent software abstraction layer between your end hosts and your physical network.

This guide includes instructions on creating routers, bridges, and ports. It also describes rule chains and several MidoNet features, including L4 load balancing, resource protection, NAT configuration, handling IP packet fragments, and L2 address matching.



### Caution

This document is a DRAFT. It may be MISSING relevant information or contain UNTESTED information. Use it at your own risk.



### Note

Please consult the [MidoNet Mailing Lists or Chat](#) if you need assistance.

Licensed under the Apache License, Version 2.0 (the "License"); you may not use this file except in compliance with the License. You may obtain a copy of the License at

<http://www.apache.org/licenses/LICENSE-2.0>

Unless required by applicable law or agreed to in writing, software distributed under the License is distributed on an "AS IS" BASIS, WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied. See the License for the specific language governing permissions and limitations under the License.

## Table of Contents

Preface .....	vii
Conventions .....	vii
1. Configuring uplinks .....	1
Edge Router Setup .....	1
BGP Setup .....	2
Static Setup .....	7
2. Authentication and authorization .....	9
Available authentication services in MidoNet .....	9
Roles in MidoNet .....	10
Using the Keystone authentication service .....	11
3. Admitting resources to MidoNet .....	13
What are tunnel zones? .....	13
Working with hosts .....	14
4. Device abstractions .....	17
Creating a router .....	17
Adding a port to a router .....	17
Adding a bridge .....	18
Adding a port to a bridge .....	18
Binding an exterior port to a host .....	18
Stateful port groups .....	19
keystone tenant-list .....	20
5. Connecting devices .....	22
Connecting a bridge to a router .....	22
Connecting two routers .....	23
6. Routing .....	24
Routing process overview .....	24
Viewing routes .....	26
Adding routes .....	27
Deleting routes .....	28
7. Rule chains .....	29
A packet's flow within a router .....	29
A packet's flow within a rule chain .....	30
Rule types .....	31
Rule order .....	32
Rule conditions .....	33
MidoNet rule chain example .....	37
Listing the bridges for the tenant .....	39
Listing the OpenStack security group rule chain .....	40
8. Network Address Translation .....	42
Static NAT .....	42
Viewing NAT rule chain information .....	42
Configuring SNAT, DNAT, and REV_DNAT .....	44
DNAT/REV_DNAT example .....	44
SNAT example .....	45
9. Layer 4 Load Balancing .....	47
Load balancer configuration .....	48
Sticky Source IP .....	50
Health monitor .....	51
10. L2 address masking .....	54
L2 address mask rule chain example .....	54
11. Handling fragmented packets .....	55
Definitions and allowed values .....	55

AFT - DRAFT - DRAFT - DRAFT - DRAFT - DRAFT - DRAFT - DRAFT -

## List of Figures

15.1. Topology with VLANs and L2 Gateway .....	102
--	-----

## List of Tables

2.1. Authentication Provider Classes .....	9
2.2. Authentication Roles .....	11
2.3. Keystone Protocol .....	11
7.1. CLI Rule Chain Attributes .....	33
7.2. CLI Rule Chain Attributes That Match Packets .....	34
13.1. Configuration Files/Locations .....	72
13.2. Event Message Files/Locations .....	72
17.1. Recommended Configuration Values .....	113
17.2. Admin Roles .....	115
17.3. System Properties for the HTTPS Key Store .....	116

# Preface

## Conventions

The MidoNet documentation uses several typesetting conventions.

## Notices

Notices take these forms:



### Note

A handy tip or reminder.



### Important

Something you must be aware of before proceeding.



### Warning

Critical information about the risk of data loss or security issues.

## Command prompts

### \$ prompt

Any user, including the root user, can run commands that are prefixed with the \$ prompt.

### # prompt

The root user must run commands that are prefixed with the # prompt. You can also prefix these commands with the **sudo** command, if available, to run them.





To create the gateway topology issue the following Neutron commands.

Create a standard neutron router:

```
neutron router-create <EDGE_ROUTER_NAME>
```

Attach the edge router to an external network:

```
neutron router-interface-add <EDGE_ROUTER_ID> <EXT_SUBNET_ID>
```

Create a special network called `uplink` network, representing the physical network outside of the cloud:

```
neutron net-create <UPLINK_NET_NAME> --tenant_id admin --
provider:network_type uplink
```

Create a subnet for the uplink network matching the CIDR used in the uplink network (could just be /30 if linked directly to another router):

```
neutron subnet-create --tenant_id admin --disable-dhcp --name
<UPLINK_SUBNET_NAME> <UPLINK_NET_NAME> <CIDR>
```

Create a port on the uplink network with a specific IP that you want to use and the binding details so that this virtual port gets bound to a specific NIC on the gateway host:

```
neutron port-create <UPLINK_NET_ID> --binding:host_id <HOST_NAME> --
binding:profile type=dict interface_name=<INTERFACE_NAME> --fixed-ip
ip_address=<IP_ADDR>
```

Attach the uplink port to the Edge Router:

```
neutron router-interface-add <EDGE_ROUTER_ID> port=<UPLINK_PORT_ID>
```

## BGP Setup

You set up a BGP link to connect MidoNet with an external Autonomous System (AS). This creates an up-link to an external network.

Typically, you connect a MidoNet network to the Internet through two independent up-link routers. In the simple case of connecting MidoNet to the Internet via two BGP-enabled routers, it's best to create two ports on the virtual router and bind them to network interfaces in two different hosts (two Gateway Nodes). This will distribute load between both Gateway Nodes hosts, as well as eliminate a single point of failure. The two ports must be configured as a stateful port pair, for details, refer to [the section called "Stateful port groups" \[19\]](#).

MidoNet uses quagga's bgpd to terminate BGP sessions on behalf of a virtual router. The routes that bgpd learns from its peers are added to the virtual router in MidoNet's topology. The quagga package is provided in the MidoNet release package repositories. Any system running Midolman should already have everything that it needs to set up the BGP. You have to keep in mind that bgpd processes run in the host where a particular virtual router port is bound.



### Important

Make sure you have the following information before setting up the BGP: Local and peer Autonomous System (AS) Numbers for the BGP session. The IP address of the BGP peer.

## Establishing BGP sessions

This section walks you through the process of setting up a BGP session.

Make sure you have the following information before setting up the BGP:

- The tenant ID that owns the Edge Router that will establish the BGP session. Typically this router is owned by the "admin" tenant.
- Local and peer Autonomous System (AS) Numbers for the BGP session. In our example, we will use 64512 and 64513.
- The IP address of the BGP peer.
- A list of routes to advertise to the BGP peer.
- The UUID of the Edge Router.

Our sample virtual topology contains one router with one port.

1. Start the midonet-cli and find the Edge Router.

To start the midonet-cli, at the system prompt, enter:

```
$ midonet-cli
```

The midonet> prompt appears, type the following commands:

```
midonet> clear  
midonet> router list  
router router0 name Edge Router
```

The clear command removes the tenant that is loaded in CLI. Because the provider router does not have tenant ID set, you need to remove the tenant first.

2. Issue the following command to load the admin tenant:

```
midonet> sett admin
```

where *admin* is your admin tenant UUID in OpenStack, for example: 12345678-90123456-123456789012. You can obtain this identifier by calling OpenStack identity service (keystone):

```
$ keystone tenant-list
```

3. Create a virtual port for the BGP session.

You need to create the virtual port to be used for BGP communication with the remote router. To create a new virtual port, enter:

```
midonet> router router0 add port address 10.12.12.1 net 10.12.12.0/24  
router0:port0
```

To verify the created port, enter:

```
midonet> router router0 list port  
port port0 device router0 state up mac 02:47:98:a1:e5:f8 address 10.12.12.1 net 10.12.12.0/24
```

4. Before creating a BGP session, assign an AS number to the router:

```
midonet> router router0 set asn 64512
```

```
midonet> router router0 show
router router0 name Edge Router state up asn 64512
midonet>
```

5. Now, continue by listing the BGP peers on the router:

```
midonet> router router0 list bgp-peer
midonet>
```

The output of this command should not return any BGP peers, since we didn't add any yet. To add a BGP peer use this command:

```
midonet> router router0 add bgp-peer asn 64513 address 10.12.12.2
router0:peer0
midonet> router router0 list bgp-peer
peer peer0 asn 64513 address 10.12.12.2
midonet>
```

We can also give this session custom timers that will take precedence over the default timers defined in MidoNet configuration:

```
midonet> router router0 bgp-peer peer0 set connect-retry 10
midonet> router router0 bgp-peer peer0 set hold-time 5
midonet> router router0 bgp-peer peer0 set keep-alive 5
midonet> router router0 list bgp-peer
peer peer0 asn 64513 address 10.12.12.2 keep-alive 5 hold-time 5
connect-retry 10
midonet>
```

6. Advertise a route.

At this point, you can advertise routes over the BGP session. In an OpenStack environment, you must advertise public floating IP ranges over BGP in order to provide external connectivity for hosted virtual machines.

```
midonet> router router0 add bgp-network net 192.168.12.0/24
router0:net0
midonet> router router0 list bgp-network
net net0 net 192.168.12.0/24
```

7. Bind the router's port to a physical network interface.

If you just created the router port to connect to the BGP peer, the port might not be bound to any network interface. You need to bind the port to an active physical network interface to enable the port (and its BGP sessions).

To create that binding, you need to know the host and network interface. With that information, you can use the following commands to bind the port to the physical network interface and activate the BGP session.



### Note

Make sure that no IP address is present on the interface you want to bind to a virtual port, and that the interface is UP.

First, list the hosts:

```
midonet> host list
host host0 name ip-10-152-161-111 alive true
host host1 name ip-10-164-23-206 alive true
```

After finding the host, you can list its network interfaces:



The first step is to add a second router port:

Now you can add a BGP peer that is reachable through the new port:

And bind the new port to a NIC in a different physical host:

At this point the MidoNet agent in host1 will bring up the new router port and set up bgpd to talk to the peer in 10.22.22.2.

As with the first port, adding a second BGP peer on the 10.22.22.0/24 network would enable host1 to load balance across two upstream routers and to keep functioning as a gateway even if one of its two BGP peers fails.

## BGP failover configuration on a BGP peer

The default BGP failover time is 2-3 minutes. However, you can reduce this time by changing some parameters on both ends of the BGP session.

You must make the change in `mn-conf(1)` on the MidoNet side, and the remote end BGP peer configuration.

The basic BGP timers are 'keepalive' and 'holdtime'. By default, keepalive timer is 60 seconds. The hold-down timer is, by convention, 3 times the keepalive interval, 180 seconds. You can go as low as 1 and 3 seconds for these values, but keep in mind that this may potentially result in the BGP session flapping.

Another important BGP timer that you can tweak is the BGP 'connect\_retry' timer, also called the 'connect' timer. You can use this timer to set the amount of time between retries to establish a connection to configured peers which have gone down for some reason.

The example below shows how to reduce the default BGP values to 1, 1, and 3 seconds, for keep-alive, hold-time, and connect-retry, respectively, on the BGP peer's session end (e.g. Quagga or Cisco):

```
neighbor 192.0.2.1 timers 1 3
neighbor 192.0.2.1 timers connect 1
```

To match those settings you would have to set the following parameters on the MidoNet end of the BGP session:

```
agent {
  midolman {
    bgp_connect_retry : 1s
    bgp_holdtime : 3s
    bgp_keepalive : 1s
  }
}
```


## Static Setup

If you are not connecting through a BGP link, or you just want to use static routing follow this section.

This creates a static up-link to connect VMs to the external network.

### 1. Create fake uplink

We are going to create the following topology to allow the VMs reach external networks:



### 2. Create a veth pair

```
# ip link add type veth
# ip link set dev veth0 up
# ip link set dev veth1 up
```

### 3. Create a bridge, set an IP address and attach veth0

```
# brctl addbr uplinkbridge
# brctl addif uplinkbridge veth0
# ip addr add 172.19.0.1/30 dev uplinkbridge
```

```
# ip link set dev uplinkbridge up
```

#### 4. Enable IP forwarding

```
# sysctl -w net.ipv4.ip_forward=1
```

#### 5. Route packets to 'external' network to the bridge

```
# ip route add 200.200.200.0/24 via 172.19.0.2
```

#### 6. Create a port on the Edge Router and bind it to the veth:

```
$ midonet-cli
midonet> router list
router router0 name Edge Router state up
midonet> router router0 add port address 172.19.0.2 net 172.19.0.0/30
router0:port0
midonet> router router0 add route src 0.0.0.0/0 dst 0.0.0.0/0 type
normal port router router0 port port0 gw 172.19.0.1
midonet> host list
host host0 name controller alive true
midonet> host host0 add binding port router router0 port port0 interface
veth1
host host0 interface veth1 port router0:port
```

#### 7. Add masquerading to your external interface so connections coming from the overlay with addresses that belong to the "fake" external network are NATed. Also make sure these packets can be forwarded:

```
# iptables -t nat -I POSTROUTING -o eth0 -s 200.200.200.0/24 -j
MASQUERADE
# iptables -I FORWARD -s 200.200.200.0/24 -j ACCEPT
```

Now we can reach VMs from the underlay host using their floating IPs, and VMs can reach external networks as well (as long as the host has external connectivity).

## 2. Authentication and authorization

# Table of Contents

Available authentication services in MidoNet .....	9
Roles in MidoNet .....	10
Using the Keystone authentication service .....	11

The MidoNet Application Programming Interface (API) provides its authentication and authorization services by integrating with external identity services.

It does not provide an API to create or delete tenants, but it does have an API to tag resources and filter queries with tenant IDs. Tenants are managed completely by an external identity service, and where appropriate, the string representations of tenant IDs are sent in the requests to the MidoNet API. This design makes possible a federated identity service model where one identity service provides authentication and authorization to all the services in the cloud environment, including the MidoNet API.

Although the MidoNet Cluster does not provide its own identity service, it does provide simple authentication (for validating the user) and authorization (for checking the access level of the user) functionality. For authentication, it simply takes the token included in the HTTP header and forwards it to the external identity service. To generate a new token, it also provides an API to log in to the external identity service with username/password credentials. (See the MidoNet REST API document for more information on the token.) For authorization, the MidoNet API provides a very simple Role-Based Access Control (RBAC) mechanism explained in the next section.

See the MidoNet REST API document for information on implementing authentication and authorization using the MidoNet API. Go to <http://docs.openstack.org/> and follow the links to Documentation and API for information about the OpenStack API.

## Available authentication services in MidoNet

The MidoNet Cluster package includes two authentication providers: *Keystone* authentication and *mock* authentication. You can select the current authentication provider by modifying the value of the `cluster.auth.provider_class` key using `mn-conf` to one of the following values:

### Table 2.1. Authentication Provider Classes

Class	Description
<code>org.midonet.cluster.auth.keystone.v2_0.Key</code>	Uses external Keystone identity service, version 2.
<code>org.midonet.cluster.auth.MockAuthService</code>	Disables authentication.

This section describes the Keystone authentication service, the mock authentication and some additional configurations options specific to each provider.

## Keystone authentication

In order to use the OpenStack Keystone authentication service with MidoNet, you must configure the `KeystoneService` provider class:



```
echo "cluster.auth.provider_class : org.midonet.cluster.auth.keystone.v2_0.KeystoneService" | mn-conf set -t default
```



### Important

You must restart all MidoNet Cluster instances after changing the authentication provider.

For additional Keystone configuration options, see [the section called “Enabling Keystone authentication” \[11\]](#)

## Mock authentication

Mock authentication disables the authentication system by returning a fake tokens to authenticating clients, and ignoring the sent tokens during authorization. To enable the mock authentication configure the `MockAuthService` provider class.

```
echo "cluster.auth.provider_class : org.midonet.cluster.auth.MockAuthService" | mn-conf set -t default
```



### Warning

Mock authentication is the default authentication provider for the MidoNet Cluster. However, this mode is used for testing purposes but should not be used in production.

## Roles in MidoNet

The MidoNet API implements an RBAC mechanism to perform authorization.

Defined in the `AuthRole` class, the roles in MidoNet are:

- Admin: The root administrator of the system. Users with this role are allowed to do all operations.
- TenantAdmin: Users with this role have write and read access to their own resources.
- TenantUser: Users with this role only have read access to their own resources.



### Important

Currently, the *TenantAdmin* and *TenantUser* roles are not supported.



### Note

Keep in mind that the RBAC policies defined in the external identity services are not applied to MidoNet RBAC. For example, the type of access you receive in Keystone does not directly map to the exact same access in MidoNet. The MidoNet API strictly follows the policies for the three roles described above.

## Creating admin roles for MidoNet

The authorization service relies on the MidoNet Cluster configuration to determine the role mapping.

You can use the authorization service to convert the roles in an external service (like OpenStack Keystone) to those in MidoNet. The following table contains the configuration keys corresponding to each MidoNet role.

**Table 2.2. Authentication Roles**

Configuration Key	Value	Description
cluster.auth.admin_role	<role_name>	Specifies the name for the admin role in MidoNet.
cluster.auth.tenant_admin_role	<role-name>	Specifies the name for the tenant admin role in MidoNet.
cluster.auth.tenant_user_role	<role-name>	Specifies the name for the tenant user role in MidoNet.

You can use the `mn-conf` tool to modify the name used by the identity service for each role. For example, if the name of the *Admin* role is `admin`, type:

```
$ echo "cluster.auth.admin_role : admin" | mn-conf set -t default
```



### Important

By default the MidoNet Cluster configuration does not set any name for the admin roles. Therefore, when using an external identity service that requires identity roles, such as Keystone, you must set at least the name for the *Admin* role.

## Using the Keystone authentication service

This section explains how to use the Keystone authentication service with MidoNet.

### Enabling Keystone authentication

In order to use the OpenStack Keystone authentication service with MidoNet, you must configure the following keys in the MidoNet configuration.

#### cluster.auth.provider\_class

The fully qualified path of the Java class that provides the Keystone authentication service.

```
org.midonet.cluster.auth.keystone.v2_0.KeystoneService
```

#### cluster.auth.admin\_role

Identifies the name of the admin role in MidoNet. The admin has read and write access to all the resources. We recommend re-using the OpenStack *admin* role. Optionally you can create a separate admin role for MidoNet.

#### cluster.auth.keystone.protocol

Identifies the protocol used for the Keystone service. The following values are allowed:

**Table 2.3. Keystone Protocol**

Class	Description
http	Uses plain text HTTP to communicate with the Keystone server.

Class	Description
https	Uses encrypted HTTPS to communicate with the Keystone service (recommended).

### cluster.auth.keystone.host

Identifies the host of the Keystone service (default is *localhost*).

### cluster.auth.keystone.port

Identifies the port number of the Keystone service (default is *35357*).

### cluster.auth.keystone.admin\_token

Identifies the token of the admin user in Keystone that the API uses to make requests to Keystone.

### cluster.auth.keystone.tenant\_name

Specifies the name of the tenant that is used when logging into Keystone. The log-in authentication to Keystone requires the username, password, and tenant name of the user. By specifying the tenant name here, you can avoid the need for applications to supply the tenant name when logging into Keystone through the MidoNet API.

## Disabling Keystone authentication

MidoNet lets you disable authentication by using a mock authentication service.

Using this service has the effect that no outside authentication service is used. Instead, MidoNet will return fake tokens to the authenticating clients. Likewise, the provider will ignore any tokens sent by the client when authorizing an API request.

To use the mock authentication service, you must configure the following keys in the MidoNet configuration.

### cluster.auth.provider\_class

The fully qualified path of the Java class that provides the mock authentication service.

```
org.midonet.cluster.auth.MockAuthService
```



## Deleting tunnel zones

Use this procedure to delete a tunnel zone.

1. Enter the `list tunnel-zone` command to list the tunnel zones. For example:

```
midonet> list tunnel-zone
tzone tzone0 name new-tz type gre
tzone tzone1 name gre type gre
```

2. Enter the `delete tunnel-zone tz-alias` command to delete the desired tunnel zone. For example:

```
midonet> delete tunnel-zone tzone0
```

Specify the dynamically assigned number of the alias for the tunnel zone to delete; in the above example, the assigned number is 0 (tzone0).

3. (Optional) Enter the command to list the tunnel zones to confirm the deletion:

```
midonet> list tunnel-zone
tzone tzone1 name gre type gre
```

## Viewing tunnel zone information

Use this procedure to view tunnel zone information.

```
midonet> tunnel-zone tzone0 list member
zone tzone0 host host0 address 192.168.0.3
zone tzone0 host host1 address 192.168.0.5
zone tzone0 host host2 address 192.168.0.4
zone tzone0 host host3 address 192.168.0.6
```

The above output shows the:

- Aliases for the hosts in the tunnel zone (host0, host1, and so on)
- IP addresses assigned to the hosts

## Working with hosts

This section shows how to view host information and admit new hosts to a tunnel zone.

### Viewing host information

Use this procedure to view information about hosts.

- To list the hosts enter the command:

```
midonet> list host
host host0 name controller alive true
host host2 name compute1 alive true
host host3 name compute3 alive false
host host1 name compute2 alive false
```

- To list the interfaces on a certain host enter the command:

```
midonet> host host0 list interface
iface midonet host_id host0 status 0 addresses [] mac 12:6e:b7:d0:4f:f1
mtu 1500 type Virtual endpoint DATAPATH
```



In the above command example:

- tzone0 = the tunnel zone you want to add the member (host) to
- host0 = the alias of the host you want to add
- 10.1.2.200 = the IP address of the host you want to add

## Removing a host from a tunnel zone

Use this procedure to remove a host from a tunnel zone.

1. Enter the `list tunnel-zone` command to list the tunnel zone. For example:

```
midonet> list tunnel-zone
tzone tzone0 name default_tz type gre
```

2. Enter the `tunnel-zone tunnel-zone list member` command to list the tunnel zone members (hosts). For example:

```
midonet> tunnel-zone tzone0 list member
zone tzone0 host host0 address 172.19.0.2
```

3. Enter the `tunnel-zone tunnel-zone member host host show` command to show information about a specific host. For example:

```
midonet> tunnel-zone tzone0 member host host0 show
tunnel-zone-host zone tzone0 host host0 address 172.19.0.2
```

4. Enter the `tunnel-zone tunnel-zone member host host delete` command to delete the desired host (identified by the host's alias). For example:

```
midonet> tunnel-zone tzone0 member host host0 delete
```

5. (Optional) You can add the host back to the tunnel zone, using the `tunnel-zone tunnel-zone member add host host address ip-address` command as shown below:

```
midonet> tunnel-zone tzone0 member add host host0 address 172.19.0.2
zone tzone0 host host0 address 172.19.0.2
```

## Removing a host

Use this procedure to remove inactive hosts.

1. Enter the command to list the hosts:

```
midonet> list host
host host0 name precise64 alive true
```

2. Enter the command to delete the desired host (identified by its alias):

```
midonet> host host0 delete
```





```
midonet> router router1 add port address 10.100.1.1 net 10.0.0.0/24
router1:port0
```

The above output shows the alias ("port0") assigned to the new port.

2. Enter the command to list port information for the router:

```
midonet> router router1 list port
port port0 device router1 state up mac 02:a6:81:08:ab:5d address 10.100.
1.1 net 10.0.0.0/24
```

The above output shows the:

- Alias assigned to the port ("port0")
- Device the port is attached to (router1)
- Port's state (up)
- Port's MAC address
- Port's IP and network addresses

## Adding a bridge

Use this procedure to create a bridge.

Enter the following command to create a bridge and assign it a name:

```
midonet> bridge create name test-bridge
bridge1
```

The above output shows the alias ("bridge1") assigned to the new bridge.

## Adding a port to a bridge

Use this procedure to add a port to a bridge.

1. Enter the command to list the bridges on the current tenant:

```
midonet> bridge list
bridge bridge1 name test-bridge state up
```

2. Enter the command to add a port to the desired bridge:

```
midonet> bridge bridge1 add port
bridge1:port0
```

The above output shows the alias ("port0") assigned to the new port.

## Binding an exterior port to a host

In order to connect a MidoNet-enabled cloud to an external network, you need to bind an exterior port to a host, such as a network interface card (NIC) with an ID of eth0, for example.

1. Enter the command to list the hosts:

```
midonet> list host
host host0 name compute-1 alive true
host host1 name compute-2 alive true
```

2. Enter the command to list the bridges on the current tenant:

```
midonet> list bridge
bridge bridge0 name External state up
bridge bridge1 name Management state up
bridge bridge2 name Internal state up
```

3. Enter the command to list the ports on the desired bridge:

```
midonet> bridge bridge0 list port
port port0 device bridge0 state up
port port1 device bridge0 state up
port port2 device bridge0 state up
```

4. Enter the command to list the interfaces on a certain host:

```
midonet> host host0 list interface
iface lo host_id host0 status 3 addresses [u'127.0.0.1',
u'0:0:0:0:0:0:0:1'] mac 00:00:00:00:00:00 mtu 65536 type Virtual
endpoint LOCALHOST
iface midonet host_id host0 status 0 addresses [] mac 8e:4d:60:c1:70:d7
mtu 1500 type Virtual endpoint DATAPATH
iface eth1 host_id host0 status 3 addresses
[u'fe80:0:0:0:250:56ff:fe93:7c35'] mac 00:50:56:93:7c:35 mtu 1500 type
Physical endpoint PHYSICAL
iface eth0 host_id host0 status 3 addresses [u'10.1.2.200',
u'fe80:0:0:0:250:56ff:fe93:c9a4'] mac 00:50:56:93:c9:a4 mtu 1500 type
Physical endpoint PHYSICAL
```

5. Enter the command to bind a certain host to virtual port:

```
midonet> host host0 add binding
host interface port
```

6. Enter the command to bind a virtual port on the bridge with a physical interface on the host:

```
midonet> host host0 add binding port bridge0:port0 interface eth1
host host0 interface eth1 port bridge0:port0
```

## Stateful port groups

MidoNet features stateful port groups, which are groups of virtual ports (typically two) that are logically associated, usually to perform load balancing or for link redundancy.

For such ports MidoNet keeps state local to the two endpoints of a connection. In most cases, connections that traverse MidoNet do so between a single pair of ports. Typical cases include a router with two uplink BGP ports, or an L2GW with two ports connected to a physical L2 network. In both cases, the pair of ports becomes a set of ports because packets may return through different paths. Those port pairs will share state.

You configure stateful port groups in the MidoNet CLI, using the port-group command.

## Creating stateful port groups

Follow the steps of this procedure to create a stateful group of ports, using the MidoNet CLI.

## keystone tenant-list

The output of the command shows the full list of tenants. For this procedure we will use the 'admin' tenant. 7a4937fa604a425e867f085427cc351e.

- ```
midonet> list router
router router0 name Edge Router state up
router router1 name TenantRouter state up
```

Let's assume that the router whose ports you are going to add to the port group is Edge Router, router0.

- ```
midonet> router router0 list port
port port0 device router0 state up mac 02:c2:0f:b0:f2:68 address 100.
100.100.1 net 100.100.100.0/30
port port1 device router0 state up mac 02:cb:3d:85:89:2a address 172.
168.0.1 net 172.168.0.0/16
port port2 device router0 state up mac 02:46:87:89:49:41 address 200.
200.200.1 net 200.200.200.0/24 peer bridge0:port0
port port3 device router0 state up mac 02:6b:9f:0d:c4:a8 address 169.
254.255.1 net 169.254.255.0/30
```

You want to add port0 and port1 on the router to load balance the BGP traffic on the Edge Router.

- ```
midonet-cli> sett 7a4937fa604a425e867f085427cc351e
tenant id: 7a4937fa604a425e867f085427cc351e
```

- ```
midonet-cli> port-group create name SPG stateful true
pgroup0
```

- ```
midonet> port-group pgroup0 add member port router0:port0
port-group pgroup0 port router0:port0
midonet> port-group pgroup0 add member port router0:port1
port-group pgroup0 port router0:port1
```

```
midonet> port-group pgroup0 list member
```

```
port-group pgroup0 port router0:port1  
port-group pgroup0 port router0:port0
```

## 5. Connecting devices

# Table of Contents

|                                       |    |
|---------------------------------------|----|
| Connecting a bridge to a router ..... | 22 |
| Connecting two routers .....          | 23 |

You can create a virtual topology by connecting routers to bridges, to switches, and to other routers.

## Connecting a bridge to a router

You can easily connect a virtual bridge to a virtual router via virtual ports on the two devices. Make sure you create a bridge and a router with an Interior port on each device.



## Note

See the section called “Creating a router” [17] and the section called “Adding a bridge” [18] for information about creating routers and bridges and adding router and bridge ports.

To connect a bridge to a router:

1. Enter the command to list the bridges on the current tenant:

```
midonet> list bridge
bridge bridge1 name test-bridge state up
```

2. Enter the command to list the ports on the bridge:

```
midonet> bridge bridge1 list port
port port0 device bridge1 state up
```

3. Enter the command to list the routers on the current tenant:

```
midonet> list router
router router1 name test-router state up
```

4. Enter the command to list the ports on the router:

```
midonet> router router1 list port
port port0 device router1 state up mac 02:a6:81:08:ab:5d address 10.100.
1.1 net 10.0.0.0/24
```

5. Enter the command to bind the desired router port (for example, port0 on router1) to the desired bridge port (for example, port0 on bridge1):

```
midonet> router router1 port port0 set peer bridg1:port0
```

6. Enter the command to list the ports on the router (in this example, router1):

```
midonet> router router1 list port
port port0 device router1 state up mac 02:a6:81:08:ab:5d address 10.100.
1.1 net 10.0.0.0/24 peer bridqel:port0
```

The above output shows that port0 on router1 is connected to port0 on bridge1.

## Connecting two routers

You can easily connect two virtual routers via virtual ports on each router.

Make sure you create the router ports on the two routers and assign the ports to the same subnet. See [Chapter 4, “Device abstractions” \[17\]](#) for information about creating routers and adding router ports.

To connect two routers:

1. Enter the command to list the routers on the current tenant:

```
midonet> list router
router router3 name test-router2 state up
router router1 name test-router state up
```

2. Enter the command to list the ports on one of the routers you want to connect:

```
midonet> router router1 list port
port port0 device router1 state up mac 02:a6:81:08:ab:5d address 10.100.
1.1 net 10.0.0.0/24 peer bridge1:port0
port port1 device router1 state up mac 02:fa:5f:87:bb:d2 address 10.100.
1.2 net 10.0.0.0/24
```

3. Enter the command to list the ports on the router you want to connect it to:

```
midonet> router router3 list port
port port0 device router3 state up mac 02:df:24:5b:19:9b address 10.100.
1.128 net 10.0.0.0/24
```

4. Enter the command to bind the port on one router (for example, port 1 on router1) to the port on another router (for example, port0 on router3):

```
midonet> router router1 port port1 set peer router3:port0
```

5. Enter the command to list the ports on one of the routers:

```
midonet> router router1 list port
port port0 device router1 state up mac 02:a6:81:08:ab:5d address 10.100.
1.1 net 10.0.0.0/24 peer bridge1:port0
port port1 device router1 state up mac 02:fa:5f:87:bb:d2 address 10.100.
1.2 net 10.0.0.0/24 peer router3:port0
```

The above output shows that port1 on router1 is connected to port0 on router3.

## 6. Routing

### Table of Contents

|                                |    |
|--------------------------------|----|
| Routing process overview ..... | 24 |
| Viewing routes .....           | 26 |
| Adding routes .....            | 27 |
| Deleting routes .....          | 28 |

Routing in a MidoNet-enabled network works the same as on physical routers. Virtual routers route packets to locally connected networks and hosts directly connected to it and forward packets to gateways for delivery to external networks.

### Routing process overview

For traffic that ingresses a router port, the router does the following:

- Attempts to match a given packet's destination with a route in its routing table based on the packet's source and destination, preferring the route with the lower weight value.
- For packets with more than one matching route, uses per-agent round robin selection among those routes.
- Drops packets that don't match routes with matching sources and destinations.

The router uses information in the following fields in the routing table:

- Source: defines the IP addresses and networks to filter and evaluate for delivery to directly connected networks and hosts or forward to gateways to other networks.
- Route Type: determines the action to take on the packet.
- Next Hop Port and Next Hop Gateway: determine where to route the packet.

Below are two sample routes on a tenant router (displayed using the MidoNet CLI):

```
route route2 type normal src 0.0.0.0/0 dst 172.16.3.0/24 port router0:port1
weight 100
route route3 type normal src 172.16.3.0/24 dst 169.254.169.254 gw 172.16.3.
2 port router0:port1 weight 100
```

### Source

Shows the route's source prefix for source-based routing. The algorithm to decide which route applies to the packet is briefly as follows:

1. Disregard all routes whose source prefix does not match the packet's source. The source prefix, 0.0.0.0/0, matches everything. Note that /0 denotes a bit mask of length zero, so the address 0.0.0.0 is ignored.
2. Find the route whose destination prefix matches the packet's destination and has the longest mask (a.k.a. longest-prefix matching).





## Weight

Can be used for load balancing for destinations with multiple paths. Lower weight values identify preferred paths (for example, higher bandwidth). The default weight value is 100. For routes learned from BGP peers, the BGP administrative distance becomes the route's weight. See also "Source".

## Viewing routes

You can view the routes defined on each virtual router in MidoNet. For example, you can view information about routes to virtual bridges and to other routers, including tenant routers and Edge Routers.

To display route information about the current tenant's routers:

1. Enter the command below to list the routers for the current tenant.

```
midonet> list router
router router0 name tenant-router state up infilter chain0 outfilter
chain1
```

2. Enter the command below to list the route list for the router, in this case, a tenant router (router0).

```
midonet> router router0 list route
route route0 type normal src 0.0.0.0/0 dst 169.254.255.2 port
router0:port0 weight 0
route route1 type normal src 0.0.0.0/0 dst 0.0.0.0/0 port router0:port0
weight 100
route route2 type normal src 0.0.0.0/0 dst 172.16.3.0/24 port
router0:port1 weight 100
route route3 type normal src 172.16.3.0/24 dst 169.254.169.254 gw 172.
16.3.2 port router0:port1 weight 100
route route4 type normal src 0.0.0.0/0 dst 172.16.3.1 port router0:port1
weight 0
```

The route list shows the following information:

- The source (src) for the traffic to match. route3 shows a specific source network to match; 0.0.0.0/0 means match traffic from every network.
- The destination (dst) for this traffic. This can be a network or a specific interface.
  - route0 shows an example of a route to a specific interface. This is the route to the link-local address, which, in this example, is peered with an Edge Router.
  - route2 shows a route to the 172.16.3.0/24 network, which is a private network.
  - route1 says: for traffic that matches every network (0.0.0.0/0) with a destination of any network (0.0.0.0/0), forward this traffic to port0, which is peered with an Edge Router. For traffic that matches the source IP address, MidoNet finds the route whose destination prefix matches the packet's destination and has the longest mask (a.k.a. longest-prefix matching). If the router cannot find a destination with a longer prefix than 0.0.0.0, the router sends the traffic to this default route.
- For destinations that are not directly connected to the router, the interface to the gateway to the destination is shown (next hop gateway).
  - route3 shows an example. This route says: traffic with a source that matches the 172.16.3.0/24 network (that is, traffic from the private network), with the destina-

tion, 169.254.169.254, which is the link-local address to the metadata service, forward this traffic to the gateway port, 172.16.3.2, which is the tenant router's interface to the metadata service. This kind of routes exist only when the network is served by Neutron DHCP Agent, typically to provide instance metadata service.

- route4 says: for traffic from any network (0.0.0.0/0) with the destination of the tenant router's interface (172.16.3.1), which is the tenant router's interface to the private network, forward this traffic to port1. port 1 on the tenant router is peered with port0 on router1, which is the Edge Router.

## Adding routes

Below are some examples of when you might want to add a route:

- You notice that a specific IP address or range is attacking your network. To prevent such attacks, you add a route to the Edge Router; this route's source IP matches the attacking IP address or range. You specify the type as a Blackhole to configure the Edge Router to drop packets from this source.
- If BGP dynamic routing is not available, you may configure static routes to forward traffic to the upstream router(s).

The attributes you specify are:

- dst = destination IP address or network to match
- src = source IP address or network to match
- type = for example, "normal"
- port = port to emit traffic over

To add a route using the MidoNet CLI:

1. Enter the command to add a route:

```
midonet> router router2 add route dst 169.254.255.0/30 src 0.0.0.0/0
type normal port router2:port2
router2:route2
```

The above command contains the following instructions:

- For traffic with the source any network (0.0.0.0/0) with the destination network 169.254.255.0/30, forward this traffic over port2 on router2.



### Note

Prior to adding the above route, a port was added to router2 using the following command:

```
midonet> router router2 add port address 169.254.255.3 net
169.254.255.0/30
router2:port2
```

2. Enter the command to list the routes on router2 to confirm the added route(s):

```
midonet> router router2 list route
route route0 type normal src 0.0.0.0/0 dst 10.100.1.1 port router2:port0
weight 0
```

```
route route1 type normal src 0.0.0.0/0 dst 10.100.1.2 port router2:port1
weight 0
route route2 type normal src 0.0.0.0/0 dst 169.254.255.3 port
router2:port2 weight 0
route route3 type normal src 0.0.0.0/0 dst 169.254.255.0/30 port
router2:port2 weight 0
```

## Deleting routes

If you are using MidoNet as a standalone SDN controller, there are many situations where you might want to delete routes; all related to managing your physical network devices.

For example, if you want to reverse something you did that required manually adding routes, you can delete the routes.



### Warning

It is not recommended to delete routes that were added automatically as a result of OpenStack Neutron operations.

To delete a route:

1. Enter the command to list the routes on a certain router:

```
midonet> router router2 list route
route route0 type normal src 0.0.0.0/0 dst 10.100.1.1 port router2:port0
weight 0
route route1 type normal src 0.0.0.0/0 dst 10.100.1.2 port router2:port1
weight 0
route route2 type normal src 0.0.0.0/0 dst 169.254.255.3 port
router2:port2 weight 0
route route3 type normal src 0.0.0.0/0 dst 169.254.255.0/30 port
router2:port2 weight 0
```

The above command lists the routes on router2.

2. Enter the command(s) to delete the desired route(s) from the desired router:

```
midonet> router router2 delete route route2
midonet> router router2 delete route route3
```

The above commands delete route2 and route3 from router2.

3. Enter the command to list the routes on the router to confirm the deletions:

```
midonet> router router2 list route
route route0 type normal src 0.0.0.0/0 dst 10.100.1.1 port router2:port0
weight 0
route route1 type normal src 0.0.0.0/0 dst 10.100.1.2 port router2:port1
weight 0
```



- AFT - DRAFT - DRAFT - DRAFT - DRAFT - DRAFT - DRAFT - DRAFT -

AFT - DRAFT - DRAFT - DRAFT - DRAFT - DRAFT - DRAFT -

AFT - DRAFT - DRAFT - DRAFT - DRAFT - DRAFT - DRAFT - DRAFT -

AFT - DRAFT - DRAFT - DRAFT - DRAFT - DRAFT - DRAFT - DRAFT -

AFT - DRAFT - DRAFT - DRAFT - DRAFT - DRAFT - DRAFT - DRAFT -

- AFT - DRAFT - DRAFT - DRAFT - DRAFT - DRAFT - DRAFT - DRAFT -

AFT - DRAFT - DRAFT - DRAFT - DRAFT - DRAFT - DRAFT - DRAFT -

- AFT - DRAFT - DRAFT - DRAFT - DRAFT - DRAFT - DRAFT - DRAFT -









| Attributes | Description                                                                                  |
|------------|----------------------------------------------------------------------------------------------|
|            | also contain a second address to form an address range and L4 port number or range of ports. |

**Table 7.2. CLI Rule Chain Attributes That Match Packets**

| Attributes That Match Packets               | Description                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   |
|---------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| hw-src [!]<MAC_ADDRESS>:                    | The source hardware address                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   |
| hw-dst [!]<MAC_ADDRESS>:                    | The destination hardware address                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              |
| ethertype [!]<STRING>:                      | Sets the data link layer (EtherType) of packets matched by this rule.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         |
| in-ports [!]<PORT[,PORT...]>:               | Matches the virtual port through which the packet ingress the virtual device that is currently processing the packet.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         |
| out-ports [!]<PORT[,PORT...]>:              | Matches the port through which the packet egresses the virtual device that is currently processing the packet.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                |
| tos [!]<INTEGER>:                           | The value of the packet's Type of Service (TOS) field to match. Use this field to match the differentiated services value. See <a href="#">TOS</a> for information.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                           |
| proto [!]<INTEGER>:                         | The IP protocol number to match. See <a href="#">Protocol Numbers</a> for information. Examples: ICMP = 1, IGMP = 2, TCP = 6, UDP = 17                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        |
| src [!]<CIDR>:                              | The source IP address or CIDR block                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                           |
| dst [!]<CIDR>:                              | The destination IP address or CIDR block                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      |
| src-port [!]<INTEGER[-INTEGER]>:            | The TCP or UDP source port or port range                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      |
| dst-port [!]<INTEGER[-INTEGER]>:            | The TCP or UDP destination port or port range                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 |
| flow <fwd-flow return-flow>:                | Matches the connection-tracking status of the packet. If the packet is starting a new connection, fwd-flow will match. Alternatively, if the packet belongs to a connection already known to MidoNet, return-flow will match.                                                                                                                                                                                                                                                                                                                                                                                                                                                 |
| port-group [!]<PORT_GROUP>:                 | Matches a port group. Port groups allow the grouping of virtual ports to ease the creation of chain rules. See the CLI commands help for information.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         |
| ip-address-group-src [!]<IP_ADDRESS_GROUP>: | Matches a source IP address group. IP address groups allow the grouping of IP addresses to ease the creation of chain rules. See the CLI commands help for information.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       |
| ip-address-group-dst [!]<IP_ADDRESS_GROUP>: | Matches a destination IP address group. IP address groups allow the grouping of IP addresses to ease the creation of chain rules. See the CLI commands help for information.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  |
| hw-src-mask                                 | <p><b>Source MAC address mask</b> - A 48-bit bitmask in the form xxxx.xxxx.xxxx, where x is any hexadecimal digit. Specifies which bits are to be considered when applying the rule's hw-src test.</p> <p>Default value = ffff.ffff.ffff: All bits are considered when applying the hw-src test, so a packet's source MAC address must match hw-src exactly.</p> <p>ffff.0000.0000: Only the first sixteen bits are considered when applying the hw-src test, the first sixteen bits of a packet's source MAC address must match the first sixteen bits of hw-src.</p> <p>0000.0000.0000: No bits are considered when applying the hw-src test, so any packet will match.</p> |
| hw-dst-mask                                 | <p><b>Destination MAC address mask</b> - A 48-bit bitmask in the form xxxx.xxxx.xxxx, where x is any hexadecimal digit. Specifies which bits are to be considered when applying the rule's hw-dst test.</p> <p>Default value = ffff.ffff.ffff: All bits are considered when applying the hw-dst test, so a packet's destination MAC address must match hw-dst exactly.</p>                                                                                                                                                                                                                                                                                                    |

| Attributes That Match Packets                           | Description                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                           |
|---------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
|                                                         | ffff.0000.0000: Only the first sixteen bits are considered when applying the hw-dst test, the first sixteen bits of a packet's destination MAC address must match the first sixteen bits of hw-dst.<br><br>0000.0000.0000: No bits are considered when applying the hw-dst test, so any packet will match.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            |
| fragment-policy header   nonheader   any   unfragmented | <b>fragment-policy</b> - Specifies the fragment type to match.<br><br>ANY: Matches any packet.<br><br>HEADER: Matches any packet that has a full header, that is, a header fragment or unfragmented packet.<br><br>NONHEADER: Matches only nonheader fragments.<br><br>UNFRAGMENTED: Matches only unfragmented packets.<br><br>In general, ANY is the default policy. However, if a rule has a value for the src or dst field, the NONHEADER and ANY policies are disallowed and the default is HEADER. Furthermore, if the rule's type is dnat or snat and its target is not a single IP address with no ports specified, then the policy will default to UNFRAGMENTED, which is the only policy permitted for such rules.<br><br>Unlike other rule properties, fragment-policy may not be inverted. |

## Example condition 1

Only packets whose network source is in 10.0.0.0/16 are allowed through to network 10.0.5.0/24. You can accomplish this a few different ways.

One way is to construct a DROP or REJECT rule that has a Condition and an ACCEPT rule with these attributes specify:

1. DROP when (ethertype equal 2048) AND (src NOT equal (10.0.0.0, 16))
2. ACCEPT when (dst equal (10.0.5.0, 24))
3. DROP



### Note

The unconditional drop is needed to make rule 2 meaningful.

To create a rule chain with the above attributes:

1. If necessary, use the sett command or some other means to access the desired tenant.

```
midonet> sett 10a83af63f9342118433c3a43a329528
tenant_id: 10a83af63f9342118433c3a43a329528
```

2. Enter the command to create a new rule chain and assign it a name:

```
midonet> chain create name "drop_not_src_mynetwork_INBOUND"
chain5
```

3. Enter the command to drop IPv4 traffic that does not have the source 10.0.0.0/16:

```
midonet> chain chain5 add rule ethertype 2048 src !10.0.0.0/16 type drop
chain5:rule0
```

4. Enter the command to accept IPv4 traffic with the destination 10.0.5.0/24:

```
midonet> chain chain5 add rule ethertype 2048 dst 10.0.5.0/24 pos 2 type
accept
chain5:rule2
```

5. Enter the command to list the rules added to the new rule chain:

```
midonet> chain chain5 list rule
rule rule3 ethertype 2048 src !10.0.0.0/16 proto 0 tos 0 pos 1 type drop
rule rule2 ethertype 2048 dst 10.0.5.0/24 proto 0 tos 0 pos 2 type
accept
```

## Example condition 2

Same as Example Condition 1, except here assume that you're structuring your rules differently. You want to have one DROP rule at the end of the chain that matches all packets; earlier in the chain you place ACCEPT rules that match packets/flows that are specifically allowed through.

The ACCEPT rule for the traffic allowed by Example Condition 1 would have a Condition with these attributes:

In the rule language, the chain would have:

ACCEPT when src=(10.0.0.0, 16) OR dst=(10.0.5.0, 24)

Rule at the end:

DROP all other packets

To create a rule chain with the above attributes:

1. If necessary, use the sett command or some other means to access the desired tenant.

```
midonet> sett 10a83af63f9342118433c3a43a329528
tenant_id: 10a83af63f9342118433c3a43a329528
```

2. Enter the command to create a new rule chain and assign it a name:

```
midonet> chain create name "accept_src_dst_mynetwork_INBOUND"
chain11
```

3. Enter the command to accept IPv4 traffic from the source 10.0.0.0/16:

```
midonet> chain chain11 add rule ethertype 2048 src 10.0.0.0/16 type
accept
chain11:rule0
```

4. Enter the command to accept IPv4 traffic with the destination 10.0.5.0/24:

```
midonet> chain chain11 add rule ethertype 2048 dst 10.0.5.0/24 type
accept
chain11:rule1
```

5. Enter the command to drop all IPv4 traffic (that didn't match the attributes in the preceding rules):

```
midonet> chain chain11 add rule ethertype 2048 pos 3 type drop
chain11:rule2
```

6. Enter the command to list the rules added to the new rule chain:





### Note

Ports with infiltrer (pre-routing) and outfilter (post-routing) chains are connected to VMs. port1 is connected to a VM.

## Listing the Rules for the Inbound Chain on a Port

To list the pre-routing rule chain for port 1:

1. Enter the command:

```
midonet> chain chain2 list rule
rule rule0 ethertype 2048 src !172.16.3.3 proto 0 tos 0 pos 1 type drop
rule rule1 hw-src !fa:16:3e:fb:19:07 proto 0 tos 0 pos 2 type drop
rule rule2 proto 0 tos 0 flow return-flow pos 3 type accept
rule rule3 proto 0 tos 0 pos 4 type jump jump-to chain4
rule rule4 ethertype !2054 proto 0 tos 0 pos 5 type drop
```

The pre-routing rule chain contains the following instructions:

- rule0 says: for packets that match the ethertype 2048 (IPv4) that do not match the source IP address 172.16.3.3 (the private IP address of the VM), drop these packets. This prevents the port's VM from sending packets with a forged IP address.
- rule1 says: for packets with a hardware source that does not match the listed source MAC address (the VM's MAC address), drop these packets. This prevents the VM from sending packets with a forged MAC address.
- rule2 says: for packets that match a return flow (that is, a packet that belongs to a connection already known to MidoNet), accept these packets.
- rule3 says: for packets that were not dropped or accepted as a result of matching previous rules, allow these packets to jump to the indicated chain (chain4).
- rule4 says: for packets that do not match the ethertype 2054 (ARP packets), drop these packets.

## Listing the OpenStack Security Group Rule Chain

You can list all the rule chains and then look at the rule chain for the OpenStack security group.

To list all the rule chains and examine specific rule chains:

1. Enter the command:

```
midonet> list chain
chain chain5 name OS_SG_050593ed-56ad-44ef-8489-4052d02d99ff_INGRESS
chain chain0 name OS_PRE_ROUTING_5a151b0b-dea7-4918-bd17-876c1f7f5c64
chain chain1 name OS_POST_ROUTING_5a151b0b-dea7-4918-bd17-876c1f7f5c64
chain chain6 name OS_SG_01fcelb8-c277-4a37-a8cc-86732eea186d_INGRESS
chain chain4 name OS_SG_050593ed-56ad-44ef-8489-4052d02d99ff_EGRESS
chain chain7 name OS_SG_01fcelb8-c277-4a37-a8cc-86732eea186d_EGRESS
chain chain2 name OS_PORT_6f72342b-4947-432f-8d01-0cf4e4b8d049_INBOUND
chain chain3 name OS_PORT_6f72342b-4947-432f-8d01-0cf4e4b8d049_OUTBOUND
```

Note chain5, identified as a chain for an OpenStack security group (OS\_SG) for INGRESS traffic.

To look at rule chain5:

## 2. Enter the command:

```
midonet> chain chain5 list rule
rule rule0 ethertype 2048 src 0.0.0.0/0 proto 6 tos 0 dst-port 5900 pos
1 type accept
rule rule1 ethertype 2048 src 0.0.0.0/0 proto 1 tos 0 pos 2 type accept
rule rule2 ethertype 2048 src 0.0.0.0/0 proto 6 tos 0 dst-port 22 pos 3
type accept
rule rule3 ethertype 2048 src 0.0.0.0/0 proto 6 tos 0 dst-port 80 pos 4
type accept
```

The above output shows the rule chain used to implement the security group you configured in OpenStack. These rules contain the following instructions:

- All the rules match ethertype 2048 (IPv4) packets.
- All the rules match traffic from any source network (0.0.0.0/0).
- All the rules, except rule1, match packets of IP protocol 6 (TCP) and accept them. rule1 matches packets of the ICMP type and accepts them.
- In addition to the other matches already mentioned, the rules match and accept the packets according to the security group rules you defined in OpenStack, specifically, packets with the destinations:
  - TCP port 5900 (VNC)
  - TCP port 22 (SSH)
  - TCP port 80 (HTTP)

## Listing the bridges for the tenant

Rule chains relating to OpenStack security groups are implemented on the network (bridge) ports.

To list the bridge(s) on the tenant and show the demo-private-net network (bridge) enter the command:

```
midonet> list bridgebridge bridge0 name demo-private-net state up
```

## Listing the ports on the bridge

To list information about the rule chains configured on the bridge ports, enter the command:

```
midonet> bridge bridge0 list port
port port0 device bridge0 state up
port port1 device bridge0 state up infilter chain2 outfilter chain3
port port2 device bridge0 state up peer router1:port1
```



### Note

ports with infilter (pre-routing) and outfilter (post-routing) chains are connected to VMs. port1 is connected to a VM.

## Listing the rules for the pre-routing rule chain

To list the pre-routing rule chain for port 1 enter the command:



- All the rules, except rule1, match packets of IP protocol 6 (TCP) and accept them. rule1 matches packets of the ICMP type and accepts them.
- In addition to the other matches already mentioned, the rules match and accept the packets according to the security group rules you defined in OpenStack, specifically, packets with the destinations:
  - TCP port 5900 (VNC)
  - TCP port 22 (SSH)
  - TCP port 80 (HTTP)



## 8. Network Address Translation

### Table of Contents

|                                            |    |
|--------------------------------------------|----|
| Static NAT .....                           | 42 |
| Viewing NAT rule chain information .....   | 42 |
| Configuring SNAT, DNAT, and REV_DNAT ..... | 44 |
| DNAT/REV_DNAT example .....                | 44 |
| SNAT example .....                         | 45 |

To demonstrate how MidoNet uses static NAT, this chapter shows how MidoNet implements floating IP addresses by examining a floating IP address configuration.

### Static NAT

This section demonstrates how MidoNet uses static NAT to implement floating IP addresses.

MidoNet implements floating IP addresses in a two-stage process:

1. Bring traffic to a floating IP address (that is, bring traffic from an external network to a tenant router).
2. Perform network address translation from the external network's public IP address to a private IP address and in the reverse direction.

### Assumptions

To view this example, this section assumes you have configured:

- A project
- An Edge Router
- An external network
- A tenant router
- A private network (bridge)
- At least one VM connected to the bridge
- A floating IP address assigned to at least one VM.

### Viewing NAT rule chain information

You can use the MidoNet CLI to list the routers for a tenant and list rule chains configured on the router.

The example below explains how MidoNet uses rule chains to implement source and destination NAT and shows how to use the MidoNet CLI to:

- Display information about the infilter (pre-routing) and outfilter (post-routing) chains configured on a tenant router.
- List the rules for the rule chains.

## Assumptions

For the example below, assume the following network conditions exist:

- A tenant router named "tenant-router"
- A private network with a 172.16.3.0/24 network address
- A public network with a 198.51.100.0/24 network address
- A VM with a 172.16.3.3 private IP address and a 198.51.100.3 public (floating) IP address

## Viewing a Pre-Routing rule

To list routers on the current tenant and the router rule-chain information on the router(s), enter the command:

```
midonet> list router
router router0 name tenant-router state up infilter chain0 outfilter chain1
```

As shown in the above output, chain0 is the router's pre-routing (infilter) rule chain and chain1 is the post-routing (outfilter) rule chain.

To list information about the router's pre-routing rule chain, enter the command:

```
midonet> chain chain0 list rule
rule rule0 dst 198.51.100.3 proto 0 tos 0 in-ports router0:port0 pos 1 type
  dn timer action accept target 172.16.3.3
rule rule1 dst 198.51.100.2 proto 0 tos 0 in-ports router0:port0 pos 2 type
  rev_sn timer action accept
```

rule0 of the pre-routing rule chain on the tenant router contains the following instructions:

- For packets with the destination of 198.51.100.3 (the floating IP address associated with the VM):
  - Perform a destination NAT (DNAT) translation to change the destination IP address from the VM's floating IP address (198.51.100.3) to the VM's private IP address (172.16.3.3).

## Viewing a Post-Routing rule

To list the post-routing rule on the tenant router, enter the command:

```
midonet> chain chain1 list rule
rule rule0 src 172.16.3.3 proto 0 tos 0 out-ports router1:port0 pos 1 type
  snat action accept target 198.51.100.3
rule rule1 proto 0 tos 0 out-ports router1:port0 pos 2 type snat action
  accept target 198.51.100.2:1--1
```

rule0 of the post-routing rule on tenant-router contains the following instructions:



- You want to translate traffic with the VM's public IP address to the VM's private IP address.
- You want to perform a reverse destination address translation.

To create the rule chain for the above DNAT configuration:

1. Create a new rule chain:

```
midonet> chain create name "dnat-test"
chain10
```

2. Create a rule that accepts traffic on a router port with the destination 198.51.100.4 and translates the destination to 10.100.1.150:

```
midonet> chain chain10 add rule dst 198.51.100.4 in-ports router1:port0
pos 1 type dnat action accept target 10.100.1.150
chain10:rule2
```

3. Create a rule that accepts traffic with the destination of the router's gateway to the public network and performs a reverse address translation from the public network address to the private network address.

```
midonet> chain chain10 add rule dst 198.51.100.2 in-ports router0:port0
pos 2 type rev_snat action accept
chain10:rule3
```

4. List the rules to check them:

```
midonet> chain chain10 list rule
rule rule2 dst 198.51.100.4 proto 0 tos 0 in-ports router1:port0 pos 1
type dnat action accept target 10.100.1.150
rule rule3 dst 198.51.100.2 proto 0 tos 0 in-ports router0:port0 pos 2
type rev_snat action accept
```

## SNAT example

This example shows how to use MidoNet CLI commands to configure SNAT on a router port.

For example, you might want to configure SNAT for a network device (like a VM) with a private IP address and a public floating IP address that sends data to a destination outside its local network.

Below are the assumptions regarding the rule chain for this example:

- You have two subnets: a public subnet (198.51.100.0/24) and a private subnet (10.0.0.0/24).
- You have a virtual machine connected to the tenant router with a public IP address of 198.51.100.4 and a private IP address of 10.100.1.150.
- You want to translate traffic with the VM's private IP address to the VM's public IP address.

To create the rule chain for the above SNAT configuration:

1. Create a new rule chain:

```
midonet> chain create name "snat-test"
chain7
```

2. Create a rule that accepts traffic on a router port with the source 10.100.1.150 and translates the destination to 198.51.100.4:

```
midonet> chain chain7 add rule src 10.100.1.150 out-ports router1:port0  
pos 1 type snat action accept target 198.51.100.4  
chain7:rule2
```

3. Create a rule that accepts traffic from the private network and performs SNAT to translate the source IP address to the IP address of the router's gateway to the public network.

```
midonet> chain chain7 add rule out-ports router1:port0 pos 2 type snat  
action accept target 198.51.100.2
```





```
midonet> router router1 set load-balancer lb0
```

The load balancer assigned to the router will act on traffic flowing through that router.

2. Create a pool to which target back-end servers will be assigned.

```
midonet> load-balancer lb0 create pool lb-method ROUND_ROBIN
lb0:pool0
midonet> load-balancer lb0 pool pool0 show
pool pool0 load-balancer lb0 lb-method ROUND_ROBIN state up
```

3. Next, add target back-end servers to the pool you just created.

```
midonet> load-balancer lb0 pool pool0 create member address 192.168.100.
100 protocol-port 80
lb0:pool0:pm0
midonet> load-balancer lb0 pool pool0 create member address 192.168.100.
101 protocol-port 80
lb0:pool0:pm1
midonet> load-balancer lb0 pool pool0 member pm0 show
pm pm0 address 192.168.100.1 protocol-port 80 weight 0 state up
```

For each back-end server you must add its IP address and port to the pool.

4. Create a virtual IP address (VIP) and port, then assign it to the pool against which load balancing will be performed (lb0:pool0). Typically, a VIP is an IP address from the public IP space.

```
midonet> load-balancer lb0 pool pool0 list vip
midonet> load-balancer lb0 pool pool0 create vip address 203.0.113.2
persistence SOURCE_IP protocol-port 8080
lb0:pool0:vip0
midonet> load-balancer lb0 pool pool0 vip vip0 show
vip vip0 load-balancer lb0 address 203.0.113.2 protocol-port 8080
persistence SOURCE_IP state up
```



### Note

Above example uses sticky source IP address persistence, read more about it in [the section called "Sticky Source IP" \[50\]](#).

5. Lastly, you must add a routing rule on the Edge Router (router0) so that a packet sent to the VIP is able to find its way to the Tenant Router where the LB is defined.
  - a. First, identify the ports on the Edge Router, using the `router router0 list port` command, like so:

```
midonet> router router0 list port
port port0 device router0 state up mac 02:c2:0f:b0:f2:68 address 100.
100.100.1 net 100.100.100.0/30
port port1 device router0 state up mac 02:cb:3d:85:89:2a address 172.
168.0.1 net 172.168.0.0/16
port port2 device router0 state up mac 02:46:87:89:49:41 address 200.
200.200.1 net 200.200.200.0/24 peer bridge0:port0
port port3 device router0 state up mac 02:6b:9f:0d:c4:a8 address 169.
254.255.1 net 169.254.255.0/30 peer router1:port0
...
```

Identify the port on the Edge Router that is used to route traffic to the Tenant Router (router1). In this example, we see port3 on device router0 is peered to the Tenant Router port (router1:port0).





## Health monitor

Health monitoring is the act of checking a set of pool members for "aliveness". This usually means HTTP, TCP, UDP, or ICMP connectivity is possible to the node.

In MidoNet's case, only TCP connectivity is checked. Health monitors work by sending packets to the pool members and checking whether or not they receive a reply. The node is considered ACTIVE if the pool member responds to the packet within a certain amount of time, and after a certain amount of retries. Therefore, health monitors act on the following three variables:

- **max\_retries:** How many times the health monitor sends a packet to the pool member without receiving a response before the health monitor considers the node to be INACTIVE
- **delay:** Amount of time between each transmission of a packet from the health monitor to the pool member
- **timeout:** Additional timeout after a connection has been established

The health monitor keeps track of the current state of all pool members it is assigned to. Load balancing decisions can then be made based on the "aliveness" of a pool member.

## HAProxy configuration

When using a Layer 4 load balancer, you can configure a health monitor to perform checks on the back-end servers.

Only a single host runs all health monitor instances at a given time. If that host goes down for any reason, a different host will be elected and spawn the HAProxy instances. These instances are managed by the MidoNet Agent and do not require any special set-up. However, hosts that can potentially hold the HAProxy instances have to be chosen.

To enable a MidoNet Agent host for health monitoring, its `health_monitor_enable` property has to be set to `true`.

Run the following command to check if a host is enabled for health monitoring:

```
$ mn-conf get agent.haproxy_health_monitor.health_monitor_enable
```

To toggle health monitoring for a certain host, use the following commands on that host:

```
$ echo "agent.haproxy_health_monitor.health_monitor_enable : true" | mn-conf set -h local
```

```
$ echo "agent.haproxy_health_monitor.health_monitor_enable : false" | mn-conf set -h local
```

Additionally, the hosts running the HAProxy instances must have a group called "nogroup" and a user called "nobody", otherwise HAProxy will not be able to start. While this is a default configuration on Ubuntu, on Red Hat you must create this user and group.

### How the Health Monitor works in the MidoNet Agent

- The MidoNet Agent does not implement its own health monitor. Instead, it leverages the health checker that is a part of HAProxy.



```
midonet> health-monitor hm0 pool list
pool pool0 load-balancer lb0 health-monitor hm0 lb-method ROUND_ROBIN state
up
```

## Disabling Health Monitoring

To disable health monitoring on a pool you can do perform one of the following:

- Set the `admin_state_up` on the health monitor to false. Note that all pools that are using this health monitor will have health monitoring disabled.
- Set the `health_monitor_id` on the pool to null.
- Delete the health monitor object.





A single L4 flow may generate up to two different flows: one to handle non-header fragments, another to handle all other packets.

## Fragmented packets rule chain creation example

Create a chain (this creates a rule chain with an alias, "chain0" in the example, pointing to the chain created):

```
create chain name chain0
```

Add a rule to the chain that drops header fragments:

```
chain chain0 add rule fragment-policy header pos 2 header type drop
```

### Example 1 Firewall, Does Not Account for Fragmented Packets

The example below only handles non-fragmented packets. These are the firewall rules you start with before you decide to handle fragmented packets.

Initially, you design your firewall to:

- Only allow incoming TCP port 80 (HTTP) traffic
- Drop all other packets

Without addressing fragmented packets, you create a rule chain with the following two rules:

- Rule at position 1
  - By default, this rule matches only non-fragmented packets and header fragments.
  - ACCEPTs packets with protocol=TCP and destination=80.

```
midonet> chain chain0 add rule ethertype 2048 src 0.0.0.0/0 proto 6 in-ports router2:port0 dst-port 80 pos 1 type accept
```

- Rule at position 2
  - DROPS all packets.

```
midonet> chain chain0 add rule ethertype 2048 src 0.0.0.0/0 dst 0.0.0.0/0 in-ports router2:port0 pos 2 type drop
```

```
midonet> chain chain0 list rule
rule rule0 ethertype 2048 src 0.0.0.0/0 proto 6 tos 0 dst-port 80 in-ports router2:port0 pos 1 type accept
rule rule1 ethertype 2048 src 0.0.0.0/0 dst 0.0.0.0/0 proto 0 tos 0 in-ports router2:port0 pos 2 type drop
```


With the above rule chain, MidoNet handles fragmented packet with the destination TCP port 80 as follows:

- The first half of the packet, which contains the TCP header, reaches the rule at position 1, and is accepted.

- However, the second half of the fragmented, which does not have the destination port, reaches the rule at position 1, does not match the rule's condition, and is dropped. This means the fragmented packets do not reach the Web server.

### Example 2 Firewall, Addresses Fragmented Packets


To address this problem, MidoNet provides a mechanism to handle the fragmented packets. This mechanism allows the fragmented packets to reach their destination, as shown in the following example. The drawing below simply depicts a whole, non-fragmented packet and a fragmented packet that consists of two parts, a header and non-header.



## Non-Fragmented and Fragmented Packets

For this example, consider the following packets:

- Non-fragmented packet with the destination, TCP port 80
- Fragmented packet with the destination, TCP port 80
- Non-fragmented packet with the destination, TCP port 72
- Fragmented packet with the destination, TCP port 72





Given the above packets and the rule in example 1, MidoNet processes the packets as follows:

- 58

Looking at packets 1 and 2:



## Configuration

You can specify resource protection configuration parameters using `mn-conf(1)`, in the `agent.datapath` section. The available parameters are:

- `global_incoming_burst_capacity` - this sets the size of the top-level bucket and also defines the total number of tokens in the system (corresponding to in-flight packets) that will be divided among the different levels in the HTB; the rate at which tokens are placed back in the bucket is a function of the rate at which they are processed.
- `tunnel_incoming_burst_capacity` - this sets the capacity of the bucket associated with tunnel traffic, enforcing the rate at which a MidoNet Agent can communicate with the other Agents.
- `vm_incoming_burst_capacity` - this sets the capacity of each VM leaf bucket, which is below the shared VM bucket. This parameter enforces the rate at which individual VMs can send traffic.
- `vtep_incoming_burst_capacity` - this sets the capacity of the bucket associated with the VxLAN VTEP functionality, which enforces the rate at which the MidoNet Agent can communicate with the VxLAN domain.

See the `mn-conf(1)` schemas for more information about the above parameters.

Recommended values for these properties depend on the role of the MidoNet host (Gateway vs. Compute Node) and interaction with other resource-related properties, like JVM-memory and flow-table size. Midolman RPM and Debian packages include versions of each configuration tuned for Compute/Gateway hosts respectively. You can find these configurations in `/etc/midolman`, alongside the default configuration files. See "Recommended Values" for a table of recommended values.

## Disabling Resource Protection

You can disable the resource protection feature.

To disable resource protection:

1. Specify a size value of "0" for all the parameters described in the Configuration section, except for the `global_incoming_burst_capacity` parameter.

This will cause all tokens to accumulate in the global bucket and all the traffic will be distributed from this single bucket.

## 13. MidoNet monitoring

### Table of Contents

|                                         |    |
|-----------------------------------------|----|
| Metering .....                          | 62 |
| Monitoring with Munin .....             | 64 |
| Monitoring with Zabbix .....            | 65 |
| Monitoring Network State Database ..... | 65 |
| Monitoring Midolman Agents .....        | 69 |
| Monitoring events .....                 | 71 |
| Packet Tracing .....                    | 80 |
| Port mirroring .....                    | 81 |

MidoNet is composed of various services; each service exposes a variety of metrics that can be fetched from typical monitoring services, such as Zabbix™, Munin, and so on.

This chapter describes the main available metrics for each service, as well as a procedure to configure a basic monitoring infrastructure based on Munin, based on scripts provided with the MidoNet deployment package.

### Metering

**Note:** This feature is in **experimental** status.

#### Overview

The goal of metering is to provide packets and bytes traffic counters for arbitrary slices of the traffic that travels through MidoNet.

A meter is a counter of bytes and packets, associated with a name. In order to be incremented, the meter needs to have flows associated with it. MidoNet agents will automatically associate flows with certain meters, and users can create their own custom meters setting the `meterName` attribute in chain rules.

For example, all traffic going through bridge with uuid `FOO` in MidoNet be counted under meter `meters:device:FOO`. All traffic egressing port `BAR` will also be reflected in meter `meters:port:tx:BAR`.

MidoNet agents offer these counters for their partial view of overlay traffic. In other words, each agent will provide meters that only account for the traffic that agent has simulated. For a given meter, the MidoNet-wide real value is the sum of the value of this meter across all agents.

**Note:** Metering data is meant to be polled and stored by a monitoring layer onto a time series database. Thus agents don't persist the metering data they gather, and meter values will reset to zero when an agent reboots. **Any metering data collection layer should account for this effect and detect counter resets.**

#### Querying meters

Agents publish meters over JMX and a command line tool, `mm-meter`, uses their JMX interface to list, fetch and monitor meter values.

For example code on the JMX interface, the best source is [the code of mm-meter itself](#).

Querying meters with `mm-meter` is very simple:

```
$ mm-meter --help
-h, --host <arg>      Host (default = localhost)
-p, --port <arg>      JMX port (default = 7200)
--help                Show help message

Subcommand: list - list all active meters
--help                Show help message
Subcommand: get
-n, --meter-name <arg> name of the meter
--help                Show help message

trailing arguments:
delay (not required)  delay between updates, in seconds. If no delay is
                      specified, only one report is printed. (default = 0)
count (not required) number of updates, defaults to infinity
                      (default = 2147483647)
```

The `list` command will print a list of all meters known to this agent:

```
$ mm-meter list
meters:user:port0-on-the-bridge
meters:port:rx:cf453c9d-94c4-4c27-ba32-529b7cbacf1d
meters:device:845a54bf-b702-4dc2-8958-bbe7156bc4ef
meters:port:tx:cf453c9d-94c4-4c27-ba32-529b7cbacf1d
meters:port:tx:9182485b-8f86-462d-a8be-62586060eeb9
meters:device:f0dlf093-2de7-49a1-a5ec-898f94769e34
meters:device:9182485b-8f86-462d-a8be-62586060eeb9
meters:port:rx:9182485b-8f86-462d-a8be-62586060eeb9
meters:device:cf453c9d-94c4-4c27-ba32-529b7cbacf1d
```

And the `get` command will print the *current*, *local* counters for a meter. It takes a delay, in which case it will poll the meter and print deltas periodically:

```
$ mm-meter get -n meters:port:rx:cf453c9d-94c4-4c27-ba32-529b7cbacf1d 10
  packets      bytes
    568935    4215888475
         0         0
         0         0
        23        5834
         0         0
```

## Creating a custom meter

Operators may want to meter a custom slice of their virtual network traffic. This is possible by matching on that slice using one or several chain rules in the virtual topology. The `meterName` property in chain rules will assign matching flows to the meter referred to by its value, in addition to the meters that flow would naturally feed.

Besides using the REST API, operators can use `midonet-cli` to set up such rules. The following rule will assign to meter `my-meter` all traffic that hits the rule after having traversed device `9182485b-8f86-462d-a8be-62586060eeb9`:

```
midonet> chain chain0 list rule
rule rule0 proto 0 tos 0 traversed-device 9182485b-8f86-462d-
a8be-62586060eeb9 fragment-policy any pos 1 type accept meter my-meter
```

Note that, when inspecting meters `my-meter` will turn into `meters:user:my-meter`, to avoid naming conflicts with built-in meters.

## Monitoring with Munin

Munin is composed of a master node with a cron-based process that regularly fetches values from slave nodes.

Slave nodes run `munin-node` to extract metrics from a variety of sources (Java Management Extensions (JMX) included) and expose them for the master. The data is fed to RRDTool databases and used to generate graphs.

Adding monitoring for a given service involves configuring `munin-node` in each host where an instance of the service runs, and then configuring Munin on the master node to fetch data from this node.

The MidoNet deployment repository contains automated scripts to configure all supported monitoring at `monitoring/munin/`.

This information in this guide and automated configuration scripts are based on munin 1.4.6-3ubuntu3.3. For more information, see <http://munin-monitoring.org/>.

## Configuring Munin

Follow the instructions from the Munin documentation; this information is pretty straight forward and contains basic configuration files that work out of the box.

### Master node

Install the **munin** and **munin-plugin-ins-extra** packages. Also, install `jmx2munin` from its GitHub repository (<https://github.com/tcurdt/jmx2munin>).

To add two new slaves to your master's configuration, just append these sample configs to `/etc/munin/munin.conf`:

```
[MidoStorage;node1]address 10.0.0.1 use_node_name yes
```

```
[MidoStorage;node2]address 10.0.0.2 use_node_name yes
```



### Note

The addresses above are only samples, they should be the IP addresses of the node.

This causes the Munin master to start to fetch data files from the given slaves. The "MidoStorage" name appears in the Munin interface as a group containing both of the nodes. Later sections in this guide explain how to add service-specific graphs.

### Slave Nodes

Install the **munin-node** and **munin-plugin-extra** packages. Also, install `jmx2munin` from its GitHub repository. You can reuse `/etc/munin/munin-node.conf.sample` and simply update the master's IP address.

### Plugins

Munin provides several default plugins that show metrics for disk, memory, CPU, and so on. You may not want to use these now. You can easily remove them by deleting the symlinks at `/etc/munin/plugins` in each of the slaves.

### MidoNet plugins

Fetching metrics for the MidoNet subsystems simply requires adding new plugins on the relevant slaves. There is an automated script that will do most of the work. Assuming you cloned the MidoNet deployment repository at the current directory, you just need to run the following commands on each of the slaves:

```
sudo ./install_plugins.sh
sudo service munin-node restart
```

On RedHat Enterprise Linux 7, you should use:

```
sudo systemctl restart munin-node
```

This installs all available plugins, and updates Munin configurations.

You shouldn't have to take any action on the master. When the Munin fetch process runs, it should start fetching the data. If you are impatient, you can execute the following command on the master to trigger the Munin cron job that pulls data from the slaves:

```
sudo -u munin munin-cron
```

## Monitoring with Zabbix

This section describes how to integrate Zabbix with MidoNet for monitoring events.

Zabbix is a popular monitoring tool that provides a way for system administrators to monitor their networks. See <https://www.zabbix.com/> and navigate to Documentation for details about Zabbix usage.

### Basic Steps for Using Zabbix

In Zabbix, you can monitor log files stored on the filesystem. You need to run the Zabbix agent for each node, and set up a log monitoring configuration with the file location, update interval, etc.

- Run Zabbix on each Gateway and Compute host.
- Configure log file monitoring; this includes the following tasks:
  - Verify agent parameters.
  - Configure items (an item is a piece of metric data you want to retrieve from a host).
  - Specify the path to the log file to monitor, along with the regular expressions to match.
  - Configure triggers to notify users when specified events occur.

See [https://www.zabbix.com/documentation/2.0/manual/config/items/item-types/log\\_items](https://www.zabbix.com/documentation/2.0/manual/config/items/item-types/log_items) for more details.

## Monitoring Network State Database

The Network State Database is deployed with Cassandra and ZooKeeper instances. Both offer JMX bindings.



The configuration provided with MidoNet uses only a subset of the most relevant for our use cases. Details in the sections below provide additional information about the metrics configured by MidoNet's deployment scripts, as well as an explanation about what to watch.

## Cassandra

By default, Cassandra uses port 7199 for JMX service from all its nodes and you can connect using jconsole for a comprehensive view.

Additionally, Cassandra's own nodetool utility offers commands like cfstats and tpstats that allow access to valuable stats into keyspaces, tables, column families, and so on on a given node.

For a rich reference into Cassandra monitoring, visit the official documentation (go to <http://www.datastax.com/>, and search for "monitoring a Cassandra cluster").

Below are descriptions of the graphs resulting from the example Munin configurations provided in the MidoNet deployment repository. The graphs are built from a subset of the Cassandra JMX service. The available graphs are:

### Cache Reqs vs. Hits

This is self-descriptive, ideally you want the cache hits to be as close to the requests as possible. Note that by default MidoNet Cassandra nodes only enable the Partition Key Cache, but not Row Cache, so it's normal that these stay at 0. For MidoNet the Partition Key Cache should effectively be very similar to the Row Key Cache because our column families (CF) have only one column and therefore rows are not spread across several SSTables.

### Compactions

This indicates the number of bytes being compacted. Typical workloads will present regular small spikes when the minor compaction jobs are run, and infrequent large spikes when major compactions are run. A large number of compactions indicates the need to add capacity to the cluster.

### Internal Tasks

These are internal Cassandra tasks. The most important are:

- Gossip: MidoNet's Cassandra nodes are expected to spend a fair amount of their time busy in Gossip (wherein state information transfers among peers).
- MemTable Post Flusher: memtable flushes that are waiting to be written to the commit log. These should be as low as possible, and definitely not sustained.
- Hinted Handoff tasks: the appearance of these tasks indicates cases where replicas are detected as unavailable, so non-replica nodes need to temporarily store data until the replicas become available. Frequent Hinted Handoff spikes may hint at nodes being partitioned from the cluster.
- Anti-Entropy spikes: indicate data inconsistencies detected and being resolved.
- Stream activity: involves transferring or requesting data from other nodes. Ideally these should be infrequent and short-spaced.

### Messaging Service Tasks



as possible with the lines of all Cassandra nodes overlapping. Otherwise, this indicates divergences in the host's clocks that will almost certainly end up causing problems on conflict resolution. You should attend to this urgently and ensure that all hosts are using the Network Time Protocol (NTP).

The installation script also provides graphs to monitor the state of Cassandra's Java virtual machine (JVM):

- JVM garbage-collection (GC) times
- JVM Heap Summary
- JVM Non-Heap Summary

Descriptions of these graphs are beyond the scope of this guide, but high JVM GC times are the best indication that Cassandra may be consuming too much time on garbage collection. This will correlate with high latency accessing Midolman's column families, which will propagate to Midolman. The Midolman agent will increase simulation latency and also degrade the utilization of CPU resources (experiencing more idle time while waiting for responses from Cassandra).

## ZooKeeper

The `install_plugins.sh` script also installs a set of Munin plugins and configuration files to generate graphs from ZooKeeper's exposed JMX metrics.

However, on each node, you need to indicate the ZooKeeper replica number; the script provides clear guidance on how to do this.

You can find ZooKeeper stats in the "zookeeper" category of the MidoStorage group. ZooKeeper classifies metrics in separate MBeans for leader/follower, so each node will report some values twice, one in the "Follower" role, another in the "Leader" role. Take into account that a given node may change roles (for example, if the leader shuts down, a follower node may be promoted to leader). You can easily spot these events. For example, the line in the "Connection Count as Follower" will suddenly blank out, and another will appear in the "Connection Count as Leader" graph.

Below are descriptions of the graphs resulting from the example Munin configurations provided in the MidoNet deployment repository. The graphs are built from a subset of the ZooKeeper JMX service. The available graphs are:

### Connection Count (as Follower/Leader)

These two graphs display the number of live connections to this node in its role at a given point in time.

### In Memory Data Tree (as Follower/Leader)

Exposes the size of the in-memory znode database, both data nodes and watch count.

### Latency (as Follower/Leader)

Exposes the average and maximum latency experienced in connections.

### Packet Count (as Follower/Leader)

Exposes the count of packets sent/received by the node in its role at a given point in time.

### Quorum Size

Exposes each node's view of the number of nodes agreeing on the leader's election.

ZooKeeper also exposes some information about each specific connection, this may be useful to watch for troubleshooting. Using jconsole (go to <http://www.oracle.com/technetwork/java/index.html> and search on "jconsole" for information), you can:

1. Connect to any ZooKeeper node at port 9199.
2. Navigate to org.apache.ZooKeeperService, ReplicatedServer\_idX.
3. Choose the desired replica.
4. Go into Leader or Follower, Connections to see a list of IP addresses of the connected clients. Information shown here includes:
  - latency
  - packet sent/received count
  - session ID, etc. for that specific client.

Some of the MBeans whose values are exposed in our graphs also contain (computationally intensive) operations that also offer interesting information. Using jconsole, expand org.apache.ZooKeeperService, and then the appropriate replica, and either Leader or Follower, according to its role:

- InMemoryDataTree.approximateDataSize: tells the size of the in-memory data store.
- InMemoryDataTree.countEphemerals: tells the count of ephemeral nodes.

The installation script also provides graphs to monitor the state of ZooKeeper's JVM:

- JVM GC times
- JVM Heap Summary
- JVM Non-Heap Summary

Descriptions of these graphs are beyond the scope of this document, but high JVM GC times are the best indication that ZooKeeper may be the source of problems in Midolman, which will be exhibited in high latency and under-utilization of CPU resources. ZooKeeper uses the Parallel collector, and the JVM GC times track the time of the last collection in all spaces from the java.lang:type=GarbageCollector,name=PS Scavenge MBean, which deals with all generations.

## Monitoring Midolman Agents

MidoNet Agents expose a set of internal metrics that you can use to monitor the performance and health of agent nodes.

The install\_plugins.sh script can configure all the relevant Munin plugins.

Below are descriptions of the graphs resulting from the example Munin configurations provided in the MidoNet deployment repository. The graphs are built from a subset of the Midolman JMX service. The available graphs are:

### Current Pended Packets





The configuration files are located at the following locations, depending on the type of the node.

**Table 13.1. Configuration Files/Locations**

| Type of Node          | Location of the Configuration File                 |
|-----------------------|----------------------------------------------------|
| MidoNet Network Agent | /etc/midolman/logback.xml                          |
| MidoNet API server    | /usr/share/midonet-api/WEB-INF/classes/logback.xml |

Below are the behaviors with the default configuration shipped with the MidoNet release, but you can configure the behaviors as you like. See <http://logback.qos.ch/manual/index.html> for instructions on how to configure the logback.xml file.

## Event log files locations

Event messages are stored locally on the filesystem in a separate file, in addition to the ordinary log file.

**Table 13.2. Event Message Files/Locations**

| Type of Node          | Location                                                                                                  |
|-----------------------|-----------------------------------------------------------------------------------------------------------|
| MidoNet Network Agent | /var/log/midolman/midolman.event.log                                                                      |
| MidoNet API server    | /var/log/tomcat6/midonet-api.event.log (on Red Hat)<br>/var/log/tomcat7/midonet-api.event.log (on Ubuntu) |



### Tip

In addition to midolman.event.log, /var/log/midolman/midolman.log contains additional debug information. You do not normally need to use it, but it may contain useful troubleshooting information.

## Message format

By default, event messages have the following format.

```
<pattern>%d{yyyy.MM.dd HH:mm:ss.SSS} ${HOSTNAME} %-5level %logger - %m%n
%rEx </pattern>
```

See <http://logback.qos.ch/manual/layouts.html> for details about the above placeholders.

## List of event messages

This section lists the event messages.

The event messages are organized in the following major categories:

- Virtual topology events
- API server events
- MidoNet Agent events

### Virtual topology events

This section describes the messages associated with virtual topology events.

## Router

|                   |                                          |
|-------------------|------------------------------------------|
| Logger            | org.midonet.event.topology.Router.CREATE |
| Message           | CREATE routerId={0}, data={1}.           |
| Level             | INFO                                     |
| Explanation       | Router with routerId={0} was created.    |
| Corrective Action | N/A                                      |

|                   |                                              |
|-------------------|----------------------------------------------|
| Logger            | org.midonet.event.topology.Router.UPDATE     |
| Message           | UPDATE routerId={0}, data={1}.               |
| Level             | INFO                                         |
| Explanation       | Router with routerId={0} was updated to {1}. |
| Corrective Action | N/A                                          |

|                   |                                          |
|-------------------|------------------------------------------|
| Logger            | org.midonet.event.topology.Router.DELETE |
| Message           | DELETE routerId={0}.                     |
| Level             | INFO                                     |
| Explanation       | Router with routerId={0} was deleted.    |
| Corrective Action | N/A                                      |

|                   |                                                |
|-------------------|------------------------------------------------|
| Logger            | org.midonet.event.topology.Router.ROUTE_CREATE |
| Message           | ROUTE_CREATE routerId={0}, data={1}.           |
| Level             | INFO                                           |
| Explanation       | Route={1} was created in routerId={0}.         |
| Corrective Action | N/A                                            |

|                   |                                                |
|-------------------|------------------------------------------------|
| Logger            | org.midonet.event.topology.Router.ROUTE_DELETE |
| Message           | ROUTE_DELETE routerId={0}, routeId={1}.        |
| Level             | INFO                                           |
| Explanation       | routeId={1} was deleted in routerId={0}.       |
| Corrective Action | N/A                                            |

## Bridge

|                   |                                          |
|-------------------|------------------------------------------|
| Logger            | org.midonet.event.topology.Bridge.CREATE |
| Message           | CREATE bridgeId={0}, data={1}.           |
| Level             | INFO                                     |
| Explanation       | Bridge with bridgeId={0} was created.    |
| Corrective Action | N/A                                      |

|                   |                                              |
|-------------------|----------------------------------------------|
| Logger            | org.midonet.event.topology.Bridge.UPDATE     |
| Message           | UPDATE bridgeId={0}, data={1}.               |
| Level             | INFO                                         |
| Explanation       | Bridge with bridgeId={0} was updated to {1}. |
| Corrective Action | N/A                                          |

|                   |                                          |
|-------------------|------------------------------------------|
| Logger            | org.midonet.event.topology.Bridge.DELETE |
| Message           | DELETE bridgeId={0}.                     |
| Level             | INFO                                     |
| Explanation       | Bridge with bridgeId={0} was deleted.    |
| Corrective Action | N/A                                      |



## Port

|                   |                                        |
|-------------------|----------------------------------------|
| Logger            | org.midonet.event.topology.Port.CREATE |
| Message           | CREATE portId={0}, data={1}.           |
| Level             | INFO                                   |
| Explanation       | Port with portId={0} was created.      |
| Corrective Action | N/A                                    |

|                   |                                          |
|-------------------|------------------------------------------|
| Logger            | org.midonet.event.topology.Port.UPDATE   |
| Message           | UPDATE portId={0}, data={1}.             |
| Level             | INFO                                     |
| Explanation       | Port with portId={0} was updated to {1}. |
| Corrective Action | N/A                                      |

|                   |                                        |
|-------------------|----------------------------------------|
| Logger            | org.midonet.event.topology.Port.DELETE |
| Message           | DELETE portId={0}.                     |
| Level             | INFO                                   |
| Explanation       | Port with portId={0} was deleted.      |
| Corrective Action | N/A                                    |

|                   |                                      |
|-------------------|--------------------------------------|
| Logger            | org.midonet.event.topology.Port.LINK |
| Message           | LINK portId={0}, data={1}.           |
| Level             | INFO                                 |
| Explanation       | Port with portId={0} was linked.     |
| Corrective Action | N/A                                  |

|                   |                                        |
|-------------------|----------------------------------------|
| Logger            | org.midonet.event.topology.Port.UNLINK |
| Message           | UNLINK portId={0}, data={1}.           |
| Level             | INFO                                   |
| Explanation       | Port with portId={0} was unlinked.     |
| Corrective Action | N/A                                    |

|                   |                                      |
|-------------------|--------------------------------------|
| Logger            | org.midonet.event.topology.Port.BIND |
| Message           | BIND portId={0}, data={1}.           |
| Level             | INFO                                 |
| Explanation       | Port with portId={0} was bound.      |
| Corrective Action | N/A                                  |

|                   |                                        |
|-------------------|----------------------------------------|
| Logger            | org.midonet.event.topology.Port.UNBIND |
| Message           | UNBIND portId={0}.                     |
| Level             | INFO                                   |
| Explanation       | Port with portId={0} was unbound.      |
| Corrective Action | N/A                                    |

## Chain

|                   |                                         |
|-------------------|-----------------------------------------|
| Logger            | org.midonet.event.topology.Chain.CREATE |
| Message           | CREATE chainId={0}, data={1}.           |
| Level             | INFO                                    |
| Explanation       | Chain with chainId={0} was created.     |
| Corrective Action | N/A                                     |

|                   |                                         |
|-------------------|-----------------------------------------|
| Logger            | org.midonet.event.topology.Chain.DELETE |
| Message           | DELETE chainId={0}.                     |
| Level             | INFO                                    |
| Explanation       | Chain with chainId={0} was deleted.     |
| Corrective Action | N/A                                     |

## Rule

|                   |                                        |
|-------------------|----------------------------------------|
| Logger            | org.midonet.event.topology.Rule.CREATE |
| Message           | CREATE ruleId={0}, data={1}.           |
| Level             | INFO                                   |
| Explanation       | Rule with ruleId={0} was created.      |
| Corrective Action | N/A                                    |

|                   |                                        |
|-------------------|----------------------------------------|
| Logger            | org.midonet.event.topology.Rule.DELETE |
| Message           | DELETE ruleId={0}.                     |
| Level             | INFO                                   |
| Explanation       | Rule with ruleId={0} was deleted.      |
| Corrective Action | N/A                                    |

## Tunnel Zone

|                   |                                               |
|-------------------|-----------------------------------------------|
| Logger            | org.midonet.event.topology.TunnelZone.CREATE  |
| Message           | CREATE tunnelZoneId={0}, data={1}.            |
| Level             | INFO                                          |
| Explanation       | TunnelZone with tunnelZoneId={0} was created. |
| Corrective Action | N/A                                           |

|                   |                                                      |
|-------------------|------------------------------------------------------|
| Logger            | org.midonet.event.topology.TunnelZone.UPDATE         |
| Message           | UPDATE tunnelZoneId={0}, data={1}.                   |
| Level             | INFO                                                 |
| Explanation       | TunnelZone with tunnelZoneId={0} was updated to {1}. |
| Corrective Action | N/A                                                  |

|                   |                                               |
|-------------------|-----------------------------------------------|
| Logger            | org.midonet.event.topology.TunnelZone.DELETE  |
| Message           | DELETE tunnelZoneId={0}.                      |
| Level             | INFO                                          |
| Explanation       | TunnelZone with tunnelZoneId={0} was deleted. |
| Corrective Action | N/A                                           |

|                   |                                                       |
|-------------------|-------------------------------------------------------|
| Logger            | org.midonet.event.topology.TunnelZone.MEMBER_CREATE   |
| Message           | MEMBER_CREATE tunnelZoneId={0}, data={1}.             |
| Level             | INFO                                                  |
| Explanation       | TunnelZone member={1} was added to tunnel-ZoneId={0}. |
| Corrective Action | N/A                                                   |

|         |                                                     |
|---------|-----------------------------------------------------|
| Logger  | org.midonet.event.topology.TunnelZone.MEMBER_DELETE |
| Message | MEMBER_DELETE tunnelZoneId={0}, data={1}.           |
| Level   | INFO                                                |

**BGP**

|                   |                                                               |
|-------------------|---------------------------------------------------------------|
| Explanation       | TunnelZone member={ 1 } was deleted from tunnel-ZoneId={ 0 }. |
| Corrective Action | N/A                                                           |

|                   |                                       |
|-------------------|---------------------------------------|
| Logger            | org.midonet.event.topology.Bgp.CREATE |
| Message           | CREATE bgpId={ 0 }, data={ 1 }.       |
| Level             | INFO                                  |
| Explanation       | Bgp with bgpId={ 0 } was created.     |
| Corrective Action | N/A                                   |

|                   |                                            |
|-------------------|--------------------------------------------|
| Logger            | org.midonet.event.topology.Bgp.UPDATE      |
| Message           | UPDATE bgpId={ 0 }, data={ 1 }.            |
| Level             | INFO                                       |
| Explanation       | Bgp with bgpId={ 0 } was updated to { 1 }. |
| Corrective Action | N/A                                        |

|                   |                                       |
|-------------------|---------------------------------------|
| Logger            | org.midonet.event.topology.Bgp.DELETE |
| Message           | DELETE bgpId={ 0 }.                   |
| Level             | INFO                                  |
| Explanation       | Bgp with bgpId={ 0 } was deleted.     |
| Corrective Action | N/A                                   |

|                   |                                             |
|-------------------|---------------------------------------------|
| Logger            | org.midonet.event.topology.Bgp.ROUTE_CREATE |
| Message           | ROUTE_CREATE bgpId={ 0 }, data={ 1 }.       |
| Level             | INFO                                        |
| Explanation       | Route={ 1 } was added to bgpId={ 0 }.       |
| Corrective Action | N/A                                         |

|                   |                                             |
|-------------------|---------------------------------------------|
| Logger            | org.midonet.event.topology.Bgp.ROUTE_DELETE |
| Message           | ROUTE_DELETE bgpId={ 0 }, data={ 1 }.       |
| Level             | INFO                                        |
| Explanation       | Route={ 1 } was deleted from bgpId={ 0 }.   |
| Corrective Action | N/A                                         |

**LoadBalancer**

|                   |                                                     |
|-------------------|-----------------------------------------------------|
| Logger            | org.midonet.event.topology.LoadBalancer.CREATE      |
| Message           | CREATE loadBalancerId={ 0 }, data={ 1 }.            |
| Level             | INFO                                                |
| Explanation       | LoadBalancer with loadBalancerId={ 0 } was created. |
| Corrective Action | N/A                                                 |

|                   |                                                              |
|-------------------|--------------------------------------------------------------|
| Logger            | org.midonet.event.topology.LoadBalancer.UPDATE               |
| Message           | UPDATE loadBalancerId={ 0 }, data={ 1 }.                     |
| Level             | INFO                                                         |
| Explanation       | LoadBalancer with loadBalancerId={ 0 } was updated to { 1 }. |
| Corrective Action | N/A                                                          |

|        |                                                |
|--------|------------------------------------------------|
| Logger | org.midonet.event.topology.LoadBalancer.DELETE |
|--------|------------------------------------------------|

## VIP

|                   |                                                   |
|-------------------|---------------------------------------------------|
| Message           | DELETE loadBalancerId={0}.                        |
| Level             | INFO                                              |
| Explanation       | LoadBalancer with loadBalancerId={0} was deleted. |
| Corrective Action | N/A                                               |

|                   |                                       |
|-------------------|---------------------------------------|
| Logger            | org.midonet.event.topology.VIP.CREATE |
| Message           | CREATE vipId={0}, data={1}.           |
| Level             | INFO                                  |
| Explanation       | VIP with vipId={0} was created.       |
| Corrective Action | N/A                                   |

|                   |                                        |
|-------------------|----------------------------------------|
| Logger            | org.midonet.event.topology.VIP.UPDATE  |
| Message           | UPDATE vipId={0}, data={1}.            |
| Level             | INFO                                   |
| Explanation       | VIP with vipId={0} was updated to {1}. |
| Corrective Action | N/A                                    |

|                   |                                       |
|-------------------|---------------------------------------|
| Logger            | org.midonet.event.topology.VIP.DELETE |
| Message           | DELETE vipId={0}.                     |
| Level             | INFO                                  |
| Explanation       | VIP with vipId={0} was deleted.       |
| Corrective Action | N/A                                   |

## Pool

|                   |                                        |
|-------------------|----------------------------------------|
| Logger            | org.midonet.event.topology.Pool.CREATE |
| Message           | CREATE poolId={0}, data={1}.           |
| Level             | INFO                                   |
| Explanation       | Pool with poolId={0} was created.      |
| Corrective Action | N/A                                    |

|                   |                                          |
|-------------------|------------------------------------------|
| Logger            | org.midonet.event.topology.Pool.UPDATE   |
| Message           | UPDATE poolId={0}, data={1}.             |
| Level             | INFO                                     |
| Explanation       | Pool with poolId={0} was updated to {1}. |
| Corrective Action | N/A                                      |

|                   |                                        |
|-------------------|----------------------------------------|
| Logger            | org.midonet.event.topology.Pool.DELETE |
| Message           | DELETE poolId={0}.                     |
| Level             | INFO                                   |
| Explanation       | Pool with poolId={0} was deleted.      |
| Corrective Action | N/A                                    |

## PoolMember

|             |                                               |
|-------------|-----------------------------------------------|
| Logger      | org.midonet.event.topology.PoolMember.CREATE  |
| Message     | CREATE poolMemberId={0}, data={1}.            |
| Level       | INFO                                          |
| Explanation | PoolMember with poolMemberId={0} was created. |

|                   |     |
|-------------------|-----|
| Corrective Action | N/A |
|-------------------|-----|

|                   |                                                      |
|-------------------|------------------------------------------------------|
| Logger            | org.midonet.event.topology.PoolMember.UPDATE         |
| Message           | UPDATE poolMemberId={0}, data={1}.                   |
| Level             | INFO                                                 |
| Explanation       | PoolMember with poolMemberId={0} was updated to {1}. |
| Corrective Action | N/A                                                  |

|                   |                                               |
|-------------------|-----------------------------------------------|
| Logger            | org.midonet.event.topology.PoolMember.DELETE  |
| Message           | DELETE poolMemberId={0}.                      |
| Level             | INFO                                          |
| Explanation       | PoolMember with poolMemberId={0} was deleted. |
| Corrective Action | N/A                                           |

## HealthMonitor

|                   |                                                     |
|-------------------|-----------------------------------------------------|
| Logger            | org.midonet.event.topology.HealthMonitor.CREATE     |
| Message           | CREATE healthMonitorId={0}, data={1}.               |
| Level             | INFO                                                |
| Explanation       | HealthMonitor with healthMonitorId={0} was created. |
| Corrective Action | N/A                                                 |

|                   |                                                            |
|-------------------|------------------------------------------------------------|
| Logger            | org.midonet.event.topology.HealthMonitor.UPDATE            |
| Message           | UPDATE healthMonitorId={0}, data={1}.                      |
| Level             | INFO                                                       |
| Explanation       | HealthMonitor with healthMonitorId={0} was updated to {1}. |
| Corrective Action | N/A                                                        |

|                   |                                                     |
|-------------------|-----------------------------------------------------|
| Logger            | org.midonet.event.topology.HealthMonitor.DELETE     |
| Message           | DELETE healthMonitorId={0}.                         |
| Level             | INFO                                                |
| Explanation       | HealthMonitor with healthMonitorId={0} was deleted. |
| Corrective Action | N/A                                                 |

## API server events

This section describes the messages associated with API server events.

### NSDB (Network State Database)

|                   |                                               |
|-------------------|-----------------------------------------------|
| Logger            | org.midonet.event.api.Nsdb.CONNECT            |
| Message           | CONNECT Connected to the NSDB cluster.        |
| Level             | INFO                                          |
| Explanation       | API server was connected to the NSDB cluster. |
| Corrective Action | N/A                                           |

|             |                                                    |
|-------------|----------------------------------------------------|
| Logger      | org.midonet.event.api.Nsdb.DISCONNECT              |
| Message     | DISCONNECT Disconnected from the NSDB cluster.     |
| Level       | WARNING                                            |
| Explanation | API server was disconnected from the NSDB cluster. |

|                   |                                                                                                                                                                                      |
|-------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Corrective Action | If the connection is restored after this event, no corrective action is required. If this event continues, check the network connection between the API server and the NSDB cluster. |
| Logger            | org.midonet.event.api.Nsdb.CONN_EXPIRE                                                                                                                                               |
| Message           | CONN_EXPIRE Connection to the NSDB cluster expired.                                                                                                                                  |
| Level             | ERROR                                                                                                                                                                                |
| Explanation       | The connection from the API server to the NSDB cluster expired.                                                                                                                      |
| Corrective Action | Check the network connection between the API server and the NSDB cluster and restart the MidoNet API server so it reconnects to the NSDB cluster.                                    |

## MidoNet Agent events

This section describes the messages associated with MidoNet Agent events.

### NSDB

|                   |                                                  |
|-------------------|--------------------------------------------------|
| Logger            | org.midonet.event.agent.Nsdb.CONNECT             |
| Message           | CONNECT Connected to the NSDB cluster.           |
| Level             | INFO                                             |
| Explanation       | MidoNet Agent was connected to the NSDB cluster. |
| Corrective Action | N/A                                              |

|                   |                                                                                                                                                                                         |
|-------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Logger            | org.midonet.event.agent.Nsdb.DISCONNECT                                                                                                                                                 |
| Message           | DISCONNECT Disconnected from the NSDB cluster.                                                                                                                                          |
| Level             | WARNING                                                                                                                                                                                 |
| Explanation       | MidoNet Agent was disconnected from the NSDB cluster.                                                                                                                                   |
| Corrective Action | If the connection is restored after this event, no corrective action is required. If this event continues, check the network connection between the MidoNet Agent and the NSDB cluster. |

|                   |                                                                                                                                                                          |
|-------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Logger            | org.midonet.event.agent.Nsdb.CONN_EXPIRE                                                                                                                                 |
| Message           | CONN_EXPIRE Connection to the NSDB cluster expired. Shutting down the MidoNet Agent.                                                                                     |
| Level             | ERROR                                                                                                                                                                    |
| Explanation       | The connection from the MidoNet Agent to the NSDB cluster expired. Shutting down the MidoNet Agent.                                                                      |
| Corrective Action | Check the network connection between the MidoNet Agent node and the NSDB cluster and restart the MidoNet Agent service on the node so it reconnects to the NSDB cluster. |

### Interface

|                   |                                             |
|-------------------|---------------------------------------------|
| Logger            | org.midonet.event.agent.Interface.DETECT    |
| Message           | NEW interface={0}                           |
| Level             | INFO                                        |
| Explanation       | MidoNet Agent detected a new interface={0}. |
| Corrective Action | N/A                                         |

|        |                                          |
|--------|------------------------------------------|
| Logger | org.midonet.event.agent.Interface.UPDATE |
|--------|------------------------------------------|

|                   |                                                    |
|-------------------|----------------------------------------------------|
| Message           | UPDATE interface={0} was updated.                  |
| Level             | INFO                                               |
| Explanation       | MidoNet Agent detected an update in interface={0}. |
| Corrective Action | N/A                                                |

|                   |                                                        |
|-------------------|--------------------------------------------------------|
| Logger            | org.midonet.event.agent.Interface.DELETE               |
| Message           | DELETE interface={0} was deleted.                      |
| Level             | INFO                                                   |
| Explanation       | MidoNet Agent detected that interface={0} was deleted. |
| Corrective Action | N/A                                                    |

## Service

|                   |                                       |
|-------------------|---------------------------------------|
| Logger            | org.midonet.event.agent.Service.START |
| Message           | START Service started.                |
| Level             | INFO                                  |
| Explanation       | Service started.                      |
| Corrective Action | N/A                                   |

|                   |                                                                                                                                                                           |
|-------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Logger            | org.midonet.event.agent.Service.EXIT                                                                                                                                      |
| Message           | EXIT Service exited.                                                                                                                                                      |
| Level             | WARNING                                                                                                                                                                   |
| Explanation       | Service exited.                                                                                                                                                           |
| Corrective Action | Restart the MidoNet Agent service if this event happened unintentionally. If this event recurs, file a ticket in the bug tracker for further investigation by developers. |

## Packet Tracing

To configure packet tracing (via logging) in a MidoNet Agent (Midolman), the 'mm-trace' command can be used.

A MidoNet Agent can hold a set of filters that, when matching on an incoming packet, will cause it to log everything about its simulation to the agent's log file, regardless of the configured log level.

All trace messages have a "cookie:" prefix to identify its packet, and that can be used as a grep expression to filter out any non-tracing messages.



### Important

The filters are not persistent, they are lost every time the agent is rebooted.

However, mm-trace prints the filters in exactly the same syntax that it will accept to re-add them again, allowing operators to easily replay the commands.

## Usage

All available options can be displayed with the '-help' option:

```
$ mm-trace --help
-h, --host <arg> Host (default = localhost)
```

```

-p, --port <arg>    JMX port (default = 7200)
--help              Show help message

Subcommand: add - add a packet tracing match
-d, --debug          logs at debug level
--dst-port <arg>     match on TCP/UDP destination port
--ethertype <arg>    match on ethertype
--ip-dst <arg>       match on ip destination address
--ip-protocol <arg>  match on ip protocol field
--ip-src <arg>       match on ip source address
-l, --limit <arg>    number of packets to match before disabling
this trace
--mac-dst <arg>      match on destination MAC address
--mac-src <arg>      match on source MAC address
--src-port <arg>     match on TCP/UDP source port
-t, --trace          logs at trace level
--help              Show help message

Subcommand: remove - remove a packet tracing match
-d, --debug          logs at debug level
--dst-port <arg>     match on TCP/UDP destination port
--ethertype <arg>    match on ethertype
--ip-dst <arg>       match on ip destination address
--ip-protocol <arg>  match on ip protocol field
--ip-src <arg>       match on ip source address
-l, --limit <arg>    number of packets to match before disabling
this trace
--mac-dst <arg>      match on destination MAC address
--mac-src <arg>      match on source MAC address
--src-port <arg>     match on TCP/UDP source port
-t, --trace          logs at trace level
--help              Show help message

Subcommand: flush - clear the list of tracing matches
-D, --dead-only      flush expired tracers only
--help              Show help message

Subcommand: list - list all active tracing matches
-L, --live-only      list active tracers only
--help              Show help message

```

## Example

```

$ mm-trace list
$ mm-trace add --debug --ip-dst 192.0.2.1
$ mm-trace add --trace --ip-src 192.0.2.1 --dst-port 80
$ mm-trace list
tracer: --debug --ip-dst 192.0.2.1
tracer: --trace --ip-src 192.0.2.1 --dst-port 80
$ mm-trace remove --trace --ip-src 192.0.2.1 --dst-port 80
Removed 1 tracer(s)
$ mm-trace flush
Removed 1 tracer(s)

```

## Port mirroring

Port mirroring lets operators monitor arbitrary subsets of traffic in the overlay in specified vports. This can be useful for passive monitoring or for active troubleshooting.

MidoNet v5.0 introduces port mirroring based on these concepts:

1. A new type of virtual device: **mirror**.
2. Each mirror is associated with a destination virtual port, through its **to-port** attribute. This is where mirror traffic will be copied to.







Now the operator can see all local traffic in that bridge by tcpdump'ing on the monitoring port:

```
hypervisor01$ sudo ip netns exec mon tcpdump -nei monns
tcpdump: verbose output suppressed, use -v or -vv for full protocol decode
listening on monns, link-type EN10MB (Ethernet), capture size 65535 bytes
```

By the same means, the operator could mirror any other slice of traffic and do so from any point in the virtual overlay. If a mirror is applied to the upstream facing port of the router, the mirror will see the MAC and IP addresses as that port sees them.

Each mirror can be applied at any number of devices, and can hold several match conditions to capture different slices of traffic. Similarly, each mirroring hook in a device, can have several mirrors applied. Thus the operator has total freedom in selecting which traffic to monitor in his monitoring port, or, by creating different network interfaces and adding more vports to the monitoring bridge, he could also send different kinds of traffic to different monitoring ports.

## 14. VXLAN configuration

### Table of Contents

|                                                                    |    |
|--------------------------------------------------------------------|----|
| VXLAN Gateway .....                                                | 85 |
| VXLAN Coordinator .....                                            | 86 |
| VXLAN Flooding Proxy .....                                         | 87 |
| Connecting to the VTEP .....                                       | 87 |
| Setting up a connection between a VTEP and a Neutron network ..... | 89 |
| Enabling connection between VTEP and MidoNet hosts .....           | 90 |
| Troubleshooting VTEP/VXGW configuration .....                      | 91 |
| CLI commands used for working with the VXGW .....                  | 96 |

MidoNet supports the Virtual Extensible LAN (VXLAN) technology.

#### What is VXLAN?

VXLAN is a network virtualization technology that uses a VLAN-like encapsulation technique to encapsulate MAC-based OSI layer 2 Ethernet frames within layer 3 UDP packets.

This type of encapsulation (Ethernet-in-IP) is much better suited to Software Defined Networks than either VLANs (802.1q) or even stacked VLANs (Q-in-Q).

Another important advantage of VXLAN over traditional VLAN is its 24-bit VXLAN ID thanks to which VXLAN can scale up to over 16 million logical networks. By comparison - the maximum number of VLANs is 4096.

#### How is VXLAN supported in MidoNet?

MidoNet provides VXLAN implementation through:

- VXLAN Gateway, to bridge the overlay with physical L3 hosts in the underlay.
- VXLAN tunneling between MidoNet hosts.

### VXLAN Gateway

The VXLAN Gateway (VXGW) allows a virtual bridge to be extended to a physical L2 segment that is reachable via an L3 network and a VXLAN-capable physical switch.

A VXLAN-capable physical switch is also referred to as a *hardware VTEP* (VXLAN Tunnel End Point). The VXGW allows creating one or many VXLAN-based Logical Switches that span any number of hardware VTEPs and a single MidoNet-ODP cloud.

The VXGW has the following advantages:

- Provides L2 connectivity between VMs in an overlay and servers in a physical L2 segment.
- Provides L2 connectivity across an L3 transport network. This is useful when the L2 fabric doesn't reach all the way from the racks hosting the VMs to the physical L2 segment of interest.
- Compared to a pure L2 gateway, the VXGW scales better for overlay solutions:

## VXGW Management

A VXGW will be formed by binding a Neutron network to any number of port-vlan pairs on one or multiple VTEPs.

A port-VLAN pair can only be bound to a single Logical Switch. However, a given port may be configured multiple Logical Switches as long as the binding combines different VLANs.

The MidoNet Coordinator (the section called “VXLAN Coordinator” [86]) is able to connect to the Management Service of VTEPs, create and configure Logical Switches in its OVSDb instance according to the settings applied through the MidoNet API. Additionally, the Coordinator is able to extend the Logical Switch functions described above to a Neutron network.

MidoNet simplifies and automates these configuration details which remain invisible to the user. It uses some conventions that may be useful for two reasons: troubleshooting purposes, and making MidoNet usage of the VTEP compatible with non-MidoNet related ones.



The MidoNet controller will handle the exchange of learned MACs among all VTEPs and MidoNet's Network State Database (NSDB) automatically.

## VXLAN Coordinator

The Coordinator is the component of the MidoNet architecture responsible for VXLAN support.

- Exposing VTEP state through the MidoNet REST API.
- Configuring the VTEP switch in order to implement the bindings configured through the MidoNet REST API.
- Acting as an L2 control plane for traffic flowing between MN and the VTEP.

- The weight assigned to a MidoNet Agent defaults to 1, and can be altered issuing the following command on the MidoNet CLI:

Higher weights will imply a higher probability of the host being chosen as Flooding Proxy.

Note that the Flooding Proxy may potentially process a large volume of traffic. In these circumstances it is recommended to assign a much higher weight to a dedicated host.

Use this procedure to connect MidoNet to a hardware VTEP. This step is required before any Neutron networks can be bound to port-VLAN pairs on that VTEP.

- MidoNet will expect that the `Physical_Switch` table on the VTEP contains a record with the management IP, management port and tunnel IP of this VTEP. Keep these

```
vtep-ctl list Physical_switch
```

- To test the connection to the management database, you can run:

At this point, paste this on the console:

```
{"method": "list_dbs", "id": "list_dbs", "params": []}
```

And you should see this reply:



```
$ echo "cluster.vxgw.enabled=true" | mn-conf set -t default
```



## Important

Use this procedure to set up a connection between a VTEP and a Neutron network in MidoNet.

For this procedure you will need to know the VTEP's management IP and port, the physical port on the VTEP and the VLAN ID at this port to which you are connecting, the UUID of the Neutron network which you want to connect to the VTEP, and the IP addresses of all the hosts on the Neutron network that you want to communicate with the VTEP.

- All hosts that want to communicate with the VTEP using VXLAN tunnels are required to belong to a tunnel zone of type VTEP, using the IP that each of them will use as VXLAN tunnel endpoint.

```
midonet> tunnel-zone create name vtep_zone type vtep
tzone0
```

2. Add a VTEP to MidoNet and assign it to the `vtep` tunnel zone that you created, using the local IP that this host it meant to use in VXLAN tunnels to the VTEP. Note that this IP may be the same that the host uses to communicate with other MidoNet hosts.

```
midonet> vtep add management-ip 192.168.2.10 management-port 6632
tunnel-zone tzone0
vtep0
```

```

vtep vtep0 name VTEP-NAME description OVS VTEP Emulator management-ip
192.168.2.10 management-port 6632 tunnel-zone tzone0 connection-state
connected

```

- ```
midonet> list bridge
bridge bridge0 name public state up
midonet> show bridge bridge0 id
765cf657-3cf4-4d79-9621-7d71af38a298
```

4. For the hosts on the Neutron network to be able to communicate with the VTEP, their IP addresses have to be in the same tunnel zone as the VTEP.

- 89



```

midonet> host list
host host0 name rhos5-allinone-jenkins.novalocal alive true
midonet> host host0 list interface
iface veth1 host_id host0 status 3 addresses [u'172.16.0.2',
u'fe80:0:0:0:fc2a:9eff:fef2:aa6c'] mac fe:2a:9e:f2:aa:6c mtu 1500
type Virtual endpoint DATAPATH
...

```

- b. Add the host's IP address to the same tunnel zone as the VTEP:

```
midonet> tunnel-zone tzone0 add member host host0 address 172.16.0.2
```

Repeat these steps for every host in the Neutron network that you want to communicate with the VTEP.



### Important

Normally, a host may only be assigned to one tunnel zone, *gre* or *vlan* type. A host connecting to a VTEP is an exception because you may assign it to two tunnel zones, a *gre/vlan* one and a *vtep* one. Note that a host can still use the same IP for both tunnel zones.

5. Create a binding between the VTEP's VLAN 10 and the Neutron network behind the bridge0.

In this example you are connecting the hosts on VLAN 10 with the Neutron network 765cf657-3cf4-4d79-9621-7d71af38a298 behind the bridge0:

```

midonet> vtep vtep0 add binding network-id
765cf657-3cf4-4d79-9621-7d71af38a298 physical-port swp1 vlan 10

```

Congratulations, you have just created a binding between the network behind the VTEP's VLAN 10 physical port `swp1` and the Neutron network with the UUID 765cf657-3cf4-4d79-9621-7d71af38a298 in MidoNet.



### Tip

To be able to test the connection between the VTEP and MidoNet (i.e. to *ping* MidoNet from a host on the VTEP) you have to modify the default ingress security rule, by adding to it the IP address of the host (pinging the host from MidoNet should work without any additional configuration). For more information, see [the section called "Enabling connection between VTEP and MidoNet hosts" \[90\]](#).

## Enabling connection between VTEP and MidoNet hosts

By default Neutron includes a security rule on all networks that restricts forwarding only to traffic addressed to IP/MAC of VMs on that network.

By binding a network to physical ports in a VTEP, we're effectively adding hosts to the L2 segment of this Neutron network that Neutron itself does not know about, and thus traffic addressed to these physical hosts will be dropped.

The following procedure describes changes to the default ingress security rule in order to allow traffic to hosts on the VTEP.

1. In the MidoNet CLI find out what the ingress default security rule is by issuing this command:

```
midonet> list chain
chain chain0 name OS_SG_64d9f3df-9875-4896-ad0c-ffc5bba84c5e_INGRESS
chain chain1 name OS_SG_64d9f3df-9875-4896-ad0c-ffc5bba84c5e_EGRESS
...
```

Locate the ingress security rule that is assigned to the neutron network. In this case, we'll use chain0 (OS\_SG\_64d9f3df-9875-4896-ad0c-ffc5bba84c5e\_INGRESS) rule chain, the ingress chain.

2. List the rules that implement this security rule by issuing this command:

```
midonet> chain chain0 list rule
rule rule0 ethertype 2048 proto 0 tos 0 ip-address-group-src ip-address-group0 fragment-policy unfragmented pos 1 type accept
rule rule1 ethertype -31011 proto 0 tos 0 ip-address-group-src ip-address-group0 fragment-policy unfragmented pos 2 type accept
```

The security group that is responsible for controlling ICMP packets (ethertype 2048=IP) is ip-address-group0.

3. Now, go ahead and add the IP address of the host on the VTEP to the security group ip-address-group0.

For example, if the IP address of the host is 172.16.0.3, issue this command:

```
midonet> ip-address-group ip-address-group0 add ip address 172.16.0.3
address 172.16.0.3
```

You should now be able to ping a host in MidoNet from host 172.16.0.3 on the VTEP (providing they are in the same tunnel zone).

## Troubleshooting VTEP/VXGW configuration

VTEP deployments have a relatively large number of moving pieces and potential failure points. This guide will focus on troubleshooting MidoNet and the integration with the VTEP. For specifics on the configuration of the logical switch please refer to your vendor's documentation.

### Is the MidoNet API able to connect to the VTEP

After following the procedure to add a VTEP as described in [the section called "Adding a VTEP" \[97\]](#), the expected output should be as follows:

```
midonet> vtep add management-ip 192.168.2.10 management-port 6633 tunnel-zone tzone0
vtep0
midonet> vtep list
vtep vtep0 name VTEP-NAME management-ip 192.168.2.10 management-port 6633
tunnel-zone tzone0 connection-state connected
```

The same output should appear for VTEPs already added to MidoNet.

Note that the state is `connected`. An `error` state will indicate that the VTEP's management IP is unreachable from the MidoNet API.

### Is the VTEP well configured?





```
ERROR vxqw-vtep-ba2739df-87cf-458f-9ad2-39885cab217d VTEP error
```

If the logs show problems connecting to the NSDB verify that the NSDB is active, and MidoNet Cluster is successfully able to access it.

After fetching Neutron network configuration from the NDSB, the MidoNet Cluster logs should display the following message:

```
MAC-port table of network 4659a6ab-fcd2-4744-bfbb-6a331164881e is now
watched
ARP table of network 4659a6ab-fcd2-4744-bfbb-6a331164881e is now watched
Network 4659a6ab-fcd2-4744-bfbb-6a331164881e is now watched
```

### Verify that the MidoNet coordinator connects to the VTEP(s)

```
New bindings from network 4659a6ab-fcd2-4744-bfbb-6a331164881e:
  ArrayBuffer((swpl,0))
```

```
Publishing remote MAC to VTEP: MacLocation{logicalSwitch='mn-4659a6ab-  
fcd2-4744-bfbb-6a331164881e', mac=unknown-dst, ipAddr='null',  
tunnelEndpoint=null}
```

Following a successful consolidation of state, MidoNet will start the synchronization of MACs and ARP entries:

```
VTEP table entry added: PhysicalLocatorSet{uuid=115da3cb-8926-42bd-a416-7e006a353b73, locatorIds='Set(bel04a88-5b9c-4b61-bf94-6ea3c797f612)'}
VTEP table entry added: PhysicalLocator{uuid=bel04a88-5b9c-4b61-bf94-6ea3c797f612, dstIp=172.17.2.10, encapsulation='vxlan_over_ipv4'}
VTEP table entry added: McastMac{uuid=57e5f212-72b6-4cd7-ba24-2eb3791a90c5, logicalSwitch=a8817c74-708f-438d-9a17-02377cbd01ce, mac=unknown-dst, ip=null, locatorSet=115da3cb-8926-42bd-a416-7e006a353b73}
VTEP table entry added: PhysicalPort{uuid=5b90109a-fafc-4d53-a2ae-f79736a5ae9b, name=swp1, description=null bindings=Map(0 -> a8817c74-708f-438d-9a17-02377cbd01ce) stats=Map(0 -> ac00d040-deca-45b1-a391-468d45503238) faultStatus=Set() }
```

94

If MidoNet finds a non recoverable error, the following ERROR will be displayed (assuming same management port and id as above):

```
Error on OVSDB connection status stream
```

The MidoNet coordinator will ignore this Neutron network until it's updated again. It should however be able to continue operating with all other configured networks.

### Verify that the MidoNet coordinator synchronizes state

If no errors are displayed up to here, edit the logback.xml file mentioned above and enable DEBUG logs in the vxgw processes:

```
<!-- <logger name="org.midonet.cluster.vxgw" level="DEBUG" /> -->
```

Remove the `<!--` and `–#` tags to enable this configuration and restart the MidoNet Cluster logs to begin showing DEBUG messages. Choose TRACE instead of DEBUG for more exhaustive information (none will be too verbose to have a significant performance impact).

Messages like the following show that the MidoNet coordinator is successfully exchanging MACs among Midonet and VTEPs.

```
TRACE vtep-172_17_2_10:6632 MAC remote tables updated successfully
```

### Verify that VXLAN tunnels are being established

If the coordinator is working normally, but traffic is still not flowing, you should verify that the VTEPs and MidoNet hosts are able to establish VXLAN tunnels successfully.

While keeping a ping active from the VM to the server you're trying to communicate with, log in to the MidoNet compute hosting the VM that you're trying to communicate with a server on the VTEP. Run the following command:

```
tcpdump -leni any port 4789
```

Assuming that the MidoNet compute is 192.168.2.14, and the VTEP's tunnel IP is 192.168.2.17, the output should be similar to this (depending on your tcpdump version):

```
15:51:28.183233 Out fa:16:3e:df:b7:53 ethertype IPv4 (0x0800), length 94:
192.168.2.14.39547 > 192.168.2.17.4789: VXLAN, flags [I] (0x08), vni 10012
aa:aa:aa:aa:aa:aa > ff:ff:ff:ff:ff:ff, ethertype ARP (0x0806), length 42:
Request who-has 10.0.0.1 tell 10.0.0.10, length 28
15:51:28.186891 In fa:16:3e:52:d8:f3 ethertype IPv4 (0x0800), length 94:
192.168.2.17.59630 > 192.168.2.13.4789: VXLAN, flags [I] (0x08), vni 10012
cc:dd:ee:ee:ee:ff > aa:aa:aa:aa:aa:aa, ethertype ARP (0x0806), length 42:
Reply 10.0.0.10 is-at cc:dd:ee:ee:ee:ff
```

The first line shows that the MidoNet Agent (192.168.2.14) is emitting a tunnelled packet towards the VTEP (192.168.2.17:4789), using 10012 as VNID. The encapsulated packet is shown on the second line, and corresponds to an ARP REQUEST from a VM with ip 10.0.0.10 regarding server 10.0.0.1.

In this example, the VTEP is responding correctly on the third line, showing a return packet with the same VNID.

The same example can be applied in reverse on the VTEP. A ping from the physical server connected to the VTEP should generate a tunnelled packet towards a MidoNet Agent, and receive similar return packets.







```
vtep vtep0 name VTEP-NAME management-ip 192.168.2.10 management-port 6633
tunnel-zone tzone0 connection-state connected
```

An example of an unsuccessful command:

```
midonet> vtep add management-ip 192.168.2.10 management-port 6633
Internal error: {"message":"Validation error(s) found","code":400,
"violations":[{"message":"Tunnel zone ID is not valid.",
"property":"tunnelZoneId"}]}
```

## Obtaining information about a VTEP

Use this command to obtain information about a selected VTEP.

### Syntax

```
vtep <vtep-alias> show <property>
```

where *property* is one of the following VTEP's attributes:

- name
- description
- management-ip
- management-port
- connection-state
- tunnel-zone

### Result

The command returns the following information about the VTEP:

- name
- description
- management IP address (the same as the IP used with the command)
- mgmt\_port (the same as the port values used by the command)
- tunnel IP addresses
- connection state (one of: connected, disconnected, error. The state is error if the end-point is not a VXLAN End Point)
- the tunnel-zone to which this VTEP belongs.

### Example

Successful command:

```
midonet> vtep vtep0 show id
ba2739df-87cf-458f-9ad2-39885cab217d
```

```
midonet> vtep vtep0 show management-ip
192.168.2.10
```

## Adding a VTEP binding

Use this command to bridge the port-VLAN pair on a VTEP to a specified Neutron network.

### Syntax

```
vtep <vtep-alias> add binding physical-port <port-name> vlan <vlan-id>
network-id <neutron-network-id>
```

where *neutron-network-id* is the UUID of the network to which the port-VLAN assignment is to be made.

### Result

If the command is successful, the result is a description of the Neutron network, VTEP physical port and VLAN ID tuple:

```
physical-port swp1 vlan 0 network-id 4659a6ab-fcd2-4744-bfbb-6a331164881e
```

When creating the first binding to a network, MidoNet will create a new port on the corresponding virtual bridge called a 'VXLAN port'. This port represents the Neutron network's wiring to the VTEP. The same VXLAN port is used for subsequent port-VLAN pairs bound to the same Neutron network.

The command will fail in these conditions:

- the hardware VTEP does not have a physical port with the specified name (code 401)
- the hardware VTEP is not configured (code 503).
- the Neutron network does not exist (code 400).

### Example

Successful command:

```
midonet> vtep vtep0 add binding physical-port swp1 vlan 0 network-id
4659a6ab-fcd2-4744-bfbb-6a331164881e
physical-port swp1 vlan 0 network-id 4659a6ab-fcd2-4744-bfbb-6a331164881e
```

Unsuccessful command:

```
midonet> vtep vtep0 add binding physical-port swp10 vlan 0 network-id
4659a6ab-fcd2-4744-bfbb-6a331164881e
Internal error: {"message":"The VTEP at 192.168.2.10:6632 does not have a
port named swp10.","code":401}
```

```
midonet> vtep vtep0 add binding physical-port swp10 vlan 0 network-id
4659a6ab-fcd2-4744-bfbb-6a331164881e
Internal error: {"message":"Cannot add binding to VTEP 192.168.2.10:6632
because the physical switch is not configured.","code":503}
```

```
midonet> vtep vtep0 add binding physical-port swp10 vlan 0 network-id
f00f00f0-0f00-f00f-00f0-0f00f00f00f0
Internal error: {"message":"There is no Network with ID f00f00f0-0f00-
f00f-00f0-0f00f00f00f0.","code":400}
```

## Obtaining descriptions of VTEP bindings

The MidoNet CLI offers a command to obtain the descriptions of all bindings on a given VTEP, as well as all the VTEPs to which a specific Neutron network is bound to.



You can delete a single VTEP binding to a Neutron network. If that was the VTEP's last remaining port-VLAN pair bound to the network, then the Neutron network's VXLAN port is also deleted.

### Example

Examples of successfully run commands:

```
midonet> vtep vtep0 delete binding physical-port swp1
```

An example of a unsuccessful command:

```
midonet> vtep vtep0 delete binding
Syntax error at: ...binding
```

## Deleting a VTEP

Use this command to delete a VTEP.

### Syntax

```
vtep <vtep-alias> delete
```

### Result

Issuing this command completely deletes a VTEP from MidoNet's list of known VTEPs.

The command will fail if any of the VTEP's port-VLAN pairs are bound to any Neutron networks. For more information, see [the section called "Removing a VTEP binding" \[100\]](#)

### Example

```
midonet> vtep vtep0 delete
```

## Table of Contents

This section describes how to set up an L2 gateway between MidoNet's virtual bridges and physical switches.



This feature is not currently implemented in OpenStack Neutron. Therefore, you cannot use an L2 gateway to extend a MidoNet network (or bridge) to a Neutron bridge.


You can configure MidoNet's bridge virtual ports with a single VLAN ID, thereby introducing a change in the behavior of the processing of VLAN-tagged frames.

This guide refers to a bridge that owns one or more VLAN-configured ports as a "VLAN Aware Bridge" or VAB. A VAB may contain multiple virtual ports configured with a VLAN ID, but these tags must be unique in the VAB. A VAB may contain any number of trunk ports (that is, ports configured to support VLAN trunk links), but only one of the ports is expected to be active, according to the high-availability mechanism.

This guide refers to any bridge that has no virtual ports configured with a VLAN ID as a "VLAN Unaware Bridge" or VUB. VUBs may only have one virtual port linked to a VAB.

The diagram below depicts a typical L2 gateway topology.

### Figure 15.1. Topology with VLANs and L2 Gateway



The VAB in this example has two trunk ports that are bound to physical interfaces (either on the same or different physical hosts). Each of these ports has L2 connectivity to physical switches and may carry VLAN-tagged traffic.



```
midonet> host host1 binding add interface eth1 port bridge0:port3
```

# Fail-over/Fail-back

In combination with the Spanning Tree Protocol (STP) enabled on the physical bridges, MidoNet VABs are able to provide fail-over capabilities by forwarding Bridge Protocol Data Unit (BPDU) frames across their trunk ports.

Assuming that both physical switches belong to the same bridged network, as a result of the STP, both devices detect a loop through MidoNet's VAB and one switch chooses to block its trunk. For example, let's assume the left switch blocks. The VAB only sees ingress traffic from the right trunk, and thus associates all source MAC addresses seen in those frames to the right trunk.

A variety of events, including failures in the network, may result in the switches deciding to invert the state of the trunks. An example could be MidoNet losing connection to the left switch, and thus stop forwarding BPDUs to/from the right bridge and undoing the loop.

In such a fail-over scenario, traffic would start flowing from the other switch. With this change, MidoNet now detects ingress traffic on a new port, and thus updates its internal MAC-port associations. If the former state of the topology is restored (that is, MidoNet recovers connectivity to the left switch), MidoNet will again react and update its MAC-port associations.

The fail-over/fail-back times depend on the STP configuration on the switches, mainly the "forward delay," and the nature of the traffic. With standard values, and continuous traffic ingressing from the trunks, fail-over and fail-back cycles should be completed in 50 seconds, plus MAC learning time.

## 16. Working with the MidoNet CLI

### Table of Contents

Using the MidoNet CLI ..... 105

You can explore and edit all of MidoNet's virtual topology through the CLI, however, you should use write operations with caution, as they are likely to create inconsistencies between MidoNet's idea of the virtual network and OpenStack's view of it.



#### Note

When using MidoNet with OpenStack, please be careful not to introduce inconsistencies between OpenStack and MidoNet virtual topologies.

With that warning in mind, there are certain tasks for which the CLI can be particularly useful:

- Creating an Edge Router
- Setting up the cloud's up-link using the Border Gateway Protocol (BGP)
- Upgrading MidoNet
- Registering MidoNet Agents
- Setting up an L2 gateway
- Troubleshooting problems with the MidoNet API. Because the CLI uses the MidoNet API directly, it's the easiest way to make requests to it to verify that it works.
- Viewing and exploring MidoNet's virtual topology and the status and network addresses of all hosts running the MidoNet agent

### Using the MidoNet CLI

To use the MidoNet CLI you need to connect to the MidoNet host running it.

1. Using SSH to connect to the host running the MidoNet CLI.

You must know the IP address of the machine you are connecting to as well as your login credentials, that is your username and password. Example of an SSH command:

```
$ ssh root@192.168.17.5
root@192.168.17.5's password:
```

You have already provided your username, 'root' as part of the command, and now the server is prompting you for a password. Type in your password to get in.

2. The CLI is documented in a set of man pages. To view the man pages, from the system command line, enter:

```
$ man midonet-cli
```

3. To start the midonet-cli, at the system prompt, enter:



```
$ midonet-cli  
midonet>
```

The midonet> prompt that gets displayed indicates system readiness to accept MidoNet commands. Type in help and hit Enter to get a list of all available commands. You can also infer proper usage and syntax from context-aware auto-complete and by using the describe command.







Dumps the entire selected configuration.

- `--host HOST_ID, -h HOST_ID`: Selects a host id for which to dump configuration. The special value `local` will resolve to the local host id.
- `--template TEMPLATE, -t TEMPLATE`: Asks for a dump of a particular configuration template.
- `--schema, -s`: Asks for a dump of the configuration schema.
- `--host-only, -H`: If `-h` was given, print only the node-specific configuration for the given host. Otherwise `mn-conf` will print the configuration the host would have at runtime, combining the node-specific config with its template, the defaults and the schema.

```
get [-h HOST_ID | -t TEMPLATE_NAME | -s] [-H] CONFIG_KEY
```

Print the value assigned to a particular configuration key. See the above, in `dump`, the options for selecting the configuration source(s) to read from.

```
set [-h HOST_ID | -t TEMPLATE_NAME`] [-c] <var>`
```

Reads configuration from STDIN and stores it in the selected configuration source. The input will be merged on top of the existing configuration, unless `--clear` is given, in that case the input will replace the existing configuration. See above, in `dump`, the options for selecting the configuration source to write to.

- `-c, --clear`: Clear the configuration before storing the values read from standard input.

```
unset [-h HOST_ID | -t TEMPLATE_NAME`] CONFIG_KEY
```

Clears the value of a configuration key in a selected configuration source. See above, in `dump`, the options for selecting the configuration source to write to.

```
template-get [-a | -h HOST_ID`]`
```

Queries the assignments of configuration templates to MidoNet node IDs.

- `-a, --all`: Prints all template assignments.
- `-h HOST_ID, --host HOST_ID`: Prints the template assignment for the given host id. The special value `local` will resolve to the local host id.

```
template-set -h HOST_ID -t TEMPLATE_NAME
```

Assigns a configuration template to a host id.

```
template-clear -h HOST_ID
```

Clears the template assignment for a host id

```
template-list
```

Lists existing templates and the hosts that use them.

```
hosts
```

Displays information about hosts that have custom configurations or non-default templates assigned to them.













Configuration Key	Default Value	Description
		instance where the configuration applies.
<code>cluster.rest_api.http_port</code>	8181	Specifies the listening port for the HTTP end-point.
<code>cluster.rest_api.https_port</code>	8443	Specifies the listening port for the HTTPS end-point.

## Specifying the private and public keys for HTTPS

To enable the HTTPS end-point of the MidoNet Cluster REST API service, you must configure a JKS key store containing the private and public key X.509 certificate used for encrypting such connections.

The location of the key store file and the password for the private key are specified as the following Java system properties.

**Table 17.3. System Properties for the HTTPS Key Store**

Property Name	Default Value	Description
<code>midonet.keystore_path</code>	<code>/etc/midonet-cluster/ssl/midonet.jks</code>	The name of the key store file.
<code>midonet.keystore_password</code>	<i>none</i>	The password for the private key entry. If not set, the HTTPS end-point of the REST API will be disabled (default).

To change the previous properties, and enable HTTPS, you can add the corresponding property values to the environmental MidoNet Cluster script file found at `/etc/midonet-cluster/midonet-cluster-env.sh`:

```
JVM_OPTS="$JVM_OPTS -Dmidonet.keystore_path=<key-store-file>"
JVM_OPTS="$JVM_OPTS -Dmidonet.keystore_password=<key-entry-password>"
```

## Generating self-signed keys

To generate a self-signed key, you can use the following procedure. Note that you will be prompted for passwords during this process, and need to keep the keystore password for later use.

```
openssl genrsa -des3 -out midonet.key 2048
openssl rsa -in midonet.key -out midonet.key
openssl req -sha256 -new -key midonet.key -out midonet.csr -subj '/CN=localhost'
openssl x509 -req -days 365 -in midonet.csr -signkey midonet.key -out midonet.crt
```

Now we will combine the private key into the cert, because we generated them separately:

```
openssl pkcs12 -inkey midonet.key -in midonet.crt -export -out midonet.pkcs12
```

And load the certificate into the keystore:

```
keytool -importkeystore -srckeystore midonet.pkcs12 -srcstoretype PKCS12 -destkeystore midonet.jks
```

Now place the keystore in the default location:

```
mv midonet.jks /etc/midonet-cluster/ssl
```

For more advanced key management, including adding your own certificate to the key-store, please refer to the following documentation:

<https://www.eclipse.org/jetty/documentation/current/configuring-ssl.html>

## Cassandra cache

This section describes details relative to the Cassandra-based implementation of the Cassandra cache used for connection tracking and NAT mappings.

## Client library and normal operation

Cassandra operations are now asynchronous, so losing connectivity to Cassandra should not impact simulations.

The loss of connectivity to a majority of nodes creates a risk that connections will break on vport migration or MidoNet restart. But this is a low risk if the operator can avoid vport migrations and MidoNet Agent restarts until Cassandra is returned to normal operation.

To summarize, MidoNet can function with Cassandra down (but vport migrations and agent restarts may break connections) so it should only be tolerated for very brief periods.

## Agent behavior on node failure

The MidoNet Agent writes to Cassandra asynchronously after processing a packet that produced stateful connection data, such as NAT mappings or connection tracking keys.

The data written to Cassandra is purely a back up, as MidoNet agents share all stateful connection data directly amongst themselves. The back up is used upon agent reboot (to prevent lost connections across the reboot) and upon port migration. An agent binding a port will fetch the existing connection state from Cassandra for all connections traversing that port.

Should a Cassandra node fail, agents connected to it will fail over to other nodes in the Cassandra cluster. If the host tries to bind a port during that interval it may fail to fetch the state for the port, breaking pre-existing connections on that port. Additionally, state for flows processed during that interval may not be written to Cassandra, making it unavailable if it's needed later in the process of binding a port. State is refreshed every minute, thus a port migration would only break connections that were established in the minute prior to the port migration and only if the disconnection happened in that interval.

## Network State Database connectivity

In order to modify the MidoNet Network State Database, you must configure the following parameters in your `web.xml` file:

- zookeeper-zookeeper\_hosts
- zookeeper-session\_timeout
- cassandra-servers

Below are example web.xml snippets.



### Note

The rest of the configuration is cloud-controller dependent and is covered in the relevant sections of the documentation.

## zookeeper-zookeeper\_hosts

Lists the ZooKeeper hosts used to store the MidoNet configuration data. The entries are comma delimited:

```
<context-param>
  <param-name>zookeeper-zookeeper_hosts</param-name>
  <param-value>192.168.1.100:2181,192.168.1.101:2181,192.168.1.102:2181</param-value>
</context-param>
```

## zookeeper-session\_timeout

Sets the timeout value (in milliseconds) after which ZooKeeper considers clients to be disconnected from the ZooKeeper server:

```
<context-param>
  <param-name>zookeeper-session_timeout</param-name>
  <param-value>30000</param-value>
</context-param>
```

# 18. MidoNet and OpenStack TCP/UDP service ports

## Table of Contents

Services on the Controller node .....	119
Services on the Network State Database nodes .....	120
Services on the Compute nodes .....	121
Services on the Gateway Nodes .....	121

This section lists the TCP/UDP ports used by services in MidoNet and OpenStack.

## Services on the Controller node

This section lists the TCP/UDP ports used by the services on the Controller node.

Category	Service	Prot ocol	Port	Self	Controller	Compute	Mgmt. PC
OpenStack	glance-api	TCP	9292	x	x	x	x
OpenStack	httpd (Hori- zon)	TCP	80	x			x
MidoNet	midonet-api	TCP	8080	x	x		x
OpenStack	swift-ob- ject-server	TCP	6000	x	x	x	
OpenStack	swift-contain- er-server	TCP	6001	x	x	x	
OpenStack	swift-ac- count-server	TCP	6002	x	x	x	
OpenStack	keystone	TCP	35357	x	x	x	x
OpenStack	neutron-serv- er	TCP	9696	x	x	x	x
OpenStack	nova-novnc- proxy	TCP	6080	x	x		x
OpenStack	heat-api	TCP	8004	x	x		x
OpenStack	nova-api	TCP	8773	x	x		x
Tomcat	Tomcat shut- down control channel	TCP	8005	x	x		
OpenStack	nova-api	TCP	8774	x	x	x	x
OpenStack	nova-api	TCP	8775	x	x	x	x
OpenStack	glance-reg- istry	TCP	9191	x	x	x	
OpenStack	qpidd	TCP	5672	x	x	x	
OpenStack	keystone	TCP	5000	x	x	x	x
OpenStack	cinder-api	TCP	8776	x	x	x	x
Tomcat	Tomcat man- agement port (not used)	TCP	8009	x	x		
OpenStack	ceilome- ter-api	TCP	8777	x	x	x	x

Category	Service	Prot ocol	Port	Self	Controller	Compute	Mgmt. PC
OpenStack	mongod (ceilometer)	TCP	27017	x	x	x	
OpenStack	MySQL	TCP	3306	x	x	x	

## Services on the Network State Database nodes

This section lists the TCP/UDP ports used by the services on the Network State Database nodes.

Category	Service	Prot ocol	Port	Self	Controller	NSDB	Compute	Comment
MidoNet	ZooKeeper communication	TCP	3888	x		x		
MidoNet	ZooKeeper leader	TCP	2888	x		x		
MidoNet	ZooKeeper/Cassandra	TCP	random	x				ZooKeeper/Cassandra "LISTEN" to a TCP high number port. The port number is randomly selected on each ZooKeeper/Cassandra host.
MidoNet	Cassandra Query Language (CQL) native transport port	TCP	9042					
MidoNet	Cassandra cluster communication	TCP	7000	x		x		
MidoNet	Cassandra cluster communication (Transport Layer Security (TLS) support)	TCP	7001	x		x		
MidoNet	Cassandra JMX	TCP	7199	x				JMX monitoring port. If you're using this port to monitor Cassandra health, enable communication from the monitoring server.
MidoNet	ZooKeeper client	TCP	2181	x	x	x	x	
MidoNet	Cassandra clients	TCP	9160	x	x	x	x	

## Services on the Compute nodes

This section lists the TCP/UDP ports used by the services on the Compute nodes.

Category	Service	Protocol	Port	Self	Controller	Comment
OpenStack	qemu-kvm vnc	TCP	From 5900 to 5900 + # of VM		x	
MidoNet	midolman	TCP	random	x		midolman "LISTEN"s to a TCP high number port. The port number is randomly selected on each MN Agent host.
OpenStack	libvirtd	TCP	16509	x	x	
MidoNet	midolman	TCP	7200	x		JMX monitoring port If you're using this port to monitor health, enable communication from the monitoring server.
MidoNet	midolman	TCP	9697	x		If enabled, MidoNet Metadata Proxy listens on 169.254.169.254:9697 to accept metadata requests.

## Services on the Gateway Nodes

This section lists the TCP/UDP ports used by the services on the Gateway Nodes.

Category	Service	Protocol	Port	Self	Misc.	Comment
MidoNet	midolman	TCP	random	x		midolman LISTEN"s to a TCP high number port. The port number is randomly selected on each MN Agent host.
MidoNet	midolman	TCP	7200	x	x	JMX monitoring port If you're using this port to monitor health, enable communication from the monitoring server.
MidoNet	quagga bgpd control	TCP	2606	x		Network-NameSpace mbgp[Peer Number]_ns
MidoNet	quagga bgpd bgp	TCP	179		BGP neighbor	Network-NameSpace mbgp[Peer Number]_ns