BOOSTING

BOOSTING

THE BASIC CHALLENGE

- Take a weak learner (one slightly better than random guessing)
- Turn it into a strong learner (one with arbitrary accuracy)

THE CONCEPTUAL IMPLEMENTATION

- Fit a learner to your data
- Evaluate the residuals
- Fit a learner to the residuals
- Grab the predictions from this model (which should correct the errors from the first model)
- Add the predictions to form your new predictions
- Repeat M times

THE CONCEPTUAL IMPLEMENTATION

$$F(x) = \sum_{i=1}^{M} F_i(x)$$


- Once we fit a learner, we keep its prediction
- We want to improve the prediction by seeing where it went wrong
- Predict the degree to which it went wrong
- Correct the original predictions

THE CONCEPTUAL MODEL


- h(x) is a weak learner
- Fit $F_1(x)$ to your data
- $F_2(x) = F_1(x) + h(x)$
- $F_3(x) = F_2(x) + h(x)$
- and so on, for M iterations

LET'S SEE HOW THIS MIGHT WORK

- Gradient descent is a way to minimize a function
- The idea is to follow a curve down its steepest path







- Sometimes a "learning rate" α is added, so you don't move the whole way
- $F_k(x) = F_{k-1}(x) + \alpha h(x)$
- This is to slow things down
- If α is small and M is large, then you will get to minimum. # Loss functions

- Conceptually think of residuals
- However, in reality, think in direction of gradient

LOSS FUNCTION MINIMIZATION

- We want to minimize a chosen loss function L(y, X)
- The gradient of this loss function is \$
- This is a vector with length = number of columns of
- Compute this at each point
- Move in that direction

SQUARED ERROR LOSS

- $L(y, x) = (y_i x_i)^2/2$
- Gradient $G(x, y) = -(y_i x_i)$
- Note that this is essentially the residual

LOGISTIC LOSS

- $L(y, x) = \log(1 + e^{-yx})$
- Gradient $G(x, y) = -ye^{-yx}/(1 + e^{-yx})$
- This is often used for binary targets, where $y \in 0, 1,$ and x is the predicted probabilities

STOCHASTIC GRADIENT DESCENT

STOCHASTIC GRADIENT DESCENT

- We can overfit our data using just gradient descent
- Instead, fit learner to random subset of data, predict on remainder

STOCHASTIC GRADIENT DESCENT

- Also, at each stage, take a random sample of predictors
- Fit the model using this random sample of predictors

GRADIENT BOOSTED TREES

GRADIENT BOOSTED TREES

- Weak learners are decision trees (in particular regression trees)
- Fit a regression tree to your data
- Compute residuals or gradients at each point
- Fit a regression tree to the residuals/gradients and predict
- Add the predictions to the previous predictions
- Repeat