

CSE 591 Semantic Web Mining

Arizona State University, Spring 2015

Lecture 4: Association Rule in Web
Mining

Instructor: Hanghang Tong
Hanghang.tong@asu.edu

Acknowledgement

- Part of Slides are from
 - Bing Liu (UIC)

Outline

- Introduction – Why Association Rule Mining (in Web Mining)
- Basic Concepts of Association Rule
- Apriori algorithm
- More on Association Rules

Introduction – Why Association Rule?

- **Web usage mining:** automatic discovery of patterns in clickstreams and associated data collected or generated as a result of user interactions with one or more Web sites.
- **Goal:** analyze the behavioral patterns and profiles of users interacting with a Web site.
- The discovered patterns are usually represented as collections of pages, objects, or resources that are frequently accessed by groups of users with common interests.

Introduction – Why Association Rule?

- Data in Web Usage Mining:
 - Web server logs
 - Site contents
 - Data about the visitors, gathered from external channels
 - Further application data
- Not all these data are always available.
- When they are, they must be integrated.
- A large part of Web usage mining is about processing usage/ clickstream data.
 - After that various data mining algorithm can be applied.

Web server logs

1	2006-02-01 00:08:43 1.2.3.4 - GET /classes/cs589/papers.html - 200 9221 HTTP/1.1 maya.cs.depaul.edu Mozilla/4.0+(compatible;+MSIE+6.0;+Windows+NT+5.1;+SV1;+.NET+CLR+2.0.50727) http://dataminingresources.blogspot.com/
2	2006-02-01 00:08:46 1.2.3.4 - GET /classes/cs589/papers/cms-tai.pdf - 200 4096 HTTP/1.1 maya.cs.depaul.edu Mozilla/4.0+(compatible;+MSIE+6.0;+Windows+NT+5.1;+SV1;+.NET+CLR+2.0.50727) http://maya.cs.depaul.edu/~classes/cs589/papers.html
3	2006-02-01 08:01:28 2.3.4.5 - GET /classes/ds575/papers/hyperlink.pdf - 200 318814 HTTP/1.1 maya.cs.depaul.edu Mozilla/4.0+(compatible;+MSIE+6.0;+Windows+NT+5.1) http://www.google.com/search?hl=en&lr=&q=hyperlink+analysis+for+the+web+survey
4	2006-02-02 19:34:45 3.4.5.6 - GET /classes/cs480/announce.html - 200 3794 HTTP/1.1 maya.cs.depaul.edu Mozilla/4.0+(compatible;+MSIE+6.0;+Windows+NT+5.1;+SV1) http://maya.cs.depaul.edu/~classes/cs480/
5	2006-02-02 19:34:45 3.4.5.6 - GET /classes/cs480/styles2.css - 200 1636 HTTP/1.1 maya.cs.depaul.edu Mozilla/4.0+(compatible;+MSIE+6.0;+Windows+NT+5.1;+SV1) http://maya.cs.depaul.edu/~classes/cs480/announce.html
6	2006-02-02 19:34:45 3.4.5.6 - GET /classes/cs480/header.gif - 200 6027 HTTP/1.1 maya.cs.depaul.edu Mozilla/4.0+(compatible;+MSIE+6.0;+Windows+NT+5.1;+SV1) http://maya.cs.depaul.edu/~classes/cs480/announce.html

Association rule mining

- Proposed by **Agrawal et al in 1993**.
- It is an important data mining model studied extensively by the database and data mining community.
- Assume all data are categorical.
- No good algorithm for numeric data.
- Initially used for **Market Basket Analysis** to find how items purchased by customers are related.

Bread \rightarrow Milk [sup = 5%, conf = 100%]

The model: data

- $I = \{i_1, i_2, \dots, i_m\}$: a set of *items*.
- Transaction t :
 - t a set of items, and $t \subseteq I$.
- Transaction Database T : a set of transactions
 $T = \{t_1, t_2, \dots, t_n\}$.

Transaction data: supermarket data

■ Market basket transactions:

t1: {bread, cheese, milk}

t2: {apple, eggs, salt, yogurt}

...

...

tn: {biscuit, eggs, milk}

■ Concepts:

- ❑ *An item*: an item/article in a basket
- ❑ *I*: the set of all items sold in the store
- ❑ *A transaction*: items purchased in a basket; it may have TID (transaction ID)
- ❑ *A transactional dataset*: A set of transactions

Transaction data: a set of documents

- **A text document data set. Each document is treated as a “bag” of keywords**

doc1: Student, Teach, School

doc2: Student, School

doc3: Teach, School, City, Game

doc4: Baseball, Basketball

doc5: Basketball, Player, Spectator

doc6: Baseball, Coach, Game, Team

doc7: Basketball, Team, City, Game

The model: rules

- A transaction t contains X , a set of items (itemset) in I , if $X \subseteq t$.
- An association rule is an implication of the form:
$$X \rightarrow Y, \text{ where } X, Y \subset I, \text{ and } X \cap Y = \emptyset$$
- An itemset is a set of items.
 - E.g., $X = \{\text{milk, bread, cereal}\}$ is an itemset.
- A k -itemset is an itemset with k items.
 - E.g., $\{\text{milk, bread, cereal}\}$ is a 3-itemset

Rule strength measures

- **Support:** The rule holds with **support** sup in T (the transaction data set) if $sup\%$ of transactions contain $X \cup Y$.
 - $sup = \Pr(X \cup Y)$.
- **Confidence:** The rule holds in T with **confidence** $conf$ if $conf\%$ of transactions that contain X also contain Y .
 - $conf = \Pr(Y | X)$
- An association rule is a pattern that states when X occurs, Y occurs with certain probability.

Support and Confidence

- **Support count:** The support count of an itemset X , denoted by $X.count$, in a data set T is the number of transactions in T that contain X . Assume T has n transactions.
- Then,

$$support = \frac{(X \cup Y).count}{n}$$

$$confidence = \frac{(X \cup Y).count}{X.count}$$

Goal and key features

- **Goal:** Find all rules that satisfy the user-specified *minimum support* (minsup) and *minimum confidence* (minconf).
- **Key Features**
 - **Completeness:** find all rules.
 - **No target item(s)** on the right-hand-side
 - Mining with data on **hard disk** (not in memory)

An example



t1:	Beef, Chicken, Milk
t2:	Beef, Cheese
t3:	Cheese, Boots
t4:	Beef, Chicken, Cheese
t5:	Beef, Chicken, Clothes, Cheese, Milk
t6:	Chicken, Clothes, Milk
t7:	Chicken, Milk, Clothes

- Transaction data

- Assume:

minsup = 30%

minconf = 80%

- An example **frequent itemset**:

{Chicken, Clothes, Milk} [sup = 3/7]

- **Association rules** from the itemset:

Clothes → Milk, Chicken [sup = 3/7, conf = 3/3]

...

...

Clothes, Chicken → Milk, [sup = 3/7, conf = 3/3]

Transaction data representation

- A simplistic view of shopping baskets,
- Some important information not considered.
E.g,
 - the quantity of each item purchased and
 - the price paid.

Many mining algorithms

- **There are a large number of them!!**
- They use different strategies and data structures.
- Their resulting sets of rules are all the same.
 - Given a transaction data set T , and a minimum support and a minimum confident, the set of association rules existing in T is uniquely determined.
- Any algorithm should find the same set of rules although their computational efficiencies and memory requirements may be different.
- We study only one: **the Apriori Algorithm**

The Apriori algorithm

- **The best known algorithm**

- **Two steps:**

- Find all itemsets that have minimum support (*frequent itemsets*, also called large itemsets).
- Use frequent itemsets to **generate rules**.

- E.g., a frequent itemset


{Chicken, Clothes, Milk} [sup = 3/7]

and one rule from the frequent itemset

Clothes \rightarrow Milk, Chicken [sup = 3/7, conf = 3/3]

Step 1: Mining all frequent itemsets

- A **frequent *itemset*** is an itemset whose support is $\geq \text{minsup}$.
- **Key idea:** The **apriori property** (**downward closure property**): any subsets of a frequent itemset are also frequent itemsets



The Algorithm

- **Iterative algo.** (also called **level-wise search**):
Find all 1-item frequent itemsets; then all 2-item frequent itemsets, and so on.
 - In each iteration k , only consider itemsets that contain some $k-1$ frequent itemset.

- Find frequent itemsets of size 1: F_1
- **From $k = 2$**
 - C_k = candidates of size k : those itemsets of size k that could be frequent, given F_{k-1}
 - F_k = those itemsets that are actually frequent, $F_k \subseteq C_k$ (need to scan the database once).

Example – Finding frequent itemsets

Dataset T
minsup=0.5

TID	Items
T100	1, 3, 4
T200	2, 3, 5
T300	1, 2, 3, 5
T400	2, 5

itemset:count

1. scan T \rightarrow C_1 : {1}:2, {2}:3, {3}:3, {4}:1, {5}:3

\rightarrow F_1 : {1}:2, {2}:3, {3}:3, {5}:3

\rightarrow C_2 : {1,2}, {1,3}, {1,5}, {2,3}, {2,5}, {3,5}

2. scan T \rightarrow C_2 : {1,2}:1, {1,3}:2, {1,5}:1, {2,3}:2, {2,5}:3, {3,5}:2

\rightarrow F_2 : {1,3}:2, {2,3}:2, {2,5}:3, {3,5}:2

\rightarrow C_3 : {2, 3,5}

3. scan T \rightarrow C_3 : {2, 3, 5}:2 \rightarrow F_3 : {2, 3, 5}

Details: ordering of items

- The items are sorted in **lexicographic order** (which is a total order).
- The order is used throughout the algorithm in each itemset.
- $\{w[1], w[2], \dots, w[k]\}$ represents a k -itemset w consisting of items $w[1], w[2], \dots, w[k]$, where $w[1] < w[2] < \dots < w[k]$ according to the total order.

Details: the algorithm

Algorithm Apriori(T)

```
 $C_1 \leftarrow \text{init-pass}(T);$   
 $F_1 \leftarrow \{f \mid f \in C_1, f.\text{count}/n \geq \text{minsup}\};$  //  $n$ : no. of transactions in  $T$   
for ( $k = 2$ ;  $F_{k-1} \neq \emptyset$ ;  $k++$ ) do  
     $C_k \leftarrow \text{candidate-gen}(F_{k-1});$   
    for each transaction  $t \in T$  do  
        for each candidate  $c \in C_k$  do  
            if  $c$  is contained in  $t$  then  
                 $c.\text{count}++$ ;  
            end  
        end  
     $F_k \leftarrow \{c \in C_k \mid c.\text{count}/n \geq \text{minsup}\}$   
end  
return  $F \leftarrow \bigcup_k F_k$ ;
```

Apriori candidate generation

- The **candidate-gen** function takes F_{k-1} and returns a **superset** (called the candidates) of the set of all **frequent k -itemsets**. It has two steps
 - **join step**: Generate all possible candidate itemsets C_k of length k
 - **prune step**: Remove those candidates in C_k that cannot be frequent.

Candidate-gen function

Function candidate-gen(F_{k-1})

$C_k \leftarrow \emptyset$;

forall $f_1, f_2 \in F_{k-1}$

 with $f_1 = \{i_1, \dots, i_{k-2}, i_{k-1}\}$

 and $f_2 = \{i_1, \dots, i_{k-2}, i'_{k-1}\}$

 and $i_{k-1} < i'_{k-1}$ **do**

$c \leftarrow \{i_1, \dots, i_{k-1}, i'_{k-1}\}$; // join f_1 and f_2

$C_k \leftarrow C_k \cup \{c\}$;

for each $(k-1)$ -subset s of c **do**

if ($s \notin F_{k-1}$) **then**

 delete c from C_k ; // prune

end

end

return C_k ;

An example

- $F_3 = \{\{1, 2, 3\}, \{1, 2, 4\}, \{1, 3, 4\}, \{1, 3, 5\}, \{2, 3, 4\}\}$
- After join
 - $C_4 = \{\{1, 2, 3, 4\}, \{1, 3, 4, 5\}\}$
- After pruning:
 - $C_4 = \{\{1, 2, 3, 4\}\}$
because $\{1, 4, 5\}$ is not in F_3 ($\{1, 3, 4, 5\}$ is removed)

Step 2: Generating rules from frequent itemsets

- Frequent itemsets \neq association rules
- One more step is needed to generate association rules
- For each frequent itemset X ,
For each proper nonempty subset A of X ,
 - Let $B = X - A$
 - $A \rightarrow B$ is an association rule if
 - Confidence($A \rightarrow B$) \geq minconf,
support($A \rightarrow B$) = support($A \cup B$) = support(X)
confidence($A \rightarrow B$) = support($A \cup B$) / support(A)

Generating rules: an example

- Suppose $\{2,3,4\}$ is frequent, with $\text{sup}=50\%$
 - Proper nonempty subsets: $\{2,3\}$, $\{2,4\}$, $\{3,4\}$, $\{2\}$, $\{3\}$, $\{4\}$, with $\text{sup}=50\%$, 50% , 75% , 75% , 75% , 75% respectively
 - These generate these association rules:
 - $2,3 \rightarrow 4$, confidence= 100%
 - $2,4 \rightarrow 3$, confidence= 100%
 - $3,4 \rightarrow 2$, confidence= 67%
 - $2 \rightarrow 3,4$, confidence= 67%
 - $3 \rightarrow 2,4$, confidence= 67%
 - $4 \rightarrow 2,3$, confidence= 67%
 - All rules have support = 50%

Generating rules: summary

- To recap, in order to obtain $A \rightarrow B$, we need to have $\text{support}(A \cup B)$ and $\text{support}(A)$
- All the required information for confidence computation has already been recorded in itemset generation. No need to see the data T any more.
- This step is not as time-consuming as frequent itemsets generation.

On Apriori Algorithm

Seems to be very expensive

- Level-wise search
- K = the size of the largest itemset
- It makes at most K passes over data
- In practice, K is bounded (10).
- The algorithm is very fast. Under some conditions, all rules can be found in **linear time**.
- Scale up to large data sets

More on Association Rule Mining

- Mining with multiple minimum supports
- Mining class association rules
- Sequential pattern mining