

Getting Started

David J Dorer Dorer Community Service Foundation

Installation

- 1a. (Linux/Ubuntu) Download tar.gz file for current version of PAT e.g. PAT_0.5.tar.gz
- 1b. (Windows) Download zip file for current version of PAT e.g. PAT_0.5.zip
 2. Decide on and create the folder where you want to store files.
 3. Create sub-folders/directories:
 - 3a. logs
 - 3b. data
 - 3c. output

Setup Within R

Once

- 4a. (Windows) in an R session run

```
install.packages(pkgs="path_to PAT_<vers>.zip",repos=NULL);
```
- 4b. (Ubuntu/Linux) in an R session run

```
install.packages(pkgs="path_to PAT_<vers>.tar.gz",repos=NULL);
```

Initialization

1. run `require(PAT)`
2. Set your census key `PAT.census.key("your_key_here")` You can get your census key at Census key request https://api.census.gov/data/key_signup.html
3. Set your root folder/directory `PAT.root("path_to_base_folder");`
The default for the root folder is your working directory `getwd()` this is probably not what you want.
4. Optionally set `nraces` (number of race categories) for PUMS derived variables and Detail/Subject/DataProfile tables.
 - 3a. To see current value use `print(PAT.race.code())`
 - 3b. To change `PAT.race.code("new_value");`
 - 3c. To see choices `help(Pat.race.code)`
5. Optionally set `nages` (number of ages categories) for PUMS derived variables and Detail/Subject/DataProfile tables.
 - 4a. To see current value use `(print(PAT.age.code()));`
 - 4b. To change `PAT.age.code("new_value");`

4c. To see choices `help(Pat.age.code);`

6. Check/Set other options:

`PAT.vintage()`

`PAT.period()`

`PAT.pums.vintage()`

`PAT.pums.period()`

`PAT.verbose()`

v1.3 11 Dec 2023 12:58