

COMMONWEALTH OF AUSTRALIA

Copyright Regulations 1969

WARNING

This material has been reproduced and communicated to you by or on behalf of the University of Sydney pursuant to Part VB of the Copyright Act 1968 (**the Act**). The material in this communication may be subject to copyright under the Act. Any further copying or communication of this material by you may be the subject of copyright protection under the Act.

Do not remove this notice.

Data structures and Algorithms

Lecture 2b: stacks and queues [GT 2.1]

Dr. Julian Mestre

School of Computer Science



THE UNIVERSITY OF
SYDNEY

Stacks and queues

These ADTs are restricted forms of List, where insertion and removal happen only in particular locations:

- stacks follow last-in-first-out (LIFO)
- queues follows first-in-first-out (FIFO)

So why should we care are a less general ADT?

- operations names are part of computing culture
- numerous applications
- simpler/more efficient implementations than Lists

Stack ADT



Main stack operations:

- **push**(e): inserts an element, e
- **pop**(): removes and returns the last inserted element

Auxiliary stack operations:

- **top**(): returns the last inserted element without removing it
- **size**(): returns the number of elements stored
- **isEmpty**(): indicates whether no elements are stored

Stack Example

operation	returns	stack
push(5)	-	[5]
push(3)	-	[5, 3]
size()	2	[5, 3]
pop()	3	[5]
isEmpty()	False	[5]
pop()	5	[]
isEmpty()	True	[]
push(7)	-	[7]
push(9)	-	[7, 9]
top()	9	[7, 9]
push(4)	-	[7, 9, 4]
pop()	4	[7, 9]

Stack Applications

Direct applications

- Keep track of a history that allows undoing such as Web browser history or undo sequence in a text editor
- Chain of method calls in a language supporting recursion
- Context-free grammars

Indirect applications

- Auxiliary data structure for algorithms
- Component of other data structures

Method Stacks

The runtime environment keeps track of the chain of active methods with a stack, thus allowing **recursion**

When a method is called, the system pushes on the stack a frame containing

- Local variables and return value
- Program counter

When a method ends, we pop its frame and pass control to the method on top

```
main() {  
    int i = 5;  
    foo(i);  
}  
  
foo(int j) {  
    int k;  
    k = j+1;  
    bar(k);  
}  
  
bar(int m) {  
    ...  
}
```

bar
PC = 1
m = 6

foo
PC = 3
j = 5
k = 6

main
PC = 2
i = 5

Parentheses Matching

Each “(”, “{”, or “[” must be paired with a matching “)”, “}”, or “]”

- correct: ()(()){([()])}
- correct: ((()(()){([()])}
- incorrect:)(()){([()])}
- incorrect: ({[]})
- incorrect: (

Scan input string from left to right:

- If we see an opening character, push it to a stack
- If we see a closing character, pop character on stack and check that they match

Stack implementation based on arrays

A simple way of implementing the Stack ADT uses an array:

- Array has capacity **N**
- Add elements from left to right
- A variable keeps track of the index of the top element

```
def size()  
    return t + 1
```

```
def pop()  
    if isEmpty() then  
        return null  
    else  
        t ← t - 1  
        return S[t + 1]
```



Stack implementation based on arrays

- The array storing the stack elements may become full
- A push operation will then either grow the array or signal a “stack overflow” error.

```
def push(e)
  if  $t = N - 1$  then
    return “stack overflow”
  else
     $t \leftarrow t + 1$ 
     $S[t] \leftarrow e$ 
```



Stack implementation based on arrays


Performance

- Let n be the number of elements in the stack
- The space used is $O(n)$
- Each operation runs in time $O(1)$

Qualifications

- Trying to push a new element into a full stack causes an implementation-specific exception or
- Pushing an item on a full stack causes the underlying array to double in size, which implies each operation runs in $O(1)$ amortized time.

Queue ADT



Main queue operations:

- **enqueue(e)**: inserts an element, e, at the end of the queue
- **dequeue()**: removes and returns element at the front of the queue

Auxiliary queue operations:

- **first()**: returns the element at the front without removing it
- **size()**: returns the number of elements stored
- **isEmpty()**: indicates whether no elements are stored

Boundary cases:

- Attempting the execution of dequeue or first on an empty queue signals an error or returns null

Queue Example

Operation		Output	Q
enqueue(5)	—	(5)	
enqueue(3)	—	(5, 3)	
dequeue()	5	(3)	
enqueue(7)	—	(3, 7)	
dequeue()	3	(7)	
first()	7	(7)	
dequeue()	7	()	
dequeue()	<i>null</i>	()	
isEmpty()	<i>true</i>	()	
enqueue(9)	—	(9)	
enqueue(7)	—	(9, 7)	
size()	2	(9, 7)	
enqueue(3)	—	(9, 7, 3)	
enqueue(5)	—	(9, 7, 3, 5)	
dequeue()	9	(7, 3, 5)	

Queue applications

Buffering packets in streams, e.g., video or audio

Direct applications

- Waiting lists, bureaucracy
- Access to shared resources (e.g., printer)
- Multiprogramming


Indirect applications

- Auxiliary data structure for algorithms
- Component of other data structures

Queue application: Round Robin Schedulers

Implement a round robin scheduler using a queue Q by repeatedly performing the following steps:

1. $e = Q.dequeue()$
2. Service element e
3. $Q.enqueue(e)$



Queue implementation based on arrays

Use an array of size N in a circular fashion


Two variables keep track of the front and size

start : index of the front element

end : index past the last element

size : number of stored elements


These are related as follows $\text{end} = (\text{start} + \text{size}) \bmod N$,
so we only need two, **start** and **size**



Queue Operations: Enqueue

Return an error if the array is full. Alternatively, we could grow the underlying array as dynamic arrays do

```
def enqueue(e)
  if size = N then
    return "queue full"
  else
    last  $\leftarrow$  (first + size) mod N
    Q[last]  $\leftarrow$  e
    size  $\leftarrow$  size + 1
```




Queue Operations: Dequeue

Note that operation dequeue returns error if the queue is empty

One could alternatively signal an error

```
def dequeue()  
    if isEmpty() then  
        return "queue empty"  
    else  
        e ← Q[first]  
        first ← (first + 1) mod N  
        size ← (size - 1)  
        return e
```



Double-ended queues: Deques

- A linear structure that allows insertions and deletions at both ends

Method	Time
size, isEmpty	$O(1)$
getFirst, getLast	$O(1)$
addFirst, addLast	$O(1)$
removeFirst, removeLast	$O(1)$

Table 5.4: Performance of a deque realized by a doubly linked list.

Double-ended queue operations

The deque abstract data type is richer than both the stack and the queue ADTs. The fundamental methods of the deque ADT are as follows:

- `addFirst(e)`: Insert a new element e at the head of the deque.
- `addLast(e)`: Insert a new element e at the tail of the deque.
- `removeFirst()`: Remove and return the first element of the deque; an error occurs if the deque is empty.
- `removeLast()`: Remove and return the last element of the deque; an error occurs if the deque is empty.

Additionally, the deque ADT may also include the following support methods:

- `getFirst()`: Return the first element of the deque; an error occurs if the deque is empty.
- `getLast()`: Return the last element of the deque; an error occurs if the deque is empty.
- `size()`: Return the number of elements of the deque.
- `isEmpty()`: Determine if the deque is empty.