

Time Series

About the Data

In this notebook, we will be working with 5 data sets:

- (CSV) Facebook's stock price daily throughout 2018 (obtained using the stock_analysis package).
- (CSV) Facebook's OHLC stock data from May 20, 2019 - May 24, 2019 per minute from Nasdaq.com.
- (CSV) melted stock data for Facebook from May 20, 2019 - May 24, 2019 per minute from Nasdaq.com.
- (DB) stock opening prices by the minute for Apple from May 20, 2019 - May 24, 2019 altered to have seconds in the time from Nasdaq.com.
- (DB) stock opening prices by the minute for Facebook from May 20, 2019 - May 24, 2019 from Nasdaq.com.

Setup

```
In [3]: import numpy as np
import pandas as pd

fb = pd.read_csv("fb_2018.csv", index_col="date", parse_dates=True).assign(
    trading_volume=lambda x: pd.cut(x.volume, bins=3, labels=["low", "med", "high"])
)

fb.head()
```

```
Out[3]:
```

	open	high	low	close	volume	trading_volume
date						
2018-01-02	177.68	181.58	177.5500	181.42	18151903	low
2018-01-03	181.88	184.78	181.3300	184.67	16886563	low
2018-01-04	184.90	186.21	184.0996	184.33	13880896	low
2018-01-05	185.59	186.90	184.9300	186.85	13574535	low
2018-01-08	187.20	188.90	186.3300	188.28	17994726	low

Time-based selection and filtering

Remember, when we have a DatetimeIndex, we can use datetime slicing. We can provide a range of dates. We only get three days back because the stock market is closed on the weekends:

```
In [5]: fb["2018-10-11":"2018-10-15"]
```

```
Out[5]:
```

	open	high	low	close	volume	trading_volume
date						
2018-10-11	150.13	154.81	149.1600	153.35	35338901	low
2018-10-12	156.73	156.89	151.2998	153.74	25293492	low
2018-10-15	153.32	155.57	152.5500	153.52	15433521	low

We can select ranges of months and quarters:

```
In [7]: fb.loc["2018-Q1"].equals(fb["2018-01":"2018-03"])
```

```
Out[7]: True
```

The first() method will give us a specified length of time from the beginning of the time series. Here, we ask for a week. January 1, 2018 was a holiday—meaning the market was closed. It was also a Monday, so the week here is only four days:

```
In [9]: fb.first("1W")
```

C:\Users\Eleazar\AppData\Local\Temp\ipykernel_4892\2895274103.py:1: FutureWarning: first is deprecated and will be removed in a future version. Please create a mask and filter using `.loc` instead
fb.first("1W")

```
Out[9]:
```

	open	high	low	close	volume	trading_volume
date						
2018-01-02	177.68	181.58	177.5500	181.42	18151903	low
2018-01-03	181.88	184.78	181.3300	184.67	16886563	low
2018-01-04	184.90	186.21	184.0996	184.33	13880896	low
2018-01-05	185.59	186.90	184.9300	186.85	13574535	low

The last() method will take from the end:

```
In [11]: fb.last("1W")
```

C:\Users\Eleazar\AppData\Local\Temp\ipykernel_4892\2941757881.py:1: FutureWarning: last is deprecated and will be removed in a future version. Please create a mask and filter using `.loc` instead
fb.last("1W")

```
Out[11]:
```

	open	high	low	close	volume	trading_volume
date						
2018-12-31	134.45	134.64	129.95	131.09	24625308	low

For the next few examples, we need datetimes, so we will read in the stock data per minute file:

```
In [13]: stock = pd.read_csv(
    "fb_week_of_may_20_per_minute.csv", index_col="date", parse_dates=True,
    date_parser=lambda x: pd.to_datetime(x, format="%Y-%m-%d %H-%M")
)
stock.head()
```

C:\Users\Eleazar\AppData\Local\Temp\ipykernel_4892\3153863462.py:1: FutureWarning: The argument 'date_parser' is deprecated and will be removed in a future version. Please use 'date_format' instead, or read your data in as 'object' dtype and then call 'to_datetime'.

```
stock = pd.read_csv(
```

```
Out[13]:
```

	open	high	low	close	volume
date					
2019-05-20 09:30:00	181.6200	181.6200	181.6200	181.6200	159049.0
2019-05-20 09:31:00	182.6100	182.6100	182.6100	182.6100	468017.0
2019-05-20 09:32:00	182.7458	182.7458	182.7458	182.7458	97258.0
2019-05-20 09:33:00	182.9500	182.9500	182.9500	182.9500	43961.0
2019-05-20 09:34:00	183.0600	183.0600	183.0600	183.0600	79562.0

We can use the Grouper to roll up our data to the daily level along with first and last

```
In [15]: stock.groupby(pd.Grouper(freq="1D")).agg({
    "open": "first",
    "high": "max",
    "low": "min",
    "close": "last",
    "volume": "sum"
})
```

```
Out[15]:
```

	open	high	low	close	volume
date					
2019-05-20	181.62	184.1800	181.6200	182.72	10044838.0
2019-05-21	184.53	185.5800	183.9700	184.82	7198405.0
2019-05-22	184.81	186.5603	184.0120	185.32	8412433.0
2019-05-23	182.50	183.7300	179.7559	180.87	12479171.0
2019-05-24	182.33	183.5227	181.0400	181.06	7686030.0

The `at_time()` method allows us to pull out all datetimes that match a certain time. Here, we can grab all the rows from the time the stock market opens (930 AM):

```
In [17]: stock.at_time("9:30")
```

```
Out[17]:
```

	open	high	low	close	volume
date					
2019-05-20 09:30:00	181.62	181.62	181.62	181.62	159049.0
2019-05-21 09:30:00	184.53	184.53	184.53	184.53	58171.0
2019-05-22 09:30:00	184.81	184.81	184.81	184.81	41585.0
2019-05-23 09:30:00	182.50	182.50	182.50	182.50	121930.0
2019-05-24 09:30:00	182.33	182.33	182.33	182.33	52681.0

We can use `between_time()` to grab data for the last two minutes of trading daily:

```
In [19]: stock.between_time("15:59", "16:00")
```

```
Out[19]:
```

	open	high	low	close	volume
date					
2019-05-20 15:59:00	182.915	182.915	182.915	182.915	134569.0
2019-05-20 16:00:00	182.720	182.720	182.720	182.720	1113672.0
2019-05-21 15:59:00	184.840	184.840	184.840	184.840	61606.0
2019-05-21 16:00:00	184.820	184.820	184.820	184.820	801080.0
2019-05-22 15:59:00	185.290	185.290	185.290	185.290	96099.0
2019-05-22 16:00:00	185.320	185.320	185.320	185.320	1220993.0
2019-05-23 15:59:00	180.720	180.720	180.720	180.720	109648.0
2019-05-23 16:00:00	180.870	180.870	180.870	180.870	1329217.0
2019-05-24 15:59:00	181.070	181.070	181.070	181.070	52994.0
2019-05-24 16:00:00	181.060	181.060	181.060	181.060	764906.0

On average, are more shares traded within the first 30 minutes of trading or in the last 30 minutes? We can combine `between_time()` with `Groupers` and `filter()` from the `aggregation.ipynb` notebook to answer this question. For the week in question, more are traded on average around opening time than closing time:

```
In [21]: shares_first_30_min = stock\  
        .between_time("9:30", "10:00")\  
        .groupby(pd.Grouper(freq="1D"))\  
        .filter(lambda x: (x.volume > 0).all())\  
        .volume.mean()  
shares_last_30_min = stock\  
        .between_time("15:59", "16:00")  
        .groupby(pd.Grouper(freq="1D"))  
        .filter(lambda x: (x.volume > 0).all())  
        .volume.mean()
```

```

        .between_time("15:30", "16:00")\
        .groupby(pd.Grouper(freq="1D"))\
        .filter(lambda x: (x.volume > 0).all())\
        .volume.mean()
shares_first_30_min - shares_last_30_min

```

Out[21]: 18592.967741935485

In cases where time doesn't matter, we can normalize the times to midnight:

```

In [23]: pd.DataFrame(
        dict(before=stock.index, after=stock.index.normalize())
    ).head()

```

Out[23]:

	before	after
0	2019-05-20 09:30:00	2019-05-20
1	2019-05-20 09:31:00	2019-05-20
2	2019-05-20 09:32:00	2019-05-20
3	2019-05-20 09:33:00	2019-05-20
4	2019-05-20 09:34:00	2019-05-20

Note that we can also use `normalize()` on a Series object after accessing the `dt` attribute:

```

In [25]: stock.index.to_series().dt.normalize().head()

```

Out[25]:

```

date
2019-05-20 09:30:00    2019-05-20
2019-05-20 09:31:00    2019-05-20
2019-05-20 09:32:00    2019-05-20
2019-05-20 09:33:00    2019-05-20
2019-05-20 09:34:00    2019-05-20
Name: date, dtype: datetime64[ns]

```

Shifting for lagged data

We can use `shift()` to create some lagged data. By default, the shift will be one period. For example, we can use `shift()` to create a new column that indicates the previous day's closing price. From this new column, we can calculate the price change due to after hours trading (after the close one day right up to the open the following day):


```

In [27]: fb.assign(
        prior_close=lambda x: x.close.shift(),
        after_hours_change_in_price=lambda x: x.open - x.prior_close,
        abs_change=lambda x: x.after_hours_change_in_price.abs()
    ).nlargest(5, "abs_change")

```

Out[27]:

	open	high	low	close	volume	trading_volume	prior_close	after_hours_
date								
2018-07-26	174.89	180.13	173.75	176.26	169803668	high	217.50	
2018-04-26	173.22	176.27	170.80	174.16	77556934	med	159.69	
2018-01-12	178.06	181.48	177.40	179.37	77551299	med	187.77	
2018-10-31	155.00	156.40	148.96	151.79	60101251	low	146.22	
2018-03-19	177.01	177.17	170.06	172.56	88140060	med	185.09	



The `tshift()` method will shift the `DatetimeIndex` rather than the data. However, if the goal is to add/subtract time we can use `pd.Timedelta` :

```
In [29]: pd.date_range("2018-01-01", freq="D", periods=5) + pd.Timedelta("9 hours 30 minutes")
```

```
Out[29]: DatetimeIndex(['2018-01-01 09:30:00', '2018-01-02 09:30:00',
                        '2018-01-03 09:30:00', '2018-01-04 09:30:00',
                        '2018-01-05 09:30:00'],
                        dtype='datetime64[ns]', freq='D')
```

When working with stock data, we only have data for the dates the market was open. We can use `first_valid_index()` to give us the index of the first non-null entry in our data. For September 2018, this is September 4th:

```
In [31]: fb.index = pd.to_datetime(fb.index) # To change data type to "datetime"

first_valid = fb.loc["2018-09"].first_valid_index()
print(first_valid)
```

```
2018-09-04 00:00:00
```

Conversely, we can use `last_valid_index()` to get the last entry of non-null data. For September 2018, this is September 28th:

```
In [33]: last_valid = fb.loc["2018-09"].last_valid_index()
print(last_valid)
```

```
2018-09-28 00:00:00
```

We can use `asof()` to find the last non-null data before the point we are looking for, if it isn't in the index. From the previous result, we know that the market was not open on September 30th. It also isn't in the index:

```
In [35]: fb.index.isin(["2018-09-30"]).any() # Checks if "2018-09-30" exists in the index
```

C:\Users\Eleazar\AppData\Local\Temp\ipykernel_4892\3112964907.py:1: FutureWarning: The behavior of 'isin' with dtype=datetime64[ns] and castable values (e.g. strings) is deprecated. In a future version, these will not be considered matching by isin. Explicitly cast to the appropriate dtype before calling isin instead.

```
fb.index.isin(["2018-09-30"]).any() # Checks if '2018-09-30' exists in the index
```

```
Out[35]: False
```

```
In [36]: exists = fb.index.isin([pd.Timestamp("2018-09-30")])
print(exists.any())
```

```
False
```

If we ask for it, we will get the data from the index we got from fb['2018-09'].last_valid_index(), which was September 28th:

```
In [38]: fb.asof("2018-09-30")
```

```
Out[38]: open          168.33
high           168.79
low            162.56
close          164.46
volume         34265638
trading_volume low
Name: 2018-09-30 00:00:00, dtype: object
```

Differenced data

Using the diff() method is a quick way to calculate the difference between the data and a lagged version of it. By default, it will yield the result of data - data.shift() :

```
In [40]: (
    fb.drop(columns="trading_volume")
    - fb.drop(columns="trading_volume").shift()
).equals(
    fb.drop(columns="trading_volume").diff()
)
```

```
Out[40]: True
```

We can use this to see how Facebook stock changed day-over-day:

```
In [42]: fb.drop(columns="trading_volume").diff().head()
```

```
Out[42]:
```

	open	high	low	close	volume
date					
2018-01-02	NaN	NaN	NaN	NaN	NaN
2018-01-03	4.20	3.20	3.7800	3.25	-1265340.0
2018-01-04	3.02	1.43	2.7696	-0.34	-3005667.0
2018-01-05	0.69	0.69	0.8304	2.52	-306361.0
2018-01-08	1.61	2.00	1.4000	1.43	4420191.0

We can specify the number of periods, can be any positive or negative integer:m

```
In [44]: fb.drop(columns="trading_volume").diff(-3).head()
```

```
Out[44]:
```

	open	high	low	close	volume
date					
2018-01-02	-7.91	-5.32	-7.3800	-5.43	4577368.0
2018-01-03	-5.32	-4.12	-5.0000	-3.61	-1108163.0
2018-01-04	-3.80	-2.59	-3.0004	-3.54	1487839.0
2018-01-05	-1.35	-0.99	-0.7000	-0.99	3044641.0
2018-01-08	-1.20	0.50	-1.0500	0.51	8406139.0

Resampling

Sometimes the data is at a granularity that isn't conducive to our analysis. Consider the case where we have data per minute for the full year of 2018. Let's see what happens if we try to plot this. Plotting will be covered in the next module, so don't worry too much about the code. First, we import matplotlib for plotting:


```
In [47]: import matplotlib.pyplot as plt
```

Then we will look at the plot at the minute level and at the daily aggregated level (summed):

```
In [57]: np.random.seed(0)
index = pd.date_range("2018-01-01", freq="min", periods=365*24*60)
raw = pd.DataFrame(
    np.random.uniform(0, 10, size=index.shape[0]), index=index
)
fig, axes = plt.subplots(1, 2, figsize=(15, 5))
raw.plot(legend=False, ax=axes[0], title="raw data")
raw.resample("1D").sum().plot(legend=False, ax=axes[1], title="daily totals")
for ax in axes:
    ax.set_xlabel("date")
    ax.set_ylabel("events")
```



```
plt.suptitle("Raw versus Resampled Data")
plt.show()
```



The plot on the left has so much data we can't see anything. However, when we aggregate to the daily totals, we see the data. We can alter the granularity of the data we are working with using resampling. Recall our minute-by-minute stock data:

```
In [51]: stock.head()
```

```
Out[51]:
```

	open	high	low	close	volume
date					
2019-05-20 09:30:00	181.6200	181.6200	181.6200	181.6200	159049.0
2019-05-20 09:31:00	182.6100	182.6100	182.6100	182.6100	468017.0
2019-05-20 09:32:00	182.7458	182.7458	182.7458	182.7458	97258.0
2019-05-20 09:33:00	182.9500	182.9500	182.9500	182.9500	43961.0
2019-05-20 09:34:00	183.0600	183.0600	183.0600	183.0600	79562.0

We can resample this to get to a daily frequency:

```
In [53]: stock.resample("1D").agg({
    "open": "first",
    "high": "max",
    "low": "min",
    "close": "last",
    "volume": "sum"
})
```

Out[53]:

	open	high	low	close	volume
date					
2019-05-20	181.62	184.1800	181.6200	182.72	10044838.0
2019-05-21	184.53	185.5800	183.9700	184.82	7198405.0
2019-05-22	184.81	186.5603	184.0120	185.32	8412433.0
2019-05-23	182.50	183.7300	179.7559	180.87	12479171.0
2019-05-24	182.33	183.5227	181.0400	181.06	7686030.0

We can downsample to quarterly data:

In [55]: `fb.resample("Q").mean()`

```
C:\Users\Eleazar\AppData\Local\Temp\ipykernel_4892\1396362074.py:1: FutureWarning:
'Q' is deprecated and will be removed in a future version, please use 'QE' instead.
fb.resample("Q").mean()
```

TypeError

Traceback (most recent call last)

Cell In[55], line 1

```
----> 1 fb.resample("Q").mean()
```

File ~\anaconda3\Lib\site-packages\pandas\core\resample.py:1384, in Resampler.mean(self, numeric_only, *args, **kwargs)

```
1382 maybe_warn_args_and_kwargs(type(self), "mean", args, kwargs)
```

```
1383 nv.validate_resampler_func("mean", args, kwargs)
```

```
-> 1384 return self._downsample("mean", numeric_only=numeric_only)
```

File ~\anaconda3\Lib\site-packages\pandas\core\resample.py:1782, in DatetimeIndexResampler._downsample(self, how, **kwargs)

```
1779 # we are downsampling
```

```
1780 # we want to call the actual grouper method here
```

```
1781 if self.axis == 0:
```

```
-> 1782     result = obj.groupby(self._grouper).aggregate(how, **kwargs)
```

```
1783 else:
```

```
1784     # test_resample_axis1
```

```
1785     result = obj.T.groupby(self._grouper).aggregate(how, **kwargs).T
```

File ~\anaconda3\Lib\site-packages\pandas\core\groupby\generic.py:1432, in DataFrameGroupBy.aggregate(self, func, engine, engine_kwargs, *args, **kwargs)

```
1429     kwargs["engine_kwargs"] = engine_kwargs
```

```
1431 op = GroupByApply(self, func, args=args, kwargs=kwargs)
```

```
-> 1432 result = op.agg()
```

```
1433 if not is_dict_like(func) and result is not None:
```

```
1434     # GH #52849
```

```
1435     if not self.as_index and is_list_like(func):
```

File ~\anaconda3\Lib\site-packages\pandas\core\apply.py:187, in Apply.agg(self)

```
184 kwargs = self.kwargs
```

```
186 if isinstance(func, str):
```

```
--> 187     return self.apply_str()
```

```
189 if is_dict_like(func):
```

```
190     return self.agg_dict_like()
```

File ~\anaconda3\Lib\site-packages\pandas\core\apply.py:603, in Apply.apply_str(self, f)

```
601     else:
```

```
602         self.kwargs["axis"] = self.axis
```

```
--> 603 return self._apply_str(obj, func, *self.args, **self.kwargs)
```

File ~\anaconda3\Lib\site-packages\pandas\core\apply.py:693, in Apply._apply_str(self, f, obj, func, *args, **kwargs)

```
691 f = getattr(obj, func)
```

```
692 if callable(f):
```

```
--> 693     return f(*args, **kwargs)
```

```
695 # people may aggregate on a non-callable attribute
```

```
696 # but don't let them think they can pass args to it
```

```
697 assert len(args) == 0
```

File ~\anaconda3\Lib\site-packages\pandas\core\groupby\groupby.py:2452, in GroupBy.mean(self, numeric_only, engine, engine_kwargs)

```
2445     return self._numba_agg_general(
```

```
2446         grouped_mean,
```

```

2447         executor.float_dtype_mapping,
2448         engine_kwargs,
2449         min_periods=0,
2450     )
2451 else:
-> 2452     result = self._cython_agg_general(
2453         "mean",
2454         alt=lambda x: Series(x, copy=False).mean(numeric_only=numeric_only),
2455         numeric_only=numeric_only,
2456     )
2457     return result.__finalize__(self.obj, method="groupby")

```

File ~\anaconda3\Lib\site-packages\pandas\core\groupby\groupby.py:1998, in GroupBy._cython_agg_general(self, how, alt, numeric_only, min_count, **kwargs)

```

1995     result = self._agg_py_fallback(how, values, ndim=data.ndim, alt=alt)
1996     return result
-> 1998 new_mgr = data.grouped_reduce(array_func)
1999 res = self._wrap_agged_manager(new_mgr)
2000 if how in ["idxmin", "idxmax"]:

```

File ~\anaconda3\Lib\site-packages\pandas\core\internals\managers.py:1472, in BlockManager.grouped_reduce(self, func)

```

1470         result_blocks = extend_blocks(applied, result_blocks)
1471     else:
-> 1472         applied = blk.apply(func)
1473         result_blocks = extend_blocks(applied, result_blocks)
1475 if len(result_blocks) == 0:

```

File ~\anaconda3\Lib\site-packages\pandas\core\internals\blocks.py:393, in Block.apply(self, func, **kwargs)

```

387 @final
388 def apply(self, func, **kwargs) -> list[Block]:
389     """
390     apply the function to my values; return a block if we are not
391     one
392     """
--> 393     result = func(self.values, **kwargs)
395     result = maybe_coerce_values(result)
396     return self._split_op_result(result)

```

File ~\anaconda3\Lib\site-packages\pandas\core\groupby\groupby.py:1973, in GroupBy._cython_agg_general.<locals>.array_func(values)

```

1971 def array_func(values: ArrayLike) -> ArrayLike:
1972     try:
-> 1973         result = self._grouper._cython_operation(
1974             "aggregate",
1975             values,
1976             how,
1977             axis=data.ndim - 1,
1978             min_count=min_count,
1979             **kwargs,
1980         )
1981     except NotImplementedError:
1982         # generally if we have numeric_only=False
1983         # and non-applicable functions
1984         # try to python agg

```

```

1985         # TODO: shouldn't min_count matter?
1986         # TODO: avoid special casing SparseArray here
1987         if how in ["any", "all"] and isinstance(values, SparseArray):

```

File ~\anaconda3\Lib\site-packages\pandas\core\groupby\ops.py:831, in BaseGrouper._cython_operation(self, kind, values, how, axis, min_count, **kwargs)

```

829 ids, _, _ = self.group_info
830 ngroups = self.ngroups
--> 831 return cy_op.cython_operation(
832     values=values,
833     axis=axis,
834     min_count=min_count,
835     comp_ids=ids,
836     ngroups=ngroups,
837     **kwargs,
838 )

```

File ~\anaconda3\Lib\site-packages\pandas\core\groupby\ops.py:541, in WrappedCythonOp.cython_operation(self, values, axis, min_count, comp_ids, ngroups, **kwargs)

```

537 self._validate_axis(axis, values)
539 if not isinstance(values, np.ndarray):
540     # i.e. ExtensionArray
--> 541     return values._groupby_op(
542         how=self.how,
543         has_dropped_na=self.has_dropped_na,
544         min_count=min_count,
545         ngroups=ngroups,
546         ids=comp_ids,
547         **kwargs,
548     )
550 return self._cython_op_ndim_compat(
551     values,
552     min_count=min_count,
553     (...)
554     **kwargs,
555 )

```

File ~\anaconda3\Lib\site-packages\pandas\core\arrays\categorical.py:2740, in Categorical._groupby_op(self, how, has_dropped_na, min_count, ngroups, ids, **kwargs)

```

2738     if kind == "transform":
2739         raise TypeError(f"{dtype} type does not support {how} operations")
-> 2740     raise TypeError(f"{dtype} dtype does not support aggregation '{how}'")
2742 result_mask = None
2743 mask = self.isna()

```

TypeError: category dtype does not support aggregation 'mean'

```

In [59]: # To select all that are numeric in data type
fb_numeric = fb.select_dtypes(include=["number"])

# Resample and apply mean to the numeric columns
fb_resampled = fb_numeric.resample("QE").mean()
fb_resampled

```

```
Out[59]:
```

	open	high	low	close	volume
date					
2018-03-31	179.472295	181.794659	177.040428	179.551148	3.292640e+07
2018-06-30	180.373770	182.277689	178.595964	180.704688	2.405532e+07
2018-09-30	180.812130	182.890886	178.955229	181.028492	2.701982e+07
2018-12-31	145.272460	147.620121	142.718943	144.868730	2.697433e+07

We can also use `apply()`. Here, we show the quarterly change from start to end:

```
In [62]: fb.drop(columns="trading_volume").resample("QE").apply(
          lambda x: x.loc[x.index[-1]] - x.loc[x.index[0]]
        )
```

```
Out[62]:
```

	open	high	low	close	volume
date					
2018-03-31	-22.53	-20.1600	-23.410	-21.63	41282390
2018-06-30	39.51	38.3997	39.844	38.93	-20984389
2018-09-30	-25.04	-28.6600	-29.660	-32.90	20304060
2018-12-31	-28.58	-31.2400	-31.310	-31.35	-1782369

Consider the following melted stock data by the minute. We don't see the OHLC data directly:

```
In [65]: melted_stock = pd.read_csv('melted_stock_data.csv', index_col='date', parse_dates=True)
          melted_stock.head()
```

```
Out[65]:
```

	price
date	
2019-05-20 09:30:00	181.6200
2019-05-20 09:31:00	182.6100
2019-05-20 09:32:00	182.7458
2019-05-20 09:33:00	182.9500
2019-05-20 09:34:00	183.0600

We can use the `ohlc()` method after resampling to recover the OHLC columns:

```
In [68]: melted_stock.resample("1D").ohlc()["price"]
```

Out[68]:

	open	high	low	close
--	------	------	-----	-------

date				
2019-05-20	181.62	184.1800	181.6200	182.72
2019-05-21	184.53	185.5800	183.9700	184.82
2019-05-22	184.81	186.5603	184.0120	185.32
2019-05-23	182.50	183.7300	179.7559	180.87
2019-05-24	182.33	183.5227	181.0400	181.06

Alternatively, we can upsample to increase the granularity. Note this will introduce NaN values:

In [71]: `fb.resample("6h").asfreq().head()`

Out[71]:

	open	high	low	close	volume	trading_volume
--	------	------	-----	-------	--------	----------------

date						
2018-01-02 00:00:00	177.68	181.58	177.55	181.42	18151903.0	low
2018-01-02 06:00:00	NaN	NaN	NaN	NaN	NaN	NaN
2018-01-02 12:00:00	NaN	NaN	NaN	NaN	NaN	NaN
2018-01-02 18:00:00	NaN	NaN	NaN	NaN	NaN	NaN
2018-01-03 00:00:00	181.88	184.78	181.33	184.67	16886563.0	low

There are many ways to handle these NaN values. We can forward-fill with `pad()`

In [74]: `fb.resample("6h").ffill().head() # The pad does not work`

Out[74]:

	open	high	low	close	volume	trading_volume
--	------	------	-----	-------	--------	----------------

date						
2018-01-02 00:00:00	177.68	181.58	177.55	181.42	18151903	low
2018-01-02 06:00:00	177.68	181.58	177.55	181.42	18151903	low
2018-01-02 12:00:00	177.68	181.58	177.55	181.42	18151903	low
2018-01-02 18:00:00	177.68	181.58	177.55	181.42	18151903	low
2018-01-03 00:00:00	181.88	184.78	181.33	184.67	16886563	low

We can specify a specific value or a method with `fillna()` :

In [77]: `fb.resample("6h").fillna("nearest").head()`

```
C:\Users\Eleazar\AppData\Local\Temp\ipykernel_4892\1460147231.py:1: FutureWarning: DatetimeIndexResampler.fillna is deprecated and will be removed in a future version. Use obj.ffill(), obj.bfill(), or obj.nearest() instead.
fb.resample("6h").fillna("nearest").head()
```

```
Out[77]:
```

	open	high	low	close	volume	trading_volume
date						
2018-01-02 00:00:00	177.68	181.58	177.55	181.42	18151903	low
2018-01-02 06:00:00	177.68	181.58	177.55	181.42	18151903	low
2018-01-02 12:00:00	181.88	184.78	181.33	184.67	16886563	low
2018-01-02 18:00:00	181.88	184.78	181.33	184.67	16886563	low
2018-01-03 00:00:00	181.88	184.78	181.33	184.67	16886563	low

We can use `asfreq()` and `assign()` to specify the action per column:

```
In [80]: fb.resample("6H").asfreq().assign(
    volume=lambda x: x.volume.fillna(0), # Place 0 when market is closed
    close=lambda x: x.close.fillna(method="ffill"), # To carry forward
    # take the closing price if these aren't available
    open=lambda x: np.where(x.open.isnull(), x.close, x.open),
    high=lambda x: np.where(x.high.isnull(), x.close, x.high),
    low=lambda x: np.where(x.low.isnull(), x.close, x.low)
).head()
```

```
C:\Users\Eleazar\AppData\Local\Temp\ipykernel_4892\1702124778.py:1: FutureWarning: 'H' is deprecated and will be removed in a future version, please use 'h' instead.
fb.resample("6H").asfreq().assign(
C:\Users\Eleazar\AppData\Local\Temp\ipykernel_4892\1702124778.py:3: FutureWarning: Series.fillna with 'method' is deprecated and will raise in a future version. Use obj.j.ffill() or obj.bfill() instead.
close=lambda x: x.close.fillna(method="ffill"), # carry forward
```

```
Out[80]:
```

	open	high	low	close	volume	trading_volume
date						
2018-01-02 00:00:00	177.68	181.58	177.55	181.42	18151903.0	low
2018-01-02 06:00:00	181.42	181.42	181.42	181.42	0.0	NaN
2018-01-02 12:00:00	181.42	181.42	181.42	181.42	0.0	NaN
2018-01-02 18:00:00	181.42	181.42	181.42	181.42	0.0	NaN
2018-01-03 00:00:00	181.88	184.78	181.33	184.67	16886563.0	low

Merging

We saw merging examples the `querying_and_merging` notebook. However, they all matched based on keys. With time series, it is possible that they are so granular that we never have

the same time for multiple entries. Let's work with some stock data at different granularities:

```
In [84]: import sqlite3
with sqlite3.connect("stocks.db") as connection:
    fb_prices = pd.read_sql(
        "SELECT * FROM fb_prices", connection,
        index_col="date", parse_dates=["date"]
    )
    aapl_prices = pd.read_sql(
        "SELECT * FROM aapl_prices", connection,
        index_col="date", parse_dates=["date"]
    )
```

The Facebook prices are at the minute granularity:

```
In [87]: fb_prices.index.second.unique()
```

```
Out[87]: Index([0], dtype='int32', name='date')
```

However, the Apple prices have information for the second:

```
In [90]: aapl_prices.index.second.unique()
```

```
Out[90]: Index([ 0, 52, 36, 34, 55, 35,  7, 12, 59, 17,  5, 20, 26, 23, 54, 49, 19, 53,
                11, 22, 13, 21, 10, 46, 42, 38, 33, 18, 16,  9, 56, 39,  2, 50, 31, 58,
                48, 24, 29,  6, 47, 51, 40,  3, 15, 14, 25,  4, 43,  8, 32, 27, 30, 45,
                1, 44, 57, 41, 37, 28],
                dtype='int32', name='date')
```

We can perform an asof merge to try to line these up the best we can. We specify how to handle the mismatch with the direction and tolerance parameters. We will fill in with the direction of nearest and a tolerance of 30 seconds. This will place the Apple data with the minute that it is closest to, so 93152 will go with 932 and 93707 will go with 937. Since the times are on the index, we pass left_index and right_index, as we did with merges earlier this chapter:

```
In [93]: pd.merge_asof(
    fb_prices, aapl_prices,
    left_index=True, right_index=True, # datetimes are in the index
    # merge with nearest minute
    direction="nearest", tolerance=pd.Timedelta(30, unit="s")
).head()
```

Out[93]:

	FB	AAPL
date		
2019-05-20 09:30:00	181.6200	183.5200
2019-05-20 09:31:00	182.6100	NaN
2019-05-20 09:32:00	182.7458	182.8710
2019-05-20 09:33:00	182.9500	182.5000
2019-05-20 09:34:00	183.0600	182.1067

If we don't want to lose the seconds information with the Apple data, we can use `pd.merge_ordered()` instead, which will interleave the two. Note this is an outer join by default (`how` parameter). The only catch here is that we need to reset the index in order to join on it:

```
In [96]: pd.merge_ordered(
          fb_prices.reset_index(), aapl_prices.reset_index()
          ).set_index("date").head()
```

Out[96]:

	FB	AAPL
date		
2019-05-20 09:30:00	181.6200	183.520
2019-05-20 09:31:00	182.6100	NaN
2019-05-20 09:31:52	NaN	182.871
2019-05-20 09:32:00	182.7458	NaN
2019-05-20 09:32:36	NaN	182.500

We can pass a `fill_method` to handle NaN values:

```
In [99]: pd.merge_ordered(
          fb_prices.reset_index(), aapl_prices.reset_index(),
          fill_method="ffill"
          ).set_index("date").head()
```

Out[99]:

	FB	AAPL
date		
2019-05-20 09:30:00	181.6200	183.520
2019-05-20 09:31:00	182.6100	183.520
2019-05-20 09:31:52	182.6100	182.871
2019-05-20 09:32:00	182.7458	182.871
2019-05-20 09:32:36	182.7458	182.500

Alternatively, we can use `fillna()` .

In []: