

OVERVIEW	TYPE	EXAMPLE ID
TYPE	PHYSICAL - COMPONENT - ID	P-X-1
EXAMPLE	PHYSICAL - BUTTON - 1	P-B-1
EXAMPLE	PHYSICAL - FRAME - 1	P-F-1
TYPE	DIGITAL - COMPONENT - ID	D-X-1
EXAMPLE	DIGITAL - SCREEN - ID	D-S-1
EXAMPLE	DIGITAL - DATA - ID	D-D-1

ID	FUNCTION	PRIORITY	MoSCoW Alignment	DESCRIPTION
P-B-1	Primary Button Press	HIGH	Must Have	Deliberate single press increments counter (+1) for current pattern.
P-F-1	Static visual indicator	HIGH	Must Have	Non-digital visual reminder of current state (e.g., nicotine withdrawal stage).
D-S-1	Screen feedback on press	HIGH	Must Have	OLED screen displays instant visual response / count upon pressing the button.
P-B-2	5-second long hold	MEDIUM	Should Have	Switches active habit/pattern to track (matches "Track two or more patterns").
D-S-2	Milestone visual response	MEDIUM	Should Have	Displays visual symbols/animations when hitting press milestones.
D-D-1	Timestamped data logging	MEDIUM	Should Have	Stores date/time (24H + XX/XX/XXXX) to MicroSD card to enable "Tracking over time to see patterns".

NAME OF COMPONENT	TYPE	DIMENSIONS (L x W x H) in MM
Adafruit Feather nRF52840 Express	MICRO CONTROLLER	51mm x 23mm x 7.2mm
Adafruit FeatherWing OLED 128x64 (assembled, STEMMA QT) (SSD1306)	DISPLAY & 3 BUTTONS	50.9 mm x 22.9mm x 10.5mm (PRE SOLDERED)
Adafruit Adalogger FeatherWing (RTC + SD)	RTC + STORAGE (Coin-cell battery + MicroSD needed)	50.8mm x 22.9mm x 1.6mm
Adafruit 3.7V 150mAh LiPo	Battery	19.75mm x 26.02mm x 3.8mm
Adafruit panel-mount momentary pushbutton	(Main) button	18mm x 18mm x 29.4mm
Main electronics assembly + Main button (seperate)	Fully assembled	51mm x 26.02mm x 23.1mm + 18mm x 18mm x 29.4mm