



GERBANG SMS KERAJAAN

HTTP API SMS Specification v1.5.1



## CHANGE HISTORY

| Version | Author         | Description of Version  | Date                           |
|---------|----------------|---|--------------------------------|
| 1.0     | Shahrul Izzam  | Initial version   | 27 <sup>th</sup> June 2008     |
| 1.1     | Shahrul Izzam  | Added Table 1.2, 1.4 & 1.7<br>Added new param on Table 1.2 & 1.6                                    | 6 <sup>th</sup> July 2008      |
| 1.2     | Shahrul Izzam  | Added new Param (telco, guid) on Table 1.6<br>& guid on Table 1.3<br>Change type on Table 1.3 & 1.6 | 5 <sup>th</sup> August 2008    |
| 1.3     | Shahrul Izzam  | Added ErrorCode references. New param on table 1.6 (Username & Password)                            | 19 <sup>th</sup> February 2009 |
| 1.4     | Mohd Faizal M. | Added Telco TUNETALK/UMOBILE  | 13 <sup>th</sup> January 2014  |
| 1.5     | Mohd Faizal M. | Update Character for Details  | 23 <sup>th</sup> March 2015    |
| 1.5.1   | Mohd Faizal M. | Adjust Process MT to Send SMS   | 30 <sup>th</sup> March 2015    |



## FUNCTIONAL OVERVIEW

Internetworking between DAPAT and AGENCY

- Message from DAPAT to AGENCY
- Message from AGENCY to DAPAT

### DAPAT to AGENCY

#### Receive SMS




Table 1.1 – Receive SMS process flow

DAPAT deliver short message (MO) to AGENCY. AGENCY will process the request. (Eg: IOD Services)



### Transition Diagram of IOD Services




Table 1.2 – Transition diagram IOD services

### Receive SMS Parameters

| Parameter | Type         | Description   |
|-----------|--------------|---|
| Keyword   | Varchar(10)  | Keyword for agency.<br>Eg: SKMM/JPJ                             |
| Smsid     | Varchar(50)  | Id for each sms which will be unique.                           |
| Shortcode | Varchar(5)   | Shortcode. Eg: 15888  |
| Sender    | Varchar(20)  | Sender's mobile number in +6xxxxxxxxx<br>Eg: +60121123895       |
| Telco     | Varchar(10)  | Telco for sender.<br>Eg:<br>MAXIS/DIGI/CELCOM/TUNETALK /UMOBILE |
| Details   | Varchar(160) | Sender's message in string format                               |
| Guid      | Varchar(50)  | Msg id. A unique running number.                                |

Table 1.3 – Receive SMS parameters



- 1) Agency application must acknowledge the MO by returning a status code of 200.  
The transaction will be made unsuccessful under the following conditions:
  - a. Agency return other than 200 status code.
  - b. Agency returns nothing.
  - c. Agency returns error codes.
- 2) Agency to inform DAPAT of application's URL to be registered in the e-hubung portal.
- 3) All parameter names are not case sensitive.

POST/GET

/receivesms.aspx?keyword=MAMPU&smsid=235478&shortcode=15888&sender=%2B60121123456&telco=MAXIS&details=hello+world+good+morning+world&guid=1234568789

#### Receive SMS response string

| Parameter | Description   |
|-----------|---|
| deliver   | 0 – send immediately<br>1 – send later                            |
| reply     | MT message in 150 characters<br><b>Mandatory when deliver = 0</b> |

Table 1.4 – Receive SMS response string



Below is the format of the response string.

```
HTTP/1.1 200
OK deliver:0
reply:<MT message>
```

Or

```
HTTP/1.1 200
OK deliver:1
reply:
```

#### AGENCY to DAPAT

#### Send SMS




Table 1.5 – Process MT process flow

AGENCY will send an MT to DAPAT. DAPAT will acknowledge with 200 status code.



## Send SMS Parameters

| Parameter   | Type         | Condition   |
|-------------|--------------|---|
| Username    | Varchar(20)  | Username for this account.  |
| password    | Varchar(20)  | Password for this account.  |
| keyword     | Varchar(10)  | Keyword for agency.   |
| Smsid       | Varchar(50)  | SMS Id in integer format. For bulk the smsid must be set to zero.   |
| Shortcode   | Varchar(5)   | Shortcode Eg: 15888   |
| Sender      | Varchar(20)  | Receipient's mobile number in<br>+6xxxxxxxxxx<br>Must be URL encode |
| ServiceType | Varchar(20)  | ServiceType for the MT<br>Eg:<br>PREMIUM/BULK/BULKPREPAID           |
| Details     | Varchar(140) | Reply to recipient in 140 characters<br>Must be URL encode          |
| telco       | Varchar(10)  | Telco for sender.<br>Eg:<br>MAXIS/DIGI/CELCOM/TUNETALK/UMOBILE      |
| guid        | Varchar(50)  | Value of Guid from Table 1.3. For<br>broadcast set value to 0       |

Table 1.6 – Send SMS parameters

- 1) Agency will need to supply DAPAT with IP from where the application is sending MT
- 2) DAPAT will give AGENCY a different URL according to account to initiate a HTTP POST request (MT send)
- 3) After each successful POST, DAPAT will return a 200 status code as well as the smsid.
- 4) All parameter **MUST** be URL encode.
- 5) All parameter names are not case sensitive.
- 6) Noted that, starting 1st April 2015 maximum char limit will be reduced to 140 due to GST implementation by Royal Malaysian Custom Department (RMCD). This is due to 10chars will be allocated as a GST acknowledgement. Sample of New MT Format are:

RM0.00(Excl. GST) MAMPU: Terima Kasih atas maklumbalas anda.



Below is an example of **Send SMS**

Premium service:

POST/GET

```
/sendsms.aspx?username=ammo&password=12345&keyword=MAMPU&smsid=15975369&shortcode=15888&sender=%2B60121123456&servicetype=PREMIUM&details=thanks+for+reminding+me&telco=MAXIS&guid=123456789
```

Bulk service:

POST/GET

```
/sendsms.aspx?  
username=ammo&password=12345&keyword=MAMPU &sender=%2B6012  
1123456&servicetype=BULK&details=thanks+for+reminding+me&telco=MAXIS
```

#### Send SMS response string

| Parameter | Description  |
|-----------|--|
| Errorcode | 200 – success, 000x – fail, please refer to Table 1.8          |
| mtid      | MT id. AGENCY can use the id to check on the status of the MT. |

Table 1.7 – Send SMS response string





AGENCY will receive a response string to indicate if the message has been successfully sent to DAPAT.

**[mt id]|[error code]**

HTTP/1.1 200 OK

Eg: 7854627|200

Or

**[error code]**

HTTP/1.1 200 OK

Eg: 0001

## Error Code Reference

| Error Code | Error Description     | Description  |
|------------|-----------------------|--|
| 0001       | AUTHENTICATION FAILED | Your “username” and “password” values are Invalid or you do not have an account.                 |
| 0002       | INVALID SHORTCODE     | The gateway doesn’t suppose this Shortcode.  |
| 0003       | KEYWORD NOT ALLOWED   | Invalid keyword/ keyword does not exist.   |
| 0004       | MALFORMED DESTINATION | Your DESTINATION field is invalid.   |
| 0005       | MALFORMED BODY LENGTH | Your SMS Body is invalid. Must be within 1-140 characters long.                                  |
| 0006       | MALFORMED TELCO       | Your TELCO field is invalid.   |
| 0007       | INVALID CHARGE FIELD  | You have entered invalid data (non-integer) in the charge field. Charges allowed are 0000 & 0020 |
| 0008       | NO RECORD FOUND       | Your GUID does not link to any message log in our Database.                                      |
| 200        | SUCCESSFUL            | Successful transaction.  |

Table 1.8 – Error Code Reference