
NS150 Active Network Control Panel








EntryPass Active Networks are designed to enhance highly customized and rapid 'real-time' changes to the underlying network operation. Brilliantly engineered with all the power you need to enable code-sending, minus unnecessary buffer time with its distributed architecture capable of processing access demand at the edge level without leveraging at the server end.





N5150 Active Network Control Panel





ACTIVE TRANSMIT

Rather than keeping the event data in the memory awaiting for host-PC to poll, controller will actively transmits the current event data to the host server as it happens, meaning events get delivered and can be act upon faster.



BUILT IN WEB SERVER

Built-in web server where network configuration such as IP address, subnet mask, server IP can be easily done upon login. No more factory programming needed as the firmware can be upgraded via the on-board web server.



HIGH PERFORMANCE

Based on the latest HCB (Hybrid Compact Board), N5100 is a high reliability, high efficiency and highly integrated intelligent multi-application control panel targeted for physical access control industry. It features a 32bits Freescale ColdFire microcontroller running at 60MHz, this control panel can fulfill most demanding requirement in physical access control environment.



AES (ADVANCE ENCRYPTION STANDARD)

By enabling AES Encryption, the controller will only communicate with platform1 where the AES key in the P1 database is match with the controller. This can avoid hacker to tap the controller then directly communicate and control the controller, for example send a pulse door command to unlock the door.



DOOR INTERLOCKING

2 In doors interlocking within the control panel, no external wiring is needed. Cross-board interlocking is achievable by checking the interlocking signal coming from second control panel before granting the accessibility to the local control panel.

Feature Highlight

Support Single Door / 2 Doors

Support Car Park Mode

Support Dynamic Reader Location

Compatible with Various Reader Technologies

ActiveTransmit & ActiveDownload

Peer To Peer Global Anti-Passback

Configurable Digital / Supervised inputs (4)

Quick Terminal Plug-in Connectors

Firmware Upgrade via Server

Reader Output Control


Onboard & Cross-Board Door Interlocking

Dynamic Operation Profile

Support 5,000 Users and 10,000 Events Memory



Basic System Diagram



Technical Specification


Hardware	Description
Dimension	158mm (w) x 90mm (H)
MCU	32bits @ 60MHz
Memory	256K Flash Memory
	32K SRAM (Buffer)
	64Mbits Non-Volatile SPI Flash Memory (Storage)
Operating Temperature	0 °C to 40 °C
Card Holder	5,000
Event Transaction	10,000Max.
Access Level	255 Sets
Digital/Supervise Inputs	Max 4, User configurable
	(Door Sensor/Request-To-Exit/Fire Input/General Purpose)
Digital Output	Max. 2 Dry contact Relay
Network Communication Port	RJ-45 Self-Negotiate 10/100mbps
Power Protection	Resettable Fuse - 2.5A
Surge Protection	TVS - Up to 15KVA
Onboard LED Control	Power / Communication / LAN / Event / Error
AC Fail Monitoring	Yes
Battery Monitoring	Yes (Firmware threshold control to shutdown control panel)
External Short Circuit Protection	At readers
Backup Battery	Yes, Apply to RTC only

Ordering Information

EP.N5100.PCB Entrypass 2 Readers Advanced Network Door Control Panel only
EP.N5100.PSU Entrypass 2 Readers Advanced Network Door Control Panel with Power Supply Unit



N5150 Active Network Control Panel





www.entrypass.net

Malaysia

No. 40, Jalan TPP 1/10, Taman Industri Puchong, Batu 12 Jalan Puchong, 47160 Puchong Selangor Darul Ehsan, Malaysia.

Tel: +603 8068 1929
Fax: +603 8062 6937
Email: info@entrypass.net

Singapore

No. 1, UBI View, #03-03, Focus ONE Building, Singapore 408555.

Tel : +65- 6841 7242
Fax : +65- 6841 3937
Email : info@entrypass.net

Indonesia

Rukan Puri Mutiara, Block BF No.17, Jln Griya Utama, Sunter Agung, Jakarta Utara, 14350, Indonesia.

Tel : +62 21 2937 6098 Email : indonesia@entrypass.net