ylog handbook

(Tools. TianJin)

ALL MATERIALS INCLUDED HEREIN ARE COPYRIGHTED AND CONFIDENTIAL UNLESS OTHERWISE INDICATED. The information is intended only for the person or entity to which it is addressed and may contain confidential and/or privileged material. Any review, retransmission, dissemination, or other use of or taking of any action in reliance upon this information by persons or entities other than the intended recipient is prohibited.

This document is subject to change without notice. Please verify that your company has the most recent specification.

Copyright © 2016 Spreadtrum Communications Inc.

1. introduction 4
2. ylog module.....4
2.1 corresponding list between ylog source and ydst.....5
2.2 ylog source.....5
2.3 ylog attribute list.....8
3. ylog_cli command line.....9
3.1 overview of ylog_cli command line.....9
3.2 explanation of ylog_cli command line.....9
3.2.1 query class.....10
3.2.2 switch class.....12
3.2.3 setting class.....13
3.2.4 delete class.....15
3.2.5 other class.....15
3.2.6 modem/wcn log rate statistic 17
4. log analysis methods and techniques. 19
4.1 ylog directory structure.....19
4.2 ylog files analysis off line.....21
4.3 analytical method of native crash and anr log.....24

abbreviation	Description
ylog	your log

Copyright 2016 Spreadtrum Communications Inc.

Revision	Author	Date	Brief
1.0	Luther Ge	2016/02/14	Initial Draft
1.1	Yanli Chen	2016/03/02	Add ylog use help
1.2	Yanli Chen	2016/03/28	Add ylog_cli at/print2android/print2kernel cmd
1.2e	Yue Zhao	2016/03/29	Translate to English
1.3	Yanli Chen	2016/04/01	Add modem/wcn log speed statistics
1.3e	Yue Zhao	2016/04/03	Translate to English

Copyright 2016 Spreadtrum Communications Inc. Confidential and Proprietary.

1. introduction

ylog (your log) is customizable background resident service, which is used for log collection, intelligent analysis, behaviour statistic and sending AT command,etc.

By default, ylog is open in userdebug reversion, while closed in user reversion. In the meanwhile, Engineering model can control switch status.

2. ylog module

ylog is a a user-space service application started by init.rc, and its default startup behavior after the boot can be aided controlled by attribute value of persist.ylog.enabled . ylog not only supports multiple ylog source parallel inputting, but multiple ydst parallel outputting. It can assign ydst output, set ydst whether attached to cache, define restart time interval, make up whether overwrite when reach the limit of segments numbers, which is based on data structure of ylog source.

Copyright 2016 Spreadtrum Communications Inc. Confidential and Proprietary.

2.1 corresponding list between ylog source and ydst



2.2 ylog source

1. Android

It covers five types log , including android_main, android_radio, android_system, android_events, android_crash, which output into a common ydst. Meanwhile, in order to improve disk efficiency, the ydst is attached to a 1M-sized cache by default.

2. kernel

It collects kernel log, and kernel ydst is attached to a 1M-sized cache by default.

3. sys_info

It collects some system-related log in regular time(two minutes). The included specific information is listed as follows.

/proc/slabinfo
/proc/buddyinfo
/proc/zoneinfo
/proc/vmstat
/proc/vmallocinfo
/proc/pagetypeinfo
/sys/module/lowmemorykiller/parameters/adj

Copyright 2016 Spreadtrum Communications Inc. Confidential and Proprietary.

```
/sys/module/lowmemorykiller/parameters/minfree
/proc/wakelocks
/d/wakeup_sources
/sys/class/backlight/sprd_backlight/brightness
/sys/kernel/debug/binder/failed_transaction_log
/sys/kernel/debug/binder/transaction_log
/sys/kernel/debug/binder/transactions
/sys/kernel/debug/binder/stats
/sys/kernel/debug/binder/state
/sys/kernel/debug/sprd_debug/cpu/cpu_usage
```

4. tcpdump

It collects ap cap log，and tcpdump ydst is attached to a 1M-sized cache by default.

5. hcidump

It collects hci bt log，and hcidump ydst is attached to a 1M-sized cache by default.

6. ylog_debug

It collects debugging information related with log, includes log rate, space usage, running status, etc, usually takes statistics once every 20 minutes.

```
/system/bin/ylog_cli ylog
/system/bin/ylog_cli speed
/system/bin/ylog_cli space
getprop ylog.killed
```

7. info

It collects system-related static information, which is captured only once when ylog starts.

```
/proc/cmdline
/proc/version
/proc/meminfo
/proc/mounts
```

Copyright 2016 Spreadtrum Communications Inc. Confidential and Proprietary.

/proc/partitions

/proc/diskstats

/proc/modules

/proc/cpuinfo

/default.prop

/data/ylog/ylog.conf

ls -l /

ls -l /dev/block/platform/*/by-name/

ls -l /dev/

getprop

cat /*.rc

all the thread pid and tid of ylog

8. journal

It's designed for monitoring ylog running status, monitor switch, and log file deletion,etc.



9. tracer

It can make data slice storage read from /d/tracing/trace_pipe, which allows to add debug information, and ajust quota values for time critical drive modules, such as usb.

10. traces

It collects tombstones in the case of native crash, and stack trace in the case of anr.

Copyright 2016 Spreadtrum Communications Inc. Confidential and Proprietary.

11. socket

It opens ylog socket to receive dataflow from evaluation software called ylog_benchmark, which can search software and system bottleneck.

12. sys_info_manual

It can trigger ylog to capture the execution results of "busybox netstat -ap" and "ps -t" manually.

2.3 ylog attribute list

1.the following attribute values indicate running status of all kinds of log.

[ylog.svc.android_crash]: [running]

[ylog.svc.android_events]: [running]

[ylog.svc.android_main]: [running]

[ylog.svc.android_radio]: [running]

[ylog.svc.android_system]: [running]

[ylog.svc.kernel]: [running]

[ylog.svc.tcpdump]: [stopped]

[ylog.svc.hcidump]: [stopped]

[ylog.svc.info]: [stopped]

[ylog.svc.journal]: [running]

[ylog.svc.socket]: [running]

[ylog.svc.sys_info]: [running]

[ylog.svc.sys_info_manual]: [stopped]

[ylog.svc.tracer]: [running]

[ylog.svc.traces]: [running]

[ylog.svc.ylog_debug]: [running]

2.ylog service master switch control

[persist.ylog.enabled]: [1]

Copyright 2016 Spreadtrum Communications Inc. Confidential and Proprietary.

3. TF card unloaded numbers

[ylog.killed]: [0]

3. ylog_cli command line

Help information of ylog_cli command line can be obtained by “adb shell ylog_cli”.

3.1 overview of ylog_cli command line

```
=== [ ylog server supported commands ] ===
kernel     -- read kernel log
-c         -- execute shell command, ex. ylog_cli -c ls / or ylog_cli -c top
flush      -- flush all the data back to disk
loglevel   -- 0:error, 1:critical, 2:warn, 3:info, 4:debug
speed      -- max speed since ylog start
ylog       -- list all existing ylog, also can start or stop it, ex.
              ylog_cli ylog                    - show each ylog short description
              ylog_cli ylog kenrel             - show ylog kernel detailed description
              ylog_cli ylog all                - show each ylog detailed description
              ylog_cli ylog all stop           - turn off all running ylog
              ylog_cli ylog all start          - turn on the previous all running ylog
              ylog_cli ylog kernel stop        - turn off the kernel ylog
              ylog_cli ylog kernel start       - turn on the kernel ylog
              ylog_cli ylog kernel get started - get the running status of kernel ylog
              ylog_cli ylog kernel timestamp 1 - 1 with timestamp, 0 without
              ylog_cli ylog kernel bypass    1 - 1 just read, not store to disk or cache, 0 store
              ylog_cli ylog kernel ydst max_segment 5       - ajust ydst segments to 5
              ylog_cli ylog kernel ydst max_segment_size 20 - ajust ydst each segment size to 20M
              ylog_cli ylog kernel ydst segment_size 5 20   - ajust ydst segments to 5, size to 20M
              ylog_cli ylog kernel cache bypass 1           - data in the cache, 1 droped, 0 save to disk
              ylog_cli ylog kernel cache timeout 500        - cacheline timeout to 500ms
              ylog_cli ylog kernel cache debuglevel 0x03    - bit0: INFO, bit1: CRITICAL, bit7: DATA
cpath      -- change log path, named 'ylog' will be created under it, ex. ylog_cli cpath /sdcard/
quota      -- give a new quota for the ylog (unit is 'M') 500M ex. ylog_cli quota 500
rylog      -- last_ylog, remove the last_ylog folder
ryloga     -- all ylog, remove the last_ylog folder and also all the current saved ylog
rylogr     -- all ylog and restart, remove last_ylog and ylog folder, then restart ylog service
space      -- check ylog root folder and last_ylog the size of taking up
freespace  -- check ylog root folder free size left now
isignal    -- 1:ignore signal, 0:process signal(default)
benchmark  -- while (1) write data to ylog/socket/open/ without timestamp
benchmarkt -- while (1) write data to ylog/socket/open/ with timestamp
test       -- test from android
rootdir    -- get the log disk root dir
cpath_last -- get the last_ylog path
history_n  -- set keep_historical_folder_numbers
setprop    -- set property, ex. ylog_cli setprop persist.ylog.enabled 1
```

3.2 explanation of ylog_cli command line

ylog_cli connects to ylog process through sockets, and support multi-class command lines, which are queries, switches, settings, deleting, etc.

3.2.1 query class

1. **Look up the top ten read/write rate since ylog boot.**

```
Transfered 7.08M Has run 00 day 00:24:41 avg_speed=4.89K/s
01. [01-01 08:00:10.818] ~ [01-01 08:00:11.818] 00 day 00:00:09 ago 359.87K/s
02. [01-01 08:00:19.838] ~ [01-01 08:00:20.847] 00 day 00:00:18 ago 261.90K/s
03. [01-01 08:00:18.838] ~ [01-01 08:00:19.838] 00 day 00:00:17 ago 201.25K/s
04. [01-01 08:24:24.362] ~ [01-01 08:24:25.363] 00 day 00:24:23 ago 182.42K/s
05. [01-01 08:04:39.867] ~ [01-01 08:04:40.868] 00 day 00:04:38 ago 182.17K/s
06. [01-01 08:16:43.176] ~ [01-01 08:16:44.176] 00 day 00:16:41 ago 180.07K/s
07. [01-01 08:02:39.823] ~ [01-01 08:02:40.823] 00 day 00:02:38 ago 180.04K/s
08. [01-01 08:18:43.227] ~ [01-01 08:18:44.227] 00 day 00:18:41 ago 178.38K/s
09. [01-01 08:12:42.063] ~ [01-01 08:12:43.063] 00 day 00:12:40 ago 177.89K/s
10. [01-01 08:08:40.959] ~ [01-01 08:08:41.959] 00 day 00:08:39 ago 177.69K/s
```

2. **Look up all kinds of log information, such as switch status, upper limit of segments and single segment's size, log-transfer counter.**

Command format: adb shell ylog_cli ylog Response format: No Root: display the current log storage path. Quota : the upper limit of log storage space. Running: show running time of ylog.




```
SPREADTRUM\yanli.chen@yanlichenubtpc:~/bug/547540/547540 (2)/#648/external_storage/2012-01-01-08-36-16$ adb shell ylog_cli ylog
--------------------------------------------------------------------------------
root = /data/ylog/ylog quota = 200.00M, running 00 day 04:41:50
--------------------------------------------------------------------------------
benchmark_socket      -> running  -> socket/open/000 (1x10.00M/10.00M, 5.00%) -> cache.socket/open/(2x512.00K) [0.00B/0.00B]
socket                -> running  -> socket/open/000 (1x10.00M/10.00M, 5.00%) -> cache.socket/open/(2x512.00K) [0.00B/0.00B]
ylog_debug            -> running  -> ylog_debug (1x1.42M/1.42M, 0.71%) [55.70K/55.70K]
info                  -> stop     -> info (1x1.42M/1.42M, 0.71%) [0.00B/0.00B]
journal               -> running  -> ylog_journal_file (1x1.42M/1.42M, 0.71%) [374.00B/374.00B]
kernel                -> running  -> kernel/000 (1x50.00M/50.00M,25.00%) -> cache.kernel/(2x512.00K) [6.62M/6.62M]
android_main          -> running  -> android/000 (1x50.00M/50.00M,25.00%) -> cache.android/(4x512.00K) [1.48M/5.07M]
android_system        -> running  -> android/000 (1x50.00M/50.00M,25.00%) -> cache.android/(4x512.00K) [125.36K/5.07M]
android_radio         -> running  -> android/000 (1x50.00M/50.00M,25.00%) -> cache.android/(4x512.00K) [3.45M/5.07M]
android_events        -> running  -> android/000 (1x50.00M/50.00M,25.00%) -> cache.android/(4x512.00K) [19.20K/5.07M]
android_crash         -> running  -> android/000 (1x50.00M/50.00M,25.00%) -> cache.android/(4x512.00K) [0.00B/5.07M]
tcpdump               -> stop     -> tcpdump/000 (1x50.00M/50.00M,25.00%) -> cache.tcpdump/(2x512.00K) [0.00B/0.00B]
hcidump               -> stop     -> hcidump/000 (1x50.00M/50.00M,25.00%) -> cache.hcidump/(2x512.00K) [0.00B/0.00B]
traces                -> running  -> traces/000 (1x20.00M/20.00M,10.00%) [0.00B/0.00B]
sys_info              -> running  -> sys_info/000 (1x50.00M/50.00M,25.00%) [6.42M/6.42M]
sys_info_manual       -> stop     -> sys_info/000 (1x50.00M/50.00M,25.00%) [0.00B/6.42M]
tracer                -> running  -> tracer/000 (1x10.00M/10.00M, 5.00%) -> cache.tracer/(2x512.00K) [4.37K/4.37K]
cp_5mode              -> running  -> cp/5mode/000 (1x10.00M/10.00M, 5.00%) -> cache.cp/5mode/(8x512.00K) [23.26M/23.26M]
cp_wcn                -> running  -> cp/wcn/000 (1x10.00M/10.00M, 5.00%) -> cache.cp/wcn/(2x512.00K) [7.06M/7.06M]
```

3. **Look up switch status of a single log, the same as ylog.svc.**xxx

Command format : ylog_cli ylog xxx get started Response format : No Opened state : 1\n Closed state : 0\n

Note: xxx can be android_main, android_system, android_radio, android_events, android_crash, tcpdump, hcidump, kernel.

4. **Look up log storage path**

Command format: adb shell ylog_cli cpath Response format: No Without TF card: /data/ylog/ylog Note : Internal storage can't support saving history log. With TF card: /storage/BE60-0FE5/ylog/ylog

Copyright 2016 Spreadtrum Communications Inc. Confidential and Proprietary.

/storage/BE60-0FE5/ylog/last_ylog

5. Look up memory space of log

Command format：adb shell ylog_cli space

Response format：No



6. Look up free space of disk that log resides on

Command format：adb shell ylog_cli freespace

Response format：/storage/BE60-0FE5/ylog/ylog -> 7.32G

7. Look up disk path that log resides on

Command format：adb shell ylog_cli rootdir

Response format：/storage/BE60-0FE5

8. Look up history log times

Command format：adb shell ylog_cli history_n

Response format：5\n keep five history log by default

9. Look up relevant information of single ylog source

Command format：adb shell ylog_cli ylog xxx

Copyright 2016 Spreadtrum Communications Inc. Confidential and Proprietary.

```
root@sp9830a_5h10_volte:/ # ylog_cli ylog android_main
--------------------------------------------------------------------------------
root = /storage/BE60-0FE5/ylog/ylog, quota = 6.58G, running 00 day 00:15:47
--------------------------------------------------------------------------------
[ android_main ] = running {
    .loglevel = 3
    .file = logcat -v threadtime -b main
    .restart_period = 2000
    .timestamp = 0
    .bypass = 0
    .mode = 194
    .ydst = 764.78K/2.33M {
        .file = /storage/BE60-0FE5/ylog/ylog/android/000
        .max_segment  = 80
        .max_segment_size  = 50.00M
        .cache= {
            .size = 512.00K
            .num = 4
            .bypass = 0
            .timeout = 1000ms
            .debuglevel = 0x02
        }
    }
}
```

Response format：Output information, including input types of ylog source, storage path, cache size, ect.

Note：xxx can be android_main, android_system, android_radio, android_events, android_crash, tcpdump, hcidump, kernel.

10. Look up all the relevant log information

Command format：adb shell ylog_cli ylog all

Response format：Output all log information, including input types, storage path, cache size, ect.

3.2.2 switch class

1. Main switch settings of ylog

Command format：

start ylog：adb shell setprop persist.ylog.enabled 1 -----> persist.ylog.enabled 1

stop ylog：adb shell setprop persist.ylog.enabled 0 -----> persist.ylog.enabled 0

2. All switch uniform settings of log

Copyright 2016 Spreadtrum Communications Inc. Confidential and Proprietary.

Command format: adb shell ylog_cli ylog all start/stop

Response format: Output all log information, including switch status, storage path, cache size, ect.

3. Switch settings of single log

Command format: adb shell ylog_cli ylog xxx start/stop

Response format: output data structure information of the log



3.2.3 setting class

1. Setting up maximum values of log segments

Command format: adb shell ylog_cli ylog xxx ydst max_segment n

Response format: output data structure information of the log

2. Setting up individual log file size, unit: M

Command format: adb shell ylog_cli ylog xxx ydst max_segment_size 20

Response format: output data structure information of the log

Copyright 2016 Spreadtrum Communications Inc. Confidential and Proprietary.

3. Setting up maximum of log segments, upper limit for log size

Command format：adb shell ylog_cli ylog xxx ydst segment_size 5 20 Response format：output data structure information of the log

4. Setting up whether print time stamps during real kernel log printing by ylog_cli.

Command format：adb shell ylog_cli ylog kernel timestamp 1/0 (yes/no) Response format：real printing of kernel log on terminal

5. Setting up whether writing log back to disk

Command format：adb shell ylog_cli ylog xxx bypass 1/0 (yes/no) Response format：output data structure information of the log

6. Setting up cache timeout

Command format：adb shell ylog_cli ylog xxx cache timeout 500 Response format：output data structure information of the log

Copyright 2016 Spreadtrum Communications Inc. Confidential and Proprietary.

7. Setting up number of history log

Command format：adb shell ylog_cli history_n N Response format：N\n

3.2.4 delete class

1. Deleting last_ylog only

Command format：adb shell rylog Response format：done\n

2. Deleting folders of ylog, last_ylog

Command format：adb shell ryloga Response format：done\n

3. Deleting folders of ylog, last_ylog, and restart ylog

Command format：adb shell rylogr Response format：done\n

3.2.5 other class

1. Get real-time kernel log

Command format：adb shell ylog_cli kernel Response format：print kernel log in real time

```
SPREADTRUM\yanli.chen@yanlichenubtpc:~/whale2/vendor/sprd/proprietories-source/ylog$ adb shell date
Sun Jan  1 08:46:04 CST 2012
SPREADTRUM\yanli.chen@yanlichenubtpc:~/whale2/vendor/sprd/proprietories-source/ylog$ adb shell ylog_cli kernel
[01-01 08:46:07.340] <4>[ 2746.664031] c0 sensor id:0, rawdata:0x31a, temp:31223
[01-01 08:46:07.340] <4>[ 2748.082366] c0 _sprdchg_timer_interrupt
[01-01 08:46:07.350] <6>[ 2748.082489] c0 sprdbat: sprdbat_charge_works-start
[01-01 08:46:07.351] <4>[ 2748.082519] c0 sprdchg_get_chg_cur rawdata * 50+300=450
[01-01 08:46:07.351] <6>[ 2748.082550] c0 sprdbat: enter sprdbat_auto_switch_cur avg_cur=89,chg_cur=450
[01-01 08:46:07.351] <6>[ 2748.082580] c0 sprdbat: chg_end_vol_l:0x105e
[01-01 08:46:07.351] <3>[ 2748.083496] c0 chg_current warning....isense:4169....vbat:4183
```

2. Flush cache to disk

Copyright 2016 Spreadtrum Communications Inc. Confidential and Proprietary.

Command format：adb shell ylog_cli flush Response format： None

```
--------------------------------------------------------------------------------
root = /storage/BE60-0FE5/ylog/ylog, quota = 6.58G, running 00 day 01:22:34
--------------------------------------------------------------------------------
[ kernel ] = running {
    .loglevel = 3
    .file = /proc/kmsg
    .restart_period = 300
    .timestamp = 1
    .bypass = 1
    .mode = 194
    .ydst = 1.47M/1.47M {
        .file = /storage/BE60-0FE5/ylog/ylog/kernel/000
        .max_segment  = 6
        .max_segment_size  = 25.00M
        .cache= {
            .size = 512.00K
            .num = 2
            .bypass = 0
            .timeout = 200ms  cache timeout 时间为：200ms
            .debuglevel = 0x02
        }
    }
}
```

3. benchmark for evaluating disk read-write rate

a. benchmark test without time stamps.

Command format：adb shell benchmark Response format： None

Copyright 2016 Spreadtrum Communications Inc.

```
root@sp9830a_5h10_volte:/storage/BE60-0FE5/ylog # ylog_cli benchmark
cmd_benchmark -> /storage/BE60-0FE5/ylog/ylog/socket/open/000 speed 4.40M/s
cmd_benchmark -> /storage/BE60-0FE5/ylog/ylog/socket/open/000 speed 4.18M/s
cmd_benchmark -> /storage/BE60-0FE5/ylog/ylog/socket/open/000 speed 5.77M/s
cmd_benchmark -> /storage/BE60-0FE5/ylog/ylog/socket/open/000 speed 5.03M/s
cmd_benchmark -> /storage/BE60-0FE5/ylog/ylog/socket/open/000 speed 5.14M/s
```

b. benchmark test with time stamps.

Command format：adb shell benchmarkt

Response format： None

```
130|root@sp9830a_5h10_volte:/storage/BE60-0FE5/ylog # ylog_cli benchmarkt
cmd_benchmark -> /storage/BE60-0FE5/ylog/ylog/socket/open/000 speed 1.71M/s
cmd_benchmark -> /storage/BE60-0FE5/ylog/ylog/socket/open/000 speed 1.77M/s
cmd_benchmark -> /storage/BE60-0FE5/ylog/ylog/socket/open/000 speed 2.18M/s
cmd_benchmark -> /storage/BE60-0FE5/ylog/ylog/socket/open/000 speed 1.99M/s
cmd_benchmark -> /storage/BE60-0FE5/ylog/ylog/socket/open/000 speed 1.65M/s
```

4. use ylog_cli command to save kernel log

Command format: adb shell ylog_cli print2kernel + log content
eg, adb shell ylog_cli print2kernel test

Check whether log is written to “/dev/kmsg” successfully, use the command as follows, adb shell cat /dev/ksmg |grep print2

```
SPREADTRUM\yanli.chen@yanlichenubtpc:~/6.0/device/sprd$ adb shell ylog_cli print2kernel test
SPREADTRUM\yanli.chen@yanlichenubtpc:~/6.0/device/sprd$ adb shell cat /dev/kmsg |grep print2
12,4549,312735198,-;print2kernel test
```

5. use ylog_cli command to save android log

command format: adb shell ylog_cli print2android + log content
eg, adb shell ylog_cli print2android test

Check whether log is saved successfully, use the command as follows,
adb logcat |grep print2

```
SPREADTRUM\yanli.chen@yanlichenubtpc:~/Downloads$ adb shell ylog_cli print2android xxxxxxxxx
SPREADTRUM\yanli.chen@yanlichenubtpc:~/Downloads$ adb logcat |grep print2
03-29 17:24:06.707   410   519 W YLOG    : [03-29 17:24:06.707] ylog<debug> command is: print2android xxxxxxxxx
03-29 17:24:06.707   410   519 W YLOG    : [03-29 17:24:06.707] ylog<warn> print2android xxxxxxxxx
```

3.2.6 modem/wcn log rate statistic

```
cp_5mode  modem log -> running  -> cp/5mode/000 (1x10.00M/10.00M, 5.00%) -> cache.cp/5mode/(8x512.00K) [76.49M/76.49M]
cp_wcn    wcn log   -> running  -> cp/wcn/000 (1x10.00M/10.00M, 5.00%) -> cache.cp/wcn/(2x512.00K) [18.88M/18.88M]
```

The rate of modem/wcn log can be counted by ylog, then the corresponding log is stored in folder of cp.

modem log get by ylog is stored in the cache sizeof 8*512*1024, and the log will be written to disk until timeout or cache runs out of the space. Theoretically, modem log stored by ylog can not be lost, in the case that modem log rate can't exceed 4M/s.

Copyright 2016 Spreadtrum Communications Inc. Confidential and Proprietary.

1. modem log rate statistic

Various log can be counted by command, which is “adb shell ylog_cli speed”. modem log shows in the following,



2. wcn log rate statisc

Various log can be counted by command, which is “adb shell ylog_cli speed”. wcn log shows in the following,



3 . ylog can send AT command

Command format： adb shell ylog_cli at at

Response format:

a. engpc channel is open

Try to stop engpc:

getprop | grep init.svc.engpc | cut -d '.' -f 3 | cut -d ']' -f 0

or
stop engpcclientt; stop engpcclientlte; stop engpcclientw; stop engpcclienttl; stop engpcclientlf
pcclientlte; stop engpcclientw; stop engpcclienttl; stop engpcclientlf

Command to close engpc channel:

adb shell getprop | grep init.svc.engpc | cut -d '.' -f 3 | cut -d ']' -f 0 or
adb shell stop engpcclientt; stop engpcclientlte; stop engpcclientw; stop engpcclienttl; stop engpcclientlf pcclientlte; stop engpcclientw; stop engpcclienttl; stop engpcclientlf

b. engpc channel is closed

Return value of AT command

Copyright 2016 Spreadtrum Communications Inc. Confidential and Proprietary.

4. log analysis methods and techniques.

4.1 ylog directory structure

In the case of no TF card, ylog is stored in data partition with default quota value of 200M, and keep this log only. Once TF card mounts successfully, quota values will be set as 90% free space of TF card, which calculated by ylog. The free space can be dynamically assigned to each ydst. Meanwhile, log stored in data partition will be moved to TF card, and subsequent log will be stored in append mode. In the condition of a disk-out-of space, ylog can try run smaller to free space for following log. In the another way, ylog can modify disk quotas to set segments numbers or size dynamically.

Under the condition that TF card mounts normally and main switch of ylog can't restart, ylog can save last system log into folder named last_ylog, and rename ylog to ylog1. Meanwhile, the last system log will be renamed to ylog2, and so on. The default history log keeps up to 5 times, this number can be set by command, adb shell ylog_cli history_n N.

ylog directory structure stored in TF card is described as following.

Copyright 2016 Spreadtrum Communications Inc. Confidential and Proprietary.



000 is current log file, and when its size reaches the upper limit of single file size, ylog can flip it to 001. At the same time, 000 is created to continue saving log. Obvious, the smaller of file name, the newer log is. When log files reach rollover limit, there are two options, one is saving original log , the other is deleting oldest log for free space, these all depend on the property of ydst.

Analyzer.py is used for parsing log files off line, and support multiple platforms, windows/MAC/linux, etc.

Outline files record log time periods and total time used for filling log. In analyzing problems, the corresponding log segments can be addressed according to point time the problem occurred, where outline files can help to open.

The detailed steps as follows.

vim outline

1. place the cursor on 002
2. input gf
3. open file named 002 directly

Copyright 2016 Spreadtrum Communications Inc. Confidential and Proprietary.

```
002 - 2012.01.01 08:00:06 ~ 2012.01.01 14:47:00 [00 06:46:54]
001 - 2012.01.01 14:47:00 ~ 2012.01.01 14:48:31 [00 00:01:31]
000 - 2012.01.01 14:48:31 ~
```

Log information is described as following.

0 stands for files named 000, 54 is the maximum of segments.

50.00M means the maximum data size of each segment.

```
A0[ylog_segment=0/54,50.00M] 2016.02.18 14:58:27 -00d00:00:01/1551ms 0.00B/2.64G 0.00B/s
A002-18 14:40:19.312  2038  2303 E SimContactProxy: iccAasUri:content://icc/aas/subId/1
A202-18 14:39:50.800   262   888 D TelephonyManager: /proc/cmdline=loglevel=1 console=tty
d_base=9fe2e000  mem_cs=1, mem_cs0_sz=20000000  sysdump_magic=85500000   androidboot.seri
A002-18 14:40:19.316  2038  2303 E SimContactProxy: iccSneUri:content://icc/sne/subId/1
A202-18 14:39:54.037   231  1248 D use-Rlog/RLOG-RILC_ATCI: > AT Command 'AT+VGR=6'. phon
A002-18 14:40:19.316  2038  2303 E SimContactProxy: iccSdnUri:content://icc/sdn/subId/1
A102-18 14:39:43.475   184   184 I vold    : Vold 3.0 (the awakening) firing up
A202-18 14:39:54.039   305   396 I chatty  : uid=1001(radio) /system/bin/rild_sp expire 3
A002-18 14:40:19.362  2815  2815 W System  : ClassLoader referenced unknown path: /system
A002-18 14:40:19.400  2038  2134 D ContactDirectoryManager: Found com.android.exchange.di
```

4.2 ylog files analysis off line

analyzer.py contains token mapping information

```
'A0':'main.log',
'A1':'system.log',
'A2':'radio.log',
'A3':'events.log',
'A4':'crash.log',
```

After pulling ylog to the local, the parsed log can be obtained by executing command “python analyzer.py” in corresponding folder. Analysis supports log resolution and combination, and it can be customized. In addition, it supports for specified segments analysis. For instance, 000 and 001 log can be parsed separately by command that “python analyzer.py 000 001”.

Copyright 2016 Spreadtrum Communications Inc. Confidential and Proprietary.

```
SPREADTRUM\yanli.chen@yanlichenubtpc:~/tmp/ylog/android/test$ python analyzer.py 000 001
SPREADTRUM\yanli.chen@yanlichenubtpc:~/tmp/ylog/android/test$ ll
total 7424
drwxr-xr-x 2 SPREADTRUM\yanli.chen SPREADTRUM\domain^users    4096 Mar  5 19:23 ./
drwxr-xr-x 3 SPREADTRUM\yanli.chen SPREADTRUM\domain^users    4096 Mar  5 19:23 ../
-rw-r--r-- 1 SPREADTRUM\yanli.chen SPREADTRUM\domain^users  352737 Mar  5 19:23 000
-rw-r--r-- 1 SPREADTRUM\yanli.chen SPREADTRUM\domain^users 1048691 Mar  5 19:23 001
-rw-r--r-- 1 SPREADTRUM\yanli.chen SPREADTRUM\domain^users 1048623 Mar  5 19:23 002
-rw-r--r-- 1 SPREADTRUM\yanli.chen SPREADTRUM\domain^users 3735193 Mar  5 19:23 003
-rw-r--r-- 1 SPREADTRUM\yanli.chen SPREADTRUM\domain^users    1993 Mar  5 19:23 analyzer.py
-rw-r--r-- 1 SPREADTRUM\yanli.chen SPREADTRUM\domain^users       0 Mar  5 19:24 crash.log
-rw-r--r-- 1 SPREADTRUM\yanli.chen SPREADTRUM\domain^users   18474 Mar  5 19:24 events.log
-rw-r--r-- 1 SPREADTRUM\yanli.chen SPREADTRUM\domain^users  901479 Mar  5 19:24 main.log
-rw-r--r-- 1 SPREADTRUM\yanli.chen SPREADTRUM\domain^users     214 Mar  5 19:23 outline
-rw-r--r-- 1 SPREADTRUM\yanli.chen SPREADTRUM\domain^users  351560 Mar  5 19:24 radio.log
-rw-r--r-- 1 SPREADTRUM\yanli.chen SPREADTRUM\domain^users  107691 Mar  5 19:24 system.log
```

Log parsed directory is shown as follows.

```
.
├── android
│   ├── 000
│   ├── analyzer.py
│   ├── crash.log
│   ├── events.log
│   ├── main.log
│   ├── outline
│   ├── radio.log
│   └── system.log
├── hcidump
│   ├── 000
│   ├── analyzer.py
│   └── hcidump.log
├── info
├── kernel
│   ├── 000
│   ├── analyzer.py
│   ├── kernel.log
│   └── outline
├── sys_info
│   ├── 000
│   ├── analyzer.py
│   ├── outline
│   └── sys_info.log
├── tcpdump
│   ├── 000
│   ├── analyzer.py
│   ├── outline
│   └── tcpdump.log
├── tracer
│   ├── 000
│   ├── analyzer.py
│   ├── outline
│   └── tracer.log
├── traces
│   ├── 000
│   ├── analyzer.py
│   ├── outline
│   └── traces.log
├── ylog_debug
└── ylog_journal_file
```

Copyright 2016 Spreadtrum Communications Inc. Confidential and Proprietary.

4.3 analytical method of native crash and anr log

1. native crash

a. enter /ylog/ylog/traches, run “python analyzer.py”.

vim traces.log, search “ylog tombstones”.

eg. ylog_tombstones 001 [cat /data/tombstones/tombstone_00] [01-02 02:14:16.785]

time stamp : [01-02 02:14:16.785] presents the time occurred native crash.

b. enter android directory, then vim outline. You can find the segments occurred native crash at that time point.

eg. “01-02 02:14:16.785” is located in the following period, the corresponding log segment is 015.

015 - 2012.01.02 02:12:36 ~ 2012.01.02 02:40:37 [00 00:28:01]

c. obtain log, such as main, system, events, radio, crash contained in this log segment.

command : phthon analyzer.py 015.

generation: crash.log events.log main.log radio.log system.log

d. open corresponding xxx.log, then problems can be analyzed.

2. anr

a. enter /ylog/ylog/traces, run “python analyzer.py”.

vim traces.log, search “ylog traces”.

eg. ylog_traces 001 [cat /data/anr/traces.txt] [01-02 04:07:43.903]

Time stamp : [01-02 04:07:43.903] presents the time occurred anr.

b. enter android directory, vim outline. You can find the segments occurred anr at that time point.

eg. “01-02 04:07:43.903” is located in the following period, the corresponding log segment is 011.

011 - 2012.01.02 04:04:04 ~ 2012.01.02 04:29:18 [00 00:25:14]

c. obtain log, such as main, system, events, radio, crash contained in this log segment.

command: phython analyzer.py 011.

generation: crash.log events.log main.log radio.log system.log

d. open corresponding xxx.log, then problems can be analyzed.

3. log analysis related with system status (system-related log can be collected every 2 minitus)

Copyright 2016 Spreadtrum Communications Inc. Confidential and Proprietary.

Method One:

enter “ylog/ylog/sys_info”, run “python anlayzer.py”,

generation: sys_info.log (the total log collected by all the test processing)

Method Two:

a. get time point occurred problems.

b. enter “ylog/ylog/sys_info”, vim outline, you can find the segments occurred anr at that time point.

c. vim the corresponding log segment, analyze the system status about time occurred problems.

Copyright 2016 Spreadtrum Communications Inc. Confidential and Proprietary.