Ethical Hacking and Countermeasures
Google Dorks Cheat Sheet

EC-Council
Building A Culture Of Security

1.Google Advanced Search Operators
2. List of The Search Operators
3. VoIP Footprinting
4. VPN Footprinting
5. FTP Servers
6. Detecting Footholds
7. Files Containing Usernames
8. Sensitive Directories
9. Web Server Detection

1.Google Advanced Search Operators

Search Service	Search Operators
Web Search	allinanchor:, allintext:, allintitle, allinurl:, cache:, define:, filetype:, id;, inanchor:, info:, intext:, intitle:, inurl:, link:, related:, site:
Image Search	allintitle:, allinurl:, filetype:, inurl:, intitle:, site:
Groups	allintext:, allintitle:, author:, group:, insubject:, intext:, intitle:
Directory	allintext:, allintitle:, allinurl:, ext:, filetype:, intext:, intitle:, inurl:
News	allinjtext:, allintitle:, allinurl:, intext:, intitle:, inurl:, location:, source:
Product search	allintext:, allintitle:

2. List of The Search Operators

Search Operators	Description
allinanchor:	This operator restricts results to pages containing all query terms specified in the anchor text on links to the page Example: [allinanchor: best museums sydney]
allintext:	This operator restricts results to those containing all the query terms specified in the text of the page Example: [allintext: travel packing list]
allintitle:	This operator restricts results to those containing all the query terms specified in the title Example: [allintitle: detect plagiarism
allinurl:	This operator restricts results to those containing all the query terms specified in the URL. Example: [allinurl: google faq]
author:	This operator will restrict your Google Groups results to include newsgroup articles specified by the author Example: [children author:john author:doe] or [children author:doe@someaddress.com]
cache:	This operator displays Google's cached version of a web page, instead of the current version of the page. Example: [cache:www.eff.org]
define:	This operator shows definitions from pages on the web for the term that follows. Example: [define: blog]
ext:	This is an undocumented alias for filetype:.
filetype:	This operator restricts the results to pages whose names end in suffix. Example: [web page evaluation checklist filetype:pdf]
group:	This operator restricts your Google Groups results in newsgroup articles from certain groups or subareas. Example: [sleep group:misc.kids.moderated]
id:	This is an undocumented alias for info:.
inanchor:	This operator restricts the results to pages containing the query terms you specify in the anchor text or links to the page. Example: [restaurants inanchor:gourmet]
info:	This operator will present some information about the corresponding web page Example: [info:gothotel.com]
insubject:	This operator restricts articles in Google Groups to those that contain the terms you specify in the subject. Example: [insubject:"falling asleep"]
intext:	This operator restricts results to documents containing the term in the text. Example: [Hamish Reid intext:pandemonia]
intitle:	This operator restricts results to documents containing the term in the title. Example: [flu shot intitle:help]
inurl:	This operator restricts the results to documents containing that word in the URL. Example: [inurl:print site:www.googleguide.com]
link:	The operator link:URL shows pages that point to that URL. Example: [link:www.googleguide.com]:
location:	This operator finds information for a specific location. Example: [queen location:canada]
movie:	If you include this operator in your query, Google will find movie-related information. Example: see Google's Blog.
related:	This operator will list web pages that are similar to the web page you specify. Example: [related:www.consumerreports.org]
site:	This operator restricts the results to the site or domain you specify. Example: [admissions site:www.lse.ac.uk]
source:	This operator restricts your search to articles from the news source with the ID you specify. Example: [election source:new_york_times]
weather:	If you enter a query with the word weather and a city or location name, if Google recognizes the location, the forecast will appear at the top of the results page. Otherwise, your results will usually include links to sites with the weather conditions and forecast for that location. Example: [weather Sunnyvale CA]

3. VoIP Footprinting

Google Dork	Description
intitle:"Login Page" intext:"Phone Adapter Configuration Utility"	Pages containing login portals
inurl:/voice/advanced/ intitle:Linksys SPA configuration	Finds the Linksys VoIP router configuration page
intitle:"D-Link VoIP Router" "Welcome"	Pages containing D-Link login portals
intitle:asterisk.management.portal web-access	Look for the Asterisk management portal
intitle:"SPA504G Configuration"	Finds Cisco SPA504G Configuration Utility for IP phones
intitle:"Sipura.SPA.Configuration" -.pdf	Finds configuration pages for online VoIP devices
intitle:asterisk.management.portal web-access	Finds the Asterisk web management portal
inurl:8080 intitle:"login" intext:"UserLogin" "English"	Finds VoIP login portals

4. VPN Footprinting

Google Dork	Description
filetype:pcf "cisco" "GroupPwd"	Finds Cisco VPN files with group passwords for remote access
"[main]" "enc_GroupPwd=" ext:txt	Finds Cisco VPN client passwords
"Config" intitle:"Index of" intext:vpn	Finds directory with keys of VPN servers
inurl:/remote/login?lang=en	Finds FortiGate Firewall's SSL-VPN login portal
!Host=*.* intext:enc_UserPassword=* ext:pcf	Look for .pcf files which contains user VPN profiles
filetype:rcf inurl:vpn	Finds Sonicwall Global VPN Client files containing sensitive information and login
filetype:pcf vpn OR Group	Finds publicly accessible profile configuration files (.pcf) used by VPN clients
vpnssl	Retrieves login portals containing VPNSSL companies' access
intitle:"SSL VPN Service" + intext:"Your system administrator provided the following information to help understand and remedy the security conditions:"	Finds Cisco ASA login web pages
site:vpn.*.*/ intitle:"login"	Retrieves pages Containing Login Portals
Index of / *.ovpn	Finds files configuration OpenVPN, some certs, keys
inurl:"/vpn/tmindex.html" vpn	Netscaler & Citrix Gateway VPN login portals
"Config" intitle:"Index of" intext:vpn	Finds directory with keys of VPN servers
intitle:"inc. vpn 3000 concentrator"	This search will show the login page for Cisco VPN 3000 concentrators
"intitle:Cisco Systems, Inc. VPN 3000 Concentrator"	The Cisco VPN 3000 Concentrator is a remote access VPN

5. FTP Servers

Commands	Description
inurl:github.com intext:.ftpconfig -issues	Returns SFTP/FTP server credentials on Github
type:mil inurl:ftp ext:pdf | ps	Returns sensitive directories on FTP
intext:pure-ftpd.conf intitle:index of	Returns servers exposing pure-ftpd configuration files
intitle:"Index Of" intext:sftp-config.json	Extracts list of FTP/SFTP passwords from sublime text
inurl:"ftp://www." "Index of /"	Displays various online FTP servers

Ethical Hacking and Countermeasures
Google Dorks Cheat Sheet

EC-Council
Building A Culture Of Security

Commands	Description
`inurl:~/ftp://193 filetype:(php | txt | html | asp | xml | cnf | sh) ~'/html'`	Returns a List of FTP Servers by IP address, mostly Windows NT servers with guest login capabilities
`intitle:"index of" share.passwd OR cloud.passwd OR ftp.passwd -public`	Dorks containing passwords
`-pub -pool intitle:"index of" db.key OR server.key OR ftp.key OR exchange.key OR host.key OR mail.key`	This dork will give you a lot of private keys are also known as a secret key.
`intitle:"index of" "ftp.log"`	It contains FTP LOGS
`intitle:"index of" "ws_ftp.log"`	Finds sensitive directories
`intitle:"index of" inurl:ftp intext:logs`	Finds files containing Juicy items
`site:ftp.* index of /ftp/backup`	View *Backup* files on *FTP* server of various websites
`site:ftp://ftp.*.*/login -inurl:https://`	Finds Login Portals
`intitle:"index of" "ftp.passwd"`	Finds files containing password
`inurl:ftp://ftp`	Detecting FTP sites
`inurl:ftp://ftp robots.txt`	Finding robots.txt in FTP sites
`"/FTPSVC2" intitle:"index of"`	Finds Microsoft FTP server logs
`inurl:"/cgi-bin/WS_FTP.LOG"`	Find field in cgi-bin directory
`intitle:ProFTPD Admin - V1.04`	Will show you admin page, no login needed
`intext:"softperms.txt" ext:TXT`	It will generate juicy information that may lead to a parent directory, for best practice filter according to the country
`intitle:"Index Of" intext:.ftpconfig`	Retrieves FTP/SFTP credentials in. ftpconfig file from Atom text editor
`"[FFFTP]" ext:ini`	Finds files with FTP logins, server info, and more
`inurl:"http://ftp.dlink"`	Find lists of FTP directories of D-Link routers
`inurl:proftpdpasswd`	Dork of proftpd passwords
`"[HKEY_CURRENT_USER\Software\sota\FFFTP]" filetype:reg`	Finds some files with juicy information about Windows servers
`intext:"Powered by net2ftp"`	Web based FTP client login page
`inurl:"ftp" intext:"user" | "username" | "userID" | "user ID" | "logon" | "login" intext:"password" | "passcode" filetype:xls | filetype:xlsx`	Retrieves Passwords
`intext:"Powered by net2ftp"`	This dork finds open ftps. This is a base dork, where you can add intext:"ssh/" for folder search and intext:"-2015" for dates and years
`inurl:ftp inurl:Seagate inurl:Backup inurl:Plus inurl:Drive`	Finds open Seagate NAS drives
`filetype:xml inurl:/WEB-INF/ inurl:ftp:// -www`	Finds sensitive and interesting information under WEB-INF directory via ftp protocol
`inurl:ws_ftp.ini "[WS_FTP]" filetype:ini`	Finds files containing passwords

Commands	Description
`inurl:github.com intext:sftp-conf.json +intext:/wp-content/`	Find FTP logins and full path disclosures pushed to github
`site:github.com inurl:sftp-config.json`	Find disclosed FTP login credentials in GitHub repositories
`site:github.com inurl:sftp-config.json intext:/wp-content/`	Finds disclosed FTP for Wordpress installs, which have been pushed to a public repo on GitHub
`filetype:config inurl:web.config inurl:ftp`	Finds sensitive information of MySqlServer, "uid, and password" in web.config through ftp
`inurl:php intitle:"Cpanel , FTP CraCkeR"`	Locates cpanel and ftp cracker
`inurl:php intitle:"Cpanel , FTP CraCkeR"`	Locates cpanel and ftp cracker
`inurl:ftp "password" filetype:xls`	This string is used to find many low hanging fruits on FTP sites recently indexed by google
`filetype:ini "[FFFTP]" (pass|passwd|password|pwd)`	Run the password hash through John etc.
`"parent directory" +proftpdpasswd`	Usernames and password hashes from web server backups generated by cpanel for ProFTPd. Password hashes can be cracked, granting direct access to FTP accounts. Unix passwd and shadow files can sometimes be found with this query as well.
`intitle:"FTP root at"`	This dork will return some FTP root directories
`intitle:"index of" inurl:ftp (pub | incoming)`	Adding "inurl:ftp (pub | incoming)" to the "index.of" searches help to locate FTP websites
`intitle:"index of" inurl:ftp (pub | incoming)`	Adding "inurl:ftp (pub | incoming)" to the "index.of" searches help to locate FTP websites
`"index of/" "ws_ftp.ini" "parent directory"`	Cleans up the previous entry
`filetype:ini wcx_ftp`	Searches for Total commander FTP passwords (encrypted) in a file called wcx_ftp.ini
`LeapFTP intitle:"index.of./" sites.ini modified`	Finds LeapFTP client configuration file "sites.ini" holds the login credentials for those sites in plain text
`"ftp://" "www.eastgame.net"`	Finds eastgame.net FTP servers, loads of warez and that sort of thing
`filetype:ini ws_ftp pwd`	These files can be found with the "index of" keyword or by searching directly for the PWD= value inside the configuration file
`filetype:conf inurl:proftpd.conf -sample`	Standard FTP configuration file that provides far too many details about how the server is setup, including installation paths, location of log files, generic username and associated group, etc
`+htpasswd +WS_FTP.LOG filetype:log`	WS_FTP.LOG can be used in many ways to find more information about a server
`filetype:url +inurl:"ftp://" +inurl:"@"`	These are FTP Bookmarks, some of which contain plaintext login names and passwords
`intitle:index.of ws_ftp.ini`	ws_ftp.ini is a configuration file for a popular FTP client that stores usernames, (weakly) encoded passwords, sites, and directories that the user can store for later reference
`intitle:"net2ftp" "powered by net2ftp" inurl:ftp OR intext:login OR inurl:login`	net2ftp is a web-based FTP client written in PHP

6. Detecting Footholds

Google Dork	Description
`inurl:"index of" wso`	Access to WSO shell infected domains
`intitle:"freedom is real - 1945"`	Common web shell that sets the HTML title tag to '.[freedom is real - 1945]
`site:*/wp-admin/install.php intitle:WordPress Installation`	Finds files containing Juicy information
`intitle:Administration - Installation - MantisBT`	Dorks for mantisBT CMS installation
`inurl:/phpmyadmin/index.php?db=`	Finds phpmyadmin authenticated panel
`inurl:"cs.html?url="`	Open Redirects
`inurl:"urlstatusgo.html?url=" -intext:"Disallowed by URL filter"`	Open Redirects
`inurl:wp-login.php?action=register`	Finds Wordpress sites with registration enabled
`inurl:/phpMyAdmin/setup/index.php?phpMyAdmin=`	Finds access sensitive page of phpmyadmin
`inurl:"/sidekiq/busy"`	Get the sidekiq dashboard that is used to run Ruby systems
`intitle:"InfluxDB - Admin Interface" -github`	Dork about InfluxDB without password
`intitle:"FCKeditor - Connectors Tests"`	Finds unauthenticated file upload and directory list
`intitle:"FCKeditor - Uploaders Tests"`	Finds unauthenticated file upload
`intitle:"FCKeditor - Uploaders Tests"`	Finds unauthenticated file upload
`intext:"M3R1C4 SHELL BACKDOOR"`	Foothold web shell
`"index of" /wp-content/uploads/shell.php`	Google Dork discovers servers running Wordpress that are infected with web shells
`"File Manager - Current disk free"`	Google Dork to locate PhpSpy web shells
`inurl: "Mister Spy" | intext:"Mister Spy & Souheyl Bypass Shell"`	Google Dork discovers servers infected with the "Mister Spy" web shell
`inurl:"/tiny_mce/plugins/ajaxfilemanager/inc/data.php" | inurl:"/tiny_mce/plugins/ajaxfilemanager/ajax_create_folder.php" -github`	Finds tiny_mce vulnerable targets
`intitle:Upload inurl:/cgi-bin/filechucker.cgi`	AJAX-based web application / file manager - “filechucker” that lets you upload arbitary files on a website
`intitle:"Installing TYPO3 CMS"`	Finds the first install wizard of the TYPO3 CMS
`inurl:/install/stringnames.txt`	DORK is useful to search moodle cms with install folder left on the hosted server
`intitle:"Solr Admin" "Solr Query Syntax"`	Finds Apache Solr admin panels
`ext:jsp intext:"jspspy" intitle:"Jspspy web~shell V1.0"`	Find login portals of jspspy webshell

97% Of Professionals Stated That Skills Acquired in C|EH Helped Safeguard Their Organizations

Google Dork	Description
"Sorting Logs:" "Please enter your password" "Powered By" -urlscan -alamy	Finds stealer botnet control panels
intitle:"Authorization" "TF" inurl:"admin.php"	Finds a bunch of unprotected botnet control panels
ext:php intext:"-rwxr-xr-x" site:.in	Discover affected software
intitle:index of intext:@WanaDecryptor@.exe	More information about the Wannacry Ransomware infected Servers
intitle:index of intext:wncry	Dork to find servers affected by Wannacry Ransomware
inurl:"go.cgi?url="	Finds pages which can be exploited to redirect to any site
"WHMCS Auto Xploiter"	Finds WHMCS exploit shell in sites
"El Moujahidin Bypass Shell" ext:php	Simple upload/dir shell
(ext:php) (inurl:/wp-content/uploads/AAPL/loaders/)	Finds a few handy little web shells
inurl:?filesrc=**** ~"Current" ~"asp"	Different uploaded shell names
inurl:/\\filesrc=**** ~"Current" ~":/" ~"upload"	Finds the extensive list of shell backdoors implemented on websites
"File Manager Version 1.0" "Coded By"	Finds file managers web shells
inurl:"html/js/editor/ckeditor/"	Finds liferay upload file
"You have selected the following files for upload (0 Files)."	Finds file upload pages
intitle:"nstview v2.1:: nst.void.ru" | intext:"nsTView v2.1 :: nst.void.ru. Password: Host:"	Web shell
filetype:php intext:Your Email: intext:Your Name: intext:Reply-To: intext:mailer	Results in PHP mailers
intitle:"Hamdida X_Shell Backd00r"	Backdoor
"Fenix Final Version v2.0" filetype:php	Web-Shell
intitle:Automatic cPanel Finder/Cracker | 3xp1r3 Cyber Army	An exploit to find uploaded cPanel Finder/Cracker script and find cracked cpanel on it
inurl:revslider inurl:temp inurl:update_extract inurl:sym1	Symlinks to files using the revslider vulnerability
intitle:"Shell I" inurl:revslider inurl:error.php inurl:cmd	Find shells inserted using the revslider vulnerability
intext:Developed By Black.Hack3r ext:php	Upload Shell Dorks
ext:aspx intitle:aspxspy	Asp shells
intext:"Sw Bilgi" ext:php	Upload Shell Dork
intext:"Thehacker - Agd_Scorp - BLaSTER - Cr@zy_King - KinSize - JeXToXiC - s3f4 - rx5"	BLaSTER Webshell Footholds
intext:"Please select file to upload:" ext:php	Various file upload forms

Google Dork	Description
inurl:sh3llZ/c99/	ind c99 shells uploaded on websites
intitle:SN0X SHELL: WEEEEEEEEEEEEEEEEED	Google Dork that brings up ddos shell
ext:asp intext:Smart.Shell 1.0 BY P0Uy@_$3r\/3R -	New WebShell
intitle:"WSO 2.4" [Sec. Info], [Files], [Console], [Sql], [Php], [Safe mode], [String tools], [Bruteforce], [Network], [Self remove]	Dork to find uploaded WSO 2.4 shell by hacker
intitle:"=[1n73ct10n privat shell]="	The dork is used to find uploaded 1n73ct10n Shell on website
filetype:php intext:"!C99Shell v. 1.0 beta"	php backdoor: c99 shell
inurl:1337w0rm.php intitle:1337w0rm	Finds websites that have 1337w0rm's CPanel cracker uploaded
Re: intitle:Priv8 SCR	Symlink User configs
Re: inurl:"r00t.php"	Finds websites that were hacked, backdoored and contains their system information
intitle:C0ded By web.sniper	Using this dork, you can find the User and the Domains of the Server
inurl:"amfphp/browser/servicebrowser.swf"	AMFPHP service browser, debug interface. Author: syddd
allintext:"fs-admin.php"	foothold using allintext:"fs-admin.php" shows the world-readable directories of a plug-in that enables Wordpress to be used as a forum
(intitle:"SHOUTcast Administrator")|(intext:"U SHOUTcast D.N.A.S. Status")	SHOUTcast is a free-of-charge audio homesteading solution
(intitle:"WordPress ÃƒÂ¢Ã¢â€šÂ¬Ã‚Â° Setup Configuration File")|(inurl:"setup-config.php?step=")	Alter setup configuration files.add ?step=1
"index of /" (upload.cfm | upload.asp | upload.php | upload.cgi | upload.jsp | upload.pl)	Searches for scripts that let you upload files which you can then execute on the server
"Please re-enter your password It must match exactly"	Invision Powerboard registration pages
inurl:"tmtrack.dll?"	Installations of Serena Teamtrack
inurl:polly/CP	Get into admin panel without logging
intitle:MyShell 1.1.0 build 20010923	Execute commands remotely on whichever server it's hosted on
intitle:"YALA: Yet Another LDAP Administrator"	Web-based LDAP administration GUI
intitle:"ERROR: The requested URL could not be retrieved" "While trying to retrieve the URL" "The following error was encountered:"	Squid error messages, most likely from reverse proxy servers
PHPKonsole PHPShell filetype:php -echo	PHPKonsole is a little telnet like that can run commands on the webserver
filetype:php HAXPLORER "Server Files Browser"	The Haxplorer is a web-based file manager which enables the user to browse files on the webserver

Google Dork	Description
(inurl:81/cgi-bin/.cobalt/) | (intext:"Welcome to the Cobalt RaQ")	The famous Sun Linux appliance. To replace this page, transfer your new content to the directory /home/sites/home/web"
intitle:"Web Data Administrator - Login"	Web Data Administrator is a utility program implemented in ASP.NET that enables to easily manage SQL Server data
"adding new user" inurl:addnewuser -"there are no domains"	Create an account on a server running Argosoft mail server pro for windows with unlimited disk quota
intitle:"PHP Shell *" "Enable stderr" filetype:php	PHP Shell is a shell wrapped in a PHP script. It's a tool that executes arbitrary shell-commands or browses the filesystem on a remote Webserver
"Powered by PHPFM" filetype:php -username	PHPFM is an open-source file manager written in PHP
+htpasswd +WS_FTP.LOG filetype:log	WS_FTP.LOG can be used in many ways to find more information about a server
intitle:admin intitle:login	Admin Login pages

7. Files Containing Usernames

Google Dork	Description
"username.xlsx" ext:xlsx	Excel files containing a username
inurl:/_layouts/mobile/view.aspx?List=	Access Microsoft SharePoint CMS based domains
"authentication failure; logname=" ext:log	Finds log files for failed logins, containing usernames and login paths
inurl:/profile.php?lookup=1	Find administrator name in most websites and forums
site:extremetracking.com inurl:"login="	The search reveals usernames and links to the sites that are signed up with extremetracking.com
intext:"SteamUserPassphrase=" intext:"SteamAppUser=" -"username" -"user"	This will search for usernames and passwords for steam (www.steampowered.com) taken from the SteamApp.cfg file.
inurl:root.asp?acs=anon	This search jumps right to the main page of Outlook Web Access Public Folders and the Exchange Address Book
filetype:conf inurl:proftpd.conf -sample	Standard FTP configuration file that provides far too many details about how the server is setup, including installation paths, location of log files, generic username and associated group, etc
filetype:log username putty	Record info about the SSH client PUTTY. These files contain usernames, site names, IP addresses, ports and various other information about the SSH server
filetype:reg reg +intext:"internet account manager"	Reveals users' names, pop3 passwords, email addresses, servers connected to and more including IP addresses in some cases
filetype:reg reg HKEY_CURRENT_USER username	Finds registry files from the Windows Operating system
+intext:"webalizer" +intext:"Total Usernames" +intext:"Usage Statistics for"	Webalizer program displays various information but this query displays usernames that have logged into the site
inurl:php inurl:hlstats intext:"Server Username"	This page shows the half-life stat script and reveals username to the system
index.of perform.ini	This file contains information about the mIRC client and may include channel and usernames

Google Dork	Description
"index of" / lck	These lock files often contain usernames of the user that has locked the file
inurl:admin filetype:asp inurl:userlist	Reveals user lists of administrative importance. User lists found using this method can range from benign "message group" lists to system user lists containing passwords
inurl:admin inurl:userlist	Reveals user lists of administrative importance. User lists found using this method can range from benign "message group" lists to system user lists containing passwords
intitle:index.of .bash_history	The file contains what a user typed at a shell command prompt
intitle:index.of .sh_history	Consists of what a user typed at a shell command prompt

8. Sensitive Directories

Google Dork	Description
intitle:"index of" "/Cloudflare-CPanel-7.0.1"	Exposes Cloudflare-Cpanel sensitive files
-pool intitle:"index of" wget-log -pub	Provides good insight into what was downloaded in a system
intitle:"index of" "sms.log"	Contains SMS LOGS
intitle:"index of" "ftp.log"	Contains FTP LOGS
-pub -pool intitle:"index of" vagrantfile -"How to"	The primary function of the Vagrantfile is to describe the type of machine required for a project, and how to configure and provision these machines. It can contain DB passwords, private keys, usernames, etc
intitle:"index of" .oracle_jre_usage/	Provides version of Java used by the target
-pub -pool intitle:"index of" squirrelmail/	Squirrel mail configuration files and sometimes credentials
intitle:"index of" api_key OR "api key" OR apiKey -pool	API keys
intitle:"index of" domain.key -public	Domains private Keys
intitle:"index of" .zshrc~ OR .zshrc OR .zshenv OR .zshenv~ -pool -public	Z shell (Zsh) juicy info
"key" OR key.jar intitle:"index of" webstart	*Java Web Start* (also known as *JavaWS*, *javaws* or *JAWS*) allows users to start application software for the Java Platform directly from the Internet using a web browser
index of /storage/logs/	Provides informational Logs of the Laravel framework
intitle:index.of "chroot.conf"	Contains sensitive information
intitle:index of "uploads"	The file contains Juicy items
intitle:"index of" "ws_ftp.log"	Sensitive directories
intitle:index.of "htaccess.txt"	Contains htaccess.txt clear text sensitive information
intext:"index of" intext:..bak intext:config	Div backup files
intext:"Sw Bilgi" ext:php	Upload Shell Dork

Google Dork	Description
site:* index.of: /android/manifest.xml	Android Files
intitle:index.of "system.db"	Sensitive Directories
intitle:index.of "database.db"	Sensitive Directories
intitle:"Index of" wp-upload	Contains WordPress sensitive information
site:*/logs/default.htm	Sensitive directories
site:* index of: /config	Juicy Files
site:* index of: *.exe	Juicy Files
intitle:"Index of" secret	Secret Folder
intitle:"index of" "/etc/mysql/"	Sensitive directories and files
inurl:/wp-content/uploads/ninja -forms/ intitle:"index of"	WordPress Ninja Forms Plugin, Sensitive file uploads
indexof:backup/web.config	Backup files
intitle:index.of./.htaccess	Symlink User configs
inurl:/_vti_txt*	Google Dorks for Sensitive Directories
inurl:wp-content intext:backup-db	Gives result of Various backup files/Folders stored in wp-content/uploads directories of various websites It also gives database backups consisting of SQL backup files of various websites who have not secured their sensitive directories
inurl:/scgi-bin*	Google Dork Submission for Apache servers, usually publicly facing directories
inurl: /upload.php intitle:index of	Vulnerable Files
inurl:/database* ext:sql intext:index of -site:github.com	Files Containing Juicy Info
inurl:admin/data* intext:index of	Files Containing Juicy Info
inurl:/admin/ intitle:index.of	Index.of/ Sensitive Directories (i.e */admin/)
intitle:index.of.?.login	Used to find user authentication files from the website directory
site:*/wordpress/wordpress.bak/	Sensitive directory
intitle:"index of" /config.ini	Files containing password, sensitive info:
inurl:/wp/wp-admin/	Sensitive directories
intitle:index.of.?.database	Used to find sensitive database files (*.sql) from the website directory
intitle:"index of" /content/admin/	intitle:"index of" /content/admin/
intitle:index.of.?.mysql	Used to find sensitive. mysql files
intitle:index.of./.db	Dork to find the database information

Google Dork	Description
intitle:index.of.?.bak	Used to find sensitive .bak files which are backup files, in web applications
intitle:index.of./.sql	SQL files can be downloaded from websites
intitle:"Index of" login.php	Contains sensitive information & sensitive files
intitle:"Index of" wp-config.php	Contains sensitive information & sensitive files
intitle:"index of" sql inurl:./db/	Sensitive database credentials
inurl:/sites/default/private	Contains sensitive files & directories
intitle:"index of" drupal	Contains Drupal Sensitive files and information
intitle:"Index of" inurl:wp-json/oembed	Contains sensitive files, links embedded with WordPress and can be used to find CORS
intitle:"Index of" phpmyadmin	Contains sensitive information
intitle:"Index of" wp-admin	Contains WordPress sensitive information & sensitive files
intitle:index.of.?.sql	Download .sql files from website
inurl: /filemanager/dialog.php	Sensitive directories
intitle:"Index of" wp-content	Contains WordPress sensitive information
intitle:"Index of" wp-config	Contains WordPress sensitive files
intitle:"Index of" portal	Public Portal Directory's
intitle:"Index of" public	Public Folder Directories
"Index of" inurl:config inurl:production	Open Directory listing with words "config" and "production" in the URL
Index of / *.ovpn	Files configuration OpenVPN, some certs, keys
"To Parent Directory" AND "dir>" AND "web.config"	Web Servers with Open Directory Listing containing web.config file
intitle:"index of" intext:"Includes wordpress"	Wordpress based website having sensitive directories
intitle:"index of" intext:"Includes	Allows access to the sensitive directories using includes file
filetype:svn -gitlab -github inurl:"/.svn"	This potential flaw can be used to download content from the Web server that might otherwise be private
filetype:git -github.com inurl:"/.git"	This potential flaw can be used to download content from the Web server that might otherwise be private
inurl:bc.googleusercontent .com intitle:index of	Dork that enumerates GCP for sensitive directories
intitle:"index of" scada	SCADA Sensitive Directories Expose on Site
"/var/cache/registry/"	CS-Cart admin panel settings information
type:mil inurl:ftp ext:pdf | ps	Gives sensitive directories via FTP
allintitle: "index of/admin"	Access some admin login pages and parent directory structure and some vulnerable information like framework used for the web site technology used for building the web site etc
intitle: "index of" "./" "./bitcoin"	Bitcoin Directory Listing

Ethical Hacking and Countermeasures
Google Dorks Cheat Sheet

EC-Council
Building A Culture Of Security

Google Dork	Description
intitle:"index of" ".cpanel/caches/config/"	Cpanel Caches Config Directory Listing
intitle: "Index of" intext:log	File Containing Juicy Info - Dorks allow you to view logs. (e.g./log, file/log, ftplogs, server logs)
intitle:"Directory Listing For" "Filename" intext:Tomcat/5.0.28	Access the sensitive directories of any web application using Apache Tomcat/5.0.28
intitle: "index of" "includes"	Access the sensitive directories (includes, wp-includes) using "includes" file
intitle:"index of" "db"	Access the sensitive directories using "db" file
inurl:/uploads/wc-logs/	WooCommerce Classes Paypal Payment Information
inurl:/files/contao	Shows some pdf files used in contao CMS
inurl:typo3conf/l10n/	Directories from typo3 cms exploiting directory listing
intitle:"index of" ".dockerignore"	Access the Sensitive Directories using .dockerignore file
intitle:"index of" "/aws.s3/"	Access the Sensitive Directories of Amazon-Web-Services
intitle:"index of" ".pem"	Access the. pem (Privacy Enhanced Mail) file
intitle:"index of" "/bitcoin/"	Access the Sensitive Directories using bitcoin directories
"description" & "size" intitle:"index of" "owncloud"	Owncloud folders
"Last modified" intitle:"index of" "dropbox"	Dropbox folders
inurl:"/cgi-bin/CVS/"	Find filed in cgi-bin directories
"sasl_passwd" | smtpd.conf intitle:"index of"	Postfix sensitive files, also passwords
intitle:"index of" "/user" | "/users"	Show existing users in the system by simply going to the above-mentioned directories
intitle:"index of" inurl:documents backup	Backup folders containing very juicy info
inurl:"/.Trash" intitle:"index of" ~	Juicy info in some *nix Trash bins.
intitle:"index of" $Recycle.bin	Windows trash bins with a lot of juicy info
intitle:"index of" "/Windows/Recent" | "/Windows/History/"	Can access most recently used files and history data
intitle:"index of" "WindowsCookies"	Retrieve cookies from Windows users
intitle:"index of" "Application Data/Microsoft/Credentials"	Dork for finding private directories inside wordpress-popup plugin including admin data which are present in Wordpress websites
allinurl:"wp-content/plugins/wordpress-popup/views/admin/"	Dork for finding private directories inside wordpress-popup plugin including admin data which are present in Wordpress websites
allintitle:"Index of /ThinkPHP" | inurl: "/ThinkPHP/"	Dork for finding a list of private directories such as library, licence, config files, and more in ThinkPHP framework used for websites
intitle:"index of /" ssh	Obtain -Webserver Version - SSH Version - SSH Keys - SSH Logins - SSH .exe files

Google Dork	Description
intitle:"Index of /" inurl:passport	Find a lot of passports
inurl:"/irj/go/km/" intext:navigation	Extract SAP server documents - Find SAP server - Find server structure - Find usernames and passwords - Find sensitive data - To exploit, go to the site and click on "Navigation user interface" - 1.890 results at the time of writing
inurl:"/irj/go/km/docs/"	Large amounts of information - User data - Sensitive data - Documents - File structure of a server - To exploit, go to the site and click on "Navigation user interface" - You can download the entire SAP server's directory - 86.600 results at the time of writing
inurl:"/webdynpro/resources/sap.com/"	- Discover software installed on servers - Version info - SAP J2EE exploits - Exploit server software - Find adminconsole - Possible SQL Injection: - https://www.exploit-db.com/exploits/43495 - Create new users - 1.670 results at the time of writing
inurl:"ai1wm-backups"	Find WordPress backup files and publicly accessible wp-content directories
intitle:"Index of /private/"	Search Private directories also work on Yahoo
index of /etc/certs/	Certificate directories
intitle:"index of /" intext:/backup	Access to different backup files
intitle:'index of' "access_log"	Obtain various Wordpress directories containing access logs
intitle:'index of' "error_log"	Discover various Wordpress directories containing error logs.
intitle:"index of /" authorized_keys	Authorized keys ssh and some rsa file
index of /ckeditor	ckeditor directories
index of kcfinder/	kcfinder directories
inurl:/proc/tty/ index of	Gather information by parent directory to discover vulnerable or credential file
intitle:index of /.sql.gz intext:/backup/	Gather information of database schema and credentials data of MySQL backup
intitle:" - Revision" + "subversion version"	Apache subversion directory listing
Index of /.svn	Finds SVN directory
intitle:"docker" intitle:"index of" config	Finds sensitive directories expose on site
inurl:filebrowser.wcgp?subDir Communigate	Access Public and protected CommunigatePro mail server users' files
intext:"paytm" intitle:"index of"	Discovers Paytm config files and open directories of Sites

Google Dork	Description
intext:my.cnf intitle:index of	Discovers servers exposing MySQL configuration files
intext:my.cnf intitle:index of	Discovers servers exposing MySQL configuration files
intext:pure-ftpd.conf intitle:index of	Discovers servers exposing pure-ftpd configuration files
inurl:/typo3/typo3conf	Files from TYPO3 CMS installation
intitle:backup+index of	Checks for a public backup folder on the webserver, It might include the sensitive files or database
"index of" "database.sql.zip"	Discovers servers with open directories exposing database backup files
"index of" "database_log"	Discovers servers exposing sensitive SQL log data
"Index of" "database.sql"	Discovers servers with open directories exposing database files
intitle:index.of id_rsa -id_rsa.pub	A simple dork to find SSH private keys indexed by google, Where many of the keys work
inurl:/wp-includes/certificates/	Discover a lot of certificates from websites
intitle:"index of /bins" arm	Find servers infected with Mirai
allintext:'HttpFileServer 2.3k'	Dork about sensitive directory of HFS File Share Server
inurl:'listprojects.spr'	Dork show a list of projects in Codebeamer directory
inurl:"RootFolder=" Allitems "confidential" | "classified" | "passwords" | username	SharePoint directories exposing sensitive information, usernames and sometimes passwords
inurl:revslider inurl:'/revslider+port'	infos and symlinks to revslider folders upload, plugins and settings, server and port
inurl:"paypal" intitle:"index of" backup | db | access -github	Some juicy information regarding PayPal backups and more
"Powered by Apache Subversion version"	Looking for the SVN source code folder
inurl:"/wp-content/uploads/db-backup"	Searching for the backup directory of WP-DB Backup plugin (WordPress)
index of /node_modules/ -github -stackoverflow	Find several of nodejs folders with important files
intitle:"index.of" | inurl:/filemanager/connectors/ intext:uploadtest.html	Open Custom File Uploader specifically in "/FCKeditor/.."
intitle:index.of inurl:/websendmail/	Sites with WebGais – Websendmail
:DIR | intitle:index of inurl://whatsapp/	Unconfirmed Websites leaking WhatsApp Databases
intitle:"Index.Of.Applications (Parallels)" -stackoverflow -quora	Dork will give application folder of parallels virtual machines showing what is installed in the virtual machines
intitle:index.of home/000~root~000/	Lists files under Root Directory

93% Of Professionals Stated That C|EH Skills Improved Their Organizational Security

Ethical Hacking and Countermeasures
Google Dorks Cheat Sheet

Google Dork	Description
intitle:"Index Of" intext:".Trash"	Dorks containing trash folders on Linux/Unix machines
intitle:CV+index of	Search and download CV from web directory
inurl:"apps/backend/config/"	Directories containing Symfony CMS juicy info and files
intext:"Powered by ViewVC" | intitle:"ViewVC Repository Listing"	ViewVC Repository Listing
"lv_poweredBy"	Folders with a lot of shared files
intext:"/wp-content/uploads/wpsc/"	Generates juicy information
inurl:"nfs://www." "index of /"	Returns files shared in Network File System (NFS)
intitle:index.of .bashrc	Create own shortcuts using aliases and shell functions. Aliases can be declared in bash files
intext:"index of /userfiles/file/"	Generate juicy information to user files
inurl:/wp-content/plugins/seo-pressor/classes/	Generate juicy information in the parent directory, for best practice filter according to the country
intext:/wp-content/plugins/woocommerce/templates/emails/plain/	Generate juicy information in the parent directory, for best practice filter according to the country
inurl:/sym/root/ intitle:index.of	Probable symbolic links to the root file system of the web server that can be browsable
intext:"Index of /database"	Obtain private database details including SQL and other database elements and contents
intext:"Index of /.git"	Most of the web-applications are maintained using git repositories reveals sensitive information containing data like db-info, logs, configs, main-source code, etc.
intitle:index.of intext:viewvc	List those that are indexed and open for viewing
index of /htdocs	Find unauthorized web-servers, and sensitive info through 'htdocs' folder including xamp servers
intitle:"Index of /" "joomla_update.php"	Finds directories with Joomla logs, often containing juicy info
-inurl:htm -inurl:html intitle:"index of" NIKON	Explore the Images and photos uploaded and saved in Directories from Nikon
-inurl:htm -inurl:html intitle:"index of" 100CANON	Explore the Images and photos uploaded and saved in Directories from Canon
inurl:"/drive/folders/" site:drive.google.com	Google Drive folders
intitle:"index of" $Recycle.bin	Windows recycle bin
inurl:"folderview?id=" site:drive.google.com	Finds people's private folders on Google Drive
powered by h5ai	Browse through files
site:onedrive.live.com shared by	Identifies shared archives in OneDrive
"Powered by AutoIndex PHP Script" ext:php	Sensitive Directories and Files Containing Juicy Info
inurl:admin inurl:uploads	Fishes images and text from upload sites

Google Dork	Description
inurl:/fckeditor/editor/plugins/ajaxfilemanager /ajaxfilemanager.php	Refresh, Select All, Delete, Cut, Copy, Paste, New Folder, Upload ← vulnerable exploit in process for upload web shell, Close, Info Sensitive Directories and Files Containing Juicy Info
index:"html/js/editor/fckeditor/editor/ filemanager/connectors"	name =find liferay file page
inurl:/FCKeditor/editor/filemanager/upload/	Access unprotected files in the FCKeditor without authentication
inurl:pictures intitle:index.of	Access a lot of personal pictures
inurl:.ssh intitle:index.of authorized_keys	SSH Keys
intitle:Index of /__MACOSX ...	MAC OS X. Parent Directory Wordpress information
(intext:"index of /.git") ("parent directory")	This dork will find git repository's which may have sensitive information
intitle: Index of /awstats/data	Awstats Log file's directory can reveal file/directory location
inurl:/server/webapps	Apache Tomcat information disclosure
intitle:index.of.mail	Dork with juicy info
inurl:"wp-content/uploads/private"	Finds directories with juicy data
inurl:pipermail intitle:index.of parent	Finds Pipermail Archives
intitle:index.of inurl:grades site:edu	Finds directories containing grades.
intitle:index.of parent inurl:repos	Retrieve shared repositories
"Desktop" parent intitle:index.of	Find desktops shared on the interwebs
"My Documents" "parent" intitle:index.of	Search Private directories also work on Yahoo
"sql" "parent" intitle:index.of -injection	Find directories containing SQL Installs and/or SQL databases
inurl:.DS_Store intitle:index.of	Find directories with DS_Store files
inurl:/aspnet_client/system_web/	Find juice directory "ASP"
inurl:.listing intitle:index.of	Find directories with. listing files
mail spool intitle:index.of	Dork for mail spools
private parent intitle:index.of	Dork for all sorts of juicy stuff
inurl:users intitle:index.of	Find user folders containing interesting files
inurl:"default.php" intext:"website" "has been successfully installed on the server!"	Here is a list of files and directories in your public HTML folder, it bypasses the directory-listening restriction
intitle:"Index.of" "attachments"	Find directories with interesting info
intitle:"Index of" "WhatsApp Databases"	Finds db.crypt/.db files of WhatsApp conversations
intitle:"Index of" "WhatsApp Images"	Retrieve WhatsApp Images folder, usually from backups

Google Dork	Description
intitle:"Index of" "DCIM"	Access lot of camera photos dump
intext:index of sym	Retrieve All config file stored in this sym folder
intitle:index.of.pubs	Find sensitive directories
intitle:"Index of" "wwwroot"	Directory of wwwroot Dork
intitle:"index of" inurl:"no-ip.com"	Browse files stored on a personal server(home) using a dynamic DNS service to update server IP. You can replace "no-ip.com" with any other dynamic DNS hosts
inurl:private_files	Find directory private files xD
intitle:"index of" "onetoc2" "one"	View Onenote files stored in the open(*.one). These files can be read easily with Onenote or a compatible viewer, no password, no encryption
inurl:wp-admin/ intext:css/	Finds misconfigured WordPress sites
intitle:"Index of ftp"	Finds open ftps. This is a base dork, where you can add intext:"ssh/" for folder search and intext:"-2015" for dates and years
intitle:index.of.dropbox	Find sensitive directories
intitle:index.of +"Indexed by Apache::Gallery"	Google dork for finding Private pics
intitle:index.of.accounts	Dork for a directory with accounts
inurl:/wp-content/wpbackitup_backups	Sensitive data/site rips/db rips in publicly accessible folders
"Config" intitle:"Index of" intext:vpn	Directory with keys of VPN servers
"jos_users" intitle:"Index of"	Files of the configuration of user Joomla servers
inurl:/cgi-bin/.cgi	Finds open index of /cgi-bin
allinurl:/hide_my_wp=	Show plugin file folder and all file
intitle:"index of" intext:".ds_store"	Mac OSX directories
intitle:"index of" myshare	Gives access to often unconsciously shared documents, programs or sensitive information
inurl:8080 intitle:"Dashboard [Jenkins]"	Access to Jenkins Dashboard
intext:xampp-dav-unsecure:$apr1$6O9scpDQ$JGw2Tjz0jkrqfKh5hhiqD1	Text file but by URL we can travel in paren directory
inurl:"/wp-content/uploads/db-backup"	Searching for the backup directory of WP-DB Backup plugin (WordPress)
intitle:index.of intext:.bash_history	Home user's directory path indexed
"index of" inurl:sym	Steal the symlinks of other servers
"index of" inurl:root intitle:symlink	Steal Others Symlink
inurl:ckfinder intext:"ckfinder.html" intitle:"Index of /ckfinder"	Find root directory of CKFinder
inurl:/xampp	Looks for servers with xampp installed

92% Of Hiring Managers Prefer Candidates with C|EH For Jobs That Require Ethical Hacking Skills.

Ethical Hacking and Countermeasures
Google Dorks Cheat Sheet

EC-Council
Building A Culture Of Security

Google Dork	Description
allintext:"WebServerX Server at"	Quick and dirty WebserverX HTTP server google dork
intitle:index.of cisco asa -site:cisco.com	Google search for Pix/Asa images
intitle:index.of ios -site:cisco.com	Google search for Cisco IOS images
intitle:index.of.config	Give information about a web servers configuration
allintitle:"FirstClass Login"	Firstclass directory listings go to http://[target]/[path]/Search type just ' in the search field to get a list of downloadable files, and can search for robots.txt with some folders path or other info for site structure, getting unauthorized access on all files on the target server
inurl:install.pl intext:"Reading path paramaters" -edu	Everything from OS, to the forum software, etc.
"Warning: Installation directory exists at" "Powered by Zen Cart" -demo	Find fresh installations of Zen-Cartsee Full Disclosure forums for details
"Welcome to the directory listing of" "NetworkActiv-Web-Server"	NetworkActiv-Web-Server directory listing
log inurl:linklint filetype:txt -"checking"	Linklint is an Open Source Perl program that checks links on web sites
"Directory Listing for" "Hosted by Xerver"	Directory listing for Xerver web server
intitle:"Folder Listing" "Folder Listing" Name Size Date/Time File Folder	Directory listing for Fastream NETFile Web Server
intitle:"Backup-Management (phpMyBackup v.0.4 beta *)" -johnny.ihackstuff	phpMyBackup is an mySQL backup tool, with features like copying backups to a different server using FTP
intitle:"pictures thumbnails" site:pictures.sprintpcs.com	Reveals photo albums taken by Sprint PCS customers
intitle:index.of WEB-INF	Finds java powered web servers which have indexing enabled on their config directory
intitle:index.of /maildir/new/	Provides mailbox dir. that contains a lot of mails
filetype:ini Desktop.iniintext:mydocs.dll	Finds any web shared windows folder inside my docs
intitle:"Index of /" "joomla_update.php"	Finds directories with Joomla logs, often containing juicy info
filetype:torrent torrent	Torrent files
"Index of" rar r01 nfo Modified 2004	New Warez Directory Lists
"Web File Browser" "Use regular expression"	Search for a PHP script used to manage files on a server
intitle:"HFS /" +"HttpFileServer"	"The HttpFileServer is a Java-based mechanism for providing web access to a set of files on a server
intitle:upload inurl:upload intext:upload -forum -shop -support -w3c	Reveals server upload portals
intitle:"index of" inurl:ftp (pub | incoming)	Adding "inurl:ftp (pub | incoming)" to the "index.of" searches help to locate FTP websites
allinurl:"/*/_vti_pvt/" | allinurl:"/*/_vti_cnf/"	Frontpage extensions for Unix
intitle:index.of abyss.conf	Reveal the configuration file of the abyss webserver

Google Dork	Description
intitle:"index of" "parent directory" "desktop.ini" site:dyndns.org	Uses desktop.ini to track users with a webserver running on their desktop computers
intext:"Powered By: TotalIndex" intitle:"TotalIndex"	TotalIndex v2.0 is an open-source script that is designed to replace the simple, and boring default index page of a site which lists the files in an indexed folder
"intitle:Index.Of /" stats merchant cgi-* etc	Looks for indexes with the following subdirectories: stats, merchant, online-store, and cgi-local or cgi-bin
inurl:explorer.cfm inurl:(dirpath|This_Directory)	Find file manager without authentication
intitle:"index of" intext:"content.ie5"	Indicates the "Local settings" dir in most cases, and browsable server directories in general
index.of.dcim	DCIM directory is the default name for a few brands of digital cameras
intitle:"index of" -inurl:htm -inurl:html mp3	Mp3 files
intitle:"Directory Listing For" intext:Tomcat -int	Google Hackers Guide explains how to find Apache directory indexes, which are the most common found on the Internet
intitle:"webadmin - /*" filetype:php directory filename permission	Webadmin.php is a free simple Web-based file manager. This search finds sites that use this software
intitle:index.of (inurl:fileadmin | intitle:fileadmin)	TYPO3 is a free Open Source content management system for enterprise purposes on the web and in intranets, featuring a set of ready-made interfaces, functions, and modules
intitle:"Index of *" inurl:"my shared folder" size modified	These are index pages of "My Shared Folder". Sometimes they contain juicy stuff like mp3's or avi files
intitle:index.of /AlbumArt_	Find directories containing commercial music. AlbumArt_{.*}.jpg are download/create by MS-Windows Media Player in the music directory
intext:"d.aspx?id" || inurl:"d.aspx?id"	Shows files that were transmitted. A malicious user could download them from these pages
"index of" / picasa.ini	Picasa is an 'Automated Digital Photo Organizer' recently acquired by Google
intitle:"index of /phpmyadmin" modified	phpMyAdmin is a tool written in PHP intended to handle the administration of MySQL over the Web
filetype:cfg ks intext:rootpw -sample -test -howto	Anaconda is a Linux configuration tool like yast on suse linux. The root password is often encrypted - like md5 or read from the shadow. Sometimes an attacker can also get a cleartext password
intitle:"album permissions" "Users who can modify photos" "EVERYBODY"	Gallery (http://gallery.menalto.com) is software that allows users to create webalbums and upload pictures to it
"Index Of /network" "last modified"	Find directories contain information about network
intitle:intranet inurl:intranet +intext:"human resources"	Access the company's private network and provides employee listings and other sensitive information useful for any social engineering
inurl:/tmp	Reveal temporary files and directories on the webserver
"index of" inurl:recycler	Files in this directory may contain sensitive information
inurl:/pls/sample/admin_/help/	The default installation location of Oracle manuals
inurl:ojspdemos	The directory contains sample Oracle JSP scripts installed on the server

9. Web Server Detection

Google Dork	Description
inurl:j2ee/examples/jsp	The directory contains sample JSP scripts which are installed on the server
"index of cgi-bin"	CGI directories contain scripts which can often be exploited by attackers
intitle:"Index of" cfide	The top-level directory of ColdFusion, a powerful web development environment
intitle:"index.of.personal"	The directory has various personal documents and pictures
inurl:backup intitle:index.of inurl:admin	Reveals backup directories and contain various information ranging from source code, SQL tables, user lists, and even passwords
intitle:"Index of c:\Windows"	Indicate that they share the C:\WINDOWS directory, which is the system folder for many Windows installations
"Welcome to phpMyAdmin" " Create new database"	phpMyAdmin is a widely spread web frontend used to maintain SQL databases. The default security mechanism is to leave it up to the admin of the website to put a .htaccess file in the directory of the application
index.of.private	Find directory with some private files
"Index of /backup"	Reveal contents of their backup directories
intitle:"Welcome to nginx!" intext:"Welcome to nginx on Debian!" intext:"Thank you for"	Finds nginx server welcome page
intitle:"index of" "Served by Sun-ONE"	Finds Sun-ONE web servers
-pub -pool intitle:"index of" "Served by" "Web Server"	Finds LiteSpeed Webservers
intitle:"index of" "server at"	Another way to spot Apache web servers in case the service name is hidden
site:*/server-status intext:"Apache server status for"	Finds files containing Juicy information
inurl:/phpmyadmin/changelog.php -github -gitlab	Finds Phpmyadmin changelog file
inurl:"WebPortal?bankid"	Finds list of banks in ger hosted by the same hoster
intitle:"IIS Windows Server" -inurl:"IIS Windows Server"	Finds IIS windows server
intitle:"Apache2 Ubuntu Default Page: It works"	Finds Apache2 Ubuntu default welcome page.
inurl:/server-status + "Server MPM:"	Finds Apache server-status
inurl:phpinfo.php intext:build 2600	Finds web servers that have been unmaintained for literal decades.
intext:"Brought to you by eVetSites"	List of sites all hosted by eVetSites, hosting platform for veterinarians
inurl:OrganizationChart.cc	Finds all websites using ADSelfService and authorizing guest access to the LDAP directory. Access name, mail, mobile number, function...
intext:"Powered by GetSimple" -site:get-simple.info	Find sites using the GetSimple CMS
inurl:jsmol.php	Moodle sites using Jsmol
intitle:"WAMPSERVER homepage" "Server Configuration" "Apache Version"	Dork for instances of WAMPSERVER homepages

92% Of Professionals Reported that C|EH Boosted Their Self Confidence

Ethical Hacking and Countermeasures
Google Dorks Cheat Sheet

Google Dork	Description
"Powered by BOINC"	Find websites powered by BOINC
"Proudly created with Wix.com"	Find Websites made with WIX
"I have been invoked by servletToJSP"	Find many improperly set up tomcat servlets
intext:" - 2019 Cott Systems, Inc."	Local Government Websites
intitle:Test Page for the Nginx HTTP Server on Fedora	Web server detected
"Powered by vShare"	Find websites that are used to upload files and videos
intext:"Powered by Abyss Web Server"	Machines running Abyss webserver
intitle:livezilla "Server Time"	Dork to locate LiveZilla consoles and version, as well as additional information about the server such as PHP version
intext:"Powered by phpSQLiteCMS" | intitle:"phpSQLiteCMS - A simple & lightweight CMS"	phpSQLiteCMS detect
intitle:"Sucuri WebSite Firewall - Access Denied"	Sucuri Firewall detected
"This server is operated by OpenX."	Find websites using the OpenX webserver software
intext:"Powered by Nesta"	Nesta, a Ruby CMS
Coldbox | contentbox | commandbox "Powered by ContentBox"	Finds ContentBox content management tools and CMS
intext:"Powered by Typesetter"	Typesetter CMS dorks
intext:"Powered by (Quantum | Quantum CMS | CMS)	Finds sites using Quantum CMS builder
intext:"Powered by Sentora" -github.com	Finds sites using Sentora CMS
inurl:/_hcms/	Get all sites using Hubspot's Content Management system (CMS)
inurl:tests/mocks intext:autoloader	Identify websites made with codeigniter
intitle:"apache tomcat/" "Apache Tomcat examples"	Shows many examples of Server Apache Tomcat
"RDServer Product information" | inurl:"/rdagent.jsp"	Shows RDServer Product information
intitle:"apache tomcat/" + "Find additional important configuration information in:"	Apache Tomcat web server detected
intitle:"Apache2 Debian Default Page: It works"	Default Apache2 HTML page
inurl:rvsindex.php & /rvsindex.php?/user/login	Sites running rvsitebuilder CM
intitle:"miniProxy"	Finds this little script: (https://github.com/joshdick/miniProxy) And provides free proxies to be used for browsing or, as it is usable with GET parameters, to use with cURL
intitle:"Axis Happiness Page" "Examining webapp configuration"	Reveals sensitive information including a full path disclosure in Apache Axis
"var miner = new CoinHive" intext:document.domain	Finds sites that run the CoinHive crypto miner

Google Dork	Description
inurl:"server-status" "Server Version: Apache/" "Server Built: " "Server uptime:" "Total accesses" "CPU Usage:"	Shows URL which has Apache server-status file openly accessible
"Application Blocked!" "Google bot"	Retrieves pages with a blacklist or behind FortiGate firewall
inurl:readme.md intext:"Laravel"	Laravel package comes with readme.md and can identify the framework which can be further used for exploiting
inurl:phpmyadmin/themes intext:"pmahomme"	Identify websites that host PHPMyAdmin by detecting exposed theme files
intext:"Welcome to CodeIgniter!"	Identify CodeIgniter applications
inurl:readme.rst intext:"CodeIgniter"	CodeIgniter comes with a default offline readme.rst which most of the installed applications don't remove and get indexed. This can identify the framework and exploit it
intitle:"Index of" "Apache/2.4.7 (Ubuntu) Server"	Find Ubuntu servers and a certain version of Apache
intitle:"Index of /" "Proudly Served by Surftown at"	Finds Surftown HTTP servers
inurl:/pub/ inurl:_ri_	Finds servers using Oracle Responsys
ext:svc inurl:wsdl	Returns Web Services Description Language that will expose web services
inurl:/php/info.php	Php version and information page
intitle:"HFS" "Server Uptime" "Server time"	Finds HttpFileServer with open access
inurl:phpsysinfo/index.php?disp=dynamic	Shows lot of information about servers behind the webpages
intitle:"Apache Status" | intext:"Apache Server Status"	Provides Apache Server Status, Server Version, Server Built, Current Time, Restart Time, Parent Server Generation, Server uptime
intext:Apache/2.2.29 (Unix) mod_ssl/2.2.29 | intitle:"Index of /"	Finds Server Name and Port
inurl:"/web-console/" intitle:"Administration Console"	Finds Boss Application Server Info
filetype:asmx inurl:(_vti_bin|api|webservice)	Returns web service
intitle:"BadBlue: the file-sharing web server anyone can use"	Badblue file sharing web server detection
intext:"Target Multicast Group" "beacon"	Provide useful statistics and diagnostic information about a given multicast group's connectivity characteristics
intitle:"Apache Status" "Apache Server Status for"	New Apache server-status dork
inurl:wl.exe inurl:?SS1= intext:"Operating system:" -edu -gov -mil	List server apparently keeps track of many clients, not just Domains and hardware, but Operating systems as well
inurl:nnls_brand.html OR inurl:nnls_nav.html	Novell Nterprise Linux Services detection dork
(intitle:"502 Proxy Error")|(intitle:"503 Proxy Error") "The proxy server could not handle the request" -topic -mail -4suite -list -site:geocrawler.co	Enables one web server to provide content from another transparently

Google Dork	Description
intitle:"Welcome To Your WebSTAR Home Page"	This is the default page for the WebSTAR (Macintosh) web server (Headers say --> Server: WebSTAR NetCloak)
intitle:"Document title goes here" intitle:"used by web search tools" " example of a simple Home Page"	Finds IBM Http Server (AS/400)
intitle:"Welcome to the Advanced Extranet Server, ADVX!"	Webserver detection: The Advanced Extranet Server project aims to create an extensible open source web server based on Apache
intitle:"Welcome to Windows Small Business Server 2003"	Another way to find Small Business Server 2003
intitle:"IPC@CHIP Infopage"	Uses the webserver's info page which reveals interesting information
intitle:"Test Page for the Apache HTTP Server on Fedora Core" intext:"Fedora Core Test Page"	Finds Apache 2.0 on Fedore Core Test page
Powered.by.RaidenHTTPD intitle:index.of	Finds RaidenHTTPD (http://www.raidenhttpd.com/en) is a full featured web server software for Windows
(inurl:81-cobalt | inurl:cgi-bin/.cobalt)	Finds Cobal RaQ internal pages
intitle:"Resin Default Home Page"	Resin provides a fast-standalone web server and locates those servers based on the title of the default page
intitle:"Welcome To Xitami" -site:xitami.com	The default installation of Xitami web server contains test script which provides a lot of information about the server
intitle:"Welcome to Your New Home Page!" "by the Debian release"	Finds default Apache page on Debian installs
"About Mac OS Personal Web Sharing"	Mac OS Personal Web Sharing allows Mac OS users to share Folders over the Web
Mac OS Personal Web Sharing allows Mac OS users to share Folders over the Web	Finds index page of OReilly Website Professional
intitle:"Object not found!" intext:"Apache/2.0.* (Linux/SuSE)"	Detects apache web server (2.0.X/SuSE) with its error page
intitle:"Lotus Domino Go Webserver:" "Tuning your webserver" -site:ibm.com	Domino Go Webserver is a scalable high-performance Web server that runs on a broad range of platforms
intitle:"Directory Listing, Index of /*/"	Small HTTP server software for private homepage hosting or big uploads
intitle:"Object not found" netware "apache 1.."	Show NetWare apache webservers as the result
intitle:AnswerBook2 inurl:ab2/ (inurl:8888 | inurl:8889)	Indicates Solaris machines and second the web service is vulnerable to a format string attack
inurl:phpinfo.php intext:build 2600	Finds IIS 5.0 error pages = IIS 5.0 Server
"powered by" "shoutstats" hourly daily	Produces instant and dynamic usage reports in HTML format, for viewing in a standard browser
intitle:"Shoutcast Administrator"	Finds the administrator page. It can be used to detect unlisted Shoutcast servers
"Novell, Inc" WEBACCESS Username Password "Version *.*" Copyright -inurl:help -guides|guide	Find Novell Grouwise Webaccess servers

Google Dork	Description
"AnWeb/1.42h" intitle:index.of	Find Version of a web server
"CERN httpd 3.0B (VAX VMS)"	Find Version of a web server
"JRun Web Server" intitle:index.of	Find Version of a web server
"MaXX/3.1" intitle:index.of	Find Version of a web server
Find Version of a web server	Find Version of a web server
"Microsoft-IIS/4.0" intitle:index.of	Find Version of a web server
intitle:"Page rev */*/*" inurl:"admin	Find Red Hat UNIX Administration Pages
HTTP_USER_AGENT=Googlebot	Generic way of grabbing those CGI-spewed environmental var lists
intext:"Powered by Abyss Web Server"	Machines running Abyss webserver
allinurl:".nsconfig" -sample -howto -tutorial	Gives access to Web server's content, CGI scripts, and configuration files are controlled by entries in an access file
inurl:domcfg.nsf	Return a listing of servers running Lotus Domino. These servers have descriptive error messages that can obtain path and OS information
intitle:"300 multiple choices"	Shows sites that have the 300-error code and also reveal a server tag at the bottom of the page that an attacker could use to profile a system
intitle:Snap.Server inurl:Func=	Reveals the existence of a SNAP server
intitle:"Test Page for Apache"	Default web page for Apache 1.2.6 - 1.3.9. used to get information to determine the version of the webserver, or to search Google for vulnerable targets
allintitle:Netscape FastTrack Server Home Page	Finds default installations of Netscape Fasttrack Server
intitle:"Test Page for Apache" "It Worked!"	Default web page for Apache 1.2.6 - 1.3.9. where this information can be used to determine the version of the webserver and vulnerable targets
"seeing this instead" intitle:"test page for apache"	Find default web page for Apache 1.3.11 - 1.3.26
intitle:"Test Page for Apache" "It Worked!" "on this web"	Find default web page for Apache 1.2.6 - 1.3.9
inurl:tech-support inurl:show Cisco	Find Cisco products with an open web interface
intitle:"Apache HTTP Server" intitle:"documentation"	Obtain a set of online documentation when Apache web server is installed

Ethical Hacking and Countermeasures
DNSRecon Cheat Sheet

EC-Council
Building A Culture Of Security

DNSRecon
Source: https://github.com

DNSRecon is for performing the reverse DNS lookup on the target host, check NS Records for zone transfer, exploit vulnerabilities and obtain network information of a target domain and further launch Internet-based attacks, enumerate DNS Records for domains (MX, SOA, NS, A, AAAA, SPF, and TXT), perform common SRV record enumeration, Top Level Domain (TLD) expansion, check for wildcard resolution, brute Force subdomain and host A and AAAA records given a domain and a wordlist, perform a PTR Record lookup for a given IP Range or CIDR, check a DNS server cached records for A, AAAA and CNAME Records provided a list of host records in a text file to check, enumerate common mDNS records in the local network enumerate hosts and subdomains using Google.

Syntax

```
dnsrecon.py [-h] [-d DOMAIN] [-n
NS_SERVER] [-r RANGE] [-D
DICTIONARY][-f] [-t TYPE] [-a] [-s] [-g]
[-b] [-k] [-w] [-z] [--threads THREADS]
[--lifetime LIFETIME] [--tcp] [--db DB]
[-x XML] [-c CSV] [-j JSON] [--iw] [-v]
```

DNSRecon Installation

aptitude install dnsrecon On Parrot, or:
git clone https://github.com/darkoperator/dnsrecon.git
cd dnsrecon
pip install -r requirements.txt

`--db`	SQLite 3 file
`--xml`	XML file
`--json`	JSON file
`--csv`	CSV file

Command	Description
`dnsrecon -d <Target Domain> -j <results json file>`	Save results in a json file
`dnscan.py -l $domains_file -o outfile -w $wordlist`	Subdomain brute-force of domains listed in a file (one by line)
`dnscan.py -d target.com -o outfile -w $wordlist`	Subdomain brute-force of a domain
`dnssearch -domain <Target Domain> -wordlist $wordlist`	Dnssearch Subdomain brute-force
`dnsrecon -d zonetransfer.me`	Use Robin Wood's zonetransfer.me site to enumerate and Run a scan
`dnsrecon -d zonetransfer.me -D <namelist.txt> -t brt`	Brute Force scan
`dnsrecon -d zonetransfer.me -a`	Zone Transfer
`dnsrecon -d zonetransfer.me -a --db ~/Desktop/dnsrecon/dnsrecon-db`	Look at SQLite database file
`dnsrecon -d zonetransfer.me -a --xml ~/Desktop/dnsrecon/dnsrecon-xml`	Save the results in XML format
`dnsrecon -d TARGET -D /usr/share/wordlists/dnsmap.txt -t std --xml ouput.xml`	DNS Zone Transfers
`dnsrecon -d <Target IP> -t std -D /usr/share/wordlists/dnsmap.txt`	DNS (reverse) lookups / Enumeration DNS / Brute force subdomains
`$ python dnsrecon.py -n ns1.<Target Domain> -d <Target Domain> -D subdomains-top1mil-5000.txt -t brt`	DNS enumeration tool
`dnsrecon -w`	DNS Reconnaissance

Command	Description
`dnsrecon -r <Target IP range>`	Reverse DNS lookup on the target host
`dnsrecon -t axfr -d <Target Domain>`	DNS zone transfer
`dnsrecon -d <Target Domain> -z`	Zone enumeration against a target domain

`dnsrecon -d <Target Domain> -a`
`./dnsrecon.py -d <Target Domain> -a`
`or`
`dnsrecon -d <Target Domain> -t axfr`
`./dnsrecon.py -d <Target Domain> -t axfr`
	Zone transfer

`dnsrecon -r <start Target IP>-<end Target IP>`
`./dnsrecon.py -r <start Target IP>-<end Target IP>`
`./dnsrecon.py -r <Target IP range>`
	Reverse Lookup against IP range

`dnsrecon -d <Target Domain> -s` `./dnsrecon.py -d <Target Domain> -s`	Reverse Lookup against all ranges in SPF records
`dnsrecon -d <Target Domain> -D <namelist.txt> -t brt` `./dnsrecon.py -d <Target Domain> -D <namelist> -t brt`	Domain Brute Force Enumeration
`dnsrecon -d <Target Domain> -D /usr/share/wordlists/dnsmap.txt -t std --xml ouput.xml`	DNS Brute force
`dnsrecon -t snoop -n <Server IP> -D <namelist.txt>` `./dnsrecon.py -t snoop -n <Server IP> -D <dictionary file>`	Cache Snooping against name servers
`dnsrecon -d <Target Domain>` `./dnsrecon.py -d <Target Domain>`	Standard Records Enumeration/ enumerate DNS record of targeted website
`dnsrecon -d <Target Domain> -t zonewalk`	Zone Walking
`dnsrecon -d <Target Domain> -t rvl`	Reverse lookup of a given CIDR or IP range
`dnsrecon -d <Target Domain> -t brt -D <Subdomains Dictionary>`	Brute force domains and hosts using a given dictionary
`dnsrecon -d <Target Domain> -t brt -D <Subdomains Dictionary> --iw`	Brute force domains and hosts using a given dictionary. Continue brute-forcing a domain even if wildcard records are discovered
`dnsrecon -d <Target Domain> -t srv`	SRV records
`dnsrecon -d <Target Domain> -t axfr`	Test all NS servers for a zone transfer
`dnsrecon -d <Target Domain> -t goo`	Google search for subdomains and hosts
`dnsrecon -d <Target Domain> -t tld`	Remove the TLD of a given domain and test against all TLDs registered in IANA
`dnsrecon -d <Target Domain> -t zonewalk`	DNSSEC zone walk using NSEC records
`dnsrecon -d <Target Domain> --db <results sqlite File>`	Save results in a sqlite file
`dnsrecon -d demo.com --xml <results xml file>`	Save results in an xml file
`dnsrecon -d <Target Domain> -c <results csv file>`	Save results in a csv file

Arguments	
`-h, --help`	Help message and exit
`-d DOMAIN, --domain DOMAIN`	Target domain
`-n NS_SERVER, --name_server NS_SERVER`	Domain server to use. If none is given, the SOA of the target will be used
`-n nsserver.com`	Use a custom name server
`-r RANGE, --range RANGE`	IP range for reverse lookup brute force in formats (first-last) or in (range/bitmask)
`-D DICTIONARY, --dictionary DICTIONARY`	Dictionary file of subdomain and hostnames to use for brute force. Filter out of brute force domain lookup, records that resolve to the wildcard defined IP address when saving records
`-f`	Filter out of brute force domain lookup, records that resolve to the wildcard defined IP address when saving records
`-t TYPE, --type TYPE`	Type of enumeration to perform
`-a`	AXFR with standard enumeration
`-r`	Recursively scan subdomains
`-s`	Reverse lookup of IPv4 ranges in the SPF record with standard enumeration
`-T`	TLD expansion
`-g`	Google enumeration with standard enumeration
`-b`	Bing enumeration with standard enumeration
`-k`	Crt.sh enumeration with standard enumeration
`-w`	Deep whois record analysis and reverse lookup of IP ranges found through Whois when doing a standard enumeration
`-z`	DNSSEC zone walk with standard enumeration
`--threads THREADS`	Number of threads to use in reverse lookups, forward lookups, brute force, and SRV record enumeration
`--lifetime LIFETIME`	Time to wait for a server to respond to a query
`--tcp`	Use TCP protocol to make queries
`--db DB`	SQLite 3 file to save found records/ save results to SQLite database file
`-x XML, --xml XML`	XML file to save found records/ save results to the XML file
`-c CSV, --csv CSV`	Comma-separated value file
`-j JSON, --json JSON`	JSON file
`-i $file`	Output discovered IP addresses to a text file
`--iw`	Continue brute-forcing a domain even if wildcard records are discovered
`-v`	Enable verbose

Ethical Hacking and Countermeasures
OSRFramework Cheat Sheet

OSRFramework
Source: https://github.com

OSRFramework includes applications related to username checking, DNS lookups, information leaks research, deep web search, regular expression extraction, etc. Tools included in the OSRFramework package to gather information on the target are usufy.py, mailfy.py, searchfy.py, domainfy.py, phonefy.py, and entify.py.

usufy.py – Verifies a user profile against 290 different platforms

Syntax

```
usufy.py
(--info <action> | --license | -b | -f <path_to_fuzzing_list> | -l
<path_to_nick_list> | -n <nick> [<nick> ...] | --show_tags)
[-p <platform> [<platform> ...]] [-t <tag> [<tag> ...]]
[-x <platform> [<platform> ...]] [--avoid_download]
[--avoid_processing] [--fuzz_config <path_to_fuzz_list>]
[--nonvalid <not_valid_characters>]
[-e <sum_ext> [<sum_ext> ...]] [-L <path_to_log_folder] [-m]
[-o <path_to_output_folder>] [-w]
[-F <alternative_header_file>] [-T <num_threads>] [-h]
[-v <verbosity>] [--version]
```

Input options

`--info <action>`	Action to be performed such as list_platforms, list_tags
`--license`	Displays license
`-b, --benchmark`	Benchmarking tasks
`-f <path_to_fuzzing_list>, --fuzz <path_to_fuzzing_list>`	Find URLs similar to usufy
`-l <path_to_nick_list>, --list <path_to_nick_list>`	Specify the path to the file where the list of nicks to verify is stored (one per line)
`-n <nick> [<nick> ...], --nicks <nick> [<nick> ...]`	Specify a list of nicks to process
`--show_tags`	Shows platforms grouped by tags

Platform selection arguments

`-p <platform> [<platform> ...], --platforms <platform> [<platform> ...]`	Specify the platform for searching
`-t <tag> [<tag> ...], --tags <tag> [<tag> ...]`	Specify the list of tags that fit the platforms to perform the search
`-x <platform> [<platform> ...], --exclude <platform> [<platform>`	Specify the platforms you want to exclude from the processing

Processing arguments

`--avoid_download`	Use to prevent storing the downloadable version of the profiles
`--avoid_processing`	Use to prevent performing any processing task without valid profiles
`--fuzz_config <path_to_fuzz_list>`	Specify the path to the fuzzing config details
`--nonvalid <not_valid_characters>`	Specify not valid characters
`-e <sum_ext> [<sum_ext> ...], --extension <sum_ext> [<sum_ext> ...]`	Use to output extension for the summary files. Default: XLS
`-L <path_to_log_folder, --logfolder <path_to_log_folder`	Specify the path to the log folder. If none was provided, ./logs is assumed
`-m, --maltego`	Specify parameter to launch usufy.py by using Maltego Transform

Processing arguments

`-o <path_to_output_folder>, --output_folder <path_to_output_folder>`	Specify Output folder for the generated documents
`-w, --web_browser`	Specify default web browser
`-F <alternative_header_file>, --file_header <alternative_header_file>`	Specify header for the output filenames
`-T <num_threads>, --threads <num_threads>`	Specify the number of threads to be used (default 32)

Arguments

`-h, --help`	Displays help
`-v <verbosity>, --verbose <verbosity>`	Select the verbosity level: 0 - none; 1 – normal (default); 2 - debug
`--version`	Displays the version of the program

usufy.py Commands

Commands	Description
`usufy.py -n <username> -p twitter facebook youtube`	Search for a user on social media sites
`usufy.py -n <username>`	Check username (profile) on various platforms

mailfy.py – Check for the existence of a given mail

Syntax

```
mailfy.py
(--license | -m <emails> [<emails> ...] | -M
<emails_file> | -n <nicks> [<nicks> ...] | -N
<nicks_file> | --create_emails <nicks_file>)
[-e <sum_ext> [<sum_ext> ...]]
[-d <candidate_domains> [<candidate_domains> ...]]
[-o <path_to_output_folder>] [-x <domain> [<domain>
...]]
[-F <alternative_header_file>] [-T <num_threads>]
[--is_leaked] [--quiet] [-h] [--version]
```

Input options

`--license`	Displays license
`-m <emails> [<emails> ...], --emails <emails> [<emails> ...]`	Specify a list of emails for checking
`-M <emails_file>, --emails_file <emails_file>`	Input file containing a list of emails
`-n <nicks> [<nicks> ...], --nicks <nicks> [<nicks> ...]`	Specify a list of nicks for checking against domains selected
`-N <nicks_file>, --nicks_file <nicks_file>`	Input file containing a list of nicks to be checked against domains selected
`--create_emails <nicks_file>`	Input file with the list of nicks to be created in the domains selected

Processing arguments

`-e <sum_ext> [<sum_ext> ...], --extension <sum_ext> [<sum_ext> ...]`	Specify the output extension for the summary files. Default: XLS
`-d <candidate_domains> [<candidate_domains> ...], --domains <candidate_domains> [<candidate_domains> ...]`	-d <candidate_domains> [<candidate_domains> ...], --domains <candidate_domains> [<candidate_domains> ...]
`-o <path_to_output_folder>, --output_folder <path_to_output_folder>`	Specify the output folder for the generated documents
`-x <domain> [<domain> ...], --exclude <domain> [<domain> ...]`	Specify the domains to be excluded from the search
`-F <alternative_header_file>, --file_header <alternative_header_file>`	Specify the Header for the output filenames to be generated
`-T <num_threads>, --threads <num_threads>`	Specify the number of threads to be used (default 16
`--is_leaked`	Specify whether mailfy.py should search for leaked emails
`--quiet`	Inform the program not to show anything

Arguments

`-h, --help`	Shows help
`--version`	Displays version of the program and exists

mailfy.py Commands

Commands	Description
`mailfy.py -n <target email>`	Validates the existences of a given email address
`mailfy.py -m <target email>`	Check whether the given email address was used on the Internet
`mailfy.py -m <target email> <website>`	Check whether the given email address was used on the specified web site

searchfy.py – Performs a query on the platforms in OSRFramework

Syntax

```
searchfy.py
(--license | -q <searches> [<searches> ...])
[-e <sum_ext> [<sum_ext> ...]]
[-F <alternative_header_file>]
[-m] [-o <path_to_output_folder>]
[-p <platform> [<platform> ...]] [--process] [-w]
[-x <platform> [<platform> ...]] [-h] [--version]
```

Ethical Hacking and Countermeasures
OSRFramework Cheat Sheet

EC-Council
Building A Culture Of Security

Input options

`--license`	Displays license
`-q <searches> [<searches> ...], --queries <searches> [<searches> ...]`	Specify a list of queries to be performed

Processing arguments

`-e <sum_ext> [<sum_ext> ...], --extension <sum_ext> [<sum_ext> ...]`	Specify the output extension for the summary files. Default: xls
`-F <alternative_header_file>, --file_header <alternative_header_file>`	Specify header for the output filenames to be generated
`-o <path_to_output_folder>, --output_folder <path_to_output_folder>`	Specify the output folder for the generated documents
`-p <platform> [<platform> ...], --platforms <platform> [<platform> ...]`	Specify the platforms to perform the search
`--process`	Specify whether to process the info in the profiles recovered
`-w, --web_browser`	Open URIs returned in the default web browser
`-x <platform> [<platform> ...], --exclude <platform> [<platform> ...]`	Specify the platforms you want to exclude from the processing

Arguments

`-h, --help`	Shows help
`--version`	Displays version of the program

domainfy.py – Checks for the existence of domains

Syntax

```
domainfy.py (--license | -n <nicks> [<nicks> ...] | -N
<nicks_file>)
[-e <sum_ext> [<sum_ext> ...]] [-o
<path_to_output_folder>]
[-t <tld_type> [<tld_type> ...]]
[-u <new_tld> [<new_tld> ...]] [-x <domain> [<domain>
...]]
[-F <alternative_header_file>] [-T <num_threads>]
[--quiet]
[-h] [--version]
```

Input options

`--license`	Display license
`-n <nicks> [<nicks> ...], --nicks <nicks> [<nicks> ...]`	Specify a list of nicks to be checked in the selected domains
`-N <nicks_file>, --nicks_file <nicks_file>`	Specify the file having the list of nicks to be checked in the selected domains

Processing arguments

`-e <sum_ext> [<sum_ext> ...], --extension <sum_ext> [<sum_ext> ...]`	Specify parameter to launch usufy.py by using Maltego Transform
`-o <path_to_output_folder>, --output_folder <path_to_output_folder>`	Specify the output folder for the generated documents

Processing arguments

`-x <domain> [<domain> ...], --exclude <domain> [<domain> ...]`	Specify the domains to be excluded from the search
`-F <alternative_header_file>, --file_header <alternative_header_file>`	Specify header for the output filenames to be generated
`-T <num_threads>, --threads <num_threads>`	Specify the number of threads to be used (default 16)
`-t <tld_type> [<tld_type> ...], --tlds <tld_type> [<tld_type> ...]`	Specify the list of TLD types where the nick will be searched for
`--quiet`	Informs the program not to show anything

Arguments

`-h, --help`	Shows help
`--version`	Displays version of the program

domainfy.py Commands

Commands	Description
`domainfy.py -n <nicks> -t all`	Verify all top-level domains (-t all) for a registered name
`domainfy.py -whois -n <Target IP>`	Display results in table format for whois search

phonefy.py – Checks for the existence of a given series of phones

Syntax

```
phonefy.py (--license | -n <phones> [<phones> ...]) [-e
<sum_ext> [<sum_ext> ...]] [-o <path_to_output_folder>]
[-p <platform> [<platform> ...]] [-F
<alternative_header_file>] [--quiet] [-w] [-x
<platform> [<platform> ...]] [-h] [--version]
```

Input options

`--license`	Displays License
`-n <phones> [<phones> ...], --numbers <phones> [<phones> ...]`	Specify a list of phones to process

Processing arguments

`-e <sum_ext> [<sum_ext> ...], --extension <sum_ext> [<sum_ext> ...]`	Specify the output extension for the summary files. Default: XLS
`-o <path_to_output_folder>, --output_folder <path_to_output_folder>`	Specify the output folder for the generated documents
`-F <alternative_header_file>, --file_header <alternative_header_file>`	Specify header for the output filenames to be generated
`-p <platform> [<platform> ...], --platforms <platform> [<platform> ...]`	Specify the platforms where you want to perform the search
`-w, --web_browser`	Open the URIs returned in the default web browser
`-x <platform> [<platform> ...], --exclude <platform> [<platform> ...]`	Specify the platforms that you want to exclude from the processing

Arguments

`-h, --help`	Displays help
`--version`	Displays version of the program

domainfy.py Commands

Commands	Description
`phonefy.py -n <number>`	Finds URL location and platform for a given telephone number

entify.py – Use regular expressions to extract entities

Syntax

```
entify.py (-r <name> [<name> ...] | -R
<regular_expression>)
(-i <path_to_input_folder> | -w <url>)
[-e <sum_ext> [<sum_ext> ...]] [-o
<path_to_output_folder>]
[-v <verbosity>] [-F <alternative_header_file>]
[-q]
[-L <path_to_log_folder] [--recursive] [-h]
[--version]
```

Input options

`-r <name> [<name> ...], --regexp <name> [<name> ...]`	Specify the regular expressions to be searched for
`-R <regular_expression>, --new_regexp <regular_expression>`	specify a new regular expression
`-i <path_to_input_folder>, --input_folder <path_to_input_folder>`	Specify the path to the folder to analyze
`-w <url>, --web <url>`	Specify URI to be recovered and analyzed

Processing arguments

`-e <sum_ext> [<sum_ext> ...], --extension <sum_ext> [<sum_ext> ...]`	Specify the output extension for the summary files. Default: XLS
`-o <path_to_output_folder>, --output_folder <path_to_output_folder>`	Specify the output folder for the generated documents
`-F <alternative_header_file>, --file_header <alternative_header_file>`	Sepcify the verbosity level: 0 - none; 1 – normal (default); 2 - debug
`-v <verbosity>, --verbose <verbosity>`	Sepcify the verbosity level: 0 - none; 1 – normal (default); 2 - debug
`-L <path_to_log_folder, --logfolder <path_to_log_folder`	Specify the path to the log folder. If none was provided, ./logs is assumed
`--recursive`	Input variable to inform the system to perform a recursive search on the folder tree

Arguments

`-h, --help`	Shows help
`--version`	Displays version of the program

osrfconsole.py – Open Sources Research Framework console interface

Syntax
`osrfconsole.py`

Modules Available	
`- usufy`	Checks if a username exists in 291 platforms
`- mailfy`	Verifies if a username has been registered in up to 22 email providers
`- searchfy`	Finds profiles using full names and other information in 7 platforms
`- domainfy`	Verifies the existence of a given domain in up to 1567 different TLD
`- phonefy`	Specify the platforms to perform the search
`--process`	Verifies if a phone number has been linked to spam practices in 4 platforms
`- entify`	Util to look for regular expressions using 13 patterns

osrframework_server.py – Open Sources Research Framework web interface

Syntax
`./osrframework-server.py [--host <IP>] [--port <PORT>] [--debug] [-h] [--version]`

Configuration arguments	
`--host <IP>`	Select the host in which the server will be accessible Default: localhost
`--port <PORT>`	Select the port in which the server will be accessible. Use this carefully
`--debug`	Select whether error messages will be deployed

Arguments	
`-h, --help`	Shows help
`--version`	Version of the program and exists

osrframework_server.py Commands

Commands	Description
`osrframework_server.py -h`	Start a local server

Ethical Hacking and Countermeasures
Shodan Cheat Sheet

EC-Council
Building A Culture Of Security

Shodan
Source: https://www.shodan.io

Shodan is a search engine for Internet-connected devices. It is a great resource to provide passive reconnaissance on a target. It also provides a public API that allows other tools to access all the Shodan's data

1.General Filters
2. HTTP Filters
3. NTP Filters
4. SSL Filters
5. Telnet Filters
6. Shodan Search Filters Examples

1. General Filters

Filter	Description
after	Only show results after the given date (dd/mm/yyyy) string
asn	Autonomous system number string
before	Only show results before the given date (dd/mm/yyyy) string
category	Available categories: ICS, malware string
city	Name of the city string Example: cisco city:"New York"
country	The 2-letter country code string Example: webcamxp country:"US"
geo	Accepts between 2 and 4 parameters. If 2 parameters: latitude, longitude. If 3 parameters: latitude, longitude, range If 4 parameters: top left latitude, top left longitude, bottom right latitude, bottom right longitude Example: Webcamxp geo:" -50.81,201.80"
hash	Hash of the data property integer
has_ipv6	True/ False boolean
has_screenshot	True/ False boolean
hostname	The full hostname for the device string
ip	Alias for net filter string
isp	ISP managing the netblock string
net	Network range in CIDR notation (ex. 199.4.1.0/24) string
org	The organization assigned the netblock string
os	Operating system string
port	Port number for the service integer Example: https port:443
postal	Postal code (US-only) string
product	Name of the software/ product providing the banner string
region	Name of the region/ state string
state	Alias for region string
version	Version for the product string
vuln	CVE ID for a vulnerability string Example: vuln:cve-2014-0160

2. HTTP Filters

Filter	Description
http.component	Name of web technology used on the website
http.component_category	Category of web components used on the website
http.html	HTML of web banners
http.html_hash	Hash of the website HTML
http.status	Response status code
http.title	Title for the web banners website Example : title:"+tm01+" has_Screenshot:true

3. NTP Filters

Filter	Description
ntp.ip	Domain Brute Force Enumeration
ntp.ip_count	Number of IPs returned by initial monlist
ntp.more	True/ False; whether there are more IP addresses to be gathered from monlist
ntp.port	Port used by IP addresses in monlist

4. SSL Filters

Filter	Description
has_ssl	True / False
ssl	Search all SSL data
ssl.alpn	Application layer protocols such as HTTP/2 ("h2")
ssl.chain_count	Number of certificates in the chain
ssl.version	Possible values: SSLv2, SSLv3, TLSv1,TLSv1.1, TLSv1.2
ssl.cert.alg	Certificate algorithm
ssl.cert.expired	True / False
ssl.cert.extension	Names of extensions in the certificate
ssl.cert.serial	Serial number as an integer or hexadecimal string
ssl.cert.pubkey.bits	Number of bits in the public key
ssl.cert.pubkey.type	Public key type
ssl.cipher.version	SSL version of the preferred cipher
ssl.cipher.bits	Number of bits in the preferred cipher
ssl.cipher.name	Name of the preferred cipher

5. Telnet Filters

Filter	Description
telnet.option	Search all the options
telnet.do	The server requests the client do support these options
telnet.dont	The server requests the client to not support these options
telnet.will	The server supports these options
telnet.wont	The server does not support these options

6. Shodan Search Filters Examples

Filter	Description
voIP	For footprinting VoIP
VPN	For footprinting VPN
linux upnp avtech	For exploiting cams
netcam	For exploiting netcam
"default password"	For Default Passwords
iis source:ExploitDB	To find exploits for various os, servers, platforms, applications etc present on ExploitDB or Metasploit
netgear port:80	To find Netgear devices
Android Webcam Server-Authenticate	To find android webcam server
port:8333	To find Bitcoin server
Server:Thin-3.2.11-3.1.10-3 .0.19-2.3.15	Ruby on Rails Vulnerable Server(CVE-2013-0156 and CVE-2013-0155)
Jetty 3.1.8(Windows 2000 5.0 ×86)"200 OK"	DNSSEC zone walk with standard enumeration
port:5353	To find DNS service
iRidium	To search for vulnerable ICS systems
port:502	To Search for Modbus enabled ICS/SCADA systems:
"Schneider Electric"	Search for SCADA systems using PLC name
TM221ME16R	To detect Schneider Electric TM221 PLCs connected to the Internet
SCADA Country:"US"	Search for SCADA systems using geolocation
port:20000	To Search for ICS-specific protocol DNP3

Ethical Hacking and Countermeasures
theHarvester Cheat Sheet

EC-Council
Building A Culture Of Security

theHarvester

Source: http://www.edge-security.com

theHarvester is a simple, powerful, and effective tool used in the early stages of a penetration test or red team engagement. It is also used for open-source intelligence (OSINT) gathering to help determine a company's external threat landscape. It can gather emails, names, subdomains, IPs, and URLs using multiple public data sources.

1.theHarvester Options
2. theHarvester Passive Data Source
3. theHarvester Active Data Source
4. theHarvester Commands

1. theHarvester Optionseral Filters

Syntax
`theharvester options`

Options	
`-d`	Domain to search or company name
`-b: data source`	Baidu, bing, bingapi, dogpile, google, googleCSE, googleplus, google-profiles, LinkedIn, pgp, twitter, vhost, yahoo, all
`-s`	Start in result number X (default: 0)
`-v`	Verify hostname via DNS resolution and search for virtual hosts
`-f`	Save the results into an HTML and XML file
`-n`	Perform a DNS reverse query on all ranges discovered
`-c`	Perform a DNS brute force for the domain name
`-t`	Perform a DNS TLD expansion discovery
`-e`	Use this DNS server
`-l`	Limit the number of results to work with (bing goes from 50 to 50 results, google 100 to 100)
`-h`	Use SHODAN database to query discovered hosts

2. theHarvester Passive Data Source

Data Source	Description
`baidu`	Baidu search engine - www.baidu.com
`bing`	Microsoft search engine - www.bing.com
`bingapi`	Microsoft search engine, through the API
`dnsdumpster`	DNSdumpster search engine - https://dnsdumpster.com/
`dogpile`	Dogpile search engine - www.dogpile.com
`duckduckgo`	DuckDuckGo search engine - www.duckduckgo.com
`Exalead`	Meta search engine - www.exalead.com/search
`github-code`	GitHub code search engine (Requires a GitHub Personal Access Token, see below.) - www.github.com
`google`	Google search engine - www.google.com Example: theharvester -d microsoft.com -l 500 -b google -h myresults.html
`google-profiles`	Google search engine, specific search for Google profiles
`googleCSE`	Hunter search engine (Requires an API key, see below.) - www.hunter.io
`intelx`	Intelx search engine (Requires an API key, see below.) - www.intelx.io
`linkedin`	Google search engine, specific search for LinkedIn users - www.linkedin.com Example: theharvester -d microsoft -l 200 -b linkedin
`netcraft`	Internet Security and Data Mining - www.netcraft.com
`otx`	AlienVault Open Threat Exchange - otx.alienvault.com
`securityTrails`	Security Trails search engine, the world's largest repository of historical DNS data - www.securitytrails.com
`shodan`	Shodan search engine will search for ports and banners from discovered hosts - www.shodanhq.com
`Spyse`	Web research tools for professionals - spyse.com
`Suip`	Web research tools that can take over 10 minutes to run, but worth the wait - suip.biz
`threatcrowd`	Open source threat intelligence - www.threatcrowd.org
`trello`	Search trello boards
`twitter`	Twitter accounts related to a specific domain
`vhost`	Bing virtual hosts search
`virustotal`	virustotal.com domain search
`yahoo`	Yahoo search engine
`pgp`	PGP key server - pgp.rediris.es Example: theharvester -d microsoft.com -b pgp

3. theHarvester Active Data Source

Data Source	Description
`DNS brute force`	Runs dictionary brute force enumeration
`DNS reverse lookup`	Reverse lookup of IP´s discovered to find hostnames
`DNS TDL expansion`	TLD dictionary brute force enumeration

4. theHarvester Commands

Command	Description
`theharvester -d microsoft.com -l 500 -b google`	Perform passive scanning on the target domain (Microsoft.com) by limiting the results to 500 (-l 500) using Google (-b)
`theharvester -d kali.org -l 500 -b google -f output.txt`	The server requests the client do support these options
`theHarvester.py -d google.com -c -b google`	Perform active scanning and brute-forcing subdomains of the target domain (google.com) using option -c using Google (-b)