

# Theory and Practice of Finite Element Methods

Shared memory parallelisation  
Tasks, WorkStream

**Luca Heltai** <[luca.heltai@sissa.it](mailto:luca.heltai@sissa.it)>

International School for Advanced Studies ([www.sissa.it](http://www.sissa.it))  
Mathematical Analysis, Modeling, and Applications ([math.sissa.it](http://math.sissa.it))  
Master in High Performance Computing ([www.mhpc.it](http://www.mhpc.it))  
SISSA mathLab ([mathlab.sissa.it](http://mathlab.sissa.it))



# Aims for this module

- Identify parts / blocks of code that are (easily) parallelizable
- Learn how to parallelize using
  - Threads (Posix threads)
  - Tasks (Intel TBB)
  - WorkStream (Threaded building blocks)



# Reference material

- Tutorials

- [https://dealii.org/current/doxygen/deal.II/step\\_9.html](https://dealii.org/current/doxygen/deal.II/step_9.html)
- [https://dealii.org/current/doxygen/deal.II/step\\_13.html](https://dealii.org/current/doxygen/deal.II/step_13.html)
- <http://www.math.colostate.edu/~bangerth/videos.676.39.html>
- <http://www.math.colostate.edu/~bangerth/videos.676.40.html>

- Documentation:

- [https://dealii.org/current/doxygen/deal.II/group\\_\\_threads.html](https://dealii.org/current/doxygen/deal.II/group__threads.html)
- <https://www.dealii.org/current/doxygen/deal.II/namespaceWorkStream.html>
- <https://dealii.org/current/doxygen/deal.II/namespaceparallel.html>



# Identifying parallelizable code

- Consider this example:

```
template <int dim>
void MyProblem<dim>::setup_system (){
    dof_handler.distribute_dofs();
    DoFTools::make_hanging_node_constraints (...);    // 1
    DoFTools::make_sparsity_pattern (...);           // 2
    VectorTools::interpolate_boundary_values (...);   // 3
    ...
}
```

- Operations (1,2,3) are independent of one another
- Could be reordered without consequence





# Identifying parallelizable code


- “Embarrassingly parallelizable tasks”

```
template <int dim>
void MyProblem<dim>::assemble_system () {
...
for (auto cell : dof_handler.active_cells()) {
    fe_values.reinit (cell);
    ...assemble local contribution...
    ...copy local contribution into global matrix/rhs vector...
}
}
```

- Many more cells than machine cores
- Computations of local matrices/vectors are mutually independent
- **Accumulation into global system matrix/vector is not!**



# Shared memory model




- All threads have access to the same global shared memory.
- Threads also have their own private memory.
- Shared data is accessible by all threads.
- Private data can be only accessed by the thread that owns it.
- Programmers are responsible for synchronizing access (protecting) globally shared data.



# Independent threaded tasks: Option 1

- Code divergence with / without barriers (global / in-thread locks)
- Best used for small number of completely independent tasks
- Inside each thread: Shared data
  - Reading is a safe operation!
  - Use locks to allow data writing
    - Convergence point for threads (bottleneck)
    - Potential for deadlocks





# Information about the system

```
MultithreadInfo::n_cores()  
MultithreadInfo::n_threads()  
MultithreadInfo::set_threads_limit()
```

- Query number of cores, and number of enabled threads
- Set maximum number of threads you want to “spawn”





# Creating independent threaded tasks: the Threads class

```
template <int dim>
void MyProblem<dim>::setup_system (){
    dof_handler.distribute_dofs();

    Threads::Thread<void> thread1, thread2, thread3;

    thread1 = Threads::new_thread (&DoFTools::make_hanging_node_constraints,...);
    thread2 = Threads::new_thread (&DoFTools::make_sparsity_pattern, ...);
    thread3 = Threads::new_thread (&VectorTools::interpolate_boundary_values,,...);

    thread1.join();      // and same for thread2, thread3
    ...
}
```

- The call to join() is a blocking call
- Waits for the thread to finish before continuing



# Creating independent threaded tasks: the ThreadGroup class

```
void MyProblem<dim>::assemble_on_one_cell (cell_iterator &cell) {...}

void MyProblem<dim>::assemble_system () {
    Threads::ThreadGroup<void> threads;

    for (cell=dof_handler.begin_active(); ...)
        threads += Threads::new_thread (
            &MyProblem<dim>::assemble_on_one_cell,
            this, cell);

    threads.join_all ();
}
```

- Why is this inefficient?
- How do we prevent data races?



# Creating independent threaded tasks: Ranged based assembly

- Less threads created = more efficient

```
void MyProblem<dim>::assemble_on_cell_range (
    cell_iterator &range_begin,
    cell_iterator &range_end) {...};

void MyProblem<dim>::assemble_system () {
    Threads::ThreadGroup<void> threads;

    std::vector<std::pair<cell_iterator, cell_iterator> >
        sub_ranges = Threads::split_range (
            dof_handler.begin_active(),
            dof_handler.end(),
            n_virtual_cores);

    for (t=0; t<n_virtual_cores; ++t)
        threads += Threads::new_thread (
            &MyProblem<dim>::assemble_on_cell_range,
            this,
            sub_ranges[t].first,
            sub_ranges[t].second);

    threads.join_all ();
}
```





# Independent threaded tasks

```
void MyProblem<dim>::assemble_on_one_cell (cell_iterator &cell) {  
  
    static Threads::Mutex mutex;  
  
    mutex.acquire ();  
    for (unsigned int i=0; i<fe.dofs_per_cell; ++i)  
        for (unsigned int j=0; j<fe.dofs_per_cell; ++j)  
            system_matrix.add (dof_indices[i], dof_indices[j],  
                               cell_matrix(i,j));  
  
    ...same for rhs...  
    mutex.release ();  
}
```


- How do we prevent data races?





# Creating independent threaded tasks: the WorkStream class

- Task-based threading
  - Continuous use of free CPU cores
  - Create a list of tasks
  - When core free, use it to perform next task
    - Expensive operations continually executed
- Perform blocking tasks independently
  - Data copied to shared objects serially
- Optimizations:
  - “Automatic” load balancing
  - Overhead reduction: Works on data chunks





# Creating independent threaded tasks: parallelization of (per-cell) assembly

```
template <int dim>
void MyClass<dim>::assemble_on_one_cell (
    const typename DoFHandler<dim>::active_cell_iterator &cell)
{
    FEValues<dim> fe_values (...);

    FullMatrix<double> cell_matrix (...);
    Vector<double>      cell_rhs (...);
    std::vector<double> rhs_values (...);

    rhs_function.value_list (...)

    // assemble local contributions
    fe_values.reinit (cell);
    for (unsigned int i=0; i<fe.dofs_per_cell; ++i)
        for (unsigned int j=0; j<fe.dofs_per_cell; ++j)
            for (unsigned int q=0; q<n_points; ++q)
                cell_matrix(i,j) += ...;
    ...same for cell_rhs...

    // now copy results into global system
    std::vector<unsigned int> dof_indices (...);
    cell->get_dof_indices (dof_indices);
    for (unsigned int i=0; i<fe.dofs_per_cell; ++i)
        for (unsigned int j=0; j<fe.dofs_per_cell; ++j)
            system_matrix.add (...);
    ...same for rhs...
    // or constraints.distribute_local_to_global (...);
}
```

Expensive constructor call

Repeated memory allocation

Independent tasks

Serial operation



# Threading using WorkStream: the ScratchData class

- Assistant struct / class
- Contains reused data structures
  - FEValues objects
  - Helper vectors and storage containers
  - Precomputed data
- Needs a constructor and a copy constructor
  - Some objects must be manually reconstructed
  - We create one initial instance of the class
  - TBB duplicates as required (queue\_length)

```
struct ScratchData {  
    std::vector<double>      rhs_values;  
    FEValues<dim>           fe_values;  
  
    ScratchData (  
        const FiniteElement<dim> &fe,  
        const Quadrature<dim>    &quadrature,  
        const UpdateFlags        update_flags)  
        : rhs_values (quadrature.size()),  
          fe_values (fe, quadrature, update_flags)  
        {}  
  
    ScratchData (const ScratchData &rhs)  
        : rhs_values (rhs.rhs_values),  
          fe_values (rhs.fe_values.get_fe(),  
                    rhs.fe_values.get_quadrature(),  
                    rhs.fe_values.get_update_flags())  
        {}  
}
```





# Threading using WorkStream: the PerTaskData class

- Contains data structures required for serial operations
  - Multiple copies made ( $\text{queue\_length} \times \text{chunk\_size}$ )
  - Must be “self-contained”
- Used in two places
  - Threaded function
    - Bound to an instance of the threaded function
    - Used as a “data-in” object
  - Serial function
    - A used instance is passed to this function
    - Used as a “data-out” object

```
struct PerTaskData {  
    FullMatrix<double>      cell_matrix;  
    Vector<double>          cell_rhs;  
    std::vector<unsigned int> dof_indices;  
  
    PerTaskData (const FiniteElement<dim> &fe)  
    : cell_matrix (fe.dofs_per_cell,  
                  fe.dofs_per_cell),  
      cell_rhs (fe.dofs_per_cell),  
      dof_indices (fe.dofs_per_cell)  
    {}  
}
```





# Threading using WorkStream: Revised assembly

```
template <int dim>
void MyClass<dim>::assemble_on_one_cell (
    const typename DoFHandler<dim>::active_cell_iterator &cell,
    ScratchData &scratch,
    PerTaskData &data)
{
    // reinitialise data
    scratch.fe_values.reinit (cell);
    rhs_function.value_list (scratch.fe_values.get_quadrature_points,
                             scratch.rhs_values);

    ...
    data.cell_matrix = 0;
    data.cell_rhs     = 0;

    // assemble local contributions
    for (unsigned int i=0; i<fe.dofs_per_cell; ++i)
        for (unsigned int j=0; j<fe.dofs_per_cell; ++j)
            for (unsigned int q=0; q<fe_values.n_quadrature_points; ++q)
                data.cell_matrix(i,j) += ...;

    ...
}
```

- Now use objects contained within ScratchData and PerTaskData structs



# Threading using WorkStream: Serial copy operation

```
template <int dim>
void MyClass<dim>::copy_local_to_global (const PerTaskData &data)
{
    for (unsigned int i=0; i<fe.dofs_per_cell; ++i)
        for (unsigned int j=0; j<fe.dofs_per_cell; ++j)
            system_matrix.add (data.dof_indices[i], data.dof_indices[j],
                               data.cell_matrix(i,j));

    ...same for rhs...
    // or constraints.distribute_local_to_global (...);
}
```

- Uses writes “fixed” data in PerTaskData to single class object system\_matrix (and whatever else)
- Has to be a serially performed operation



# Threading (not) using WorkStream: Manual assembly using these data structures

```
ScratchData scratch_data (...);
PerTaskData per_task_data (...);

DoFHandler<deal_II_dimension>::active_cell_iterator
  cell = dof_handler.begin_active(),
  endc = dof_handler.end();
  for (; cell != endc; ++cell)
  {
    assemble_system_one_cell(cell,
                             scratch_data,
                             per_task_data);
    copy_local_to_global(per_task_data);
  }
```

- This performs the same serial assembly as we had before
- More efficient though (use of ScratchData)





# Threading using WorkStream

```
ScratchData scratch_data (...);  
PerTaskData per_task_data (...);  
  
WorkStream::run ( dof_handler.begin_active(),  
                  dof_handler.end(),  
                  *this,  
                  &MyClass::assemble_system_one_cell,  
                  &MyClass::copy_local_to_global,  
                  scratch_data,  
                  per_task_data );
```

- Execute function in threaded manner
- Only operates on functions with a specific prototype
- Theadable function:  
void function\_name(cell, scratch, per\_task\_data)
- Serial function:  
void function\_name(per\_task\_data)





# Workstream

[https://www.dealii.org/current/doxygen/deal.II/  
namespaceWorkStream.html](https://www.dealii.org/current/doxygen/deal.II/namespaceWorkStream.html)

NOTE: If your data objects are large, or their constructors are expensive, it is helpful to keep in mind that `queue_length` copies of the `ScratchData` object and `queue_length*chunk_size` copies of the `CopyData` object are generated.