

# Shopify command cheat sheet

Run commands from your theme folder. Select a store with `si <store_abr>`; then omit it. Replace `<store_abr>` with your alias. Quote theme names with spaces. Check the store with `si`.

A configured defaultStore overrides the remembered store. Personal config is created on first use at `~/ .sshops.json`.

## Commands

| Command        | What it does                                |
|----------------|---------------------------------------------|
| si <store_abr> | Select a store                              |
| si             | Show current store and theme                |
| sl             | List themes                                 |
| sd             | Start a development theme                   |
| sd "My Theme"  | Develop a named theme with editor sync      |
| sp             | Pull the live theme                         |
| sp "My Theme"  | Pull a named theme                          |
| sp -p          | Pull only live template/config JSON         |
| spl "My Theme" | Pull named theme template/config JSON       |
| sp -d          | Pull the development theme                  |
| spa            | Pull live; may delete unmatched local files |
| sc             | Check theme code                            |
| sf             | Fix supported code issues                   |
| lo             | Log out of Shopify                          |
| shelp          | Show help                                   |

## Options

| Option                | Example                  | Meaning                                                      |
|-----------------------|--------------------------|--------------------------------------------------------------|
| -g / --global         | sinit -g                 | Personal config (sinit, simport; sstores defaults to global) |
| -d / --development    | sp -d                    | Development theme (sp, spl, spa, si)                         |
| -p PORT / --port PORT | sd -p 9293               | Change the development port                                  |
| -p / --json-only      | sp -p                    | Pull only template/config JSON                               |
| -j / --json           | sl -j                    | JSON output (sl, si)                                         |
| --dry-run             | sd "My Theme" --dry-run  | Preview without running                                      |
| -s and -t             | sd -s demo -t "My Theme" | Choose store and theme                                       |

## Store aliases and setup

| Command                         | What it does                              |
|---------------------------------|-------------------------------------------|
| sstores                         | List store aliases                        |
| sstores add <alias> <store>     | Add or update an alias                    |
| sstores remove <alias>          | Remove an alias                           |
| sstores .                       | Edit stores in your config file           |
| sconfig                         | Show settings and config locations        |
| sinit                           | Create a project config                   |
| sinit -g                        | Create personal config (never overwrites) |
| simport ./base_custom_cli.sh -g | Import legacy store aliases               |

Important: `sp` overwrites matching files; `spa` may also delete unmatched files. `sd` syncs to the remote theme. `sf` changes local code. Use `--dry-run` to preview. PowerShell: append `.cmd` (for example, `sp.cmd`).

[github.com/deanschulz4/Shopify-CLI-Simplified](https://github.com/deanschulz4/Shopify-CLI-Simplified)