

G SERIES UNDERWATER SPOT LIGHT

Model: XYH105G

Lamp Description

Polished 304# Stainless steel housing and round base

316SS optional

One-pieces PMMA lens

High light transmission tempered glass


Anti-aging silicone sealing ring

Waterproof VDE H05RN-F 2*0.75/H07RN-F 4*1

Installation method: Disc type

Lamp Net Weight: 0.8kg

2 years warranty



Electrical Features:

| Product code | XYH105G-3W | XYH105G-9W |
|-------------------|---|----------------|
| Rate power | 3w | 9w |
| LEDs | 3Leds*1Watt | 3LEDs*3Watt |
| Luminous Flux | Max 330lm white | Max570lm white |
| Dimension | Dia105mm*W110mm*H90mm | |
| LED Chip | Epister/cree | |
| Voltage | AC/DC 12V AC/DC 24V AC220V | |
| Beam Angle | 30°standard. 15°/ 45° / 60° / 90° optional | |
| CRI | >80 | |
| Cable Length | 1 meter standard | |
| Work Temperature | -40°C - +45°C | |
| Color Control Way | Single control/RGB Auto-change RGB 4wires change | |

Color of lighting

white 6000-6500K

natural white 4000k-4500k

warm white 2700K-3500K

red

green

blue

yellow

RGB



Notes:

- Lamp can use in water or out of water.
- Low voltage 12v or 24v needs to have an individual transformer or power supply to operate.