Butterfly Valve

EASY INSTALLATION AND DISASSEMBLY

For commercial heavy duty usage



Material

Anti-corrosive

Max Working Pressure

250kPA/36psi/2.5bar

Factory Testing Pressure

400kPa/58psi/4.0bar

Max Water Temperature

43°C (109°F)

Code	Model	Size		
01151021	BV30	3" (90mm)		
01151022	BV40	4" (110mm)		
01151023	BV60	6" (160mm)		
01151359	BV80	8" (200mm)		
108091852	BV100	10" (250mm)		
108091889	BV120	12" (315mm)		





Valve Manifold

4 Way Butterfly Valve








4 Way Butterfly Valve BVGT100- BVGT120

Product Information

Code	Model	Valve Cor GB(mm)	nection ANSI	A (mm)	B (mm)	C (mm)	D (mm)	E (mm)
88290401	NBV30-4	90	3"	350	884	889	552	172
88290402	NBV40-4	110	4"	350	1101	963	614	210
88290403	NBV60-4	160	6"	415	1351	1228	775	287
88290404	NBV80-4	200	8"	550	1867	1500	1015	376
88290605	BVGT100-4	250	10"	710	2231	1913	1286	472
88290606	BVGT120-4	315	12"	710	2437	2106	1423	552




4 Way Butterfly Valve BVGT100- BVGT120

5 Way Butterfly Valve




5 Way Butterfly Valve NBV30-NBV80



5 Way Butterfly Valve BVGT100- BVGT120

Product Information

Code	Model	Valve Cor GB(mm)	nection ANSI	A (mm)	B (mm)	C (mm)	D (mm)	E (mm)
88290301	NBV30-5	90	3"	350	1395	889	552	172
88290302	NBV40-5	110	4"	350	1521	963	614	210
88290303	NBV60-5	160	6"	415	2039	1228	775	287
88290304	NBV80-5	200	8"	550	2832	1500	1015	376
88290505	BVGT100-5	250	10"	710	3374	1913	1286	472
88290506	BVGT120-5	315	12"	710	3692	2106	1423	552



EMAUX WATER TECHNOLOGY CO., LTD

ADDRESS: Flat A-D, 20/F., Kai Bo 22, 22 Wing Kin Road,

Kwai Chung, Hong Kong PHONE +852 2832 9880 www.emauxgroup.com

Pool & Spa Equipment

Available from: