



AquaMax Eco Premium

Efficient water movement in multiple pond zones



ACCESSORIES

Product	Product details	Item no.	Item no. (GB-Version)
Safety grid AquaMax Eco 2" > Page 146	Optional safety attachment for wet setup in a pump chamber, prevents unintentional debris reaching the suction inlet.	73536	-
Satellite filter AquaMax Eco > Page 146	Enables intake of polluted water at an additional point on the pond floor.	57177	-
AquaSkim 20 > Page 330	Skimmers for powerful suctioning of pond surfaces. Remove particles before they settle and impair the water quality.	51236	-
AquaSkim 40 > Page 330		56907	-
InScenio FM-Master 3 > Page 290	Wireless remote control garden power outlet for electronic adjustment.	36311	56473
InScenio FM-Profimaster > Page 290		56886	not available in GB!
Pumpshield > Page 147	50 x 50 cm, made from strong, durable fabric. Prevents early clogging of motors or nozzles in certain seasons.	34876	-
AquaActiv PumpClean 500 ml > Page 370		40242	75806



1. An oasis of well-being

for your home.

2. Regulation + 2nd Inlet

A 2nd inlet allows connection of a satellite filter or surface skimmer. This allows the flow through to be mechanically adjusted from 0 to 100 %.

3. Schematic diagram

AquaMax Eco Premium filter and watercourse pump in combination with an OASE flow-through filter

4. SFC switch

For AquaMax Eco Premium 12000 / 16000 / 20000. With the SFC function switched on the pump automatically optimises water flow and delivery head, and reduces them by up to 50 %.

TECHNICAL DATA

Product		AquaMax Eco Premium 4000	AquaMax Eco Premium 6000	AquaMax Eco Premium 8000	AquaMax Eco Premium 10000	AquaMax Eco Premium 12000	AquaMax Eco Premium 16000	AquaMax Eco Premium 20000
Dimensions (L x W x H)	mm	340 x 280 x 165						
Rated voltage		220 - 240 V / 50/60 Hz						
Rated voltage (primary, secondary)		-						
Power consumption	W	10 - 35	12 - 45	15 - 60	19 - 88	10 - 110	11 - 145	15 - 180
Power cable length	m	10.00						
Cable length 12 V device (with power unit)	m	-						
Net weight	kg	5.30			5.40			6.10
Guarantee (+ request guarantee) ´	Years	3 + 2						
Max. flow rate	l/min	66	100	133	166	200	260	325
Max. flow rate	l/h	4000	6000	8000	10000	12000	15600	19500
Max. head height, metres	m	3.30	3.70	4.10	4.70	5.00	5.20	5.40
Pressure-side connection		G 2						
Suction-side connection		G 2						
Hose connection	mm	25 / 32 / 38			25 / 32 / 38 / 50			
Hose connection		1", 1 ¼", 1 ½"			1", 1 ¼", 1 ½", 2"			
Filter intake surface	cm²	1000						
Max. coarse debris displacement	mm	10				11		
Electronic adjustment		Yes						
Setup type		Can be set up underwater & dry installed						
Item no. (GB-Version)		50735	50739	50741	51085	50743	50746	56409
Item no.		50734	50736	50740	51078	50742	50745	56406

*Guarantee valid under the guarantee conditions from OASE. Can be viewed at www.oase.com/guarantee
Pump performance curve overview of pond pumps (> see page 148)

