

[illegible]

NC pins are intentionally unused. SWD probe connects on the module top.

J1  
MOTION SW IN

1 +5V\_MOTION  
2 GND

C8  
10k

GND

+5V2

R8  
10k

GND

J6  
INTERNAL SERVICE KEY

1 USER\_KEY\_N  
2 GND

#FLG1  
Supply boundary  
+5V\_MOTION

#FLG2  
Supply boundary  
GND

#FLG3  
Supply boundary  
CAN\_3V3

H1  
M2 clearance

H2  
M2 clearance

H3  
M2 clearance

H4  
M2 clearance

Physical disable is JB: reset can cause a fail.

J6 is a user button. Physical disable is J8; reset can cause a fall.

[illegible]

3.3 V logic; actuator thresholds and timing remain bench items.

CLR\_N dominates. Re-arm requires a new ARM\_CLK edge: this is not a watchdog

[illegible]

CAN\_3V3 powers translator B only. It does not power the motion MCU.

3.3 V logic; actuator thresholds and timing remain bench items

[illegible]

OE\_N = request\_N OR ARM\_Q\_N. Pull-ups disable TX by default.

SPI and DRDY belong to the rigid body IMU, not the head.

1k / 10nF filters at the ADC inputs. Scaling is on the power board