

Object Oriented Programming in Python | Set 2 (Data Hiding and Object Printing)

Prerequisite : [Object Oriented Programming in Python | Set 1 \(Class, Object and Members\)](#)

[Hire with us!](#)

Data hiding

In Python, we use double underscore (Or `__`) before the attributes name and those attributes will not be directly visible outside.

Ad closed by Google

[Stop seeing this ad](#)[Why this ad? ⓘ](#)

```
class MyClass:

    # Hidden member of MyClass
    __hiddenVariable = 0

    # A member method that changes
    # __hiddenVariable
    def add(self, increment):
        self.__hiddenVariable += increment
        print (self.__hiddenVariable)

# Driver code
myObject = MyClass()
myObject.add(2)
myObject.add(5)

# This line causes error
print (myObject.__hiddenVariable)
```

Output :

2

7

Traceback (most recent call last):
File "filename.py", line 13, in



```
print (myObject.__hiddenVariable)
AttributeError: MyClass instance has
no attribute '__hiddenVariable'
```

In the above program, we tried to access hidden variable outside the class using object and it threw an exception.

We can access the value of hidden attribute by a tricky syntax:

```
# A Python program to demonstrate that hidden
# members can be accessed outside a class
class MyClass:

    # Hidden member of MyClass
    __hiddenVariable = 10

# Driver code
myObject = MyClass()
print(myObject._MyClass__hiddenVariable)
```

Output :

10

Private methods are accessible outside their class, just not easily accessible. **Nothing in Python is truly private; internally**, the names of private methods and attributes are mangled and unmangled on the fly to make them seem inaccessible by their given names [See [this](#) for source].

Printing Objects

Printing objects gives us information about objects we are working with. In C++, we can do this by adding a friend ostream& operator << (ostream&, const Foobar&) method for the class. In Java, we use toString() method. In python this can be achieved by using __repr__ or __str__ methods.

```
class Test:
    def __init__(self, a, b):
        self.a = a
        self.b = b

    def __repr__(self):
        return "Test a:%s b:%s" % (self.a, self.b)

    def __str__(self):
        return "From str method of Test: a is %s," \
               "b is %s" % (self.a, self.b)

# Driver Code
t = Test(1234, 5678)
print(t) # This calls __str__()
print([t]) # This calls __repr__()
```

Output :



From str method of Test: a is 1234,b is 5678
[Test a:1234 b:5678]

Important Points about Printing:

- If no `__str__` method is defined, print t (or print str(t)) uses `__repr__`.

```
class Test:
    def __init__(self, a, b):
        self.a = a
        self.b = b

    def __repr__(self):
        return "Test a:%s b:%s" % (self.a, self.b)

# Driver Code
t = Test(1234, 5678)
print(t)
```

Output :

Test a:1234 b:5678

- If no `__repr__` method is defined then the default is used.

```
class Test:
    def __init__(self, a, b):
        self.a = a
        self.b = b

# Driver Code
t = Test(1234, 5678)
print(t)
```

Output :

<__main__.Test instance at 0x7fa079da6710>

--->



Python Programming Tutorial | Object Oriente...



This article is contributed by **Shwetanshu Rohatgi**. Please write comments if you find anything incorrect, or you want to share more information about the topic discussed above.

ROHM Semiconductor

Ad 4-Channel White LED
Integrated FET for up to 2

ROHM

Open

Recommended Posts:

[Object Oriented Programming in Python | Set 1 \(Class, Object and Members\)](#)

[Object Oriented Programming in C++](#)

[Python | Matplotlib Sub plotting using object oriented API](#)

[Python | Matplotlib Graph plotting using object oriented API](#)

[Data type Object \(dtype\) in NumPy Python](#)

[Python | os.supports_fd object](#)

[Python Object Comparison : "is" vs "=="](#)

[Python | os.sysconf_names object](#)

[Python | os.confstr_names object](#)

[Python | os.environ object](#)

[Python | object\(\) method](#)

[Python | os.supports_bytes_environ object](#)

[Python | os.supports_bytes_environ object](#)

[Python | os.supports_dir_fd object](#)

[Python | os.supports_follow_symlinks object](#)



Article Tags : [Python](#) [School Programming](#)



22

2.6

☐

To-do

☐

Done

Based on 16 vote(s)

[Feedback/ Suggest Improvement](#)[Add Notes](#)[Improve Article](#)

Please write to us at contribute@geeksforgeeks.org to report any issue with the above content.

Writing code in comment? Please use ide.geeksforgeeks.org, generate link and share the link here.

[Load Comments](#)

A computer science portal for geeks

5th Floor, A-118,
Sector-136, Noida, Uttar Pradesh - 201305
feedback@geeksforgeeks.org

COMPANY

[About Us](#)
[Careers](#)
[Privacy Policy](#)
[Contact Us](#)

PRACTICE

[Courses](#)
[Company-wise](#)
[Topic-wise](#)
[How to begin?](#)

LEARN

[Algorithms](#)
[Data Structures](#)
[Languages](#)
[CS Subjects](#)
[Video Tutorials](#)

CONTRIBUTE

[Write an Article](#)
[Write Interview Experience](#)
[Internships](#)
[Videos](#)

@geeksforgeeks, Some rights reserved

