

Engineering progress
Enhancing lives

RAUVISIO noir™

monotonic matte surface

Sustainability factors

na.rehau.com/noir

FSC
certified
available



Properties	Test method	Property or attribute	Unit	Results
Formaldehyde emissions	EN 13986	Formaldehyde emission rating	Rating	E1
		Classification	mg/m ³	A+
		Formaldehyde	mg/m ³	≤ 0.002
		Acetaldehyde	mg/m ³	≤ 0.002
	AFNOR NF EN ISO 16000-9	Toluene	mg/m ³	≤ 0.002
		Tetrachlorethylene	mg/m ³	≤ 0.002
		Xylene	mg/m ³	≤ 0.002
		Trimethylbenzene	mg/m ³	≤ 0.002
		TVOC	mg/m ³	≤ 0.01
Evaluation of micro-organisms action	JIS Z 2801:2010	Antimicrobial activity after 24h at 35°C	bacterial viability: log reduction reduction %	> 3.6 > 99.975
Phenol Free	EN ISO 16000-9	Phenol content in resin		Phenol free

For updates to this publication, visit na.rehau.com/resourcecenter

The information contained herein is believed to be reliable, but no representations, guarantees or warranties of any kind are made as to its accuracy, suitability for particular applications or the results to be obtained therefrom. Before using, the user will determine suitability of the information for user's intended use and shall assume all risk and liability in connection therewith.

© 2022 REHAU 121.98 03.2022

