

Engineering progress
Enhancing lives

Fire ratings for RAUVISIO House lines

RAUVISIO House line	Fire behavior Test standard: DIN 4120/1 Requirements: N/A	Flame spread index Test standard: ASTM E84 Requirements: Class C: 76-250	Smoke developed index Test standard: ASTM E84 Requirements: Class A, B, C: 0-450
RAUVISIO brilliant	B2 (normal combustibility)	TBD	TBD
RAUVISIO crystal	B2 (normal combustibility)	180	750
RAUVISIO ingrain	B2 (normal combustibility)	TBD	TBD
RAUVISIO ferro	B2 (normal combustibility)	185	170

RAUVISIO House line	Fire behavior Test standard: ASTM E84 Requirements: Class A: 0-25 Class B: 26-75 Class C: 76-250	Flame spread index Test standard: ASTM E84 Requirements: Class C: 76-250	Smoke developed index Test standard: ASTM E84 Requirements: Class A, B, C: 0-450
RAUVISIO noir	Standard: Class B Fire resistant: Class A	Standard: 40 Fire resistant: 0	Standard: 40 Fire resistant: 0
RAUVISIO terra	Standard: Class B Fire resistant: Class A	Standard: 45 Fire resistant: 0	Standard: 80 Fire resistant: 0
RAUVISIO shade	TBD	TBD	TBD

For updates to publication, visit na.rehau.com/resourcecenter

The information contained herein is believed to be reliable, but no representations, guarantees or warranties of any kind are made as to its accuracy, suitability for particular applications or the results to be obtained therefrom. Before using, the user will determine suitability of the information for user's intended use and shall assume all risk and liability in connection therewith.