## Collapse All | Expand All

- Home
  - > Archived
  - > Acknowledgements

Blog and News

- > Documentation v2-0-alph
- > Documentation v1-6
- > Documentation v1-5
- > Documentation v1-1
- > Download
- → Developer

Coding conventions

Classes design v2-0

→ Database design v2-0

## Database 2-0 Tabl

Ticket Status Guide

Browser-compatibilitymatrix

Installation notes for 1 -5 development code

Notes on 1-0-1 fixes a nd stuff

International Characte r Handling

Transfering multiple fil

HTML5

- > Testing
- > Specifications

release process

Creating repositories

Developers

> Usage statistics modu

Icons

Existing installations

Feature requests

Online Demo

Project organisation

Roadmap

Release Schedule

Release status and life c

ycle

Reviews and prototypes

Support and Mailinglists

Twitter

FileSender's workflows

Installation - Linux Sourc e 2-0-Alpha-from-svn

## Database 2-0 Tables

Version 4, last updated by romanmalyshev at 2014-07-30



 <span style="color: rgb(17, 17, 17); font-family: inherit; font-size: 16p</pre> x; font-weight: bold; line-height: 18px;">Exact details per table</span><span style="color: rgb(17, 17, 17); font-family: inherit; font-size: 16px; font-weight: b old; line-height: 18px;"><br><h3 style="font-family: Arial, Helvetica, 'L iberation Sans', FreeSans, sans-serif;">Tables directly needed for file transfer</h3 ><div><h4>table: transfers< /h4>Field nameData typeDescription id<br/>td>integerPrimary key. Not null and auto-incrementing /tr>trackingidcharacter varying(10)<span>&nbsp;&nbsp; &nbsp;</span> Tracking code for the transfer (sent to sender)hot that useful d>uidcharacter varying(500)The sender's user ID, as generated by the IdPsendernamecharacter varying(250)td>The sender's namesubjectcharacter varying(80) Optional: specifies subject in the e-mail notification sent to receivers<t r>messagecharacter varying(250)optional: message from sender to receiverstr>transfer datetimestamp without time zone< td>The date and time of the transactionexpiry\_datetimesta mp without time zoneThe expiration date and time (to insure that download i s available on the last day)statuscharacter varying(20)</ td>Indicates status of the file transfer: uploading, available for download, exp iredoptionscharacter varying(250)text string, JS ON-encoded, that contains data about what options were checked</ta e="width: 991px;"><h4>table: files</h4>tr>> Field nameCtd>Data typectd>Descriptionidctd>idctd>integer Primary key. Not null and auto-incremented.tr>tr>transferid >integerForeign key. Not null. The ID handle of the transaction record the file is associated with.nametd>character varving(500) d>Name of the file, as originally specified by sender.size</td >bigint (long integer)File size in bytes.sha1 >character varying(500)</td><td>>Hash code (for file integrity verification). Should be done per chunk. But leaving it as it is for now.</div>< style="width: 991px;"><h4>table: recipients</h4>d>integerPrimary key. Not null and auto-incrementingtrans feridintegerForeign key. Not null. ID handle for the transfer the recipient is in.email address<br>varchar(80)&nbsp;<br></t >Download or voucher token for each recipient. Only the latest token for a recip ient is shown here.optionstd>varchar{250}Shows whether recipient has asked to get "download complete" e-mail<br/>/tr>c reated datetime stamp w/o time zoneThe date when the recipient rec ord was createdlast\_activitytime stamp w/o time zone Date of last activity. Used to determine if recipient is inactive and data shoul d be removed otr > </trlass="Apple-interchange-newline"><td colspan ="3"><h4>table: auditlogs</h4>Field nameData typetd> >Descriptionid<id>integerPrimary key. Not null and a t that is logged:<br/>br>UPLOAD, FAILED, DOWNLOAD, UPLOADED;<br/>br>USER\_ACTIVATED, USER\_INA CTIVE, USER\_PURGED;<br/>
CTIVE, USER\_PURGED;<br/>
CJENT,<br/>
CJENT,<br/>
CJENT,<br/>
CJENT,<br/>
CDLETED;<br/>
CJENT,<br/>
CDLETED;<br/>
CJENT,<br/>
CDLETED;<br/>
CJENT,<br/>
CDLETED;<br/>
CJENT,<br/>
CJENT,<br/>
CDLETED;<br/>
CJENT,<br/>
CJENT, The transaction that is related to a file or voucher eventvid >td>>td>>td>>td>recipientid d>The recipient that (for instance) downloaded a file<ttr>date  $<\!td\!><\!td\!><\!td\!><\!td>/\!td\!><\!tr\!><\!td>> toler occurred .<\!/td>> voucherid <\!/td>> voucherid <\/d>> voucherid <\/d>$ td > The voucher token that was used (if it's a FILE event, otherwise it's the voucher that expired, etc.)<br/>td>filenameThe file the event revolved aroundipv4ipv4 ress of the user or guest (by voucher)</div><div><div><div ><h3 style="font-family: Arial, Helvetica, 'Liberation Sans', FreeSans, sans-serif;" >Supporting tables</h3><div><br class="Apple-interchange-newline"><table style="widt >Field nameData typeDescriptioniduint</ td>Primary key. Not null and auto-incrementingvarc har(500)The user who has issued the voucher/under whose name the transfer w ill be done.tokenThe voucher token d>transfersuintNr of transfers the voucher is good fo  $r.<\!/td\!><\!/tr\!><\!td\!>created\_date<\!/td\!><\!td\!>timestamp without time zone<\!/td\!><\!td\!>Date the contract of the contract of$ e voucher token was created and sentexpiry\_datetimestamp without time zoneSpecifies the expiration date and time of the voucher

Comments are disabled for this space. In order to enable comments, Messages tool must be added to project. You can add Messages tool from Tools section on the Admin tab.