

Technical design - Packaging

debian

changelog

A log of changes in the debian packaging of filesender, not filesender itself.

compat

conf/apache.conf

File copied to /etc/apache/conf.d to configure apache to serve filesender files. Is copied by postinst

config

Configure hook that configures the database

control

Contains filesender package information like name and (build) dependencies

copyright

Copyright file, required for debian packaging

dirs

Dirs to be created during packaing

docs

Specifies which files are documentation

install

Specifies which files to be copied into the package

links

Specifies which symlinks to be created in the package

patches

Directory that contains patches to be applied before packaging

patches/dbconfig-common_support.patch

This patch will configure filesender to use the database settings generated by the debian database manager.

postinst

Script called after installation, configures database and fixes permissions, configures apache.

postrm

Script called after deinstallation and removes apache config.

preinst

Script called before installation, doesn't do anything at the moment

prerm

Script called before removes, removes database (if confirmed by user)

README.Debian

Debian package specific readme

README.source

rules

Build rules. uses CDBS so is quite minimal. Manually installs SQL script.

watch

File used for automated checking of new upstream release of filesender.

RPM

rpm/filesender-config.php

Replacement config of filesender.

rpm/filesender.htaccess

htaccess file used to configure apache.

rpm/filesender.spec

Spec file, contains all required settings for building a RPM file.