

Assignment –5

Relational and Logical Operators.

1) Write a query that will give you all orders for more than Rs. 1,000.

```
mysql>
mysql> select * from orders;
```

Onum	Amt	Odate	Cnum	Snum
3001	18.69	1990-10-03	2008	1007
3003	767.19	1990-10-03	2001	1001
3011	9891.88	1990-10-06	2006	1001
3002	1900.1	1990-10-03	2007	1004
3005	5160.45	1990-10-03	2003	1002
3006	1098.16	1990-10-03	2008	1007
3009	1713.23	1990-10-04	2002	1003
3007	75.75	1990-10-04	2004	1002
3008	4723	1990-10-05	2006	1001
3010	1309.95	1990-10-06	2004	1002

```
10 rows in set (0.00 sec)
```



```
mysql> select Amt from orders
-> where Amt>1000;
```

Amt
9891.88
1900.1
5160.45
1098.16
1713.23
4723
1309.95

```
7 rows in set (0.00 sec)
```

2) Write a query that will give you the names and cities of all salespeople in London with a commission above .10.

```
SELECT sname, city
FROM Salespeople
WHERE city = 'London' AND comm > 0.10;
```

3) Write a query on the Customers table whose output will exclude all customers with a rating <= 100, unless they are located in Rome.

Ans:

```
mysql> select * from customers
      -> where Rating>100 or city='Rome';
```

```
mysql> select * from customers
      -> where Rating>100 or city='Rome';
```

Cnum	Cname	City	Rating	Snum
2002	Giovanni	Rome	200	1003
2003	Liu	San Jose	200	1002
2004	Grass	Berlin	300	1002
2008	Cisneros	San Jose	300	1007
2007	Pereira	Rome	100	1004

```
mysql> insert into customers (Cnum,Cname,City,Rating,Snum)
      -> values
      -> (2003 , 'Liu', 'San Jose', 200 , 1002),
      -> (2004 , 'Grass', 'Berlin', 300 , 1002),
      -> (2008 , 'Cisneros', 'San Jose', 300 , 1007),
      -> (2007 , 'Pereira', 'Rome', 100 , 1004);
Query OK, 4 rows affected (0.01 sec)
Records: 4 Duplicates: 0 Warnings: 0
```

4) What will be the output from the following query? Select * from Orders where (amt < 1000 OR NOT (odate = '1990-10-03' AND cnum > 2003));

```
mysql> Select * from orders where (amt < 1000 OR NOT (odate = '1990-10-03' AND cnum > 2003));
```

Onum	Amt	Odate	Cnum	Snum
3001	18.69	1990-10-03	2008	1007
3003	767.19	1990-10-03	2001	1001
3011	9891.88	1990-10-06	2006	1001
3005	5160.45	1990-10-03	2003	1002
3009	1713.23	1990-10-04	2002	1003
3007	75.75	1990-10-04	2004	1002
3008	4723	1990-10-05	2006	1001
3010	1309.95	1990-10-06	2004	1002

```
mysql> select * from orders;
```

Onum	Amt	Odate	Cnum	Snum
3001	18.69	1990-10-03	2008	1007
3003	767.19	1990-10-03	2001	1001
3011	9891.88	1990-10-06	2006	1001
3002	1900.1	1990-10-03	2007	1004
3005	5160.45	1990-10-03	2003	1002
3006	1098.16	1990-10-03	2008	1007
3009	1713.23	1990-10-04	2002	1003
3007	75.75	1990-10-04	2004	1002
3008	4723	1990-10-05	2006	1001
3010	1309.95	1990-10-06	2004	1002

10 rows in set (0.00 sec)

5) What will be the output of the following query? Select * from Orders where NOT ((odate = '1990-10-03' OR snum > 1006) AND amt >= 1500);

```
mysql> Select * from Orders where NOT ((odate = '1990-10-03' OR snum >1006)
AND amt >= 1500);
```

Onum	Amt	Odate	Cnum	Snum
3001	18.69	1990-10-03	2008	1007
3003	767.19	1990-10-03	2001	1001
3011	9891.88	1990-10-06	2006	1001
3006	1098.16	1990-10-03	2008	1007
3009	1713.23	1990-10-04	2002	1003
3007	75.75	1990-10-04	2004	1002
3008	4723	1990-10-05	2006	1001
3010	1309.95	1990-10-06	2004	1002

6) What is a simpler way to write this query? Select snum, sname, city, comm From Salespeople where (comm > .12 OR comm <.14);

```
mysql> Select snum, sname, city, comm From Salespeople
-> where (comm > .12 OR comm <.14);
```

snum	sname	city	comm
1001	Peel	London	0.12
1003	Axelrod	New York	0.1
1002	Serres	San Jose	0.13
1004	Motika	London	0.11
1007	Rifkin	Barcelona	0.15