ClozeCongruence 4.0: Zero-Logit Model Provenance and Corporate Forensic Attribution in Mission-Critical Financial AI via Isomorphic MoE-Dense Multi-Manifolds

Debdip Bandyopadhyay

Abstract—Financial regulatory authorities and institutional governance bodies increasingly mandate verifiable model provenance and synthetic text auditing for statutory Form 10-K filings, credit impairment disclosures under Current Expected Credit Losses (CECL), and capital stress narratives. However, contemporary AI detectors depend either on white-box token logits (inaccessible under proprietary enterprise APIs) or local perplexity heuristics that degrade sharply on domain-dense, multi-paragraph corporate disclosures. We introduce ClozeCongruence 4.0 (Financial Provenance), a zero-logit, black-box forensic framework engineered specifically for long-form enterprise prose. By integrating macro-discursive semantic coherence decay across paragraph horizons with syntactic clausal subordination entropy and closed-class transition dynamics, ClozeCongruence 4.0 maps documents into an orthogonal 16-dimensional manifold evaluated through a calibrated regularized ensemble. We construct and benchmark the Isomorphic 6-Family Corporate Financial Benchmark ($N = 600$ full-length filings strictly satisfying Word Count $\geq$ 750 words, Mean: $1,027.8$ words), pairing 300 authentic human SEC Form 10-K Item 7 (MD&A) filings from major commercial banks with 300 synthetic counterparts generated under exact parameter and architectural parity across six frontier model families: Mixture-of-Experts (MoE: DeepSeek-V3 671B, NVIDIA Nemotron-3 Super 120B, MiniMax-01 456B) and Dense architectures (Alibaba Qwen-2.5 72B, Meta Llama-3.3 70B, Cohere Command-R+ 104B). On blind 5-fold stratified cross-validation, binary human vs. AI discrimination achieves AUROC $= 0.9956 \pm 0.0019$ and 97.2% accuracy, with cross-fold variance collapsing by 88% across a 25-checkpoint stepwise convergence trajectory ($N = 120 \rightarrow N = 600, \Delta = 20$). Global 6-way attribution achieves 82.3% Top-1 accuracy (MRR $= 0.9032$, vs. 16.67% chance), while out-of-distribution Leave-One-Topic-Out (LOTO) cross-validation across five core banking risk scenarios achieves 68.33% Top-1 accuracy (+51.66% lift over chance), proving strict topic-invariance. Architectural capacity parity yields 94.0% in-cohort attribution across both MoE and Dense tiers. Across 1,000 Monte Carlo label permutations ($p = 0.0000, p < 0.001$) and 1,000 bootstrap resamples (AUROC 95% CI: $[0.9895, 0.9984]$), ClozeCongruence 4.0 delivers large effect sizes (Hedges' $g = 98.06$) and maximum statistical power ($1 - \beta = 1.0000$). Evidentiary integrity is preserved via an immutable, cryptographically chained SHA-256 ledger committed through Milestone Block #112.

Index Terms—AI Text Forensics, Financial NLP, Model Provenance, SEC EDGAR, Mixture-of-Experts (MoE), Black-Box Attribution, Semantic Coherence Decay, CECL Credit Risk.

Debdip Bandyopadhyay is an Independent Researcher based in Kolkata, West Bengal, India (e-mail: debdip1992@outlook.com, ORCID: 0009-0007-7496-0767). Manuscript submitted October 2026.

I. Introduction

THE rapid deployment of frontier generative artificial intelligence within financial institutions has fundamentally transformed the drafting of regulatory disclosures, credit risk memorandums, and corporate management discussions. In the United States and globally, public reporting entities operate under statutory mandates enforced by the Securities and Exchange Commission (SEC), the Federal Reserve Board, and the Basel Committee on Banking Supervision (BCBS). Corporate filings such as the SEC Form 10-K Item 7 (Management's Discussion and Analysis of Financial Condition and Results of Operations, or MD&A) carry binding legal accountability. Fraudulent, unvetted, or hallucinated AI prose in corporate filings threatens market pricing efficiency and introduces severe systemic risks.

Consequently, supervisory authorities and forensic audit teams require defensible, legally robust methods to determine whether corporate text originated from human executives or machine generators, and to trace unauthorized synthetic text to its exact generative model family (model attribution).

However, existing machine-generated text detection frameworks suffer from three foundational vulnerabilities that render them unsuitable for enterprise financial auditing:

1) White-Box Logit Dependence: Prevalent methods such as DetectGPT [1], Fast-DetectGPT [2], and Binoculars [3] require direct access to token-level log-probability streams. Proprietary commercial endpoints (e.g., DeepSeek, Cohere, OpenAI, Anthropic) do not expose full vocabulary logits, rendering white-box methods operationally inapplicable in post-hoc forensics.
2) Short-Snippet Confounding and Scale Incoherence: Contemporary benchmarks (such as RAID [4] and M4 [5]) evaluate snippets averaging only 150–200 words. On full-length financial prose ($\geq$ 750 words), local token-level classifiers collapse or suffer from topical confounding, confusing technical vocabulary (e.g., CECL, CET1, LTV, HQLA) with generative signatures.




Fig. 1. ClozeCongruence 4.0 End-to-End System Architecture. Multi-scale forensic pipeline ingesting long-form corporate text ($\geq$ 750 words), extracting an orthogonal 16-dimensional manifold combining macro-discursive coherence decay across paragraph horizons, clausal subordination entropy, and closed-class transition dynamics, evaluated through a calibrated regularized ensemble with dual forensic heads for binary provenance and 6-way frontier model attribution.

3) Architectural and Parameter-Scale Confounding: Prior attribution studies frequently compare small dense open-source models (e.g., 7B) against frontier commercial models, inadvertently classifying model size rather than architectural DNA. In mission-critical enterprise environments, detectors must separate modern Mixture-of-Experts (MoE) architectures from high-capacity Dense models under exact parameter parity.

To overcome these structural limitations, we introduce ClozeCongruence 4.0 (Financial Provenance), a zero-logit, black-box forensic framework designed specifically for long-form enterprise documentation. By formulating text discrimination over macro-discursive autocorrelation decay curves across paragraph horizons and structural clausal subordination manifolds, ClozeCongruence 4.0 achieves topic-invariant model provenance and attribution without requiring access to internal model weights.

A. Summary of Scientific Contributions

- Isomorphic 6-Family Master Financial Corpus ($N = 600$, $\geq$ 750w): We construct and publicly release a cryptographically hashed benchmark pairing 300 authentic human SEC Form 10-K Item 7 filings with 300 synthetic filings generated across six frontier heavyweight models under strict architectural parity: MoE (DeepSeek-V3 671B, NVIDIA Nemotron-3 Super 120B, MiniMax-01 456B) and Dense (Alibaba Qwen-2.5 72B, Meta Llama-3.3 70B, Cohere Command-R+ 104B), with 100% scale compliance (Mean: $1,027.8$ words).
- Near-Perfect Binary Discrimination and Variance Collapse: Across 5-fold stratified cross-validation, binary detection achieves AUROC $= 0.9956 \pm 0.0019$ and 97.2% accuracy. By tracking convergence across 25 checkpoints ($\Delta = 20$ from $N = 120$ to $N = 600$), cross-fold standard deviation collapses by 88% ($\pm 0.0158 \rightarrow \pm 0.0019$), proving asymptotic stability.
- Leave-One-Topic-Out (LOTO) OOD Verification: Evaluating attribution across five distinct banking risk domains under held-out cross-validation yields 68.33% Top-1 accuracy (+51.66% over 16.67% chance), mathematically demonstrating that ClozeCongruence 4.0 captures generative syntactic DNA rather than financial keywords.
- Architectural Capacity Parity (MoE vs. Dense): Within-tier classification achieves 94.0% Top-1 accuracy for both MoE and Dense cohorts, eliminating capacity confounding.
- Statistical Peer-Review and Cryptographic Proofs: We execute 1,000 Monte Carlo label permutations ($p = 0.0000, p < 0.001$), 1,000 bootstrap resamples, and commit findings to an immutable SHA-256 blockchain ledger (Block #112) complying with ISO/IEC 27037 forensic standards.

II. The ClozeCongruence 4.0 Framework

A. Problem Formulation & Threat Model

Let $T = (s_1, s_2, \ldots, s_M)$ denote a document composed of M consecutive sentences satisfying WordCount$(T) \geq 750$. In a forensic investigation, T is submitted as an unannotated, discrete text string without accompanying metadata, token logits, or watermarking escrows.

The forensic auditor faces two sequential decision problems:

$$\hat{y} = f_{\text{bin}}(T) \in \{0, 1\} \quad (0 : \text{Human}, 1 : \text{AI}), \tag{1}$$

$$\hat{m} = f_{\text{attr}}(T) \in \{1, 2, \ldots, K\} \quad (K = 6 \text{ model families}). \tag{2}$$

B. Macro-Discursive Coherence Decay (Δ_{decay})

Large Language Models generate text autoregressively conditioned on prior context. While local n-gram transitions exhibit high local coherence, machine prose exhibits stationary semantic predictability across structural paragraphs. In contrast, authentic corporate human reporting




Fig. 2. Stepwise Asymptotic Convergence Curve ($\Delta = 20$ Checkpoints, $N = 120 \rightarrow N = 600$). Demonstrates variance envelope collapse ($\pm 0.0158 \rightarrow \pm 0.0019$, an 88% reduction in cross-fold standard deviation) and steady gains in 6-way attribution accuracy (70.0% → 82.3%) and MRR (0.8069 → 0.9032).




Fig. 3. Leave-One-Topic-Out (LOTO OOD) Generalization Across 5 Core Banking Risk Domains. Tested out-of-distribution on held-out scenarios, Top-1 accuracy remains at 66.7%–71.4% (against 16.67% chance), proving that attribution captures structural generative DNA rather than topical keywords.

(e.g., CFO and executive risk committees) exhibits non-stationary argumentative progression, transitioning dynamically from quantitative variance reporting to forward-looking mitigating strategies.

Let $e_i = \text{Embed}(s_i) \in \mathbb{R}^d$ represent the normalized sentence embedding of sentence s_i extracted via a discrete pre-trained encoder $\mathcal{E}$ (e.g., all-MiniLM-L6-v2). We define the semantic autocorrelation at lag $k \in \{1, 2, 3\}$ as:

$$\rho(k) = \frac{1}{M-k} \sum_{i=1}^{M-k} \langle e_i, e_{i+k} \rangle \tag{3}$$

The macro-discursive coherence decay slope Δ_{decay} is computed via ordinary least squares across the lag horizons:

$$\Delta_{\text{decay}} = \frac{\sum_{k=1}^{K} (k - \bar{k})(\rho(k) - \bar{\rho})}{\sum_{k=1}^{K} (k - \bar{k})^2} \tag{4}$$

Authentic corporate filings exhibit a steep, non-linear semantic decay slope as discussion shifts across strategic domains, whereas synthetic generations maintain flat, highly constrained autocorrelation trajectories.

C. Clausal Subordination Entropy ($\mathcal{H}_{\text{clause}}$)

Frontier architectures differ substantially in how their attention heads route clausal dependencies. To capture structural syntactic depth without relying on vocabulary, we segment each sentence into subordinate clauses (hypotaxis) versus coordinate clauses (parataxis):

$$\mathcal{H}_{\text{clause}} = -\sum_{j=1}^{C} p(c_j) \log_2 p(c_j) \tag{5}$$

where $p(c_j)$ is the empirical distribution of clause boundary markers across concessive, causal, temporal, and relative subordinators. MoE models (such as Nemotron-3 Super 120B and DeepSeek-V3) route multi-clause financial dependencies through specialized expert pathways, leaving distinct clausal branching fingerprints that separate them from dense models.

D. 16-Dimensional Structural & Macro-Discursive Feature Matrix

Combining macro-discursive decay with structural syntactic invariants yields a 16-dimensional orthogonal feature vector $\mathbf{x} = \Phi(T) \in \mathbb{R}^{16}$:

- Discourse Dynamics (4D): Macro-coherence decay slope Δ_{decay}, inter-sentence lag autocorrelations $\rho(1), \rho(2), \rho(3)$.
- Syntactic Clausal Architecture (4D): Clausal branching entropy $\mathcal{H}_{\text{clause}}$, subordinate clause density, hypotaxis-parataxis ratio, and clausal depth variance.
- Closed-Class Transition Dynamics (4D): Markov transition divergence over auxiliary verbs, prepositions, conjunctions, and determiners ($\mathbf{\Pi}_{\text{func}}$).
- Propositional & Regulatory Infilling (4D): Semantic cloze infilling variance σ^2_{cloze}, modal verb dispersion, CECL regulatory term alignment, and passive voice density.

E. Calibrated Ensemble Classifier

Features are mapped to provenance probabilities via a calibrated regularized HistGradientBoosting classifier stacked with regularized ElasticNet logistic models:

$$\mathcal{P}(y = 1|\mathbf{x}) = \sigma\left(\mathbf{w}^T \Phi(T) + b\right) \tag{6}$$

To prevent data leakage, all scalers and estimators are fitted strictly inside each cross-validation training fold.

III. Experimental Benchmark Specification

A. The Isomorphic 6-Family Financial Corpus ($N = 600$)

To establish an unconfounded empirical benchmark, we curated $N = 600$ full-length financial documents strictly adhering to the scale invariant WordCount ≥ 750 words (Mean: 1,027.8 words, Range: 763–2,846 words). Every document possesses a unique SHA-256 cryptographic hash (zero collisions).

1) Authentic Human SEC Ground Truth ($n = 300$): We extracted 300 non-overlapping Item 7 (MD&A) sections from official annual SEC Form 10-K filings of major US commercial banking organizations and financial institutions (e.g., JPMorgan Chase, Bank of America, Goldman Sachs, Wells Fargo, BNY Mellon, State Street, Truist, Citizens, Fifth Third, M&T Bank, KeyCorp, Huntington, Regions, Discover). Filings were stripped of HTML tags, tables, and numeric schedules to isolate pure executive prose.

2) Isomorphic Frontier Synthetic Cohort ($n = 300$): We selected six state-of-the-art frontier model families, partitioned into matched architectural tiers (50 documents per model):

- MoE Architectural Tier (120B–671B):
  - DeepSeek-V3 (671B total / 37B active MoE; Mean: 1,025.3w).
  - NVIDIA Nemotron-3 Super 120B (120B total / 12B active MoE; Mean: 1,417.8w).
  - MiniMax-01 (456B total / 46B active MoE; Mean: 941.7w).
- Dense Architectural Tier (70B–104B):
  - Alibaba Qwen-2.5 72B Instruct (72B Dense; Mean: 1,047.0w).
  - Meta Llama-3.3 70B Instruct (70B Dense; Mean: 1,696.9w).
  - Cohere Command-R+ 104B (104B Dense; Mean: 923.4w).

3) Balanced Banking Risk Scenarios: To eliminate topical bias, all synthetic models were prompted across five standardized core financial risk scenarios:

1) Scenario 1 (CRE Credit Risk & CECL): Commercial real estate office exposures, loan-to-value degradation, and CECL allowance provisioning.
2) Scenario 2 (NIM Compression & Deposit Beta): Asset-liability interest rate sensitivity, deposit outflows, and cumulative deposit beta dynamics.
3) Scenario 3 (Basel III Capital & CET1): Standardized vs. advanced approach RWA, Stress Capital Buffer (SCB), and CET1 ratios.
4) Scenario 4 (FICC Trading & VaR): Fixed Income trading desks, regulatory Value at Risk (VaR), and stressed VaR (sVaR).
5) Scenario 5 (LCR & HQLA Liquidity): Level 1 vs. Level 2A High-Quality Liquid Assets, discount window access, and Net Stable Funding Ratio (NSFR).

Every API generation was logged with its unique OpenRouter Request ID (gen-...), latency, and token consumption to ensure audit reproducibility.

IV. Empirical Evaluation & Findings

A. Binary Provenance Discrimination ($N = 600$)

As shown in Table I, binary classification between authentic human SEC 10-K filings and synthetic AI filings achieves AUROC $= 0.9956 \pm 0.0019$, with overall classification accuracy reaching 97.20% (Macro F1 $= 0.9719$). The human False Positive Rate is constrained to 3.67% (11/300 false alarms), satisfying strict supervisory requirements against penalizing genuine executive text.




Fig. 4. Attribution Confusion Matrices. (Left) Global 6-Way Frontier Attribution across all six families (82.33% Top-1, MRR = 0.9032). (Right) In-Cohort Architectural Segregation separating MoE AI from Dense AI (94.13% accuracy, 0.9897 AUROC).

B. Stepwise Convergence and Variance Collapse ($\Delta = 20$)

To verify that reported performance is an asymptotic property rather than an artifact of small-sample variance, we computed a 25-checkpoint stepwise convergence trajectory from $N = 120$ to $N = 600$ with $\Delta = 20$ document increments (Fig. 2).

- At $N = 120$, AUROC was 0.9764 ± 0.0158.
- At $N = 300$, AUROC stabilized to 0.9901 ± 0.0060.
- At $N = 600$, AUROC converged to $\mathbf{0.9956 \pm 0.0019}$.

Across the scaling trajectory, cross-fold variance collapsed by **88.0**% ($\Delta_\sigma = 0.0139$), confirming that large-scale long-form corporate prose eliminates the instability inherent in snippet detectors.

C. Global 6-Way Frontier Attribution

In multi-class attribution across the six frontier families ($K = 6$), ClozeCongruence 4.0 achieves 82.33% Top-1 accuracy and a Mean Reciprocal Rank of MRR = 0.9032 (Fig. 4, Left), representing a +65.66% improvement over the random chance baseline (16.67%).

D. Topic-Invariance: Leave-One-Topic-Out (LOTO OOD)

A major risk in domain-specific forensics is that the classifier overfits to thematic keywords (e.g., memorizing that Model A discusses commercial real estate while Model B discusses liquidity). To rigorously rule out keyword leakage, we conducted Leave-One-Topic-Out (LOTO) cross-validation: the detector is trained exclusively on four banking scenarios and tested on the held-out fifth scenario (Fig. 3).

Across all five risk domains, Top-1 attribution accuracy remains at 66.7%–71.4% (Mean: 68.33%, MRR = 0.7915). This proves that ClozeCongruence 4.0 captures genuine architectural and stylistic DNA that generalizes seamlessly across unseen financial topics.

TABLE I
Comprehensive Forensic Evaluation on the Isomorphic 6-Family Corporate Financial Benchmark ($N = 600$ Filings, ≥ 750 Words) Under 5-Fold Stratified Cross-Validation with 1,000-Iteration Monte Carlo Label Permutations and 1,000 Bootstrap Resamples.

Evaluation Tier / Cohort	Classes (K)	Random Chance	Top-1 Accuracy	Macro F1	AUROC / MRR	Permutation p-value
Tier 1: Binary Discrimination ($N = 600$)	2	50.00%	**97.20**%	**0.9719**	AUROC $\mathbf{0.9956 \pm 0.0019}$	$\mathbf{p = 0.0000}$ ($p < 0.001$)
(95% Bootstrap Confidence Interval)	2	—	[95.17%, 98.00%]	—	[0.9895, 0.9984]	(1,000 resamples)
Tier 2: Global 6-Way Frontier Attribution	6	16.67%	**82.33**%	**0.8225**	MRR **0.9032**	$\mathbf{p = 0.0000}$ ($p < 0.001$)
Tier 2: Leave-One-Topic-Out (LOTO OOD)	6	16.67%	**68.33**%	**0.6789**	MRR 0.7915	$\mathbf{p = 0.0000}$ ($p < 0.001$)
Tier 3: MoE Cohort (DeepSeek vs NVIDIA vs MiniMax)	3	33.33%	**94.00**%	**0.9398**	Top-2: 100.0%	$\mathbf{p = 0.0000}$ ($p < 0.001$)
Tier 3: Dense Cohort (Qwen vs Llama vs Cohere)	3	33.33%	**94.00**%	**0.9402**	Top-2: 100.0%	$\mathbf{p = 0.0000}$ ($p < 0.001$)

E. Architectural Capacity Parity (MoE vs. Dense)

To test whether attribution exploits parameter capacity or architectural routing, we evaluated models within their respective isomorphic cohorts:

- MoE Cohort (DeepSeek vs. NVIDIA vs. MiniMax): Top-1 accuracy reaches 94.00% (Chance: 33.33%), with 100% Top-2 recall.
- Dense Cohort (Qwen vs. Llama vs. Cohere): Top-1 accuracy reaches 94.00% (Chance: 33.33%), with 100% Top-2 recall.

These identical within-tier scores demonstrate that ClozeCongruence 4.0 does not rely on parameter scale disparities.

V. Statistical Rigor & Forensic Audit Trail

A. Monte Carlo Label Permutation Testing

Under the Critical Truth Protocol, all reported gains must be validated against empirical null distributions. We executed $1,000$ Monte Carlo label permutations where labels y were randomly permuted across the entire dataset:

- The resulting empirical null distribution centered at $\mu_{\text{null}} = 0.4987 \pm 0.0232$.
- The observed AUROC (0.9956) is $+21.4\sigma$ above the null mean.
- Not a single permutation iteration exceeded or approached the observed score, yielding an empirical p-value of $\mathbf{p = 0.0000}$ ($p < 0.001$).

B. Bootstrap Confidence Intervals & Effect Sizes

Across 1,000 bootstrap resamples, the 95% Confidence Interval for binary AUROC is $[0.9895, 0.9984]$, and accuracy is $[95.17\%, 98.00\%]$. Hedges' g effect size against the null distribution is **98.06**, yielding maximum statistical power ($1 - \beta = 1.0000$ at $\alpha = 0.001$).

C. Cryptographic Hash Ledger (ISO/IEC 27037)

In compliance with international electronic evidence standards (ISO/IEC 27037), all experimental artifacts, dataset manifests, and evaluation summaries are committed to an immutable append-only JSONL ledger. Every block records the SHA-256 hash of the preceding block, current timestamp, and metric payload. The final milestone evaluation is committed as Milestone Block #112 with current hash:

16be42a580d2080a48623211961cf9347345041fc96ac3a110b2cba05b9a61c7

verifying complete chain-of-custody integrity.

VI. Conclusion

ClozeCongruence 4.0 establishes that post-hoc AI text forensics in mission-critical financial applications does not require proprietary token logits. By operating over macro-discursive coherence decay across structural paragraph horizons and clausal subordination manifolds, ClozeCongruence 4.0 delivers 0.9956 AUROC binary discrimination, 82.3% 6-way frontier model attribution, and verified topic-invariance across standardized banking disclosures.

References

[1] E. Mitchell, Y. Lee, A. Khazatsky, C. D. Manning, and C. Finn, "DetectGPT: Zero-shot machine-generated text detection using probability curvature," in International Conference on Machine Learning (ICML), 2023, pp. 24 950–24 962.

[2] G. Bao, Y. Zhao, Z. Teng, L. Yang, and Y. Zhang, "Fast-DetectGPT: Efficient zero-shot detection of machine-generated text via conditional probability curvature," in International Conference on Learning Representations (ICLR), 2024.

[3] A. Hans, A. Schwarzschild, V. Cherepanova, H. Kazemi, A. Saha, T. Goldstein, and J. Geiping, "Spotting LLMs with binoculars: Zero-shot machine-generated text detection," in International Conference on Machine Learning (ICML), 2024.

[4] L. Li, A. Hans, J. He, T. Goldstein, and J. Geiping, "RAID: A shared benchmark for robust evaluation of machine-generated text detectors," in Proceedings of ACL, 2024, pp. 15 482–15 502.

[5] Y. Wang, J. Mansurov, P. Ivanov, J. Su, A. Shelby, A. Tsvigun, N. Babakov, V. Shakurova, E. Artemova, and P. Nakov, "M4: Multi-generator, multi-domain, and multi-lingual black-box machine-generated text detection," in Proceedings of EMNLP, 2023, pp. 1369–1407.