

Debian-specific information about T_EX packages

The Debian T_EX mailing list <debian-tex-maint@lists.debian.org>

generated from \$Id: T_EX-on-Debian.sgml 1926 2006-11-03 12:33:08Z frank \$

Abstract

This document covers Debian-specific information for *users* of the Debian teT_EX packages (tetex-bin, tetex-base, tetex-extra, tetex-doc, tetex-doc-nonfree and tetex-src) and Debian T_EX Live packages (all packages named texlive-something). Further information, especially for *developers*, can be found in the Debian T_EX Policy draft in /usr/share/doc/tex-common/. Information for people upgrading from teT_EX 2.0.2 in sarge is in the NEWS.Debian file.

Copyright Notice

Copyright © 2004-2006 Frank Küster, Florent Rougon, Norbert Preining

This document is free software; you may redistribute it and/or modify it under the terms of the GNU General Public License as published by the Free Software Foundation; either version 2, or (at your option) any later version.

This document is distributed in the hope that it will be useful, but *without any warranty*; without even the implied warranty of merchantability or fitness for a particular purpose. See the GNU General Public License for more details.

A copy of the GNU General Public License is available as `/usr/share/common-licenses/GPL` (`file:///usr/share/common-licenses/GPL`) in the Debian distribution or on the World Wide Web at The GNU General Public Licence (<http://www.gnu.org/copyleft/gpl.html>). You can also obtain it by writing to the Free Software Foundation, Inc., 51 Franklin St, Fifth Floor, Boston, MA 02110-1301, USA.

Contents

1	Overview of the packages	1
2	Changing your configuration, file placement	3
2.1	Available <i>TEXMF</i> trees for users and system administrators	3
2.2	General hints	4
2.2.1	System-wide versus user-specific configuration	4
2.2.2	Configuration file placement	4
2.2.3	What is configured where?	4
2.3	Hyphenation	5
2.4	The files <code>texmf.cnf</code> , <code>fmtutil.cnf</code> , <code>updmap.cfg</code> and <code>language.dat</code>	5
2.4.1	<code>texmf.cnf</code> and <code>update-texmf</code>	6
2.4.2	<code>fmtutil.cnf</code> and <code>update-fmtutil</code> , <code>updmap.cfg</code> and <code>update-updmap</code> , <code>language.dat</code> and <code>update-language</code>	6
2.4.3	Per user configuration changes	7
2.5	Font caching	7
3	Usage hints, Debian-specific adaptations	9
3.1	Note on <code>dvips</code>	9
3.2	Note on <code>dvipdfm</code>	9
3.3	“ <i>T_EX</i> capacity exceeded” and similar errors	9
4	How to install additional or updated (La)<i>T_EX</i> packages or fonts	11
4.1	(La) <i>T_EX</i> input files	11
4.2	Complex installations	12
4.3	Font installation	12
4.4	User-specific installation	13

5 Problems, bug reports**15**

Chapter 1

Overview of the packages

The Debian teTeX packages are comprised of:

tetex-bin provides the binary files

tetex-base provides the most basic $\text{T}_{\text{E}}\text{X}$ and $\text{L}^{\text{A}}\text{T}_{\text{E}}\text{X}$ input files, and will be sufficient for some simple documents, e.g. to build the documentation of other Debian packages (hopefully)

tetex-extra contains lots of fonts and add-on packages for $\text{L}^{\text{A}}\text{T}_{\text{E}}\text{X}$ and $\text{T}_{\text{E}}\text{X}$ development. If you want to use $\text{L}^{\text{A}}\text{T}_{\text{E}}\text{X}$ to write and format your own documents, you will probably need many of these.

tetex-doc the free part (according to the Debian Free Software Guidelines) of the documentation for **tetex-bin**, **tetex-base** and **tetex-extra**. It is not needed to build existing documents, but as an author, you will for sure want to install it.

tetex-doc-nonfree the non-free part (according to the Debian Free Software Guidelines) of the documentation for **tetex-bin**, **tetex-base** and **tetex-extra**

tetex-src the sources (i.e., `.dtx` files) of all the $\text{T}_{\text{E}}\text{X}$ / $\text{L}^{\text{A}}\text{T}_{\text{E}}\text{X}$ files in **tetex-base** and **tetex-extra**, and of the documentation in **tetex-doc**. This package will only be needed by (La) $\text{T}_{\text{E}}\text{X}$ developers, or if you want to look up licensing information.

The Debian $\text{T}_{\text{E}}\text{X}$ Live packages are comprised of (currently) 76 packages in total. The most important are:

texlive-base-bin provides the basic binaries and basic $\text{T}_{\text{E}}\text{X}$ input files

texlive-latex-base provides the most basic $\text{L}^{\text{A}}\text{T}_{\text{E}}\text{X}$ input files, and will be sufficient for some simple documents

texlive-latex-recommended a recommended set of $\text{L}^{\text{A}}\text{T}_{\text{E}}\text{X}$ packages which are sufficient for most typesetting purposes if you don't have any special requirements

texlive-fonts-recommended a recommended set of fonts which are sufficient for most typesetting purposes if you don't have any special requirements

texlive-context the complete ConT_EXt environment

texlive a meta-package depending on a decent selection of packages, comprising all of the above

texlive-full a meta-package depending on all packages from the T_EX Live group and on some other packages to create something similar to a full T_EX Live installation

texlive-doc-* packages like `texlive-doc-en` and `texlive-doc-de` provide documentation in the respective language

texlive-lang-* packages like `texlive-lang-dutch` and `texlive-lang-spanish` provide language-specific support, like hyphenation patterns

There are many more packages, providing extra functionality and extra fonts. Please see the respective descriptions of these packages.

Chapter 2

Changing your configuration, file placement

2.1 Available *TEXMF* trees for users and system administrators

The following *TEXMF* trees are available. They are displayed below in the order they are searched, where earlier ones override later ones.

TEXMFCONFIG Default location: `$HOME/.texmf-config/`

Contains user-specific configuration

TEXMFVAR Default location: `$HOME/.texmf-var/`

Contains user-specific generated files

TEXMFHOME Default location: `$HOME/texmf/`

Contains user-specific static input files, e.g. new \LaTeX packages.

TEXMFSYSCONFIG Default location: `/etc/texmf`

Contains system-wide configuration

TEXMFSYSVAR Default location: `/var/lib/texmf/`

Contains system-wide generated files

TEXMFLOCAL Default location: `/usr/local/share/texmf/`

Contains system-wide input files

TEXMFMAIN Default location: `/usr/share/texmf/`

Contains system-wide, `dpkg`-managed input files (\TeX add-on packages)

TEXMFDIST Default location: `/usr/share/texmf- $\{\text{tetex}, \text{texlive}\}$`

Contains system-wide, `dpkg`-managed input files (basic \TeX packages)

If you want to add files, you should usually use *TEXMFLOCAL* or *TEXMFHOME*, depending on whether you are the system administrator or a user. If needed, a system administrator can add additional trees to the *TEXMF* variable in `/etc/texmf/texmf.d/05TEXMF.cnf` (earlier entries take precedence). *TEXMFCONFIG* and *TEXMFVAR* are used by the user-specific `texconfig`, `updmap`, and `fmtutil` commands. Note that `texconfig` creates a copy of configuration files from *TEXMFMAIN* (or `/etc/texmf`) at the time it is first invoked, and does not track later system-wide changes, and it does not know about `update-*` programs (see below ‘The files `texmf.cnf`, `fmtutil.cnf`, `updmap.cfg` and `language.dat`’ on the facing page).

2.2 General hints

2.2.1 System-wide versus user-specific configuration

\TeX Live as well as, since version 3.0, $\text{te}\TeX$, supports a complete user-specific configuration setup in the user’s home directory. System administrators must use the commands `texconfig-sys`, `fmtutil-sys` and `updmap-sys` which act on the system-wide configuration files. Users can invoke their user counterparts `texconfig`, `fmtutil` and `updmap`. This will put copies of the system-wide configuration files into the user’s *TEXCONFIG* directory (by default, `$HOME/.texmf-config`), modify them and generate according formats, if applicable.

2.2.2 Configuration file placement

On a \TeX system, in principle every \TeX input file can be used to *change the behavior of the system* and hence could be treated as a configuration file. To avoid an inflation of configuration files, those that are used to control the typeset output - the appearance of documents - are not installed as configuration files. It makes more sense to keep changed versions in the current directory for a certain project, or in *TEXMFHOME* or *TEXMFCONFIG* of a particular user. However, local admins can take any file they want from the *TEXMFDIST* (`/usr/share/texmf-tetex`) or *TEXMFMAIN* (`/usr/share/texmf`) trees and put changed copies into the respective directories below `/etc/texmf` (*TEXMFSYSCONFIG* which sorts before all other trees).

Since the package management system does not know whether a file is treated as a configuration file on a specific system, it is up to the site admin or local user to check whether one of their changed files has changed in *TEXMFMAIN* or *TEXMFDIST*.

2.2.3 What is configured where?

The central system-wide configuration files `texmf.cnf` (which controls the basic operation and file search paths for the included programs), `fmtutil.cnf` (which specifies the available \TeX formats), `updmap.cfg` (font configuration) and `language.dat` (hyphenation patterns)

for many formats) are handled through a Debian-specific mechanism that allows the basic \TeX packages, add-on packages and local administrators to combine their changes (see ‘The files `texmf.cnf`, `fmtutil.cnf`, `updmap.cfg` and `language.dat`’ on the current page below).

For some configuration changes, there is a program called `texconfig-dialog` (or simply `texconfig` for a commandline frontend); alternatively, you can of course make the necessary changes in configuration files by hand.

2.3 Hyphenation

Hyphenation should pretty much work out of the box. In $\text{te}\text{\TeX}$, there have been some changes in the past — see `NEWS.Debian` and `changelog.Debian` — but currently (nearly) all available patterns are enabled. If you want to use a reduced set of hyphenation patterns (which might gain you a trifle more speed), you can exclude them from the format file by changing the file specified in the third column of `fmtutil.cnf` — usually `language.dat` — and rebuild the formats with `fmtutil` or `fmtutil-sys`. Please note that in Debian, `language.dat` is a generated file (see ‘The files `texmf.cnf`, `fmtutil.cnf`, `updmap.cfg` and `language.dat`’ on this page).

For users of the norwegian language and $\text{te}\text{\TeX}$, there are several alternatives. For norwegian, there are different sets of patterns, and upstream chose `nohyphb.tex`. Details can be found in `/usr/share/texmf/doc/generic/nohyph/README.nohyph` — you can choose another one by editing `language.dat` or rather `/etc/texmf/language.d/01tetex.cnf`.

For users of the ukranian language (with $\text{te}\text{\TeX}$ and \TeX live), the right pattern file depends on the output encoding (see `/usr/share/texmf- $\{\text{tetex}, \text{texlive}\}$ /tex/generic/ukrhyph/ukrhyph.tex`); you can also choose different rule sets in the file.

There are currently no free hyphenation patterns for british english. Before enabling british/UKenglish, you need to get the non-free `ukhyphen.tex` - otherwise the format generation will fail. Don’t forget to complain to the UK TUG about how annoying this is. .

2.4 The files `texmf.cnf`, `fmtutil.cnf`, `updmap.cfg` and `language.dat`

In the following we describe ways to configure these files for the *system administrator*, i.e. one that has write access to the `/etc/texmf` hierachy. In ‘Per user configuration changes’ on page 7 we describe a per-user configuration.

The files `texmf.cnf`, `fmtutil.cnf`, `updmap.cfg` and `language.dat` contain configuration options from $\text{te}\text{\TeX}$ and/or \TeX Live, possibly from you, and from other \TeX -related packages. They are generated by scripts and should not — in fact, except `texmf.cnf` may not — be edited directly. Rather, you work with the source files in the respective directories below `/etc/texmf/`.

In order to make updates smooth, you should *avoid editing* system-wide files as far as possible, and instead *add new files* to change settings. For `texmf.cnf` snippets, this is particularly easy, since earlier entries override any later entries. Only for removing settings from `fmtutil.cnf`, `updmap.cfg` or `language.dat` is it necessary to edit existing files.

2.4.1 `texmf.cnf` and `update-texmf`

The \TeX binaries are built to look for `texmf.cnf` (the master config file for \TeX and Meta-Font) in `/usr/share/texmf/web2c/texmf.cnf` (or `$HOME/.texmf-config/web2c/texmf.cnf` if it exists). The system-wide file is a symbolic link to `/etc/texmf/texmf.cnf`. The Debian packaging includes a mechanism for constructing `texmf.cnf` from a collection of files under `/etc/texmf/texmf.d/`. To customize `texmf.cnf` while retaining the Debian-supplied configuration, create an appropriate file (or files) in `/etc/texmf/texmf.d/`, or change existing files, and then run `update-texmf`. This will generate the desired `texmf.cnf` for you.

You should not edit this file directly! While changes made by the local administrator will not be overwritten, they will cause you trouble once a package is updated and brings in a configuration change. You will be shown the differences between the edited and the newly generated file. We will try to merge our and your changes, but that might not always work, and you will probably have to edit again.

Therefore, if you want a smooth upgrade, please edit the files in `/etc/texmf/texmf.d`, or create an additional one, and invoke `update-texmf`. This will write your changes into `/etc/texmf/texmf.cnf`.

You should name your customization file something like `40macros.cnf`; the leading numerals will decide the order in which configuration fragments will be assembled by `update-texmf`, so it might be important to place your customizations in an appropriate place in the sequence — earlier definitions take precedence over later ones. In previous versions the extension `.cnf` was not necessary, and all files in the directory were used. If you had \TeX installed in woody, you might still have private files which need the extension to be added.

2.4.2 `fmtutil.cnf` and `update-fmtutil`, `updmap.cfg` and `update-updmap`, `language.dat` and `update-language`

These files are also generated files, just as it has been explained above for `texmf.cnf`. The difference to `texmf.cnf` is that the system-wide files will be put into `/var/lib/texmf/web2c`, and any change made in these files will be **unconditionally overwritten** by `update-fmtutil`, `update-language` and `update-updmap`, respectively. Only the files in `/etc/texmf/updmap.d/`, `/etc/texmf/fmt.d/` and `/etc/texmf/language.d/` will be treated as configuration files. Furthermore, there is no built-in merge mechanism at runtime, the files `fmtutil.cnf`, `updmap.cfg` and `language.dat` are used on a first-found-first-used basis.

Just as for `texmf.cnf`, the right way to change settings is to edit or add files in `/etc/texmf/updmap.d/`, `/etc/texmf/fmt.d/` or `/etc/texmf/language.d/`. The details have been

described above (see ‘`texmf.cnf` and `update-texmf`’ on the facing page). Note, however, that the extension for `updmap.cfg` snippets in `/etc/texmf/updmap.d/` is `.cfg`, not `.cnf`.

`updmap-sys(8)` provides options for enabling or disabling font map files. When enabling a new map file that is not mentioned, `updmap-sys` will first create or edit `10local.cfg` in the `/etc/texmf/updmap.d` directory and then call `update-updmap`. Note that `updmap-sys`’s `--edit` and `--syncwithtrees` options cannot be used on a Debian system.

2.4.3 Per user configuration changes

`update-texmf` is only available for root; if a user wants to maintain their own `texmf.cnf`, they can put it into `TEXMFCONFIG/web2c` and must manually edit it. Since all `texmf.cnf` files are read, with earlier definitions taking precedence over later ones, it is best to keep only a minimal set of definitions in the user-specific file.

In contrast to the above — \TeX reading and merging all `texmf.cnf` files — the *first* found occurrence of one of the files `updmap.cfg`, `language.dat`, `fmtutil.cnf` are used. Thus, when called by a user, the other configuration update programs also work with files in `TEXMFCONFIG/updmap.d`, `TEXMFCONFIG/fmt.d` or `TEXMFCONFIG/language.d`, where `TEXMFCONFIG` is usually `HOME/.texmf-config`. They combine files in these directories with the files in the system-wide directories — naturally the user-specific ones take precedence if the names are equal (see ‘User-specific installation’ on page 13) — and drop the respective generated file into the user’s `TEXMFVAR`, effectively overriding the system-wide config files. Note that changes to existing configuration file snippets made by package updates will not be propagated to the user’s files.

`upmap(1)` provides the same options for enabling and disabling map files as `updmap-sys(8)`, see above. `10local.cfg` is created or edited in `TEXMFCONFIG/updmap.d`.

2.5 Font caching

A \TeX system needs to generate new font data (pixel data, metric, sources) on the fly. These files can be saved into the \TeX font cache and later be reused. By default, a separate font cache is created for each user in their own `TEXMFVAR` directory (`$HOME/.texmf-var/`). If this directory is not writable, e.g. during automated package building, a directory called `VARTEXFONTS`, `/tmp/textfonts/`, is used instead, but this directory is cleaned up regularly.

On multi-user machines, it might be advisable that the local administrator enables a site-wide font cache and sets `VARTEXFONTS` to a persistent directory, e.g. `/var/cache/fonts`. The variable is set in `/etc/texmf/texmf.d/05 \TeX MF.cnf` and can either be changed there or preferably overwritten in a file that sorts before `05 \TeX MF.cnf`, e.g. `/etc/texmf/texmf.d/04VARTEXFONTS.cnf`. Do not forget to run `update-texmf` after making the change. To enable a site-wide font caching the admin should edit `/etc/texmf/web2c/mktex.cnf` and use ‘`varfonts`’ instead of ‘`texmfvar`’ in `MT_FEATURES`. Care should be taken to specify appropriate permissions for the directory containing the font

cache. Either the local admin should create all available font data and not allow write access, or else write access should be limited to trusted users. Yet another alternative is to bind-mount `/var/cache/fonts` from a separate partition, so that users are not able to fill up the `/var` partition with font data.

Chapter 3

Usage hints, Debian-specific adaptations

3.1 Note on dvips

Per default, `dvips` is in secure mode and won't execute shell commands in `\special` commands, like backticks in `\DeclareGraphicsRule`, etc. To enable this, change `z1` to `z0` in `/etc/texmf/dvips/config.ps` (second entry) (for `teTeX`) and in `/etc/texmf/texlive/dvips/config.ps` (for `TeX Live`).

3.2 Note on dvipdfm

In Debian `teTeX` packages, `dvipdfm` uses the settings in `/etc/papersize` to determine the default papersize. This only takes effect if the paper geometry is not set explicitly in the (La)`TeX` source, e.g. using the packages `geometry` or `hyperref`.

The Debian `TeX Live` packages currently do not evaluate the settings of `/etc/papersize`, please set the paper geometry explicitly in the (La)`TeX` source, e.g. using the packages `geometry` or `hyperref`.

3.3 “TeX capacity exceeded” and similar errors

In most cases, this error is the symptom of a syntax error in the document — `TeX` is getting into an infinite loop, and after some time all its internal registers have been used. Sometimes, however, a large document that loads a package that uses a lot of `TeX`'s registers leads to that error, or to a similar error message. The package documentation, the Google archive, or `TeX`-related mailing-lists or newsgroups will be helpful to find out which parameter needs to be changed in `/etc/texmf/texmf.cnf` (or rather in `/etc/texmf/texmf.d/95NonPath.cnf`, (see ‘`texmf.cnf` and `update-texmf`’ on page 6)).

Chapter 4

How to install additional or updated (La)T_EX packages or fonts

If you want to install additional (La)T_EX stuff, you have to:

- 1 install it at a place where T_EX can find it;
- 2 register it properly.

This can generally be done site-wide (by an administrator who has write access to at least `/usr/local/share/texmf` and `/etc/texmf`), or on a per-user basis. This can be done by any user on the system, without requiring write access to system directories. Some people might also find it more convenient in case they share their home directory between a couple of machines, even if they do have administrator rights.

In the following, we first explain the principles by describing a site-wide setup; then we explain the details for user-specific setup.

4.1 (La)T_EX input files

This is usually quite easy. Put the files in an appropriate directory below *TEXMFLOCAL*, which is the directory tree rooted at `/usr/local/share/texmf`.

For L^AT_EX packages, create the directory `tex/latex/packagename` within that tree (or use `tex/latex/misc`) and put the files there; the documentation should be put into `doc/latex/packagename`. If the package comes as a pair of `.dtx` and `.ins` files, you need to run `latex` over the `.ins` file in order to produce the package files, and over the `.dtx` file to produce the documentation. After that, the `.dtx` and `.ins` files are no longer needed. Please refer to the README file of the package if there is one.

After that, *registering* is easy: just run the command `mktexlsr` (also called `texhash`). This will regenerate the `ls-R` file for all *TEXMF* trees you have write access to.

4.2 Complex installations

With some packages, e.g. when they contain fonts, the procedure is more complicated. Please follow the instructions given in the package. The Debian-specific part comes in when the configuration files `texmf.cnf`, `fmtutil.cnf`, `updmap.cfg`, or `language.dat` need to be changed. See the description above ('The files `texmf.cnf`, `fmtutil.cnf`, `updmap.cfg` and `language.dat`' on page 5), the manual pages for `update-updmap`, `update-texmf`, `update-fmtutil`, `update-language` and 'Font installation' on this page.

4.3 Font installation

If you wish to install a font package in a system-wide manner, please follow the instructions in this section. If you are preparing a Debian package containing fonts, you should refer to the Debian TeX policy instead, which is shipped in the `tex-common` package.

Generally, you should first have a look at the installation instructions that come with the font package, in case there is something specific to that package with respect to installation. But you should make sure that you install most files in a subdirectory of `TEXMFLOCAL` (see 'Available TEXMF trees for users and system administrators' on page 3). This is because we are describing here a system-wide installation that is not done by Debian packages.

For instance, AFM files should be stored into `TEXMFLOCAL/fonts/afm/supplier/typeface/` where *supplier* identifies the supplier of the fonts (for instance, *adobe*, *urw* or *public*) and *typeface* refers to the name of the font family (e.g., *marvosym* or *lm*). If in doubt, you should have a look at the system trees managed by Debian packages, `/usr/share/texmf`, `/usr/share/texmf-tetex` and `/usr/share/texmf-texlive`; they follow the same layout, called the TeX Directory Structure (which is documented at <http://www.tug.org/tds/>).

In order for the various TeX-related programs to be able to use a font, you need to somehow register its map files (simply copying the files to `TEXMFLOCAL` is not enough). You can do this with the following steps, performed as `root`, where *foo* stands for the name of the font package you are installing:

- 1 Make sure you have stored all the relevant files shipped in the package (`.afm`, `.tfm`, `.pfb`, `.pfa`, `.mf`, `.fd`, `.enc`, `.map`, `.sty` are all relevant in this context) in the appropriate subdirectories of `TEXMFLOCAL`, as explained above.

Note: in `teTeX 3` and current `TeX Live` (as opposed to `teTeX 2`):

- `.map` files should go to `TEXMFLOCAL/fonts/map/syntax/foo/`
- `.enc` files should go to `TEXMFLOCAL/fonts/enc/syntax/foo/`

where *syntax* indicates the syntax followed by the files (it is often `dvips`). Please refer to the `teTeX` Manual for details. You can read this manual with the command

```
texdoc TETEXDOC
```


- 2 Create a configuration file `/etc/texmf/updmap.d/10local-foo.cfg` (the extension `.cfg` is important! You can also use one `10local.cfg` for all your locally installed fonts). The file should list the map files you stored in step 1 under `TEXMFLOCAL`, with one line per file, as in:

```
# This is a comment line
Map foo.map
Map other-map-file-from-package-foo.map
```

If a font is available both as bitmap and outline, you should use `MixedMap` instead of `Map`. Please refer to the manual pages for `update-updmap` and `updmap-sys` for details.

You can also use `updmap-sys --enable Map foo.map`; this will create the `10local.cfg` file for you.

- 3 Run the program `update-updmap`. This will generate an appropriate `updmap.cfg` file under `/var/lib/texmf/web2c/` (not `/etc/texmf/!`), containing the `Map` and/or `MixedMap` lines taken from `10local-foo.cfg`.

Note: modifying `updmap.cfg` directly is not supported in Debian, because Debian font packages need to update it when they are installed or removed. This is why `updmap.cfg` is not stored under `/etc` and why you have to use `update-updmap` whenever you want to modify it.

- 4 Run the program `mktexlsr` (or `texhash`, which is the same). This will record all the newly created files in `ls-R` files (these are used by TeX-related programs as indices to find the files they need when operating).
- 5 Run the program `updmap-sys`. This will use your updated `updmap.cfg` to generate files that are needed by `dvips`, `pdflatex`, `dvipdfm`, etc., such as `psfonts.map` and `pdftex.map`.

At this point, the font package should be properly installed for all users on the system.

4.4 User-specific installation

Instead of a system-wide installation, one can also install input files and fonts in the private `TEXMFHOME`, which is set to `$HOME/texmf` by default. For fonts, compared to the system-wide installation explained above, the following changes have to be made:

- In step 1, copy all relevant files to the appropriate subdirectories in `TEXMFHOME`.
- The configuration file created in step 2 should be placed in `TEXMFCONFIG` (`$HOME/.texmf-config` by default). An appropriate place would be `TEXMFCONFIG/updmap.d/`. Note that most likely you will have to create this directory first.

As for the site-wide installation, you can also use `updmap --enable Map foo.map`.

- After updating the `ls-R` files with `mktexlsr` or `texhash` (step 4), one has to generate the map files in step 5. This is done by running the program `updmap` instead of `updmap-sys`. The generated files are created in directories below *TEXMFVAR*.

Note that `update-updmap` merges the configuration files in `$HOME/.texmf-config/web2c/updmap.d` and in `/etc/texmf/updmap.d`. Therefore, all system-wide installed fonts are accessible without duplicating their configuration files. Merging the configuration files is done on the basis of file names: If a file exists in both directories, the version in *TEXMFCONFIG* takes precedence. Thus, you can also use this mechanism to change settings compared to the site-wide configuration, e.g. by keeping a changed copy of `00updmap.cfg` in *TEXMFCONFIG/updmap.d/*.

Keep in mind that you still have to call `update-updmap` whenever the system-wide installation changes. If you keep a changed copy of a file from the site-wide directories, you need to manually merge any changes to this file, if desired.

Chapter 5

Problems, bug reports

If the installation failed, please check the following points:

- Is there enough room on your hard disk?
- Is there any privately-compiled T_EX system besides the Debian packages?
- Does the command:


```
kpsewhich --format=cnf texmf
return /usr/share/texmf/web2c/texmf.cnf?
```
- Is `texmf.cnf` modified a lot? Please check `/etc/texmf/texmf.d/`.
- Did you set any T_EX-related environment variable?
- Try again. This might work in some cases.
- For `amstex`, `metapost`, `eurosym`, `texdoctk`, `txfonts`, `pxfonts`, etc., you need `tetex-extra` at present. (`pdftex`/`pdflatex` should work basically only with `tetex-base` now.)
- Is your `language.dat` correct?

How to report a bug:

- Please calm down anyway. ;)
- Please check the Debian Bug Tracking System first.
- Please read carefully the error messages, if any. It will help both you and us.
- Please use `reportbug` and include all information it gathers
- Please attach a simple and short sample file which causes the problem you want to report.
- Be prepared that we will have to ask more questions: You should have time to exchange a couple of e-mails with us
- It will be helpful to show us the output of the command:


```
ls /etc/texmf/texmf.d/*
```
- If you see something like:


```
Unpacking replacement tetex-base ...
dpkg: error processing /var/cache/./tetex-base*_all.deb (--unpack): t
```

 then the problem should be of package `foo`, not of `tetex-base`.
- Note that t_EX is not further developed upstream, and new features will only be integrated in T_EX Live. The Debian maintainers will not include anything in the T_EX Live packages that is not already in T_EX Live upstream.