

BPC-EA-310

NVIDIA Jetson Series

Edge AI Computing



BPC-EA-310 NVIDIA Jetson Series Edge AI Computing

Overview:

The **BPC-EA-310** is an industrial-grade embedded system designed for edge AI applications, powered by the NVIDIA Jetson Xavier NX core module from the NVIDIA Jetson Series. Delivering efficient AI processing capabilities, it serves critical domains including security surveillance systems, smart retail solutions, healthcare technologies, and industrial automation platforms.



Specification:

System	
CPU	NVIDIA Jetson Xavier NX Module, 6 x NVIDIA Carmel ARM v8.2. The PWR consumption is 10W/15W.
Memory	Onboard 8GB LPDDR4X (16GB optional)
Storage	Onboard 16GB eMMC
OS	Linux OS
Communication	
Gigabit Ethernet	2 x Gigabit Ethernet ports
Display	
Display	1 x HDMI output
MIPI CSI	2 x MIPI CSI
I/O	
	2 x USB3.0 1 x RS485/RS422/RS232 4 x GPIO 1 x CAN 1 x 30-pin I/O (GPIO/I2S/I2C/AUDIO/SPI/UART)
Expansion	
	1 x MiniPCIe/1 x M.2 E-Key 2230 for WiFi 1 x M.2 M-Key 2280 NVME (PCIe) 1 x M.2 B-Key for LTE/5G 1 x Nano SIM slot 1 x TF slot
Power Supply	
Power Input	DC 12~24V
Mechanical & Environmental	
Enclosure Material	Steel and aluminum alloy
Dimension	189mm(W) x 96.7mm(H) x 57.5mm(D) (±0.5mm)
Operating Temp.	-20°C to +60°C CPU/GPU Full Loaded Operation; -20°C to +75°C Frequency Reduction Operation
Storage Temp.	-40°C to +70°C

Safety Instruction:

To avoid malfunction or damage to this product please observe the following:

- Disconnect the device from the DC power supply before cleaning. Use a rag. Do not use liquid detergents or spray-on detergents.
- Keep the device away from moisture.
- During installation, put the device on a reliable table. It will be damaged if you drop it.
- Before connecting the power supply, ensure that the voltage is in the required range.
- Put the power cable in place to avoid stepping on it.
- If the device is not used for a long time, power it off to avoid damage caused by sudden overvoltage.
- Do not pour liquid into the hole of the enclosure, as this could cause fire or electrocution.
- For safety reasons, the device can only be disassembled by professional personnel.
- Do not place the device in a place where the ambient temperature is below -40°C or above 70°C . This will damage the machine. It needs to be kept in an environment at controlled temperature.

Contact Us:

Headquarters: DEBIX Technology Inc., 8345 Gold River Ct., Las Vegas, NV 89113, USA

Factory: 5-6/F., East Zone, Shunheda A2 Building, Liuxiandong Industrial Park, Xili, Nanshan Dist., Shenzhen, China

Email: info@debix.io

Website: www.debix.io

Community: <https://discord.com/invite/adaHHaDkH2>

