

Rated Current : 1.5AMP
Contact Resistance: 20mΩ Max
Withstanding Voltage: 500V AC/DC
Insulation Resistance:1000MΩ Min
Operation Temperature: -40° to +105°

Contact Material: Brass
Insulator Material: Polyester (UL 94V-0)
Contact Plating: Au or Sn Over Ni
Max Processing Temp: 230 °C for 30–60seconds
(260°C for 10 seconds)

$$\frac{\text{PH4087}}{\textcircled{1}} \frac{\text{6}}{\textcircled{2}} \frac{\text{A}}{\textcircled{3}} - \frac{\text{R}}{\textcircled{4}} \frac{\text{2}}{\textcircled{5}} \times \frac{\text{**}}{\textcircled{6}} - \frac{\text{**}}{\textcircled{7}}$$

①: PH4087: Series NO
②: 6: Right angle DIP Type
③: A: Plug
④: R: RoHS
⑤: 2: Double Row
⑥: PIN POS: 01:2POS ~ 40:80POS
⑦: Plating: 01:Gold Flash 02:1u" Gold 03:1.5u" Gold
04:2u" Gold 05:3u" Gold 06:5u" Gold
07:10U" Gold 08:15U" Gold 09:Tin

Dimension Antitheses List				
ITEM	PA	PC	H	L
Standard	3.9	2.8	2.0	8.7

Figure 1: Schematic diagram of the layout of the test chip. The diagram shows a horizontal row of 10 octagonal cells. Each cell contains a small square with a cross inside. Dimension lines indicate the overall width as $2.0 \times n_{Pin} \pm 0.2$ and the height of the cells as 2.0 ± 0.1 . A vertical dimension line on the right indicates the total height of the chip as 4.0 ± 0.15 .

Technical drawing of a 12-pin connector. The drawing shows a side view of the connector with 12 pins. Dimension lines indicate a total length of $2.0 \times (n-1) \text{ Pin} \pm 0.2$, a pin pitch of 2.0 ± 0.1 , and a pin diameter of $SQ \ 0.5$.

Figure 1: Detail of the reinforcement layout. The diagram shows a rectangular cross-section of a beam with two rows of reinforcement. The top row has 10 bars and the bottom row has 10 bars. The spacing between the bars in the top row is 2.0. The spacing between the bars in the bottom row is 2.0. The total width of the beam is $2.0 \times (n-1) \text{ Pin}$. A diagonal bar is shown with a diameter of 0.8.

Recommended P.C.B Layout(Top Side)
(PCB BOARD TOLERANCE±0.05)

PD.011.0029
PH40876A-R2*20-01

比例	SCALE
N/A	

单 位 UNIT
mm

一般公差	
GENERAL TOLERANCE	
***	± 0.05 ± 0.5°
**	± 0.10 ± 1°
*	± 0.20 ± 2°
	± 0.30 ± 5°

绘图
DR.
HOU BING
2012.03.30

校 图
CHK.
FU LONG
2012.03.30

核 准 APPD.
YANG BINGQIANG 2012.03.30

版本: REV.	A
页码: PAGE	1 of 1

品名:	PH2.0Pitch 2XnPin
TITLE	H2.0 180° DIP
料号:	PH40876A-R2×XX-XX
P/N	