

-- SQL Cheat Sheet | Pizza Sales Analysis

USE PROJECT_SQL;

1) Total Orders

```
SELECT COUNT(order_id) AS total_orders FROM orders;
```

2) Total Revenue

```
SELECT SUM(od.quantity*p.price) AS total_revenue
FROM order_details od
JOIN pizzas p ON p.pizza_id=od.pizza_id;
```

3) Top 5 Highest Priced Pizzas

```
SELECT p.pizza_id, pt.name, p.price
FROM pizzas p
JOIN pizza_types pt ON pt.pizza_type_id=p.pizza_type_id
ORDER BY p.price DESC LIMIT 5;
```

4) Most Common Pizza Size

```
SELECT size, COUNT(*) AS order_count
FROM pizzas p
JOIN order_details od ON p.pizza_id=od.pizza_id
GROUP BY size ORDER BY order_count DESC;
```

5) Top 5 Pizza Types

```
SELECT pt.name,SUM(od.quantity) qty
FROM pizza_types pt
JOIN pizzas p ON pt.pizza_type_id=p.pizza_type_id
JOIN order_details od ON od.pizza_id=p.pizza_id
GROUP BY pt.name ORDER BY qty DESC LIMIT 5;
```

6) Quantity by Category

```
SELECT category,SUM(quantity) pizza_count
FROM pizza_types pt
JOIN pizzas p ON p.pizza_type_id=pt.pizza_type_id
JOIN order_details od ON od.pizza_id=p.pizza_id
GROUP BY category;
```

7) Orders by Hour

```
SELECT HOUR(time),COUNT(order_id)
FROM orders
GROUP BY HOUR(time);
```

8) Category Distribution

```
SELECT category,COUNT(name)
FROM pizza_types GROUP BY category;
```

9) Daily Orders

```
SELECT date,AVG(order_id)
FROM orders GROUP BY date;
```

10) Top Revenue Pizzas

```
SELECT name,SUM(price*quantity) revenue
FROM pizza_types
JOIN pizzas USING(pizza_type_id)
JOIN order_details USING(pizza_id)
GROUP BY name ORDER BY revenue DESC LIMIT 5;
```

11) Revenue %

```
SELECT category,
ROUND(SUM(price*quantity)*100/
SUM(SUM(price*quantity)) OVER(),2) revenue_pct
FROM pizza_types pt
JOIN pizzas p ON p.pizza_type_id=pt.pizza_type_id
JOIN order_details od ON od.pizza_id=p.pizza_id
GROUP BY category;
```

12) Cumulative Revenue

```
SELECT date,  
SUM(SUM(price*quantity)) OVER(ORDER BY date)  
FROM orders o  
JOIN order_details od ON od.order_id=o.order_id  
JOIN pizzas p ON p.pizza_id=od.pizza_id  
GROUP BY date;
```