OpenAI Platform

Tokenizer

Learn about language model tokenization

OpenAI's large language models process text using **tokens**, which are common sequences of characters found in a set of text. The models learn to understand the statistical relationships between these tokens, and excel at producing the next token in a sequence of tokens. Learn more.

You can use the tool below to understand how a piece of text might be tokenized by a language model, and the total count of tokens in that piece of text.

GPT-5.x & O1/3 GPT-4 & GPT-3.5 (legacy) GPT-3 (legacy)

Many words map to one token, but some don't: indivisible.

Unicode characters like emojis may be split into many tokens containing the underlying bytes: 🤚🏾

Sequences of characters commonly found next to each other may be grouped together: 1234567890

Clear Show example

Tokens 53

Characters 252

```
Many words map to one token, but some don't: indivisible.

Unicode characters like emojis may be split into many tokens containing the
 underlying bytes: ????

Sequences of characters commonly found next to each other may be grouped
 together: 1234567890
```

Text Token IDs

A helpful rule of thumb is that one token generally corresponds to ~4 characters of text for common English text. This translates to roughly ¾ of a word (so 100 tokens ~= 75 words).

If you need a programmatic interface for tokenizing text, check out our tiktoken package for Python. For JavaScript, the community-supported @dbdq/tiktoken package works with most GPT models.