

AEM Content Fragment JSON output provides structured, raw content (text, numbers, boolean, references) designed for frontend frameworks like React or Vue. The JSON structure includes metadata, model definitions, and field-specific data (`_path` , `_metadata` , and field names). [🔗](#)

Sample Content Fragment JSON (Simple Data Types)

This represents a basic "Article" fragment with title, date, and body text. [🔗](#)

json



```
{
  "properties": {
    "title": "Example Article Title",
    "date": "2026-02-04",
    "body": {
      "plaintext": "This is the body content of the article...",
      "json": {
        "content": [
          {
            "nodeType": "paragraph",
            "content": [
              {
                "nodeType": "text",
                "value": "This is the body content of the article..."
              }
            ]
          }
        ]
      }
    }
  },
  "title": "Example Article Title",
  "description": "A sample article",
  "_path": "/content/dam/project/example-article",
  "_metadata": {
    "string": [
      "lastModified",
      "1738670000000"
    ]
  }
}
```

Key Aspects of Headless JSON:

- **Structure:** Content follows defined Content Fragment Models.

- **Data Types:** Supports text, numbers, JSON objects, and asset references.
- **Rich Text:** Multi-line fields can output as raw HTML or JSON structure.
- **Delivery:** Accessed via AEM GraphQL API or Assets HTTP API.
- **Raw Content:** Unlike Experience Fragments, Content Fragments contain no layout information. [🔗](#)

Sample Nested Content Fragment (Reference Type)

json



```
{
  "title": "Page with Feature",
  "heroImage": {
    "_path": "/content/dam/project/image.jpg",
    "mimeType": "image/jpeg"
  },
  "relatedContent": {
    "_path": "/content/dam/project/related-article",
    "title": "Related Article"
  }
}
```