

CSS Demo: transition

```
transition: margin-right 2s;
```

```
transition: margin-right 2s 0.5s;
```

```
transition: margin-right 2s ease-in-out;
```

```
transition: margin-right 2s ease-in-out 0.5s;
```

```
transition:  
  margin-right 2s,  
  color 1s;
```

```
transition: all 1s ease-out;
```

Hover to see
the transition.

Transitions enable you to define the transition between two states of an element. Different states may be defined using [pseudo-classes](#) like `:hover` or `:active` or dynamically set using JavaScript.

Constituent properties

This property is a shorthand for the following CSS properties:

- `transition-behavior`
- `transition-delay`
- `transition-duration`
- `transition-property`
- `transition-timing-function`

Syntax

CSS

```
/* Apply to 1 property */
/* property name | duration */
transition: margin-right 4s;

/* property name | duration | delay */
transition: margin-right 4s 1s;

/* property name | duration | easing function */
transition: margin-right 4s ease-in-out;

/* property name | duration | easing function | delay */
transition: margin-right 4s ease-in-out 1s;

/* property name | duration | behavior */
transition: display 4s allow-discrete;

/* Apply to 2 properties */
transition:
  margin-right 4s,
  color 1s;

/* Apply to all changed properties */
transition: all 0.5s ease-out allow-discrete;
transition: 200ms linear 50ms;

/* Global values */
transition: inherit;
transition: initial;
transition: revert;
transition: revert-layer;
transition: unset;
```

The `transition` property value is specified as one of the following:

- The special value `none`, which specifies that no transitions will occur on this element. This is the default value.
- One or more single-property transitions, separated by commas.

Each single-property transition describes the transition that should be applied to a single property or all properties. It includes:

- zero or one value representing the property or properties to which the transition should apply. This can be set as:
 - A `<custom-ident>` representing a single property.
 - The special value `all`, which specifies that the transition will be applied to all properties that change as the element changes state.
 - No value, in which case a value of `all` will be inferred and the specified transition will still apply to all changing properties.
- zero or one `<easing-function>` value representing the easing function to use

- zero, one, or two `<time>` values. The first value that can be parsed as a time is assigned to the `transition-duration`, and the second value that can be parsed as a time is assigned to `transition-delay`.
- zero or one value declaring whether to start transitions for properties whose animation behavior is `discrete`. The value, if present, is either the keyword `allow-discrete` or the keyword `normal`.

If you specify `all` as the transition property for one single-property transition, but then specify subsequent single-property transitions with `<custom-ident>` values, those subsequent transitions will override the first one. For example:

CSS

```
transition:
  all 200ms,
  opacity 400ms;
```

In this case, all the properties that change as the element changes state will transition with a duration of `200ms` except for `opacity`, which will take `400ms` to transition.

See [how things are handled](#) when lists of property values aren't the same length. In short, extra transition descriptions beyond the number of properties actually being animated are ignored.

Formal definition

Initial value	as each of the properties of the shorthand:	
	• <code>transition-delay</code>: <code>0s</code> • <code>transition-duration</code>: <code>0s</code> • <code>transition-property</code>: <code>all</code> • <code>transition-timing-function</code>: <code>ease</code> • <code>transition-behavior</code>: <code>normal</code>	
Applies to	all elements, <code>::before</code> and <code>::after</code> pseudo-elements	
Inherited	no	
Computed value	as each of the properties of the shorthand:	
	• <code>transition-delay</code>: as specified • <code>transition-duration</code>: as specified • <code>transition-property</code>: as specified • <code>transition-timing-function</code>: as specified • <code>transition-behavior</code>: as specified	
Animation type	Not animatable	

Formal syntax

```

transition =
  <single-transition>#

<single-transition> =
  [ none | <single-transition-property> ] ||
  <time> ||
  <easing-function> ||
  <time> ||
  <transition-behavior-value>

<single-transition-property> =
  all |
  <custom-ident>

<easing-function> =
  <linear-easing-function> |
  <cubic-bezier-easing-function> |
  <step-easing-function>

<transition-behavior-value> =
  normal |
  allow-discrete

<linear-easing-function> =
  linear |
  <linear()>

<cubic-bezier-easing-function> =
  ease |
  ease-in |
  ease-out |
  ease-in-out |
  <cubic-bezier()>

<step-easing-function> =
  step-start |
  step-end |
  <steps()>

<linear()> =
  linear( [ <number> && <percentage>{0,2} ]# )

<cubic-bezier()> =
  cubic-bezier( [ <number [0,1]> , <number> ]#{2} )

<steps()> =
  steps( <integer> , <step-position>? )

<integer> =

```

<number-token>

<step-position> =

jump-start |

jump-end |

jump-none |

jump-both |

start |

end

This syntax reflects the latest standard as per [CSS Easing Functions Level 2](#), [CSS Transitions Module Level 1](#), [CSS Transitions Module Level 2](#), [CSS Values and Units Module Level 4](#). Not all browsers may have implemented every part. See [Browser compatibility](#) for support information.

Examples

Basic example

In this example, when the user hovers over the element, there is a half-second (500ms) delay before a two-second background-color transition occurs.

HTML

HTML

```
<a class="target">Hover over me</a>
```

CSS

We include two <time> values. In the transition shorthand, the first <time> value is the transition-duration. The second time value is the transition-delay. Both default to 0s if omitted.

CSS

```
.target {  
  font-size: 2rem;  
  background-color: palegoldenrod;  
  transition: background-color 2s 500ms;  
}  
  
.target:hover {  
  background-color: darkorange;  
}
```

Hover over me

Specifications

Specification
CSS Transitions Module Level 1 # transition-shorthand-property ↗

Browser compatibility

[Report problems with this compatibility data](#) [↗](#) • [View data on GitHub](#) [↗](#)

												
	 Chrome	 Edge	 Firefox	 Opera	 Safari	 Chrome Android	 Firefox for Android	 Opera Android	 Safari on iOS	 Samsung Internet	 WebView Android	 WebView on iOS
transition	✓ 26 ...	✓ 12 ...	✓ 16 *... ..	✓ 12.1 ...	✓ 9 ...	✓ 26 ...	✓ 16 *... ..	✓ 12.1 ...	✓ 9 ...	✓ 1.5 ...	✓ 4.4 ...	✓ 9 ...
all	✓ 1	✓ 12	✓ 4	✓ 15	✓ 3.1	✓ 18	✓ 4	✓ 14	✓ 2	✓ 1	✓ 4.4	✓ 2
allow-discrete	✓ 37	✓ 12	✓ 4	✓ 24	✓ 10	✓ 37	✓ 4	✓ 24	✓ 10	✓ 3	✓ 37	✓ 10
ease	✓ 1	✓ 12	✓ 4	✓ 15	✓ 3.1	✓ 18	✓ 4	✓ 14	✓ 2	✓ 1	✓ 4.4	✓ 2
ease-in	✓ 1	✓ 12	✓ 4	✓ 15	✓ 3.1	✓ 18	✓ 4	✓ 14	✓ 2	✓ 1	✓ 4.4	✓ 2
ease-in-out	✓ 1	✓ 12	✓ 4	✓ 15	✓ 3.1	✓ 18	✓ 4	✓ 14	✓ 2	✓ 1	✓ 4.4	✓ 2
ease-out	✓ 1	✓ 12	✓ 4	✓ 15	✓ 3.1	✓ 18	✓ 4	✓ 14	✓ 2	✓ 1	✓ 4.4	✓ 2
Gradients can be animated	✗ No	✗ 12–18	✗ No	✗ No	🧪 TP	✗ No	✗ No	✗ No	✗ No	✗ No	✗ No	✗ No