



Log into or connect to Bitbucket Cloud

The following methods can be used for authenticating with Bitbucket Cloud:

- If you're logging into Bitbucket in a web browser, use your [Atlassian account login credentials](#).
- If you're using the Git CLI (`git`), use a [personal SSH key](#).
- If you require read-only SSH access to a repository or project for scripting, CI/CD tools, or integrations, use [repository and project Access keys](#).
- If you require user-level access for scripting, CI/CD tools, Bitbucket Cloud apps, or Bitbucket Cloud integrations, use [App passwords](#).
- If you're developing a Bitbucket Cloud app or integration, improve your user's experience by configuring [OAuth](#).

Atlassian account login credentials

Use your login credentials to log into [bitbucket.org](#) and other Atlassian products using your web browser. These login credentials can be either:

- an email and a password.
- a login from a third-party provider such as Google or Microsoft.

If you're not logging into [bitbucket.org](#) using a web browser, you'll need to use one of the other methods described on this page.

For information on Atlassian accounts, read:

- [Atlassian Support — What is an Atlassian account?](#)
- [Atlassian Support — Log in to your Atlassian account](#)

Personal SSH keys

Manage your plans and settings in Bitbucket Cloud

[Manage your plan and billing](#)

[Bitbucket Cloud Premium plan](#)

- [Log into or connect to Bitbucket Cloud](#)

[Configure SSH and two-step verification](#)

[App passwords](#)

[Show more](#) ▼

On this page

[Atlassian account login credentials](#)

[Personal SSH keys](#)

[Repository and project Access keys](#)

[App passwords](#)

[OAuth](#)

Community

[Questions, discussions, and](#)

Personal SSH keys are used for connecting to Bitbucket using the Git command line interface (`git`). These SSH keys are suitable for everyday usage of Git. An SSH key may need to be configured to use Bitbucket Cloud with some [Git GUI \(graphical user interface\) apps](#) (where the Git GUI app does not connect through a web browser dialog) such as [Git Extensions](#) and [TortoiseGit](#). [articles](#)

If a read-only Access key is suitable; for example, in a CI/CD tool that only uses Git to clone or pull code, use [repository and project Access keys](#).

To set up a Personal SSH key, read [Set up an SSH key](#).

Repository and project Access keys

SSH-based repository and project Access keys are used for connecting to Bitbucket using the Git command line interface (`git`), and provide read-only access to the repository or project they're created for. These Access keys are useful where read-only SSH access to Bitbucket is required for scripts and automation tools (including CI/CD tools).

To create a SSH-based Access key for:

- a single Bitbucket repository, read how to [Add a repository Access key](#).
- the all the repositories in a Bitbucket project, read how to [Add a project Access key](#).

App passwords

App passwords are single purpose access tokens with reduced user access. These passwords can be useful for scripting, CI/CD tools, and testing Bitbucket connected applications while they're in development. They're sometimes required by third-party applications to connect to Bitbucket Cloud. For details, see: [App passwords](#).

OAuth

OAuth is a method of authentication used for connecting third-party apps to Bitbucket Cloud, such as [Sourcetree](#) and the [Visual Studio Code Jira and Bitbucket extension](#). Users who are logged into Bitbucket are prompted to authorize access to specific information on Bitbucket. To learn about app development with Bitbucket APIs and OAuth, visit: [Atlassian Developer — Getting started](#).