

Yes, a GraphQL request can still result in a **400 Bad Request** error visible to a fetch interceptor, even if you expect success. This happens because the "success" or "failure" of a request is determined at different layers of the networking stack. 

Why a 400 error can still occur

- **Infrastructure/Server Layer (The 400 Error):** Before the request ever reaches the GraphQL engine, it must pass through web servers (like Nginx), firewalls, or API gateways. If the extra slash in the URL is interpreted as a syntax error or a malformed request line by these systems, they will return a [400 Bad Request](#) before GraphQL can process it.
- **GraphQL Layer (The 200 Success):** GraphQL is "transport-agnostic" and often returns a **200 OK** status even when the query itself contains application-level errors. If your server's routing is lenient, it might ignore the extra slash and successfully execute the query, returning a 200. 

Behavior in Fetch Interceptors

- **Interceptor Visibility:** A fetch interceptor sees the raw [HTTP status code](#) returned by the server.
- **The "Trap":** The native [Fetch API](#) does **not** reject the promise for 400 or 500 status codes; it only rejects on true network failures (e.g., DNS issues).
- **Manual Checks:** To catch this in an interceptor or wrapper, you must manually check the [response.ok property](#), which is `false` for any status outside the 200–299 range. 

Summary Table

Layer 	Result if Extra Slash is an Issue	Result if Extra Slash is Ignored
Server/Gateway	400 Bad Request	200 OK
GraphQL Engine	Never reached	Executes Query
Fetch Interceptor	Sees <code>status: 400</code> , <code>ok: false</code>	Sees <code>status: 200</code> , <code>ok: true</code>

To troubleshoot, use the Chrome DevTools Network tab to see exactly which status code the server is sending back. 