

These are results for [how to add custom headers to *intl Middleware\(request\)* response](#)

Search instead for [how to add custom headers to intlMiddleware\(req\) response](#)

✦ AI Overview

⋮

To add custom headers to the `next-intl` middleware response, you must wrap the default `createMiddleware` function in a custom middleware handler. This allows you to capture the response object and use the standard [Headers API](#) to modify it.

Implementation Steps

1. **Initialize the i18n Middleware:** Define your routing configuration using `createMiddleware`.
2. **Intercept the Response:** In your main `middleware` function, call the i18n handler and store its return value.
3. **Set Custom Headers:** Use `response.headers.set()` on the captured response before returning it. [🔗](#)

typescript

```
import createMiddleware from 'next-intl/middleware';
import { NextRequest } from 'next/server';

// 1. Define routing configuration
const handleI18nRouting = createMiddleware({
  locales: ['en', 'de'],
  defaultLocale: 'en'
});

export default function middleware(request: NextRequest) {
  // 2. Capture the response from next-intl
  const response = handleI18nRouting(request);

  // 3. Add your custom headers to the response
  response.headers.set('x-custom-header', 'my-value');
  response.headers.set('x-another-header', 'another-value');

  return response;
}

export const config = {
  // Match only internationalized pathnames
```

```
matcher: ['/', '/(de|en)/:path*']  
};
```

Key Considerations

- **Request vs. Response Headers:** If you need to add headers that your Server Components can read (request headers), you must modify the `request` object **before** calling the `intlMiddleware`, then pass the new headers via `NextResponse.next({ request: { headers: newHeaders } })`.
- **Composition:** When combining `next-intl` with other middlewares (like authentication), ensure you pass the response object through each layer so headers are not overwritten.
- **Overwriting:** Using `response.headers.set()` will overwrite any existing header with the same name. Use `response.headers.append()` if you want to add multiple values to the same header key. [GitHub +4](#)