

# Invariant Violation: Could not find "store" in either the context or props of "Connect(SportsDatabase)"

Asked 5 years, 3 months ago · Active 1 year, 3 months ago · Viewed 148k times



Full code here: <https://gist.github.com/js08/0ec3d70dfda76d7e9fb4>

160

Hi,



41



- I have an application where it shows different templates for desktop and mobile on basis of build environment.
- I am successfully able to develop it where I need to hide the navigation menu for my mobile template.
- right now I am able to write one test case where it fetches all the values through the proptypes and renders correctly
- but not sure how to write the unit test cases when its mobile it should not render nav component.
- I tried but I am facing an error...can you tell me how to fix it.
- provding code below.

## Test case

```
import {expect} from 'chai';
import React from 'react';
import TestUtils from 'react-addons-test-utils';
import {SportsTopPortion} from '../src/components/sports-top-portion/sports-top-portion.jsx';
require('../test-utils/dom');

describe('"sports-top-portion" Unit Tests', function() {
  let shallowRenderer = TestUtils.createRenderer();

  let sportsContentContainerLayout = 'mobile';
  let sportsContentContainerProfile = {'exists': 'hasSidebar'};
  let sportsContentContainerAuthExchange = {hasValidAccessToken: true};
  let sportsContentContainerHasValidAccessToken = 'test';

  it('should render correctly', () => {
    shallowRenderer.render(<SportsTopPortion sportsWholeFramework=
    {sportsContentContainerLayout} sportsPlayers={sportsContentContainerProfile}
    sportsAuthentication={sportsContentContainerAuthExchange} sportsUpperBar=
    {{activeSportsLink: 'test'}} />);
    //shallowRenderer.render(<SportsTopPortion sportsWholeFramework=
    {sportsContentContainerLayout} sportsPlayers={sportsContentContainerProfile}
```

Join Stack Overflow to learn, share knowledge, and build your career.

Sign up



```

    expect(renderedElement).to.exist;
  });

  it('should not render sportsNavigationComponent when sports.build is mobile', () =>
  {
    let sportsNavigationComponent = TestUtils.renderIntoDocument(<SportsTopPortion
sportsWholeFramework={sportsContentContainerLayout} sportsPlayers=
{sportsContentContainerProfile} sportsAuthentication=
{sportsContentContainerAuthExchange} sportsUpperBar={{activeSportsLink:'test'}} />);
    console.log("sportsNavigationComponent----->" +
JSON.stringify(sportsNavigationComponent));

    //let footnoteContainer =
TestUtils.findRenderedDOMComponentWithClass(sportsNavigationComponent, 'linkPack--
standard');

    //expect(footnoteContainer).to.exist;
  });
});

```

## Code snippet where test case need to be written

```

if (sports.build === 'mobile') {
  sportsNavigationComponent = <div />;
  sportsSideMenu = <div />;
  searchComponent = <div />;
  sportsPlayersWidget = <div />;
}

```

## Error

```

1) "sports-top-portion" Unit Tests should not render sportsNavigationComponent when
sports.build is mobile:
  Invariant Violation: Could not find "store" in either the context or props of
"Connect(SportsDatabase)". Either wrap the root component in a <Provider>, or
explicitly pass "store" as a prop to "Connect(SportsDatabase)".
    at Object.invariant [as default] (C:\sports-whole-
page\node_modules\invariant\invariant.js:42:15)
    at new Connect (C:\sports-whole-page\node_modules\react-
redux\lib\components\createConnect.js:135:33)
    at [object Object].ReactCompositeComponentMixin.mountComponent (C:\sports-whole-
page\node_modules\react\lib\ReactCompositeComponent.js:148:18)
    at [object Object].wrapper [as mountComponent] (C:\sports-whole-
page\node_modules\react\lib\ReactPerf.js:66:21)
    at Object.ReactReconciler.mountComponent (C:\sports-whole-
page\node_modules\react\lib\ReactReconciler.js:37:35)
    at ReactDOMComponent.ReactMultiChild.Mixin.mountChildren (C:\sports-whole-
page\node_modules\react\lib\ReactMultiChild.js:241:44)
    at ReactDOMComponent.Mixin._createContentMarkup (C:\sports-whole-
page\node_modules\react\lib\ReactDOMComponent.js:591:32)
    at ReactDOMComponent.Mixin.mountComponent (C:\sports-whole-
page\node_modules\react\lib\ReactDOMComponent.js:470:30)

```

```
page\node_modules\react\lib\ReactMultiChild.js:241:44)
  at ReactDOMComponent.Mixin._createContentMarkup (C:\sports-whole-
page\node_modules\react\lib\ReactDOMComponent.js:591:32)
  at ReactDOMComponent.Mixin.mountComponent (C:\sports-whole-
page\node_modules\react\lib\ReactDOMComponent.js:479:29)
  at Object.ReactReconciler.mountComponent (C:\sports-whole-
page\node_modules\react\lib\ReactReconciler.js:37:35)
  at [object Object].ReactCompositeComponentMixin.mountComponent (C:\sports-whole-
page\node_modules\react\lib\ReactCompositeComponent.js:225:34)
  at [object Object].wrapper [as mountComponent] (C:\sports-whole-
page\node_modules\react\lib\ReactPerf.js:66:21)
  at Object.ReactReconciler.mountComponent (C:\sports-whole-
page\node_modules\react\lib\ReactReconciler.js:37:35)
  at ReactDOMComponent.ReactMultiChild.Mixin.mountChildren (C:\sports-whole-
page\node_modules\react\lib\ReactMultiChild.js:241:44)
  at ReactDOMComponent.Mixin._createContentMarkup (C:\sports-whole-
page\node_modules\react\lib\ReactDOMComponent.js:591:32)
  at ReactDOMComponent.Mixin.mountComponent (C:\sports-whole-
page\node_modules\react\lib\ReactDOMComponent.js:479:29)
  at Object.ReactReconciler.mountComponent (C:\sports-whole-
page\node_modules\react\lib\ReactReconciler.js:37:35)
  at [object Object].ReactCompositeComponentMixin.mountComponent (C:\sports-whole-
page\node_modules\react\lib\ReactCompositeComponent.js:225:34)
  at [object Object].wrapper [as mountComponent] (C:\sports-whole-
page\node_modules\react\lib\ReactPerf.js:66:21)
  at Object.ReactReconciler.mountComponent (C:\sports-whole-
page\node_modules\react\lib\ReactReconciler.js:37:35)
  at ReactDOMComponent.ReactMultiChild.Mixin.mountChildren (C:\sports-whole-
page\node_modules\react\lib\ReactMultiChild.js:241:44)
  at ReactDOMComponent.Mixin._createContentMarkup (C:\sports-whole-
page\node_modules\react\lib\ReactDOMComponent.js:591:32)
  at ReactDOMComponent.Mixin.mountComponent (C:\sports-whole-
page\node_modules\react\lib\ReactDOMComponent.js:479:29)
  at Object.ReactReconciler.mountComponent (C:\sports-whole-
page\node_modules\react\lib\ReactReconciler.js:37:35)
  at [object Object].ReactCompositeComponentMixin.mountComponent (C:\sports-whole-
page\node_modules\react\lib\ReactCompositeComponent.js:225:34)
  at [object Object].wrapper [as mountComponent] (C:\sports-whole-
page\node_modules\react\lib\ReactPerf.js:66:21)
  at Object.ReactReconciler.mountComponent (C:\sports-whole-
page\node_modules\react\lib\ReactReconciler.js:37:35)
  at [object Object].ReactCompositeComponentMixin.mountComponent (C:\sports-whole-
page\node_modules\react\lib\ReactCompositeComponent.js:225:34)
  at [object Object].wrapper [as mountComponent] (C:\sports-whole-
page\node_modules\react\lib\ReactPerf.js:66:21)
  at Object.ReactReconciler.mountComponent (C:\sports-whole-
page\node_modules\react\lib\ReactReconciler.js:37:35)
  at mountComponentIntoNode (C:\sports-whole-
page\node_modules\react\lib\ReactMount.js:266:32)
  at ReactReconcileTransaction.Mixin.perform (C:\sports-whole-
page\node_modules\react\lib\Transaction.js:136:20)
  at batchedMountComponentIntoNode (C:\sports-whole-
page\node_modules\react\lib\ReactMount.js:282:15)
  at ReactDefaultBatchingStrategyTransaction.Mixin.perform (C:\sports-whole-
page\node_modules\react\lib\Transaction.js:136:20)
  at Object.ReactDefaultBatchingStrategy.batchedUpdates (C:\sports-whole-
page\node_modules\react\lib\ReactDefaultBatchingStrategy.js:62:19)
  at Object.batchedUpdates (C:\sports-whole-
page\node_modules\react\lib\ReactUpdates.js:94:20)
  at Object.ReactMount._renderNewRootComponent (C:\sports-whole-
page\node_modules\react\lib\ReactMount.js:476:18)
```

Join Stack Overflow to learn, share knowledge, and build your career.

Sign up



```

    at Object.ReactMount.render (C:\sports-whole-
page\node_modules\react\lib\ReactDOM.js:570:23)
    at Object.wrapper [as render] (C:\sports-whole-
page\node_modules\react\lib\ReactPerf.js:66:21)
    at Object.ReactTestUtils.renderIntoDocument (C:\sports-whole-
page\node_modules\react\lib\ReactTestUtils.js:76:21)
    at Context.<anonymous> (C:/codebase/sports-whole-page/test/components/sports-top-
portion/sports-top-portion-unit-tests.js:28:41)
    at callFn (C:\sports-whole-page\node_modules\mocha\lib\runnable.js:286:21)
    at Test.Runnable.run (C:\sports-whole-
page\node_modules\mocha\lib\runnable.js:279:7)
    at Runner.runTest (C:\sports-whole-page\node_modules\mocha\lib\runner.js:421:10)
    at C:\sports-whole-page\node_modules\mocha\lib\runner.js:528:12
    at next (C:\sports-whole-page\node_modules\mocha\lib\runner.js:341:14)
    at C:\sports-whole-page\node_modules\mocha\lib\runner.js:351:7
    at next (C:\sports-whole-page\node_modules\mocha\lib\runner.js:283:14)
    at Immediate._onImmediate (C:\sports-whole-
page\node_modules\mocha\lib\runner.js:319:5)

```

reactjs

mocha.js

redux

Share Improve this question Follow

edited Mar 25 '16 at 17:50

asked Mar 24 '16 at 23:32



user6015171

## 9 Answers

Active

Oldest

Votes



209



It's pretty simple. You're trying to test the wrapper component generated by calling `connect()` (`MyPlainComponent`). That wrapper component expects to have access to a Redux store. Normally that store is available as `context.store`, because at the top of your component hierarchy you'd have a `<Provider store={myStore} />`. However, you're rendering your connected component by itself, with no store, so it's throwing an error.

You've got a few options:

- Create a store and render a `<Provider>` around your connected component
- Create a store and directly pass it in as `<MyConnectedComponent store={store} />`, as the connected component will also accept "store" as a prop
- Don't bother testing the connected component. Export the "plain", unconnected version, and test that instead. If you test your plain component and your `mapStateToProps` function, you can safely assume the connected version will work correctly.

You probably want to read through the "Testing" page in the Redux docs:

<https://redux.js.org/recipes/writing-tests>.

**Join Stack Overflow** to learn, share knowledge, and build your career.

Sign up



After actually seeing that you posted source, and re-reading the error message, the real problem is not with the SportsTopPane component. The problem is that you're trying to "fully" render SportsTopPane, which also renders all of its children, rather than doing a "shallow" render like you were in the first case. The line `searchComponent = <SportsDatabase sportsWholeFramework="desktop" />;` is rendering a component that I assume is also connected, and therefore expects a store to be available in React's "context" feature.

At this point, you have two new options:

- Only do "shallow" rendering of SportsTopPane, so that you're not forcing it to fully render its children
- If you do want to do "deep" rendering of SportsTopPane, you'll need to provide a Redux store in context. I highly suggest you take a look at the Enzyme testing library, which lets you do exactly that. See <http://airbnb.io/enzyme/docs/api/ReactWrapper/setContext.html> for an example.

Overall, I would note that you might be trying to do too much in this one component and might want to consider breaking it into smaller pieces with less logic per component.

Share Improve this answer Follow

edited Nov 8 '19 at 5:53



Aakash

14.5k ● 5 ● 79 ● 65

answered Mar 25 '16 at 5:11



markerikson

42.8k ● 7 ● 90 ● 112

I tried but not sure how to do...can you update in my test cases – user6015171 Mar 25 '16 at 16:13

1 I'm assuming that in SportsTopPortion.js, you have `let SportsTopPortion = connect(mapStateToProps)(SomeOtherComponent)`. The easiest answer is to test that *other* component, not the component returned by `connect`. – markerikson Mar 25 '16 at 16:38

1 Aha. Now I see what's happening. The problem is not with SportsTopPane itself. The problem is that you're doing a "full" render of SportsTopPane, not a "shallow" render, so React is trying to fully render all children. The error message refers to the line `searchComponent = <SportsDatabase sportsWholeFramework="desktop" />;`. That is the connected component that is expecting a store and breaking. So, two new suggestions: either only do shallow rendering of SportsTopPane, or use a library like Enzyme to test. See [airbnb.io/enzyme/docs/api/ReactWrapper/setContext.html](http://airbnb.io/enzyme/docs/api/ReactWrapper/setContext.html). – markerikson Mar 25 '16 at 16:44

can you tell me how to write the test case for this scenario "" but not sure how to write the unit test cases when its mobile it should not render nav component. "" – user6015171 Mar 25 '16 at 17:52

4 Answering someone who is stuck or puzzled with the phrase "it's pretty simple" can come off as disparaging or harsh. Please use sparingly. – jayqui May 6 '19 at 21:05

Possible solution that worked for me with jest

Join Stack Overflow to learn, share knowledge, and build your career.

Sign up





```
import configureMockStore from "redux-mock-store";
import TestPage from "../TestPage";

const mockStore = configureMockStore();
const store = mockStore({});

describe("Testpage Component", () => {
  it("should render without throwing an error", () => {
    expect(
      shallow(
        <Provider store={store}>
          <TestPage />
        </Provider>
      ).exists(<h1>Test page</h1>)
    ).toBe(true);
  });
});
```

Share Improve this answer Follow

answered Apr 23 '18 at 0:08



codeislife

1,316 ● 1 ● 9 ● 7

- works well, instead of having to pass props one by one. – [heygema](#) Nov 26 '18 at 12:10
- Thank you, a very nice solution. I had this problem because I am using a top-level App component with routing and the store is provided to the child app in each route so I don't have to pass props into the router. I changed it a little for my use. `const wrapper = shallow(<Provider store={store}><App /></Provider>); expect(wrapper.contains(<App />)).toBe(true);` – [Little Brain](#) Dec 26 '18 at 0:24



As the official [docs](#) of redux suggest, better to export the unconnected component as well.

75



In order to be able to test the App component itself without having to deal with the decorator, we recommend you to also export the undecorated component:



```
import { connect } from 'react-redux'

// Use named export for unconnected component (for tests)
export class App extends Component { /* ... */ }

// Use default export for the connected component (for app)
export default connect(mapStateToProps)(App)
```

Since the default export is still the decorated component, the import statement pictured above will work as before so you won't have to change your application code. However, you can now import the undecorated App components in your test file like this:

```
// Note the curly braces: grab the named export instead of default export
import { App } from './App'
```

Join Stack Overflow to learn, share knowledge, and build your career.

Sign up



```
import ConnectedApp, { App } from './App'
```

In the app itself, you would still import it normally:

```
import App from './App'
```

You would only use the named export for tests.

Share Improve this answer Follow

edited Apr 9 '18 at 14:13



Erowlin

4,554 ● 3 ● 29 ● 58

answered Apr 2 '18 at 5:44



JS dev

8,566 ● 12 ● 68 ● 111

1 This answer is legit as well. Edited your link to match the anchor. – Erowlin Apr 9 '18 at 13:33

This answer makes perfect sense! It may not be the right thing in all cases, but definitely better than playing with the Provider and all that when it's not necessary. – lokori Jul 26 '18 at 9:27

Thanks @lokori Happy you like it! – JS dev Jul 26 '18 at 10:41

2 This was the quickest and simplest way to get my test passing again. – Mike Lyons May 14 '19 at 21:12

2 "You would only use the named export for tests." -- Works for me. – technazi Aug 19 '19 at 17:34



7



When we put together a react-redux application we should expect to see a structure where at the top we have the `Provider` tag which has an instance of a redux store.

That `Provider` tag then renders your parent component, lets call it the `App` component which in turn renders every other component inside the application.

Here is the key part, when we wrap a component with the `connect()` function, that `connect()` function expects to see some parent component within the hierarchy that has the `Provider` tag.

So the instance you put the `connect()` function in there, it will look up the hierarchy and try to find the `Provider`.

Thats what you want to have happen, but in your test environment that flow is breaking down.

Why?

Why?

When we go back over to the assumed sportsDatabase test file, you must be the sportsDatabase component by itself and then trying to render that component by itself in isolation.

**Join Stack Overflow** to learn, share knowledge, and build your career.

Sign up





There is not store or `Provider` tag in the context or prop of that component and so the component throws an error because it want to see a `Provider` tag or store in its parent hierarchy.

So that's what that error means.

Share Improve this answer Follow

answered Sep 10 '18 at 22:35



Daniel

9,230 ● 9 ● 64 ● 105

in my case just

6

```
const myReducers = combineReducers({
  user: UserReducer
});
```

```
const store: any = createStore(
  myReducers,
  applyMiddleware(thunk)
);
```

```
shallow(<Login />, { context: { store } });
```

Share Improve this answer Follow

answered Sep 12 '18 at 16:07



jose920405

7,636 ● 4 ● 37 ● 64

For me it was import issue, hope it helps. default import by WebStorm was wrong.

5

replace

```
import connect from "react-redux/lib/connect/connect";
```

with

```
import {connect} from "react-redux";
```

Share Improve this answer Follow

edited Feb 6 '20 at 17:06

answered Feb 6 '20 at 17:00



ATQSHL

181 ● 1 ● 8

This happened to me when I upgraded. I had to downgrade back.

**Join Stack Overflow** to learn, share knowledge, and build your career.

Sign up





Share Improve this answer Follow

answered Feb 12 '20 at 23:00



codie

31 ● 1

This is more of a comment than an answer – sudo97 Feb 12 '20 at 23:06

There was a lot of breaking changes. I recommend watching this video to better understand the changes [youtube.com/watch?v=yOZ4MI9LIWE](https://youtube.com/watch?v=yOZ4MI9LIWE) – Kamil Dzieńszewski Apr 7 '20 at 8:53

just do this import { shallow, mount } from "enzyme";

2

```
const store = mockStore({
  startup: { complete: false }
});

describe("==== Testing App =====", () => {
  const setUpFn = props => {
    return mount(
      <Provider store={store}>
        <App />
      </Provider>
    );
  };

  let wrapper;
  beforeEach(() => {
    wrapper = setUpFn();
  });
```

Share Improve this answer Follow

answered Nov 16 '19 at 6:15



Hilal Aissani

533 ● 4 ● 3

in the end of your Index.js need to add this Code:

2

```
import React from 'react';
import ReactDOM from 'react-dom';
import { BrowserRouter } from 'react-router-dom';

import './index.css';
import App from './App';

import { Provider } from 'react-redux';
import { createStore, applyMiddleware, compose, combineReducers } from 'redux';
import thunk from 'redux-thunk';

//its your redux ex
import productReducer from './redux/reducer/admin/product/product.reducer.js'
```

Join Stack Overflow to learn, share knowledge, and build your career.

Sign up



```
const composeEnhancers = window._REDUX_DEVTOOLS_EXTENSION_COMPOSE_ || compose;
const store = createStore(rootReducer, composeEnhancers(applyMiddleware(thunk)));

const app = (
  <Provider store={store}>
    <BrowserRouter basename="/">
      <App />
    </BrowserRouter >
  </Provider>
);
ReactDOM.render(app, document.getElementById('root'));
```

[▶ Run code snippet](#)[🔗 Expand snippet](#)[Share](#) [Improve this answer](#) [Follow](#)

answered Mar 15 '20 at 19:38

[Mehrdad](#)

51 ● 4